

Contents

Part 1 General Information 2

Part 2 Outdoor unit 13

Part 3 Indoor unit 137

Part 4 Installation of outdoor units 353

Part 5 Controller System 378

Part 7 Trouble shooting..... 407

Part 1 General Information

HAVC system has advantages such as intelligent and energy-saving operation, convenient design & installation, flexible & diversified placement, small occupation space in building, convenient usage, low operation cost, free of A/C room, non-water system and simple maintenance, which is popularized rapidly with the economic development in recent years. It is not only extensively applied in household, villa, small office, restaurant, beauty saloon, but also gradually applied in office building, complex building and large entertainment place where conventional HAVC system dominates. The unit uses R410A environment-friendly refrigerant, which is more efficient, more energy-saving, more environment-friendly and enjoys more and more promising market prospect.

1 GRV Characteristics



Energy Saving Technology


◇ **Innovation technique for full DC inverter compressor**

High-performance, low-sound DC inverter compressor operates at a faster frequency, reducing start-up time. This helps the unit to bring the room temperature up to the set level quickly.



1. the new structure enhances the mid-frequency performance .
2. special scroll design profile for R410a.
3. more compact , weight is reduced by 50%.
4. advanced permanent magnet DC motor improves low frequency band performance





H-P: High pressure chamber compressor
L-P: Low pressure chamber compressor

- H-P compressor assures sufficient oil at low frequency condition
- L-P compressor with higher super-heating because the suction side refrigerant go through the motor and absorb heating, resulting in low enthalpy per unit refrigerant.
- H-P compressor adopt high pressure chamber as a damper to reduce the noise level.

◇ **Big capacity DC inverter compressor**

The products have adopt larger capacity DC compressor, so the piping system can be simple, and the energy loss is low. And the welding points are less , the possibility of leakage is small.



◇ **DC brushless fan motor**



DC brushless motor adjust the fan speed according to the stem pressure, enhance the efficiency by 45%. The Super Aero fan provide a large air volume and high static pressure , and at the same time it produces low level of noise.



Notes: Only for 8HP/10HP/12HP.


◇ **Sub-cooling technology**

- Prevent heat exchange between outlet and inlet
- Enhance degree of sub cooling
- Reduce the pressure resistance
- 17.6°C sub-cooling
- Enhance cooling capacity
- Extend longer pipe length



◇ **Improved refrigerant circuit**

Refrigerant circuit design increase the heat exchanging efficiency, and enhance the ratio of liquid refrigerant which flow to the evaporator.




◇ **Wide operation range**

No matter when it is as high as 52°C in hot summer or -20°C in cold winter, the unit could operate perfectly, making you feel like spring all year around. Advanced system design and strict system matching and test.



◇ **Wide operation voltage range**

Normally the voltage divitation of the power supply is aroud $\pm 10\%$, the product can operate within $\pm 15\%$. Specially in the place with unstable power supply, it is useful and effective.



◇ **Convenient piping design**


corresponding selection software can easily select the outdoor and indoor units, and automatically calculate he piping size, also the branch model. Finally it can output the report which list the material of the designed system.

◇ **Non-polar communication**

Signal wire connect no polarity required, the installation of GRV is simple and reliable.

◇ **Changeable ESP**

Advanced fan and high static pressure fan, provide outdoor unit up to 82Pa Static pressure. External static pressure by field setting to meet the requirements for installation on each floor, often requested for large-sized buildings



◇ **Auto address**



After System installation and turn to commissioning, through debugging buttons, the outdoor units distribute indoor system address automatically.

No need manually setting. More convenient and saving the installation time,system also check connected indoor unit quantity real time, automatic alarm when an error occurs.



◇ **Non- oil balance pipe**

Patented oil return technique, with oil separator and gas separator, no need install oil balance pipe among modules, oil throwing technique, high efficiency oil separator, ensure no oil insufficient, reduce installation cost.




- 1 compressor oil tank
- 2 oil throwing pipe
- 3 oil separator
- 4 oil return capillary
- 5 assistantSV1
- 6 oil return program

◇ **Extend pipe length and height**

Because of using DC inverter control technology and sub-cooling control circuit technology, it is possible to design a system with longer piping length and world-class elevation difference. The designer's working time is reduced and allowing more efficient design.

- * Max. total piping length-----1000m
- * Max. actual piping length-----175m
- * Max. level difference between IDU~IDU-----15m
- * Max. level difference between ODU~ODU-----90m
- * Max. piping length from 1st branch to the farthest IDU---40m
- * Max. level difference in the same system between ODU~ODU-----5m



Convenience And Comfort

◇ **Different operation modes**

Add more operation mode for various applications. Through outdoor PCB switch easy change system operation mode.



Heating priority mode(default)



Cooling only



Cooling priority mode



Heating only



First on priority




Majority priority


Heating priority : System will work in heating mode only.Other mode demand will no response
 Cooling priority: System will work in cooling mode only.Other mode demand will no response
 First on priority: The first start indoor unit operation mode will Decide system operation , others different demand will no response.
 Majority priority: System operation mode is decided by majoritydemand.

◇ **Silent operation**

By using optimized fan blades and the computational Fluid Dynamics technology, the product is equipped with the night low-noise operation function. Provide more quiet operation during the night. Minimum operation noise only 45dB(A)



Night silent operation (Compare with normal operation, silent operation noise reduce 12dB(A))



◇ **Economic lock function**


Special designed economic locking function, through outdoorPCB switch setting. If work in economic lock, AC lowest work cooling temperature will keep in 26°C and highest heating temperature keep 20°C.

Save energy and keep provide comfortable, friend environment
 Economic locking mode is superior to heating priority, cooling priority, cooling only, heating only, first on priority and majority priority mode.




◇ **VIP design**

Special VIP control function, the VIP room will decide the whole system operation mode, prior to other mode or economic locking function, ensure the priority of the important room.




◇ **Precise temperature control**

The unit uses PI calculation principle to calculate the percentage of indoor capacity demand according to indoor temperature fluctuations, to perform real-time control to the compressor operating frequency and achieve precision control to the indoor temperature.



◇ **Intelligent defrosting**

GREEN intelligent defrosting technique extend the heating operation and decrease the frequency of defrosting. Result in stable room temperature, offer comfort life.



Reliable & Stable

◇ Module sequence operation

The operation priority sequence of the outdoor unit modules will be changed when start up, maximize the life span of each outdoor unit.



1st time operation

2nd time operation

3rd time operation

◇ Black box function


The E-rom of the controller can memorize the operation information 30 minutes before the malfunction happening. It is useful for engineer on job site , it can be used as instruction for trouble shooting.



◇ All-around Black box function

The product have some safety protection design as following.

- Discharge temperature protection
- High/low pressure protection
- Drive module protection
- Phase sequence protection
- Refrigerant lack protection
- Four-way valve protection
- Indoor unit quantity decreasing alarm function
- Compressor over-current protection



Intelligent Control

◇ Remote control

Self diagnosis software can be used as remote controller, it is recommended for commissioning. It can monitor the running state of the outdoor and indoor units real time. And display the malfunction, be convenient to do the commissioning and trouble shooting work.

◇ Net work control

GREEN do have the independent central control software and the centralcontrol software with the billing function. Can be combined with the BMS adapter ,such as the Lonworks,BACnet and Modbus protocol adapter.

Central control software

Billing system

◇Flexible and Diversified Matching of Indoor and Outdoor Unit

Indodor unit series, specifications and models can be selected freely according to applicable place. Indodor unit series that are available include four-way cassette series, slim-duct series, low ESP duct series, middle ESP duct series, ceiling & floor series and wall-mounted series.

2 External Appearance

Indoor units

Indoor unit series	Cassette	Ceiling & Floor	Slim Duct	Low ESP Duct	Middle ESP Duct	High ESP Duct	Wall-mounted	HRV
Cooling capacity range of indoor unit (kW)	2.2		●	●			●	200
	2.8	●		●	●		●	300
	3.6	●		●	●		●	400
	4.5	●	●	●	●	●	●	500
	5.6	●	●	●	●	●	●	800
	7.1	●	●	●	●	●	●	1000
	8.0	●	●			●		1500
	9.0	●	●			●		2000
	10.0	●	●			●		2500
	11.2	●	●			●	●	3000
	12.5	●	●			●	●	4000
	14.0	●	●			●	●	5000
	15.0					●	●	200
	22.0						●	/
	28.0						●	/
	45.0						●	/
56.0						●	/	

Outdoor Units

8, 10,12 HP	14,16, 18 HP	20 HP
22, 24, 26, 28, 30, 32 HP	34, 36, 38, 40, 42, 44, 46, 48 HP	
50, 52, 54, 56, 58, 60, 62, 64, 66, 68, 70, 72,74,76,78,80 HP		

3 Combinations of Outdoor Units

Capacity (HP)	Recommend combination							Max. connection indoor units
	8(HP)	10(HP)	12(HP)	14(HP)	16(HP)	18(HP)	20(HP)	
8	●							13
10		●						16
12			●					16
14				●				16
16					●			20
18						●		20
20							●	24
22		●	●					24
24		●		●				28
26		●			●			28
28			●		●			28
30				●	●			32
32					●●			32
34		●●		●				36
36		●●			●			36
38		●	●		●			36
40		●		●	●			42
42		●			●●			42
44			●		●●			42
46				●	●●			48
48					●●●			48
50	●	●			●●			54
52		●●			●●			54
54		●	●		●●			54
56		●		●	●●			58
58		●			●●●			58
60			●		●●●			58
62				●	●●●			64
64					●●●●			64
66					●●●	●		64
68					●●	●●		64
70					●	●●●		64
72						●●●●		64
74						●●●	●	64
76						●●	●●	64
78						●	●●●	64
80							●●●●	64

Notice:

The system enables the connection of indoor units with a total capacity of between 50 % to 130% of that of the corresponding outdoor unit but when this capacity ratio exceeds 100% then the actual capacity of each indoor unit will decrease compared to rated capacity when all the units operated simultaneously.



Part 2 Outdoor unit

1.Features	14
2.Specifications	17
3.Demensions	18
4. Refrigeration cycle diagram	21
5.Wire Diagrams	35
6.Capacity Tables	39
7.Control discipline	103
8.Electric Characteristic	111
9.Sound level	112
10.Explode View	113
11.Spare parts lists	133

1.Features

◇ Innovation technique for full DC inverter compressor

High-performance, low-sound DC inverter compressor operates at a faster frequency, reducing start-up time. This helps the unit to bring the room temperature up to the set level quickly.



H-P

L-P

H-P: High pressure chamber compressor
L-P: Low pressure chamber compressor

- H-P compressor assures sufficient oil at low frequency condition
- L-P compressor with higher super-heating because the suction side refrigerant go through the motor and absorb heating, resulting in low enthalpy per unit refrigerant.
- H-P compressor adopt high pressure chamber as a damper to reduce the noise level.

◇ DC brushless fan motor



DC brushless motor adjust the fan speed according to the stem pressure, enhance the efficiency by 45%. The Super Aero fan provide a large air volume and high static pressure , and at the same time it produces low level of noise.



Notes: Only for 8HP/10HP/12HP


◇ Sub-cooling technology

- Prevent heat exchange between outlet and inlet
- Enhance degree of sub cooling
- Reduce the pressure resistance
- 17.6°C sub-cooling
- Enhance cooling capacity
- Extend longer pipe length




◇ **Improved refrigerant circuit**

Refrigerant circuit design increase the heat exchanging efficiency, and enhance the ratio of liquid refrigerant which flow to the evaporator.



◇ **Changeable ESP**


Advanced fan and high static pressure fan, provide outdoor unit up to 82Pa Static pressure. External static pressure by field setting to meet the requirements for installation on each floor, often requested for large-sized buildings



◇ **Extend pipe length and height**


Because of using DC inverter control technology and sub-cooling control circuit technology, it is possible to design a system with longer piping length and world-class elevation difference. The designer's working time is reduced and allowing more efficient design.

- * Max. total piping length-----1000m
- * Max. actual piping length-----175m
- * Max. level difference between IDU~IDU-----15m
- * Max. level difference between ODU~ODU-----90m
- * Max. piping length from 1st branch to the farthest IDU---40m
- * Max. level difference in the same system between ODU~ODU-----5m



◇ **Different operation modes**

Add more operation mode for various applications. Through outdoor PCB switch easy change system operation mode.



Heating priority : System will work in heating mode only. Other mode demand will no response

Cooling priority: System will work in cooling mode only. Other mode demand will no response

First on priority: The first start indoor unit operation mode will Decide system operation , others different demand will no response.

Majority priority: System operation mode is decided by majority demand.

◇ **Economic lock function**

Special designed economic locking function, through outdoor PCB switch setting. If work in economic lock, AC lowest work cooling temperature will keep in 26°C and highest heating temperature keep 20°C.

Save energy and keep provide comfortable, friend environment
Economic locking mode is superior to heating priority, cooling priority, cooling only, heating only, first on priority and majority priority mode.



◇ **VIP design**

Special VIP control function, the VIP room will decide the whole system operation mode, prior to other mode or economic locking function, ensure the priority of the important room.

◇ **Module and compressor sequence operation**

The operation priority sequence of the outdoor unit modules will be changed when start up, maximize the life span of each outdoor unit.



2.Specifications

Model	Outdoor		GRV08P3T3/4	GRV10P3T3/4	GRV12P3T3/4
Capacity	Cooling	kW	25.2	28.0	33.5
	Heating	kW	28.0	31.5	37.5
Electric Data	Power Supply	V~,Hz,Ph	380~415,50,3	380~415,50,3	380~415,50,3
	Cooling Power Input	kW	5.8	7.1	8.9
	Heating Power Input	kW	6.1	7.6	9.1
	Cooling Current	A	8.8	10.8	13.5
	Heating Current	A	9.3	11.5	13.8
Performance	Air Flow Volume	m ³ /h	12000	12000	12000
	Noise Level	dB(A)	45-58	45-58	45-58
Piping Limite	Vertical Pipe Length	m	90	90	90
	Actual Pipe Length	m	165	165	165
	Equivalent Pipe Length	m	190	190	190
	Total Pipe length	m	1000	1000	1000
Max. No. of Indoor Units		unit	13	16	19
Connection Ratio		%	50~130	50~130	50~130
Dimension(WxDxH)	Net	mm	930x765x1680	930x765x1680	930x765x1680
	Packing	mm	980x810x1850	980x810x1850	980x810x1850
Weight	Net	kg	223	223	248
	Gross	kg	243	243	268
Refrigerant Type			R410a	R410a	R410a
Pipe Diameter	Liquid Side	mm	12.7(1/2)	12.7(1/2)	12.7(1/2)
	Gas Side	mm	22.2(7/8)	22.2(7/8)	22.2(7/8)
Operation Range	Cooling	℃	-15℃~52℃	-15℃~52℃	-15℃~52℃
	Heating	℃	-20℃~24℃	-20℃~24℃	-20℃~24℃
Stuffing Quantity	20/40/40H	unit	14/28/28	14/28/28	14/28/28

Notes:

1. Cooling Capacity: Indoor temperature 27℃DB/19℃WB;Outdoor temperature:35℃DB/24℃WB.;
2. Heating Capacity:Indoor temperature 20℃DB;Outdoor temperature:7℃DB/6℃WB.;
3. Piping Length:Equivalent piping length:7.5m,level difference:0m;
4. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditons ;
5. The above designs and specifications are subject to change of product improvement without prior notice.


Model	Outdoor		GRV14P3T3/4	GRV16P3T3/4	GRV18P3T3/4
Capacity	Cooling	kW	40.0	45.0	50.4
	Heating	kW	45.0	50.0	55.5
Electric Data	Power Supply	V~,Hz,Ph	380~415,50,3	380~415,50,3	380~415,50,3
	Cooling Power Input	kW	11.3	12.9	14.3
	Heating Power Input	kW	11.2	12.8	15.0
	Cooling Current	A	18.7	21.1	23.3
	Heating Current	A	16.9	19.5	22.8
Performance	Air Flow Volume	m ³ /h	7250x2	7500x2	7500x2
	Noise Level	dB(A)	47-61	47-61	47-61
Piping Limite	Vertical Pipe Length	m	90	90	90
	Actual Pipe Length	m	165	165	165
	Equivalent Pipe Length	m	190	190	190
	Total Pipe length	m	1000	1000	1000
Max. No. of Indoor Units		unit	16	20	23
Connection Ratio		%	50~130	50~130	50~130
Dimension(WxDxH)	Net	mm	1340x765x1680	1340x765x1680	1340x765x1680
	Packing	mm	1400x810x1850	1400x810x1850	1400x810x1850
Weight	Net	kg	303	303	318
	Gross	kg	325	325	340
Refrigerant Type			R410a	R410a	R410a
Pipe Diameter	Liquid Side	mm	12.7(1/2)	12.7(1/2)	12.7(1/2)
	Gas Side	mm	28.6(9/8)	28.6(9/8)	28.6(9/8)
Operation Range	Cooling	℃	-15℃~52℃	-15℃~52℃	-15℃~52℃
	Heating	℃	-20℃~24℃	-20℃~24℃	-20℃~24℃
Stuffing Quantity	20/40/40H	unit	11/22/22	11/22/22	11/22/22

Notes:

1. Cooling Capacity: Indoor temperature 27℃DB/19℃WB;Outdoor temperature:35℃DB/24℃WB.;
2. Heating Capacity:Indoor temperature 20℃DB;Outdoor temperature:7℃DB/6℃WB.;
3. Piping Length:Equivalent piping length:7.5m,level differnce:0m;
4. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditons ;
5. The above designs and specifications are subject to change of product improvement without prior notice.



3.Dimensions

3.1 8/10/12 HP



3.2 14/16/18HP






Notes:

1. Ensure necessary installation and maintenance space, and modules of the same system must be placed at the same height (see the following diagram).
2. If two rows of outdoor units, we suggest face to face, because easy to maintenance; no air short circuit.


4. Refrigeration cycle diagram

4.1 Piping diagrams


8/10/12 HP




8/10/12 HP



14/16/18 HP



14/16/18 HP




4.2 Refrigerant circuit

8/10/12 HP		
Code	Component name	Main function
1	DC inverter compressor	Driving module from unit electrical box will control the DC inverter compressor operation, compressor work frequency range is 20~100Hz.
2	DC inverter compressor exhaust temperature sensor	Protect DC inverter compressor. Through check the DC inverter compressor exhaust air temperature to control compressor speed and bypass electromagnetic valve work.
3	DC inverter compressor separator (Gas, oil)	Separate lubricating oil from compressor exhaust air. The lubricating oil will remain in the separator bottom.
4	One-way valve	When the unit stop, avoid the exhaust air suck back to DC inverter compressor
5	Filter	Filter lubricating oil impurities , avoid oil return capillary block.
6	DC inverter compressor oil return electromagnetic valve	Start before DC inverter compressor work, take lubricating oil back to inverter compressor.
7	Oil return capillary	Take the oil which deposited in the bottom of oil-gas separator to DC inverter compressor gas return pipe and control the oil return speed.
8	Filter	Filter lubricating oil impurities.
9	Gas bypass electromagnetic valve	Start before model work and after model stop, balance high/low pressure; Start when the compressor with high exhaust air temperature to reduce it.
10	High pressure switch	When the system pressure exceed the switch setting value, the switch will stop unit for protect system.
11	4-way valve	When the heating/cooling mode switch, change the refrigerant flow direction.
12	Condenser	Heat exchange, made the high temperature, pressure refrigerant (gas state) to liquid in cooling mode and the low temperature, pressure refrigerant (gas, liquid complex state)
13	Outdoor unit fan and fan motor	Force outdoor room air blow to condenser , make heat exchange to cooling or heating refrigerant. Fan motor have high, middle , low, three speeds.
14	Defrost control temperature sensor	Control the defrosting mode.
15	Ambient temperature sensor	Check the ambient temperature, control the outdoor fan speed, defrost with other temperature sensor.
16	One way valve	Avoid the exhaust air return to fix speed compressor when the unit stop.
17	Heating mode EXV	Throttling in heating mode
18	Subcooling mode EXV	Step through the valve adjusting control super-cooling degree within target values
19	Plate heat exchanger	Improve the cooling liquid refrigerant super-cooling degree
20	Total fluid pipe temperature sensor	Check the condenser middle position temperature, avoid the condensertemperature overheat in cooling mode.
21	liquid pipe stop valve	Cut off indoor and outdoor side refrigerant flow.
22	Gas pipe stop valve	Cut off indoor and outdoor side refrigerant flow.
23	Fliter	Filter lubricating oil, avoid oil return capillary block.
24	Whole suction temperature sensor	Work with defrosting temperature sensor to adjust EXV opening degree.
25	gas-liquid separator	Separate the liquid refrigerant from return gas, avoid it flow back to compressor, take the remained lubricating oil return to DC inverter compressor.
26	Low pressur e switch	When the system pressure less than switch setting value, the switch will stop unit for protect system.
27	High pressure sensor	Check system high pressure
28	Low pressure sensor	Check system low pressure


14/16/18 HP		
Code	Component name	Main function
1	DC inverter compressor	Driving module from unit electrical box will control the DC inverter compressor operation, compressor work frequency range is 30~90Hz.
2	DC inverter compressor exhaust temperature sensor	Protect DC inverter compressor. Through check the DC inverter compressor exhaust air temperature to control compressor speed and bypass electromagnetic valve work.
3	DC inverter compressor separator (Gas, oil)	Separate lubricating oil from compressor exhaust air. The lubricating oil will remain in the separator bottom.
4	Filter	Filter lubricating oil impurities, avoid oil return capillary block.
5	DC inverter compressor oil return electromagnetic valve	Start before DC inverter compressor work, take lubricating oil back to inverter compressor.
6	Oil return capillary	Take the oil which deposited in the bottom of oil-gas separator to DC inverter compressor gas return pipe and control the oil return speed.
7	Filter	Filter lubricating oil, avoid oil return cross capillary block.
8	Gas bypass solenoid valve	The valve will open before unit start and after unit stop, to balance system pressure; When the DC inverter or fix compressor discharge overheat, the valve will open to reduce discharge temperature.
9	Fix speed compressor	When the DC inverter compressor capacity can't meet indoor units requirement increased, fix speed compressor will start to assist it, otherwise will not.
10	Fix speed compressor exhaust temperature sensor	Protect compressor. Through check the fix speed compressor exhaust air temperature to control compressor and bypass electromagnetic valve work.
11	Fix speed compressor oil return electromagnetic valve	Start before fix speed compressor work, take lubricating oil back to fix speed compressor.
12	Oil return cross capillary	Take the oil which deposited in the bottom of oil-gas separator to fix speed compressor gas return pipe and control the oil return speed.
13	High pressure switch	When the system pressure exceed the switch setting value, the switch will stop unit for protect system.
14	One-way valve	Avoid the exhaust air return to gas-liquid separator
15	4-way valve	When the heating/cooling mode switch, change the refrigerant flow direction.
16	Condenser	Heat exchange, made the high temperature, pressure refrigerant (gas state) to liquid in cooling mode and the low temperature, pressure refrigerant (gas, liquid complex state)
17	Outdoor unit fan and fan motor	Force outdoor room air blow to condenser, make heat exchange to cooling or heating refrigerant. Fan motor have high, middle, low, three speeds.
18	Defrost control temperature sensor	Control the defrosting mode.
19	Ambient temperature sensor	Check the ambient temperature, control the outdoor fan speed, defrost with other temperature sensor.
20	One-way valve	In heating mode, force the refrigerant flow to heating mode EXV
21	Heating mode EXV	Throttling in heating mode
22	Subcooling mode EXV	Step through the valve adjusting control super-cooling degree within target values
23	Plate heat exchanger	Improve the cooling liquid refrigerant super-cooling degree
24	Filter	Filter lubricating oil, avoid oil return cross capillary block.
25	Total fluid pipe temperature sensor	Check the condenser middle position temperature, avoid the condensertemperature overheat in cooling mode.
26	liquid pipe stop valve	Cut off indoor and outdoor side refrigerant flow.
27	Gas pipe stop valve	Cut off indoor and outdoor side refrigerant gas circulation.
28	Filter	Filter lubricating oil, avoid oil return cross capillary block.
29	Whole suction temperature sensor	Work with defrosting temperature sensor to adjust EXV opening degree.
30	Low pressure switch	When the system pressure less than switch setting value, the switch will stop unit for protect system.
31	gas-liquid separator	Separate lubricating oil from compressor exhaust air. The lubricating oil will remain in the separator bottom.
32	High pressure sensor	Check system high pressure
33	Low pressure sensor	Check system low pressure

4.3 Function Layout
8/10/12 HP


Plan




Front view



14/16/18 HP
Plan




Front view




4.4 Piping diagrams Refrigerant flow direction for each operation mode

8/10/12 HP

Cooling operation/refrigeration oil return operation /heating oil return operation/defrost operation




Heating operation




14/16/18 HP

Cooling operation/refrigeration oil return operation /heating oil return operation




Heating operation/defrost operation




5. Wire Diagrams

8/10/12 HP



Electric connection diagram outdoor unit 16A37010000200


14/16/18 HP




Electric connection diagram outdoor unit 164.37010000201

Fielding wiring

outdoor units wiring diagram




outdoor and indoor unit communication wiring diagram



Recommended cable


model	power	Cable size (mm ²)	Cable length (m)	Circuit breaker Rated current (A)	Leakage circuit breaker	Ground wire (mm ²)
8 HP	380V 3N ~ 50Hz	10	20	32	40A,30mA,0.1s	6
10 HP		10	20	32	40A,30mA,0.1s	6
12 HP		10	20	32	40A,30mA,0.1s	6
14 HP		16	20	50	63A,30mA,0.1s	16
16 HP		16	20	50	63A,30mA,0.1s	16
18 HP		16	20	50	63A,30mA,0.1s	16




6.Capacity Tables

6.1 Operation limits

Cooling mode



Heating mode



6.2 Capacity index table

Allowable combinations are indicated in indoor unit combination total capacity index table.

In general, outdoor unit can be selected as follows though the location of the unit, zoning and usage of the rooms may be considered. The indoor and outdoor unit combination is determined that the sum of indoor unit capacity index is nearest to and smaller than the capacity index at 100% combination ratio of each outdoor unit. Up to 8~16 indoor units can be connected to one outdoor unit. It is recommended to choose a larger outdoor unit if the installation space is large enough.

If the combination ratio is greater than 100%, the indoor unit selection shall be reviewed by using actual capacity of each indoor unit.

INDOOR UNIT COMBINATION TOTAL CAPACITY INDEX TABLE

Outdoor Unit	Indoor Unit Combination Ratio (kW)								
	130%	120%	110%	100%	90%	80%	70%	60%	50%
8HP	32.8	30.2	27.7	25.2	22.7	20.1	17.6	15.1	12.6
10HP	36.4	33.6	30.8	28.0	25.2	22.4	19.6	16.8	14.0
12HP	43.6	40.2	36.9	33.5	30.2	26.8	23.5	20.2	16.8
14HP	52.0	48.0	44.0	40.0	36.0	32.0	28.0	24.0	20.0
16HP	58.5	54.0	49.5	45.0	40.5	36.0	31.5	27.0	22.5
18HP	69.2	63.8	58.5	53.2	47.9	42.6	37.2	31.9	26.6
20HP	72.8	67.2	61.6	56.0	50.4	44.8	39.2	33.6	28.0
22HP	80.0	73.8	67.7	61.5	55.4	49.2	43.1	36.9	30.8
24HP	88.4	81.6	74.8	68.0	61.2	54.4	47.6	40.8	34.0
26HP	94.9	87.6	80.3	73.0	65.7	58.4	51.1	43.8	36.5
28HP	102.1	94.2	86.4	78.5	70.7	62.8	55.0	47.1	39.3
30HP	110.5	102.0	93.5	85.0	76.5	68.0	59.5	51.0	42.5
32HP	117.0	108.0	99.0	90.0	81.0	72.0	63.0	54.0	45.0
34HP	124.8	115.2	105.6	96.0	86.4	76.8	67.2	57.6	48.0
36HP	131.3	121.2	111.1	101.0	90.9	80.8	70.7	60.6	50.5
38HP	138.5	127.8	117.2	106.5	95.9	85.2	74.6	63.9	53.3
40HP	146.9	135.6	124.3	113.0	101.7	90.4	79.1	67.8	56.5
42HP	153.4	141.6	129.8	118.0	106.2	94.4	82.6	70.8	59.0
44HP	160.6	148.2	135.9	123.5	111.2	98.8	86.5	74.1	61.8
46HP	169.0	156.0	143.0	130.0	117.0	104.0	91.0	78.0	65.0
48HP	175.5	162.0	148.5	135.0	121.5	108.0	94.5	81.0	67.5
50HP	186.2	171.8	157.5	143.2	128.9	114.6	100.2	85.9	71.6
52HP	189.8	175.2	160.6	146.0	131.4	116.8	102.2	87.6	73.0
54HP	197.0	181.8	166.7	151.5	136.4	121.2	106.1	90.9	75.8
56HP	205.4	189.6	173.8	158.0	142.2	126.4	110.6	94.8	79.0
58HP	211.9	195.6	179.3	163.0	146.7	130.4	114.1	97.8	81.5
60HP	219.1	202.2	185.4	168.5	151.7	134.8	118.0	101.1	84.3
62HP	227.5	210.0	192.5	175.0	157.5	140.0	122.5	105.0	87.5
64HP	234.0	216.0	198.0	180.0	162.0	144.0	126.0	108.0	90.0
66HP	241.02	222.48	203.94	185.4	166.86	148.32	129.78	111.24	92.7
68HP	248.04	228.96	209.88	190.8	171.72	152.64	133.56	114.48	95.4
70HP	255.06	235.44	215.82	196.2	176.58	156.96	137.34	117.72	98.1
72HP	262.08	241.92	221.76	201.6	181.44	161.28	141.12	120.96	100.8

6.3 Cooling Capacity table
8 HP

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	10	19.1	2.00	22.6	2.49	26.0	2.99	27.6	3.24	29.2	3.49	29.9	3.50	30.5	3.54
	12	19.1	2.04	22.6	2.54	26.0	3.04	27.6	3.30	29.2	3.56	29.9	3.57	30.5	3.60
	14	19.1	2.08	22.6	2.59	26.0	3.10	27.6	3.36	29.2	3.62	29.9	3.63	30.5	3.67
	16	19.1	2.11	22.6	2.63	26.0	3.15	27.6	3.42	29.2	3.69	29.9	3.70	30.5	3.73
	18	19.1	2.15	22.6	2.68	26.0	3.21	27.6	3.48	29.2	3.75	29.9	3.76	30.5	3.80
	19	19.1	2.19	22.6	2.73	26.0	3.26	27.6	3.54	29.2	3.82	29.9	3.83	30.5	3.86
	21	19.1	2.35	22.6	2.92	26.0	3.50	27.6	3.79	29.2	4.09	29.9	4.10	30.5	4.14
	23	19.1	2.51	22.6	3.13	26.0	3.75	27.6	4.06	29.2	4.38	29.9	4.40	30.5	4.44
	25	19.1	2.69	22.6	3.35	26.0	4.01	27.6	4.35	29.2	4.69	29.9	4.70	30.5	4.75
	27	19.1	2.87	22.6	3.58	26.0	4.29	27.6	4.65	29.2	5.01	29.9	5.03	30.5	5.08
	29	19.1	3.07	22.6	3.82	26.0	4.58	27.6	4.96	29.2	5.35	29.9	5.37	30.5	5.42
	31	19.1	3.27	22.6	4.08	26.0	4.88	27.6	5.29	29.2	5.71	29.9	5.72	30.5	5.78
	33	19.1	3.49	22.6	4.34	26.0	5.20	27.6	5.64	29.2	6.08	29.9	6.10	30.5	6.16
	35	19.1	3.71	22.6	4.62	26.0	5.53	27.6	6.00	29.2	6.47	29.9	6.49	30.5	6.55
	37	19.1	3.94	22.6	4.91	26.0	5.88	27.6	6.38	29.2	6.88	29.9	6.90	30.5	6.97
	39	19.1	3.96	22.6	4.93	26.0	5.91	27.6	6.41	29.2	6.91	29.9	6.93	30.5	7.00
	41	18.7	3.98	21.3	4.96	25.2	5.94	26.4	6.44	28.3	6.94	28.3	6.96	30.5	7.03
	43	18.7	4.00	21.3	4.98	25.2	5.96	26.4	6.47	28.3	6.97	28.3	6.99	30.5	7.06
	46	17.5	4.02	20.4	5.00	24.3	5.99	25.2	6.50	27.1	7.00	27.1	7.03	29.3	7.09
	48	17.5	4.03	20.4	5.03	24.3	6.02	25.2	6.53	27.1	7.04	27.1	7.06	29.3	7.13
50	15.2	4.05	19.7	5.05	23.1	6.05	24.3	6.56	25.9	7.07	26.3	7.09	28.1	7.16	
52	15.2	4.13	19.7	5.10	23.1	6.09	24.3	6.68	25.9	7.11	26.3	7.15	28.1	7.20	
120%	10	18.8	1.99	22.2	2.48	25.6	2.97	27.2	3.22	28.7	3.47	29.4	3.48	30.0	3.51
	12	18.8	2.03	22.2	2.52	25.6	3.02	27.2	3.28	28.7	3.53	29.4	3.54	30.0	3.58
	14	18.8	2.06	22.2	2.57	25.6	3.08	27.2	3.34	28.7	3.60	29.4	3.61	30.0	3.64
	16	18.8	2.10	22.2	2.62	25.6	3.13	27.2	3.40	28.7	3.66	29.4	3.67	30.0	3.71
	18	18.8	2.14	22.2	2.66	25.6	3.19	27.2	3.46	28.7	3.73	29.4	3.74	30.0	3.77
	19	18.8	2.17	22.2	2.71	25.6	3.24	27.2	3.52	28.7	3.79	29.4	3.80	30.0	3.84
	21	18.8	2.33	22.2	2.90	25.6	3.48	27.2	3.77	28.7	4.06	29.4	4.08	30.0	4.12
	23	18.8	2.50	22.2	3.11	25.6	3.72	27.2	4.04	28.7	4.35	29.4	4.37	30.0	4.41
	25	18.8	2.67	22.2	3.33	25.6	3.98	27.2	4.32	28.7	4.66	29.4	4.67	30.0	4.72
	27	18.8	2.85	22.2	3.56	25.6	4.26	27.2	4.62	28.7	4.98	29.4	4.99	30.0	5.04
	29	18.8	3.05	22.2	3.80	25.6	4.55	27.2	4.93	28.7	5.32	29.4	5.33	30.0	5.38
	31	18.8	3.25	22.2	4.05	25.6	4.85	27.2	5.26	28.7	5.67	29.4	5.69	30.0	5.74
	33	18.8	3.46	22.2	4.31	25.6	5.16	27.2	5.60	28.7	6.04	29.4	6.06	30.0	6.12
	35	18.8	3.68	22.2	4.59	25.6	5.49	27.2	5.96	28.7	6.42	29.4	6.44	30.0	6.51
	37	18.8	3.92	22.2	4.88	25.6	5.84	27.2	6.34	28.7	6.83	29.4	6.85	30.0	6.92

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	39	18.8	3.93	22.2	4.90	25.6	5.87	27.2	6.37	28.7	6.86	29.4	6.88	30.0	6.95
	41	18.8	3.95	22.2	4.92	25.6	5.90	27.2	6.39	28.7	6.89	29.4	6.91	30.0	6.98
	43	18.8	3.97	22.2	4.95	25.6	5.92	27.2	6.42	28.7	6.93	29.4	6.95	30.0	7.01
	46	17.5	3.99	21.3	4.97	24.2	5.95	26.5	6.45	27.3	6.96	28.1	6.98	29.2	7.05
	48	17.5	4.01	21.3	4.99	24.2	5.98	26.5	6.48	27.3	6.99	28.1	7.01	29.2	7.08
	50	15.9	4.03	20.1	5.02	23.4	6.01	25.2	6.51	26.5	7.02	27.3	7.04	28.3	7.11
	52	15.9	4.09	20.1	5.06	23.4	6.05	25.2	6.57	26.5	7.06	27.3	7.08	30.0	7.16
	110%	10	18.5	1.98	21.9	2.46	25.2	2.95	26.7	3.20	28.3	3.45	28.9	3.46	29.5
12		18.5	2.01	21.9	2.51	25.2	3.00	26.7	3.26	28.3	3.51	28.9	3.52	29.5	3.55
14		18.5	2.05	21.9	2.55	25.2	3.06	26.7	3.32	28.3	3.57	28.9	3.58	29.5	3.62
16		18.5	2.09	21.9	2.60	25.2	3.11	26.7	3.37	28.3	3.64	28.9	3.65	29.5	3.68
18		18.5	2.12	21.9	2.64	25.2	3.17	26.7	3.43	28.3	3.70	28.9	3.71	29.5	3.75
19		18.5	2.16	21.9	2.69	25.2	3.22	26.7	3.49	28.3	3.77	28.9	3.78	29.5	3.81
21		18.5	2.31	21.9	2.88	25.2	3.45	26.7	3.74	28.3	4.04	28.9	4.05	29.5	4.09
23		18.5	2.48	21.9	3.09	25.2	3.70	26.7	4.01	28.3	4.32	28.9	4.34	29.5	4.38
25		18.5	2.65	21.9	3.30	25.2	3.96	26.7	4.29	28.3	4.63	28.9	4.64	29.5	4.69
27		18.5	2.84	21.9	3.53	25.2	4.23	26.7	4.59	28.3	4.95	28.9	4.96	29.5	5.01
29		18.5	3.03	21.9	3.77	25.2	4.52	26.7	4.90	28.3	5.28	28.9	5.30	29.5	5.35
31		18.5	3.23	21.9	4.02	25.2	4.82	26.7	5.22	28.3	5.63	28.9	5.65	29.5	5.70
33		18.5	3.44	21.9	4.28	25.2	5.13	26.7	5.56	28.3	6.00	28.9	6.02	29.5	6.08
35		18.5	3.66	21.9	4.56	25.2	5.46	26.7	5.92	28.3	6.38	28.9	6.40	29.5	6.46
37		18.5	3.89	21.9	4.85	25.2	5.81	26.7	6.30	28.3	6.79	28.9	6.81	29.5	6.87
39		18.5	3.91	21.9	4.87	25.2	5.83	26.7	6.32	28.3	6.82	28.9	6.84	29.5	6.90
41	18.5	3.93	21.9	4.89	25.2	5.86	26.7	6.35	28.3	6.85	28.9	6.87	29.5	6.94	
43	18.5	3.94	21.9	4.91	25.2	5.88	26.7	6.38	28.3	6.88	28.9	6.90	29.5	6.97	
46	17.4	3.96	20.5	4.94	24.3	5.91	25.2	6.41	27.1	6.91	27.1	6.93	28.2	7.00	
48	17.4	3.98	20.5	4.96	24.3	5.94	25.2	6.44	27.1	6.94	27.1	6.96	28.2	7.03	
50	16.3	4.00	19.3	4.98	23.5	5.97	24.3	6.47	26.3	6.98	25.9	7.00	27.4	7.06	
52	16.3	4.03	19.3	5.02	23.5	6.03	24.3	6.51	26.3	7.02	25.9	7.06	27.4	7.10	
100%	10	17.5	1.96	20.6	2.44	23.8	2.93	25.2	3.18	26.7	3.42	27.2	3.43	27.8	3.47
	12	17.5	2.00	20.6	2.49	23.8	2.98	25.2	3.23	26.7	3.49	27.2	3.50	27.8	3.53
	14	17.5	2.03	20.6	2.54	23.8	3.04	25.2	3.29	26.7	3.55	27.2	3.56	27.8	3.60
	16	17.5	2.07	20.6	2.58	23.8	3.09	25.2	3.35	26.7	3.61	27.2	3.62	27.8	3.66
	18	17.5	2.11	20.6	2.63	23.8	3.14	25.2	3.41	26.7	3.68	27.2	3.69	27.8	3.72
	19	17.5	2.14	20.6	2.67	23.8	3.20	25.2	3.47	26.7	3.74	27.2	3.75	27.8	3.79
	21	17.5	2.30	20.6	2.86	23.8	3.43	25.2	3.72	26.7	4.01	27.2	4.02	27.8	4.06
	23	17.5	2.46	20.6	3.07	23.8	3.67	25.2	3.98	26.7	4.29	27.2	4.31	27.8	4.35
	25	17.5	2.63	20.6	3.28	23.8	3.93	25.2	4.26	26.7	4.60	27.2	4.61	27.8	4.65

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	27	17.5	2.82	20.6	3.51	23.8	4.20	25.2	4.56	26.7	4.91	27.2	4.93	27.8	4.98
	29	17.5	3.01	20.6	3.75	23.8	4.49	25.2	4.87	26.7	5.25	27.2	5.26	27.8	5.31
	31	17.5	3.21	20.6	4.00	23.8	4.78	25.2	5.19	26.7	5.59	27.2	5.61	27.8	5.67
	33	17.5	3.42	20.6	4.26	23.8	5.10	25.2	5.53	26.7	5.96	27.2	5.98	27.8	6.03
	35	17.5	3.63	20.6	4.53	23.8	5.42	25.2	5.80	26.7	6.34	27.2	6.36	27.8	6.42
	37	17.5	3.86	20.6	4.82	23.8	5.77	25.2	6.25	26.7	6.74	27.2	6.76	27.8	6.83
	39	17.5	3.88	20.6	4.84	23.8	5.79	25.2	6.28	26.7	6.77	27.2	6.79	27.8	6.86
	41	17.5	3.90	20.6	4.86	23.8	5.82	25.2	6.31	26.7	6.80	27.2	6.82	27.8	6.89
	43	17.5	3.92	20.6	4.88	23.8	5.84	25.2	6.34	26.7	6.83	27.2	6.85	27.8	6.92
	46	16.3	3.94	19.3	4.90	22.5	5.87	24.3	6.37	25.2	6.86	26.5	6.89	26.4	6.95
	48	16.3	3.95	19.3	4.93	22.5	5.90	24.3	6.40	25.2	6.90	26.5	6.92	26.4	6.98
	50	15.2	3.97	18.2	4.95	21.4	5.93	23.5	6.43	24.3	6.93	25.2	6.95	25.2	7.02
	52	15.2	4.00	18.2	4.98	21.4	5.97	23.5	6.48	24.3	6.99	25.2	7.00	25.2	7.08
	90%	10	15.7	1.67	18.5	2.08	21.4	2.49	22.7	2.70	24.0	2.91	24.5	2.92	25.0
12		15.7	1.70	18.5	2.12	21.4	2.54	22.7	2.75	24.0	2.97	24.5	2.98	25.0	3.01
14		15.7	1.73	18.5	2.16	21.4	2.58	22.7	2.80	24.0	3.02	24.5	3.03	25.0	3.06
16		15.7	1.76	18.5	2.20	21.4	2.63	22.7	2.85	24.0	3.08	24.5	3.09	25.0	3.12
18		15.7	1.79	18.5	2.24	21.4	2.68	22.7	2.90	24.0	3.13	24.5	3.14	25.0	3.17
19		15.7	1.83	18.5	2.27	21.4	2.72	22.7	2.95	24.0	3.18	24.5	3.19	25.0	3.22
21		15.7	1.96	18.5	2.44	21.4	2.92	22.7	3.17	24.0	3.41	24.5	3.42	25.0	3.46
23		15.7	2.10	18.5	2.61	21.4	3.13	22.7	3.39	24.0	3.66	24.5	3.67	25.0	3.70
25		15.7	2.24	18.5	2.79	21.4	3.35	22.7	3.63	24.0	3.91	24.5	3.92	25.0	3.96
27		15.7	2.40	18.5	2.99	21.4	3.58	22.7	3.88	24.0	4.18	24.5	4.20	25.0	4.24
29		15.7	2.56	18.5	3.19	21.4	3.82	22.7	4.14	24.0	4.47	24.5	4.48	25.0	4.52
31		15.7	2.73	18.5	3.40	21.4	4.07	22.7	4.42	24.0	4.76	24.5	4.78	25.0	4.82
33		15.7	2.91	18.5	3.62	21.4	4.34	22.7	4.71	24.0	5.07	24.5	5.09	25.0	5.14
35		15.7	3.09	18.5	3.85	21.4	4.62	22.7	5.01	24.0	5.40	24.5	5.41	25.0	5.47
37		15.7	3.29	18.5	4.10	21.4	4.91	22.7	5.32	24.0	5.74	24.5	5.76	25.0	5.81
39		15.7	3.30	18.5	4.12	21.4	4.93	22.7	5.35	24.0	5.76	24.5	5.78	25.0	5.84
41	15.7	3.32	18.5	4.14	21.4	4.95	22.7	5.37	24.0	5.79	24.5	5.81	25.0	5.86	
43	15.7	3.34	18.5	4.16	21.4	4.98	22.7	5.40	24.0	5.82	24.5	5.84	25.0	5.89	
46	14.6	3.35	17.3	4.17	20.4	5.00	21.3	5.42	23.1	5.84	23.1	5.86	24.1	5.92	
48	14.6	3.37	17.3	4.19	20.4	5.02	21.3	5.45	23.1	5.87	23.1	5.89	24.1	5.95	
50	13.2	3.38	16.5	4.21	19.2	5.05	20.5	5.47	20.9	5.90	22.4	5.92	22.8	5.97	
52	13.2	3.42	16.5	4.26	19.2	5.11	20.5	5.52	20.9	5.95	22.4	5.96	22.8	6.01	
80%	10	14.0	1.42	16.5	1.77	19.0	2.12	20.2	2.30	21.3	2.47	21.8	2.48	22.3	2.51
	12	14.0	1.44	16.5	1.80	19.0	2.16	20.2	2.34	21.3	2.52	21.8	2.53	22.3	2.55
	14	14.0	1.47	16.5	1.83	19.0	2.20	20.2	2.38	21.3	2.57	21.8	2.57	22.3	2.60

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	16	14.0	1.50	16.5	1.87	19.0	2.23	20.2	2.42	21.3	2.61	21.8	2.62	22.3	2.65
	18	14.0	1.52	16.5	1.90	19.0	2.27	20.2	2.47	21.3	2.66	21.8	2.67	22.3	2.69
	19	14.0	1.55	16.5	1.93	19.0	2.31	20.2	2.51	21.3	2.70	21.8	2.71	22.3	2.74
	21	14.0	1.66	16.5	2.07	19.0	2.48	20.2	2.69	21.3	2.90	21.8	2.91	22.3	2.94
	23	14.0	1.78	16.5	2.22	19.0	2.66	20.2	2.88	21.3	3.10	21.8	3.11	22.3	3.14
	25	14.0	1.90	16.5	2.37	19.0	2.84	20.2	3.08	21.3	3.32	21.8	3.33	22.3	3.37
	27	14.0	2.04	16.5	2.54	19.0	3.04	20.2	3.29	21.3	3.55	21.8	3.56	22.3	3.60
	29	14.0	2.17	16.5	2.71	19.0	3.24	20.2	3.52	21.3	3.79	21.8	3.80	22.3	3.84
	31	14.0	2.32	16.5	2.89	19.0	3.46	20.2	3.75	21.3	4.04	21.8	4.06	22.3	4.10
	33	14.0	2.47	16.5	3.08	19.0	3.68	20.2	4.00	21.3	4.31	21.8	4.32	22.3	4.36
	35	14.0	2.63	16.5	3.27	19.0	3.92	20.2	4.25	21.3	4.58	21.8	4.60	22.3	4.64
	37	14.0	2.79	16.5	3.48	19.0	4.17	20.2	4.52	21.3	4.87	21.8	4.89	22.3	4.94
	39	14.0	2.81	16.5	3.50	19.0	4.19	20.2	4.54	21.3	4.90	21.8	4.91	22.3	4.96
	41	14.0	2.82	16.5	3.51	19.0	4.21	20.2	4.56	21.3	4.92	21.8	4.93	22.3	4.98
	43	14.0	2.83	16.5	3.53	19.0	4.23	20.2	4.58	21.3	4.94	21.8	4.96	22.3	5.00
	46	13.2	2.85	15.3	3.55	18.1	4.24	19.1	4.60	20.2	4.96	20.5	4.98	21.1	5.03
	48	13.2	2.86	15.3	3.56	18.1	4.26	19.1	4.63	20.2	4.99	20.5	5.00	21.1	5.05
	50	12.1	2.87	14.2	3.58	16.8	4.28	18.3	4.65	19.0	5.01	19.3	5.02	20.0	5.07
	52	12.1	2.92	14.2	3.62	16.8	4.33	18.3	4.69	19.0	5.06	19.3	5.05	20.0	5.10
	70%	10	12.2	1.17	14.4	1.46	16.6	1.75	17.6	1.90	18.7	2.05	19.1	2.05	19.5
12		12.2	1.20	14.4	1.49	16.6	1.78	17.6	1.93	18.7	2.08	19.1	2.09	19.5	2.11
14		12.2	1.22	14.4	1.52	16.6	1.82	17.6	1.97	18.7	2.12	19.1	2.13	19.5	2.15
16		12.2	1.24	14.4	1.54	16.6	1.85	17.6	2.00	18.7	2.16	19.1	2.17	19.5	2.19
18		12.2	1.26	14.4	1.57	16.6	1.88	17.6	2.04	18.7	2.20	19.1	2.21	19.5	2.23
19		12.2	1.28	14.4	1.60	16.6	1.91	17.6	2.07	18.7	2.24	19.1	2.24	19.5	2.27
21		12.2	1.37	14.4	1.71	16.6	2.05	17.6	2.22	18.7	2.40	19.1	2.40	19.5	2.43
23		12.2	1.47	14.4	1.83	16.6	2.20	17.6	2.38	18.7	2.57	19.1	2.58	19.5	2.60
25		12.2	1.58	14.4	1.96	16.6	2.35	17.6	2.55	18.7	2.75	19.1	2.76	19.5	2.78
27		12.2	1.68	14.4	2.10	16.6	2.51	17.6	2.73	18.7	2.94	19.1	2.95	19.5	2.98
29		12.2	1.80	14.4	2.24	16.6	2.68	17.6	2.91	18.7	3.14	19.1	3.15	19.5	3.18
31		12.2	1.92	14.4	2.39	16.6	2.86	17.6	3.10	18.7	3.35	19.1	3.36	19.5	3.39
33		12.2	2.04	14.4	2.55	16.6	3.05	17.6	3.31	18.7	3.56	19.1	3.57	19.5	3.61
35		12.2	2.17	14.4	2.71	16.6	3.24	17.6	3.52	18.7	3.79	19.1	3.80	19.5	3.84
37		12.2	2.31	14.4	2.88	16.6	3.45	17.6	3.74	18.7	4.03	19.1	4.04	19.5	4.08
39		12.2	2.32	14.4	2.89	16.6	3.46	17.6	3.76	18.7	4.05	19.1	4.06	19.5	4.10
41	12.2	2.33	14.4	2.91	16.6	3.48	17.6	3.77	18.7	4.07	19.1	4.08	19.5	4.12	
43	12.2	2.34	14.4	2.92	16.6	3.49	17.6	3.79	18.7	4.09	19.1	4.10	19.5	4.14	
46	11.3	2.35	13.2	2.93	15.3	3.51	16.4	3.81	17.8	4.11	18.0	4.12	18.2	4.16	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
48	48	11.3	2.36	13.2	2.95	15.3	3.53	16.4	3.83	17.8	4.12	18.0	4.14	18.2	4.18
	50	10.5	2.38	12.5	2.96	14.5	3.54	15.2	3.84	16.4	4.14	16.8	4.16	17.0	4.20
	52	10.5	2.42	12.5	3.01	14.5	3.58	15.2	3.86	16.4	4.17	16.8	4.20	17.0	4.23
60%	10	10.5	0.96	12.4	1.19	14.3	1.43	15.1	1.55	16.0	1.67	16.3	1.67	16.7	1.69
	12	10.5	0.97	12.4	1.21	14.3	1.45	15.1	1.58	16.0	1.70	16.3	1.71	16.7	1.72
	14	10.5	0.99	12.4	1.24	14.3	1.48	15.1	1.61	16.0	1.73	16.3	1.74	16.7	1.75
	16	10.5	1.01	12.4	1.26	14.3	1.51	15.1	1.63	16.0	1.76	16.3	1.77	16.7	1.78
	18	10.5	1.03	12.4	1.28	14.3	1.53	15.1	1.66	16.0	1.79	16.3	1.80	16.7	1.82
	19	10.5	1.05	12.4	1.30	14.3	1.56	15.1	1.69	16.0	1.82	16.3	1.83	16.7	1.85
	21	10.5	1.12	12.4	1.40	14.3	1.67	15.1	1.81	16.0	1.96	16.3	1.96	16.7	1.98
	23	10.5	1.20	12.4	1.50	14.3	1.79	15.1	1.94	16.0	2.09	16.3	2.10	16.7	2.12
	25	10.5	1.29	12.4	1.60	14.3	1.92	15.1	2.08	16.0	2.24	16.3	2.25	16.7	2.27
	27	10.5	1.37	12.4	1.71	14.3	2.05	15.1	2.22	16.0	2.40	16.3	2.40	16.7	2.43
	29	10.5	1.47	12.4	1.83	14.3	2.19	15.1	2.37	16.0	2.56	16.3	2.57	16.7	2.59
	31	10.5	1.56	12.4	1.95	14.3	2.33	15.1	2.53	16.0	2.73	16.3	2.74	16.7	2.76
	33	10.5	1.67	12.4	2.08	14.3	2.49	15.1	2.70	16.0	2.91	16.3	2.92	16.7	2.94
	35	10.5	1.77	12.4	2.21	14.3	2.64	15.1	2.87	16.0	3.09	16.3	3.10	16.7	3.13
	37	10.5	1.89	12.4	2.35	14.3	2.81	15.1	3.05	16.0	3.29	16.3	3.30	16.7	3.33
	39	10.5	1.89	12.4	2.36	14.3	2.82	15.1	3.06	16.0	3.30	16.3	3.31	16.7	3.35
	41	10.5	1.90	12.4	2.37	14.3	2.84	15.1	3.08	16.0	3.32	16.3	3.33	16.7	3.36
	43	10.5	1.91	12.4	2.38	14.3	2.85	15.1	3.09	16.0	3.33	16.3	3.34	16.7	3.38
	46	9.3	1.92	11.2	2.39	13.1	2.86	14.2	3.11	14.9	3.35	15.2	3.36	15.3	3.39
	48	9.3	1.93	11.2	2.40	13.1	2.88	14.5	3.12	14.9	3.36	15.2	3.37	15.3	3.41
50	8.2	1.94	10.3	2.41	11.9	2.89	13.0	3.14	13.5	3.38	13.9	3.39	14.0	3.42	
52	8.2	1.99	10.3	2.45	11.9	2.93	13.0	3.17	13.5	3.41	13.9	3.42	14.0	3.45	
50%	10	8.7	0.76	10.3	0.95	11.9	1.14	12.6	1.23	13.3	1.33	13.6	1.33	13.9	1.35
	12	8.7	0.78	10.3	0.97	11.9	1.16	12.6	1.26	13.3	1.35	13.6	1.36	13.9	1.37
	14	8.7	0.79	10.3	0.99	11.9	1.18	12.6	1.28	13.3	1.38	13.6	1.38	13.9	1.40
	16	8.7	0.80	10.3	1.00	11.9	1.20	12.6	1.30	13.3	1.40	13.6	1.41	13.9	1.42
	18	8.7	0.82	10.3	1.02	11.9	1.22	12.6	1.32	13.3	1.43	13.6	1.43	13.9	1.45
	19	8.7	0.83	10.3	1.04	11.9	1.24	12.6	1.35	13.3	1.45	13.6	1.46	13.9	1.47
	21	8.7	0.89	10.3	1.11	11.9	1.33	12.6	1.44	13.3	1.56	13.6	1.56	13.9	1.58
	23	8.7	0.96	10.3	1.19	11.9	1.43	12.6	1.55	13.3	1.67	13.6	1.67	13.9	1.69
	25	8.7	1.02	10.3	1.28	11.9	1.53	12.6	1.66	13.3	1.79	13.6	1.79	13.9	1.81
	27	8.7	1.09	10.3	1.36	11.9	1.63	12.6	1.77	13.3	1.91	13.6	1.91	13.9	1.93
	29	8.7	1.17	10.3	1.46	11.9	1.74	12.6	1.89	13.3	2.04	13.6	2.04	13.9	2.06
	31	8.7	1.25	10.3	1.55	11.9	1.86	12.6	2.02	13.3	2.17	13.6	2.18	13.9	2.20
	33	8.7	1.33	10.3	1.65	11.9	1.98	12.6	2.15	13.3	2.31	13.6	2.32	13.9	2.34

GREEN-GRV 4 Outdoor unit

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
35	8.7	1.41	10.3	1.76	11.9	2.11	12.6	2.28	13.3	2.46	13.6	2.47	13.9	2.49	
37	8.7	1.50	10.3	1.87	11.9	2.24	12.6	2.43	13.3	2.62	13.6	2.63	13.9	2.65	
39	8.7	1.51	10.3	1.88	11.9	2.25	12.6	2.44	13.3	2.63	13.6	2.64	13.9	2.66	
41	8.7	1.51	10.3	1.89	11.9	2.26	12.6	2.45	13.3	2.64	13.6	2.65	13.9	2.68	
43	8.7	1.52	10.3	1.90	11.9	2.27	12.6	2.46	13.3	2.65	13.6	2.66	13.9	2.69	
46	7.3	1.53	9.2	1.90	10.5	2.28	11.3	2.47	12.1	2.67	12.3	2.68	12.5	2.70	
48	7.3	1.54	9.2	1.91	10.5	2.29	11.3	2.49	12.1	2.68	12.3	2.69	12.5	2.71	
50	6.1	1.54	8.0	1.92	9.2	2.30	10.0	2.50	11.0	2.69	11.2	2.70	11.4	2.73	
52	6.1	1.58	8.0	1.96	9.2	2.35	10.0	2.56	11.0	2.74	11.2	2.76	11.4	2.80	

10 HP

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	10	24.6	3.32	29.3	4.05	34.0	4.82	35.3	4.93	35.7	4.83	36.6	4.63	37.5	4.41
	12	24.6	3.38	29.3	4.13	34.0	4.92	34.8	4.90	35.3	4.80	36.1	4.59	37.0	4.52
	14	24.6	3.44	29.3	4.21	33.9	4.98	34.4	4.88	34.8	4.77	35.7	4.73	36.6	4.78
	16	24.6	3.50	29.3	4.30	33.5	4.96	33.9	4.92	34.3	4.94	35.2	4.99	36.1	5.03
	18	24.6	3.57	29.3	4.38	33.0	5.14	33.4	5.17	33.9	5.20	34.8	5.25	35.7	5.30
	19	24.6	3.65	29.3	4.67	32.5	5.39	33.0	5.42	33.4	5.45	34.3	5.50	35.2	5.56
	21	24.6	3.74	29.3	4.83	32.3	5.52	32.8	5.55	33.2	5.58	34.1	5.64	35.0	5.68
	23	24.6	4.02	29.3	5.18	31.9	5.77	32.3	5.80	32.7	5.83	33.6	5.89	34.5	5.95
	25	24.6	4.29	29.3	5.55	31.4	6.02	31.9	6.05	32.3	6.09	33.2	6.15	34.1	6.21
	27	24.6	4.58	29.3	5.94	31.0	6.31	31.4	6.31	31.8	6.34	32.7	6.41	33.6	6.48
	29	24.6	4.89	29.3	6.34	30.5	6.53	30.9	6.57	31.4	6.61	32.3	6.67	33.2	6.74
	31	24.6	5.22	29.2	6.71	30.0	6.79	30.5	6.81	30.9	6.86	31.8	6.94	32.7	7.01
	33	24.6	5.56	28.7	6.96	29.6	7.03	30.0	7.08	30.5	7.12	31.4	7.20	32.2	7.28
	35	24.6	5.93	28.2	7.22	29.1	7.30	29.6	7.34	30.0	7.38	30.9	7.47	31.8	7.55
	37	24.6	6.31	27.8	7.48	28.7	7.57	29.1	7.60	29.6	7.65	30.4	7.74	31.3	7.83
	39	24.6	6.71	27.3	7.73	28.2	7.82	28.7	7.87	29.1	7.92	30.0	8.00	30.9	8.01
	41	23.8	7.04	26.9	8.10	27.7	8.16	28.3	8.20	28.3	8.35	30.0	8.38	29.8	8.61
	43	23.8	7.50	26.9	8.46	27.7	8.52	28.3	8.59	28.3	8.54	29.6	8.51	29.8	8.65
46	22.4	7.26	26.9	8.23	25.5	8.30	26.0	8.35	26.0	8.58	28.7	8.60	28.3	8.69	
48	22.4	6.80	25.8	7.76	25.5	7.81	26.0	7.89	26.0	8.62	26.7	8.64	27.5	8.73	
50	21.0	6.35	23.8	7.35	23.8	7.46	24.1	7.58	24.1	8.66	25.4	8.68	27.5	8.77	
52	21.0	5.94	23.8	7.01	23.8	7.12	24.1	7.20	24.1	8.76	24.3	8.75	26.8	8.84	
120%	10	22.7	3.03	27.0	3.70	31.4	4.39	33.6	4.75	35.2	4.76	36.0	4.76	36.8	4.58
	12	22.7	3.08	27.0	3.76	31.4	4.48	33.6	4.84	34.7	4.85	35.5	4.80	36.3	4.55

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	14	22.7	3.14	27.0	3.84	31.4	4.57	33.6	4.94	34.2	4.90	35.1	4.83	35.9	4.74
	16	22.7	3.20	27.0	3.92	31.4	4.66	33.4	4.98	33.8	4.96	34.6	4.96	35.4	5.00
	18	22.7	3.26	27.0	4.00	31.4	4.82	32.9	5.14	33.3	5.16	34.1	5.21	35.0	5.26
	19	22.7	3.33	27.0	4.15	31.4	5.18	32.5	5.39	32.9	5.41	33.7	5.46	34.5	5.51
	21	22.7	3.36	27.0	4.30	31.4	5.36	32.2	5.52	32.6	5.54	33.5	5.59	34.3	5.65
	23	22.7	3.59	27.0	4.61	31.4	5.74	31.8	5.76	32.2	5.79	33.0	5.85	33.8	5.90
	25	22.7	3.83	27.0	4.93	30.9	5.99	31.8	6.01	31.7	6.04	32.6	6.10	33.4	6.16
	27	22.7	4.09	27.0	5.27	30.5	6.24	30.9	6.28	31.3	6.31	32.1	6.36	32.9	6.42
	29	22.7	4.37	27.0	5.63	30.0	6.49	30.4	6.53	30.8	6.56	31.6	6.63	32.5	6.68
	31	22.7	4.66	27.0	6.00	29.6	6.75	30.0	6.78	30.4	6.82	31.2	6.89	32.0	6.95
	33	22.7	4.96	27.0	6.41	29.1	7.00	29.5	7.04	29.9	7.07	30.7	7.15	31.5	7.22
	35	22.7	5.28	27.0	6.83	28.6	7.26	29.0	7.29	29.5	7.33	30.3	7.41	31.1	7.49
	37	22.7	5.62	27.0	7.28	28.2	7.52	28.6	7.56	29.0	7.60	29.8	7.67	30.6	7.76
	39	22.7	5.98	27.0	7.68	27.7	7.77	28.1	7.82	28.5	7.86	29.4	7.94	30.2	8.02
	41	22.7	6.05	27.0	7.72	27.7	7.81	28.0	7.85	28.3	7.90	29.0	8.00	29.5	8.06
	43	22.7	6.05	27.0	7.78	26.4	7.86	27.5	7.90	27.8	7.96	28.6	8.05	29.1	8.12
	46	21.3	6.11	25.9	7.85	25.2	7.95	26.0	7.99	26.7	8.00	27.5	8.10	28.6	8.19
	48	21.3	6.13	25.9	7.89	25.2	8.00	26.0	8.06	26.7	8.06	27.5	8.16	28.6	8.25
	50	20.0	6.15	24.1	7.93	24.3	8.06	25.1	8.12	25.4	8.13	26.3	8.23	27.4	8.32
	52	20.0	6.20	24.1	7.96	24.3	8.11	25.1	8.16	25.4	8.20	26.3	8.27	27.4	8.37
110%	10	20.8	2.75	24.8	3.35	28.8	3.98	30.8	4.30	32.8	4.63	35.3	4.91	36.1	4.74
	12	20.8	2.80	24.8	3.41	28.8	4.05	30.8	4.38	32.8	4.71	34.9	4.89	35.6	4.75
	14	20.8	2.85	24.8	3.47	28.8	4.13	30.8	4.46	32.8	4.80	34.4	4.90	35.2	4.75
	16	20.8	2.90	24.8	3.54	28.8	4.21	30.8	4.55	32.8	4.90	34.0	4.92	34.7	4.97
	18	20.8	2.96	24.8	3.61	28.8	4.30	30.8	4.68	32.8	5.13	33.5	5.17	34.3	5.22
	19	20.8	3.02	24.8	3.69	28.8	4.55	30.8	5.02	32.3	5.38	33.1	5.42	33.8	5.47
	21	20.8	3.05	24.8	3.79	28.8	4.71	30.8	5.21	32.1	5.51	32.8	5.55	33.6	5.60
	23	20.8	3.19	24.8	4.06	28.8	5.05	30.8	5.59	31.6	5.75	32.4	5.81	33.1	5.86
	25	20.8	3.40	24.8	4.35	28.8	5.40	30.8	5.98	31.2	6.00	31.9	6.06	32.7	6.11
	27	20.8	3.63	24.8	4.65	28.8	5.78	30.8	6.24	30.7	6.26	31.5	6.31	32.2	6.37
	29	20.8	3.87	24.8	4.96	28.8	6.18	29.9	6.49	30.3	6.52	31.0	6.58	31.8	6.63
	31	20.8	4.12	24.8	5.29	28.8	6.60	29.4	6.74	29.8	6.77	30.6	6.83	31.3	6.90
	33	20.8	4.38	24.8	5.64	28.8	6.95	29.0	6.99	29.4	7.02	30.1	7.09	30.9	7.16
	35	20.8	4.67	24.8	6.00	28.8	7.21	28.5	7.25	28.9	7.28	29.6	7.35	30.4	7.42
	37	20.8	4.97	24.8	6.39	27.7	7.47	28.1	7.50	28.4	7.54	29.2	7.61	29.9	7.58
	39	20.8	5.28	24.8	6.81	27.2	7.72	27.6	7.76	28.0	7.80	28.7	7.88	29.5	7.95
41	20.8	5.37	24.8	6.93	26.5	8.01	27.1	7.89	27.5	8.01	28.2	8.02	29.0	8.19	
43	20.8	5.42	24.8	7.01	26.5	8.19	26.5	8.05	27.0	8.19	27.5	8.26	28.6	8.39	
46	19.3	5.48	23.3	7.14	25.2	8.24	25.4	8.16	26.5	8.35	27.0	8.39	27.3	8.52	

GREEN-GRV 4 Outdoor unit

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
48	48	19.3	5.55	23.3	7.20	25.2	8.30	25.4	8.24	25.9	8.46	26.3	8.52	26.8	8.68
	50	18.1	5.61	22.1	7.26	24.1	8.37	24.2	8.33	24.9	8.52	25.2	8.65	25.9	8.83
	52	18.1	5.68	22.1	7.35	24.1	8.46	24.2	8.42	24.9	8.60	25.2	8.79	25.9	8.99
100%	10	18.9	2.48	22.5	3.02	26.2	3.57	28.0	3.85	29.8	4.16	30.3	4.28	30.9	4.32
	12	18.9	2.52	22.5	3.06	26.2	3.62	28.0	3.90	29.8	4.24	30.3	4.36	30.9	4.40
	14	18.9	2.56	22.5	3.11	26.2	3.68	28.0	3.98	29.8	4.32	30.3	4.44	30.9	4.48
	16	18.9	2.62	22.5	3.18	26.2	3.76	28.0	4.06	29.8	4.42	30.3	4.52	30.9	4.56
	18	18.9	2.68	22.5	3.25	26.2	3.83	28.0	4.14	29.8	4.50	30.3	4.59	30.9	4.64
	19	18.9	2.72	22.5	3.30	26.2	3.96	28.0	4.36	29.8	4.79	30.3	4.92	30.9	4.97
	21	18.9	2.74	22.5	3.33	26.2	4.10	28.0	4.51	29.8	4.95	30.3	5.27	30.9	5.33
	23	18.9	2.81	22.5	3.56	26.2	4.40	28.0	4.85	29.8	5.32	30.3	5.64	30.9	5.70
	25	18.9	2.99	22.5	3.79	26.2	4.68	28.0	5.16	29.8	5.70	30.3	6.03	30.9	6.09
	27	18.9	3.20	22.5	4.05	26.2	5.03	28.0	5.54	29.8	6.11	30.3	6.44	30.9	6.50
	29	18.9	3.39	22.5	4.33	26.2	5.38	28.0	5.92	29.7	6.47	30.3	6.87	30.9	6.94
	31	18.9	3.61	22.5	4.61	26.2	5.73	28.0	6.38	29.3	6.74	30.3	7.32	30.9	7.39
	33	18.9	3.84	22.5	4.91	26.2	6.11	28.0	6.75	28.8	6.98	30.3	7.79	30.9	7.86
	35	18.9	4.08	22.5	5.22	26.2	6.51	28.0	7.10	28.3	7.23	30.3	8.28	30.9	8.36
	37	18.9	4.35	22.5	5.56	26.2	6.94	27.5	7.46	27.9	7.49	30.3	8.32	30.9	8.40
	39	18.6	4.63	22.3	5.93	25.9	7.39	27.1	7.70	27.9	7.74	30.3	8.35	30.9	8.43
	41	18.0	4.89	21.9	6.15	25.5	7.53	26.5	7.86	27.5	7.89	30.2	8.39	30.9	8.47
	43	17.4	5.06	21.4	6.37	25.0	7.75	26.1	8.03	27.2	8.03	30.0	8.43	30.5	8.51
	46	16.8	5.30	20.8	6.58	24.3	7.96	25.7	8.27	26.5	8.21	29.3	8.47	30.0	8.55
48	16.1	5.56	20.2	6.80	23.8	8.10	25.0	8.50	25.8	8.43	28.7	8.51	29.2	8.59	
50	15.3	5.79	19.8	7.03	23.2	8.32	24.3	8.73	24.8	8.69	28.0	8.63	28.5	8.67	
52	15.3	6.00	19.1	7.29	22.4	8.56	23.8	8.96	23.9	8.85	27.1	8.75	27.6	8.75	
90%	10	17.5	2.05	20.6	2.55	23.8	3.05	25.2	3.31	26.7	3.57	27.2	3.58	27.8	3.61
	12	17.5	2.08	20.6	2.60	23.8	3.11	25.2	3.37	26.7	3.63	27.2	3.65	27.8	3.68
	14	17.5	2.12	20.6	2.64	23.8	3.17	25.2	3.43	26.7	3.70	27.2	3.71	27.8	3.75
	16	17.5	2.16	20.6	2.69	23.8	3.22	25.2	3.49	26.7	3.77	27.2	3.78	27.8	3.81
	18	17.5	2.20	20.6	2.74	23.8	3.28	25.2	3.56	26.7	3.83	27.2	3.84	27.8	3.88
	19	17.5	2.24	20.6	2.78	23.8	3.33	25.2	3.62	26.7	3.90	27.2	3.91	27.8	3.95
	21	17.5	2.40	20.6	2.99	23.8	3.57	25.2	3.88	26.7	4.18	27.2	4.19	27.8	4.23
	23	17.5	2.57	20.6	3.20	23.8	3.83	25.2	4.15	26.7	4.48	27.2	4.49	27.8	4.53
	25	17.5	2.75	20.6	3.42	23.8	4.10	25.2	4.44	26.7	4.79	27.2	4.81	27.8	4.85
	27	17.5	2.94	20.6	3.66	23.8	4.38	25.2	4.75	26.7	5.12	27.2	5.14	27.8	5.19
	29	17.5	3.13	20.6	3.91	23.8	4.68	25.2	5.07	26.7	5.47	27.2	5.49	27.8	5.54
	31	17.5	3.34	20.6	4.17	23.8	4.99	25.2	5.41	26.7	5.83	27.2	5.85	27.8	5.91
	33	17.5	3.56	20.6	4.44	23.8	5.31	25.2	5.76	26.7	6.21	27.2	6.23	27.8	6.29
35	17.5	3.79	20.6	4.72	23.8	5.65	25.2	6.13	26.7	6.61	27.2	6.63	27.8	6.69	

GREEN-GRV 4 Outdoor unit

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	37	17.5	4.03	20.6	5.02	23.8	6.01	25.2	6.52	26.7	7.03	27.2	7.05	27.8	7.12
	39	17.5	4.05	20.6	5.04	23.8	6.04	25.2	6.55	26.7	7.06	27.2	7.08	27.8	7.15
	41	17.2	4.06	20.4	5.06	23.5	6.06	24.8	6.58	26.4	7.09	26.8	7.11	27.4	7.18
	43	16.8	4.08	20.0	5.09	23.0	6.09	24.0	6.61	25.8	7.12	26.1	7.15	26.8	7.21
	46	16.3	4.10	19.3	5.11	22.3	6.12	23.2	6.64	25.0	7.16	25.4	7.18	26.0	7.25
	48	15.4	4.12	18.7	5.14	21.5	6.15	22.5	6.67	24.3	7.19	24.7	7.21	25.4	7.28
	50	14.6	4.14	18.0	5.16	20.8	6.18	21.7	6.70	23.6	7.22	23.9	7.24	24.8	7.32
	52	13.8	4.18	17.2	5.23	20.0	6.34	20.9	6.89	22.8	7.30	23.0	7.35	23.6	7.42
	80%	10	15.5	1.74	18.3	2.16	21.1	2.59	22.4	2.81	23.7	3.03	24.2	3.04	24.7
12		15.5	1.77	18.3	2.20	21.1	2.64	22.4	2.86	23.7	3.09	24.2	3.10	24.7	3.13
14		15.5	1.80	18.3	2.24	21.1	2.69	22.4	2.92	23.7	3.14	24.2	3.15	24.7	3.18
16		15.5	1.83	18.3	2.28	21.1	2.74	22.4	2.97	23.7	3.20	24.2	3.21	24.7	3.24
18		15.5	1.87	18.3	2.32	21.1	2.78	22.4	3.02	23.7	3.25	24.2	3.26	24.7	3.30
19		15.5	1.90	18.3	2.36	21.1	2.83	22.4	3.07	23.7	3.31	24.2	3.32	24.7	3.35
21		15.5	2.03	18.3	2.54	21.1	3.04	22.4	3.29	23.7	3.55	24.2	3.56	24.7	3.59
23		15.5	2.18	18.3	2.72	21.1	3.25	22.4	3.53	23.7	3.80	24.2	3.81	24.7	3.85
25		15.5	2.33	18.3	2.91	21.1	3.48	22.4	3.77	23.7	4.07	24.2	4.08	24.7	4.12
27		15.5	2.49	18.3	3.11	21.1	3.72	22.4	4.03	23.7	4.35	24.2	4.36	24.7	4.40
29		15.5	2.66	18.3	3.32	21.1	3.97	22.4	4.31	23.7	4.64	24.2	4.66	24.7	4.70
31		15.5	2.84	18.3	3.54	21.1	4.24	22.4	4.59	23.7	4.95	24.2	4.97	24.7	5.02
33		15.5	3.02	18.3	3.77	21.1	4.51	22.4	4.89	23.7	5.27	24.2	5.29	24.7	5.34
35		15.5	3.22	18.3	4.01	21.1	4.80	22.4	5.21	23.7	5.61	24.2	5.63	24.7	5.68
37		15.5	3.42	18.3	4.26	21.1	5.10	22.4	5.54	23.7	5.97	24.2	5.99	24.7	6.04
39		15.5	3.44	18.3	4.28	21.1	5.13	22.4	5.56	23.7	5.99	24.2	6.01	24.7	6.07
41		15.3	3.45	18.0	4.30	20.8	5.15	22.0	5.59	23.4	6.02	23.8	6.04	24.3	6.10
43		15.0	3.47	17.6	4.32	20.2	5.17	21.6	5.61	22.8	6.05	23.4	6.07	23.6	6.13
46	14.6	3.48	17.0	4.34	19.6	5.20	20.8	5.64	22.0	6.08	22.6	6.10	22.8	6.16	
48	14.0	3.50	16.4	4.36	19.0	5.22	20.0	5.66	21.4	6.11	22.0	6.12	22.0	6.18	
50	13.5	3.52	15.8	4.38	18.4	5.25	19.6	5.69	20.6	6.13	21.3	6.15	21.2	6.21	
52	12.8	3.79	15.0	4.56	17.5	5.42	19.0	5.85	19.3	6.20	20.5	6.20	20.4	6.32	
70%	10	13.6	1.44	16.0	1.79	18.5	2.14	19.6	2.33	20.7	2.51	21.2	2.51	21.6	2.54
	12	13.6	1.46	16.0	1.82	18.5	2.18	19.6	2.37	20.7	2.55	21.2	2.56	21.6	2.59
	14	13.6	1.49	16.0	1.86	18.5	2.22	19.6	2.41	20.7	2.60	21.2	2.61	21.6	2.63
	16	13.6	1.52	16.0	1.89	18.5	2.26	19.6	2.45	20.7	2.65	21.2	2.65	21.6	2.68
	18	13.6	1.54	16.0	1.92	18.5	2.30	19.6	2.50	20.7	2.69	21.2	2.70	21.6	2.73
	19	13.6	1.57	16.0	1.96	18.5	2.34	19.6	2.54	20.7	2.74	21.2	2.75	21.6	2.77
	21	13.6	1.68	16.0	2.10	18.5	2.51	19.6	2.72	20.7	2.94	21.2	2.94	21.6	2.97
	23	13.6	1.80	16.0	2.25	18.5	2.69	19.6	2.92	20.7	3.14	21.2	3.15	21.6	3.18
	25	13.6	1.93	16.0	2.40	18.5	2.88	19.6	3.12	20.7	3.37	21.2	3.38	21.6	3.41

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	27	13.6	2.06	16.0	2.57	18.5	3.08	19.6	3.34	20.7	3.60	21.2	3.61	21.6	3.64
	29	13.6	2.20	16.0	2.74	18.5	3.28	19.6	3.56	20.7	3.84	21.2	3.85	21.6	3.89
	31	13.6	2.35	16.0	2.93	18.5	3.50	19.6	3.80	20.7	4.10	21.2	4.11	21.6	4.15
	33	13.6	2.50	16.0	3.12	18.5	3.73	19.6	4.05	20.7	4.36	21.2	4.38	21.6	4.42
	35	13.6	2.66	16.0	3.32	18.5	3.97	19.6	4.31	20.7	4.64	21.2	4.66	21.6	4.70
	37	13.6	2.83	16.0	3.53	18.5	4.22	19.6	4.58	20.7	4.94	21.2	4.95	21.6	5.00
	39	13.6	2.84	16.0	3.54	18.5	4.24	19.6	4.60	20.7	4.96	21.2	4.97	21.6	5.02
	41	13.3	2.86	15.8	3.56	18.0	4.26	19.3	4.62	20.4	4.98	20.8	5.00	21.2	5.04
	43	12.8	2.87	15.2	3.57	17.3	4.28	18.6	4.64	19.8	5.00	20.1	5.02	20.6	5.07
	46	12.1	2.88	14.6	3.59	16.5	4.30	18.0	4.66	19.0	5.03	19.5	5.04	19.8	5.09
	48	11.6	2.90	14.0	3.61	15.8	4.32	17.5	4.68	18.3	5.05	18.7	5.07	18.9	5.11
	50	11.0	2.91	13.4	3.62	14.9	4.34	16.4	4.71	17.6	5.07	17.9	5.09	18.0	5.14
	52	10.5	3.00	12.8	3.85	13.7	4.41	15.6	4.93	15.9	5.13	17.0	5.20	17.3	5.26
	60%	10	11.6	1.17	13.7	1.46	15.8	1.75	16.8	1.90	17.8	2.04	18.2	2.05	18.5
12		11.6	1.19	13.7	1.49	15.8	1.78	16.8	1.93	17.8	2.08	18.2	2.09	18.5	2.11
14		11.6	1.22	13.7	1.51	15.8	1.81	16.8	1.97	17.8	2.12	18.2	2.13	18.5	2.15
16		11.6	1.24	13.7	1.54	15.8	1.85	16.8	2.00	17.8	2.16	18.2	2.16	18.5	2.19
18		11.6	1.26	13.7	1.57	15.8	1.88	16.8	2.04	17.8	2.20	18.2	2.20	18.5	2.22
19		11.6	1.28	13.7	1.60	15.8	1.91	16.8	2.07	17.8	2.23	18.2	2.24	18.5	2.26
21		11.6	1.37	13.7	1.71	15.8	2.05	16.8	2.22	17.8	2.39	18.2	2.40	18.5	2.43
23		11.6	1.47	13.7	1.83	15.8	2.19	16.8	2.38	17.8	2.57	18.2	2.57	18.5	2.60
25		11.6	1.57	13.7	1.96	15.8	2.35	16.8	2.55	17.8	2.74	18.2	2.75	18.5	2.78
27		11.6	1.68	13.7	2.10	15.8	2.51	16.8	2.72	17.8	2.93	18.2	2.94	18.5	2.97
29		11.6	1.80	13.7	2.24	15.8	2.68	16.8	2.91	17.8	3.13	18.2	3.14	18.5	3.17
31		11.6	1.92	13.7	2.39	15.8	2.86	16.8	3.10	17.8	3.34	18.2	3.35	18.5	3.38
33		11.6	2.04	13.7	2.54	15.8	3.04	16.8	3.30	17.8	3.56	18.2	3.57	18.5	3.60
35		11.6	2.17	13.7	2.70	15.8	3.24	16.8	3.51	17.8	3.79	18.2	3.80	18.5	3.83
37	11.6	2.31	13.7	2.88	15.8	3.44	16.8	3.74	17.8	4.03	18.2	4.04	18.5	4.08	
39	11.6	2.32	13.7	2.89	15.8	3.46	16.8	3.75	17.8	4.04	18.2	4.06	18.5	4.10	
41	11.6	2.33	13.4	2.90	15.4	3.47	16.3	3.77	17.4	4.06	17.6	4.07	18.2	4.11	
43	11.4	2.34	12.9	2.92	14.8	3.49	15.8	3.79	16.8	4.08	17.0	4.09	17.6	4.13	
46	10.9	2.35	12.4	2.93	14.0	3.51	15.0	3.80	16.0	4.10	16.2	4.11	17.0	4.15	
48	10.2	2.36	11.8	2.94	13.6	3.52	14.2	3.82	15.3	4.12	15.6	4.13	16.4	4.17	
50	9.8	2.37	11.3	2.96	13.0	3.54	13.7	3.84	14.7	4.14	14.9	4.15	15.8	4.19	
52	9.0	2.43	10.8	3.06	12.3	3.64	13.0	4.00	14.0	4.23	14.3	4.30	15.0	4.35	
50%	10	9.7	0.93	11.5	1.16	13.2	1.39	14.0	1.51	14.8	1.63	15.1	1.63	15.5	1.65
	12	9.7	0.95	11.5	1.18	13.2	1.42	14.0	1.54	14.8	1.66	15.1	1.66	15.5	1.68
	14	9.7	0.97	11.5	1.21	13.2	1.44	14.0	1.57	14.8	1.69	15.1	1.69	15.5	1.71
	16	9.7	0.99	11.5	1.23	13.2	1.47	14.0	1.59	14.8	1.72	15.1	1.72	15.5	1.74

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
18	9.7	1.00	11.5	1.25	13.2	1.50	14.0	1.62	14.8	1.75	15.1	1.75	15.5	1.77	
19	9.7	1.02	11.5	1.27	13.2	1.52	14.0	1.65	14.8	1.78	15.1	1.78	15.5	1.80	
21	9.7	1.09	11.5	1.36	13.2	1.63	14.0	1.77	14.8	1.91	15.1	1.91	15.5	1.93	
23	9.7	1.17	11.5	1.46	13.2	1.75	14.0	1.90	14.8	2.04	15.1	2.05	15.5	2.07	
25	9.7	1.25	11.5	1.56	13.2	1.87	14.0	2.03	14.8	2.19	15.1	2.19	15.5	2.21	
27	9.7	1.34	11.5	1.67	13.2	2.00	14.0	2.17	14.8	2.34	15.1	2.34	15.5	2.37	
29	9.7	1.43	11.5	1.78	13.2	2.13	14.0	2.31	14.8	2.50	15.1	2.50	15.5	2.53	
31	9.7	1.53	11.5	1.90	13.2	2.28	14.0	2.47	14.8	2.66	15.1	2.67	15.5	2.70	
33	9.7	1.62	11.5	2.02	13.2	2.42	14.0	2.63	14.8	2.83	15.1	2.84	15.5	2.87	
35	9.7	1.73	11.5	2.15	13.2	2.58	14.0	2.80	14.8	3.02	15.1	3.02	15.5	3.05	
37	9.7	1.84	11.5	2.29	13.2	2.74	14.0	2.98	14.8	3.21	15.1	3.22	15.5	3.25	
39	9.7	1.85	11.5	2.30	13.2	2.75	14.0	2.99	14.8	3.22	15.1	3.23	15.5	3.26	
41	9.6	1.85	11.2	2.31	12.8	2.77	13.6	3.00	14.5	3.24	14.7	3.25	15.2	3.28	
43	9.0	1.86	10.7	2.32	12.3	2.78	13.1	3.02	14.0	3.25	14.2	3.26	14.7	3.29	
46	8.4	1.87	10.3	2.33	11.8	2.79	12.5	3.03	13.3	3.27	13.6	3.28	14.2	3.31	
48	7.9	1.88	9.7	2.34	11.2	2.81	11.9	3.04	12.8	3.28	13.0	3.29	13.6	3.32	
50	7.3	1.89	9.1	2.35	10.6	2.82	11.3	3.06	12.0	3.30	12.4	3.31	12.9	3.34	
52	6.9	2.00	8.4	2.50	10.0	3.00	10.6	3.11	11.2	3.46	11.8	3.49	12.0	3.53	

12 HP

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8, WB:14		DB:23.3, WB:16		DB:25.8, WB:18		DB:27, WB:19		DB:28.2, WB:20		DB:30.7, WB:22		DB:32, WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	10	25.4	3.08	30.0	3.84	34.6	4.60	36.7	4.99	38.8	5.38	39.7	5.39	40.5	5.44
	12	25.4	3.14	30.0	3.91	34.6	4.68	36.7	5.08	38.8	5.47	39.7	5.49	40.5	5.54
	14	25.4	3.20	30.0	3.98	34.6	4.77	36.7	5.17	38.8	5.57	39.7	5.59	40.5	5.65
	16	25.4	3.25	30.0	4.05	34.6	4.85	36.7	5.26	38.8	5.67	39.7	5.69	40.5	5.75
	18	25.4	3.31	30.0	4.12	34.6	4.94	36.7	5.36	38.8	5.77	39.7	5.79	40.5	5.85
	19	25.4	3.37	30.0	4.19	34.6	5.02	36.7	5.45	38.8	5.87	39.7	5.89	40.5	5.95
	21	25.4	3.61	30.0	4.50	34.6	5.38	36.7	5.84	38.8	6.30	39.7	6.32	40.5	6.38
	23	25.4	3.87	30.0	4.82	34.6	5.77	36.7	6.26	38.8	6.74	39.7	6.76	40.5	6.83
	25	25.4	4.14	30.0	5.15	34.6	6.17	36.7	6.69	38.8	7.22	39.7	7.24	40.5	7.31
	27	25.4	4.42	30.0	5.51	34.6	6.60	36.7	7.16	38.8	7.71	39.7	7.74	40.5	7.81
	29	25.4	4.72	30.0	5.88	34.6	7.04	36.7	7.64	38.8	8.24	39.7	8.26	40.5	8.34
	31	25.4	5.04	30.0	6.27	34.6	7.51	36.7	8.15	38.8	8.78	39.7	8.81	40.5	8.90
	33	25.4	5.36	30.0	6.68	34.6	8.00	36.7	8.68	38.8	9.36	39.7	9.39	40.5	9.48
	35	25.4	5.71	30.0	7.11	34.6	8.51	36.7	9.23	38.8	9.95	39.7	9.98	40.5	10.08
	37	25.4	6.07	30.0	7.56	34.6	9.05	36.7	9.82	38.8	10.59	39.7	10.62	40.5	10.72
	39	25.4	6.10	30.0	7.59	34.6	9.09	36.7	9.86	38.8	10.63	39.7	10.67	40.5	10.77
	41	25.2	6.12	29.7	7.63	34.4	9.13	36.4	9.91	38.4	10.68	39.5	10.71	40.2	10.82
	43	25.0	6.15	29.4	7.66	34.1	9.18	35.8	9.95	38.0	10.73	39.1	10.76	39.8	10.87
46	24.4	6.18	28.2	7.70	33.6	9.22	35.0	10.00	37.2	10.78	38.4	10.81	39.1	10.92	
48	23.8	6.21	27.6	7.74	32.8	9.26	34.2	10.05	36.0	10.83	37.5	10.86	38.5	10.97	
50	23.0	6.24	26.9	7.77	32.0	9.31	33.8	10.09	35.3	10.88	36.8	10.91	37.8	11.02	
52	22.4	6.27	26.0	7.81	31.2	9.35	33.0	10.14	34.1	10.93	35.9	10.95	37.0	11.07	
120%	10	25.0	3.06	29.5	3.81	34.1	4.57	36.1	4.95	38.2	5.34	39.0	5.36	39.9	5.41
	12	25.0	3.12	29.5	3.88	34.1	4.65	36.1	5.04	38.2	5.44	39.0	5.45	39.9	5.51
	14	25.0	3.17	29.5	3.96	34.1	4.74	36.1	5.14	38.2	5.54	39.0	5.55	39.9	5.61
	16	25.0	3.23	29.5	4.03	34.1	4.82	36.1	5.23	38.2	5.64	39.0	5.65	39.9	5.71
	18	25.0	3.29	29.5	4.10	34.1	4.90	36.1	5.32	38.2	5.73	39.0	5.75	39.9	5.81
	19	25.0	3.34	29.5	4.17	34.1	4.99	36.1	5.41	38.2	5.83	39.0	5.85	39.9	5.91
	21	25.0	3.59	29.5	4.47	34.1	5.35	36.1	5.80	38.2	6.25	39.0	6.27	39.9	6.33
	23	25.0	3.84	29.5	4.78	34.1	5.73	36.1	6.21	38.2	6.70	39.0	6.72	39.9	6.78
	25	25.0	4.11	29.5	5.12	34.1	6.13	36.1	6.65	38.2	7.17	39.0	7.19	39.9	7.26
	27	25.0	4.39	29.5	5.47	34.1	6.55	36.1	7.11	38.2	7.66	39.0	7.69	39.9	7.76
	29	25.0	4.69	29.5	5.84	34.1	7.00	36.1	7.59	38.2	8.18	39.0	8.21	39.9	8.29
	31	25.0	5.00	29.5	6.23	34.1	7.46	36.1	8.09	38.2	8.73	39.0	8.75	39.9	8.84
	33	25.0	5.33	29.5	6.64	34.1	7.95	36.1	8.62	38.2	9.29	39.0	9.32	39.9	9.41
	35	25.0	5.67	29.5	7.06	34.1	8.46	36.1	9.17	38.2	9.89	39.0	9.92	39.9	10.01
37	25.0	6.03	29.5	7.51	34.1	8.99	36.1	9.76	38.2	10.52	39.0	10.55	39.9	10.65	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	39	25.0	6.05	29.5	7.54	34.1	9.03	36.1	9.80	38.2	10.56	39.0	10.59	39.9	10.70
	41	24.8	6.08	39.3	7.58	33.8	9.07	35.8	9.84	37.8	10.61	38.7	10.64	39.6	10.75
	43	24.5	6.11	29.0	7.61	33.5	9.12	35.5	9.89	37.4	10.66	38.4	10.69	39.4	10.80
	46	23.8	6.14	28.2	7.65	32.6	9.16	34.8	9.93	36.8	10.71	37.8	10.74	38.9	10.85
	48	23.3	6.17	27.3	7.68	31.8	9.20	34.0	9.98	36.0	10.76	37.0	10.79	38.0	10.90
	50	22.5	6.20	26.1	7.72	31.0	9.24	33.2	10.03	35.2	10.81	36.3	10.84	37.3	10.95
	52	21.3	6.25	25.2	7.76	30.3	9.28	31.6	10.09	34.6	10.85	35.6	10.89	36.5	10.99
110%	10	22.7	3.03	27.2	3.78	32.3	4.54	34.3	4.92	37.1	5.31	38.2	5.33	39.0	5.38
	12	22.7	3.09	27.2	3.85	32.3	4.62	34.3	5.01	37.1	5.41	38.2	5.42	39.0	5.48
	14	22.7	3.14	27.2	3.93	32.3	4.71	34.3	5.11	37.1	5.51	38.2	5.52	39.0	5.58
	16	22.7	3.20	27.2	4.00	32.3	4.79	34.3	5.20	37.1	6.61	38.2	5.62	39.0	5.68
	18	22.7	3.26	27.2	4.07	32.3	4.87	34.3	5.29	37.1	5.70	38.2	5.72	39.0	5.78
	19	22.7	3.31	27.2	4.14	32.3	4.96	34.3	5.38	37.1	5.80	38.2	5.82	39.0	5.88
	21	22.7	3.56	27.2	4.44	32.3	5.32	34.3	5.77	37.1	6.22	38.2	6.24	39.0	6.30
	23	22.7	3.81	27.2	4.75	32.3	5.70	34.3	6.18	37.1	6.67	38.2	6.69	39.0	6.75
	25	22.7	4.08	27.2	5.09	32.3	6.10	34.3	6.62	37.1	7.14	38.2	7.16	39.0	7.23
	27	22.7	4.36	27.2	5.44	32.3	6.52	34.3	7.08	37.1	7.63	38.2	7.66	39.0	7.73
	29	22.7	4.66	27.2	5.81	32.3	6.97	34.3	7.56	37.1	8.15	38.2	8.18	39.0	8.26
	31	22.7	4.97	27.2	6.20	32.3	7.43	34.3	8.06	37.1	8.70	38.2	8.72	39.0	8.81
	33	22.7	5.30	27.2	6.61	32.3	7.92	34.3	8.59	37.1	9.26	38.2	9.29	39.0	9.38
	35	22.7	5.64	27.2	7.01	32.3	8.43	34.3	9.14	37.1	9.86	38.2	9.89	39.0	9.98
	37	22.7	6.00	27.2	7.47	32.3	8.96	34.3	9.73	37.1	10.49	38.2	10.52	39.0	10.62
	39	22.7	6.02	27.2	7.51	32.3	9.00	34.3	9.77	37.1	10.53	38.2	10.56	39.0	10.67
	41	22.5	6.05	26.8	7.55	32.0	9.04	34.0	9.81	36.8	10.58	37.9	10.61	38.6	10.72
43	22.1	6.08	26.5	7.58	31.6	9.09	33.6	9.86	36.4	10.63	37.5	10.66	38.3	10.77	
46	21.4	6.11	26.0	7.62	31.0	9.13	33.0	9.90	33.8	10.68	36.9	10.71	37.8	10.82	
48	20.6	6.14	25.2	7.65	30.5	9.17	32.4	9.95	33.0	10.73	36.1	10.76	37.2	10.87	
50	19.7	6.17	24.3	7.69	29.8	9.21	31.7	10.00	32.1	10.78	35.5	10.81	36.4	10.92	
52	18.5	6.22	23.4	7.73	29.0	9.25	31.0	10.06	31.4	10.82	34.3	10.86	35.3	10.96	
100%	10	21.5	2.60	25.8	3.23	30.1	3.87	32.2	4.19	35.4	4.52	36.3	4.53	37.5	4.57
	12	21.5	2.65	25.8	3.29	30.1	3.94	32.2	4.27	35.4	4.60	36.3	4.61	37.5	4.66
	14	21.5	2.70	25.8	3.35	30.1	4.01	32.2	4.34	35.4	4.68	36.3	4.70	37.5	4.74
	16	21.5	2.74	25.8	3.41	30.1	4.08	32.2	4.42	35.4	4.76	36.3	4.78	37.5	4.83
	18	21.5	2.79	25.8	3.47	30.1	4.15	32.2	4.50	35.4	4.85	36.3	4.86	37.5	4.91
	19	21.5	2.84	25.8	3.53	30.1	4.22	32.2	4.58	35.4	4.93	36.3	4.95	37.5	4.99
	21	21.5	2.04	25.8	3.78	30.1	4.52	32.2	4.90	35.4	5.28	36.3	5.30	37.5	5.35
	23	21.5	3.26	25.8	4.05	30.1	4.84	32.2	5.25	35.4	5.66	36.3	5.67	37.5	5.73
25	21.5	3.48	25.8	4.33	30.1	5.18	32.2	5.62	35.4	6.05	36.3	6.07	37.5	6.13	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	27	21.5	3.72	25.8	3.63	30.1	5.54	32.2	6.00	35.4	6.47	36.3	6.49	37.5	6.55
	29	21.5	3.97	25.8	4.94	30.1	5.91	32.2	6.41	35.4	6.90	36.3	6.82	37.5	6.99
	31	21.5	4.23	25.8	5.27	30.1	6.30	32.2	6.83	35.4	7.36	36.3	7.38	37.5	7.45
	33	21.5	4.51	25.8	5.61	30.1	6.71	32.2	7.27	35.4	7.84	36.3	7.86	37.5	7.94
	35	21.5	4.79	25.8	5.96	30.1	7.13	32.2	7.74	35.4	8.34	36.3	8.36	37.5	9.44
	37	21.5	5.09	25.8	6.34	30.1	7.59	32.2	8.23	35.4	8.86	36.3	8.89	37.5	9.98
	39	21.5	5.12	25.8	6.37	30.1	7.62	32.2	8.26	35.4	8.90	36.3	8.93	37.5	9.02
	41	21.3	5.14	25.5	6.40	29.8	7.65	31.9	8.30	35.1	8.95	36.0	8.97	37.2	9.05
	43	21.0	5.16	25.1	6.43	29.4	7.69	31.6	8.34	34.7	8.98	35.7	9.01	36.9	9.10
	46	20.5	5.19	24.3	6.46	28.8	7.72	31.0	8.37	33.4	9.03	34.8	9.05	36.0	9.14
	48	19.8	5.21	23.6	6.49	28.0	7.76	30.4	8.41	32.2	9.07	33.6	9.09	35.1	9.18
	50	19.0	5.23	23.0	6.52	27.2	7.79	29.2	8.45	31.3	9.11	32.4	9.14	33.9	9.22
	52	18.3	5.29	22.1	6.56	26.4	7.81	28.1	8.50	30.4	9.16	31.1	9.20	32.8	9.27
	90%	10	20.9	2.57	24.7	3.20	28.4	3.84	30.2	4.16	31.9	4.49	32.6	4.50	33.3
12		20.9	2.62	24.7	3.26	28.4	3.91	30.2	4.24	31.9	4.57	32.6	4.58	33.3	4.63
14		20.9	2.67	24.7	3.32	28.4	3.98	30.2	4.31	31.9	4.65	32.6	4.67	33.3	4.71
16		20.9	2.71	24.7	3.38	28.4	4.05	30.2	4.39	31.9	4.73	32.6	4.75	33.3	4.80
18		20.9	2.76	24.7	3.44	28.4	4.12	30.2	4.47	31.9	4.82	32.6	4.83	33.3	4.88
19		20.9	2.81	24.7	3.50	28.4	4.19	30.2	4.55	31.9	4.90	32.6	4.92	33.3	4.96
21		20.9	3.01	24.7	3.75	28.4	4.49	30.2	4.87	31.9	5.25	32.6	5.27	33.3	5.32
23		20.9	3.23	24.7	4.02	28.4	4.81	30.2	5.22	31.9	5.63	32.6	5.64	33.3	5.70
25		20.9	3.45	24.7	4.30	28.4	5.15	30.2	5.59	31.9	6.02	32.6	6.04	33.3	6.10
27		20.9	3.69	24.7	4.60	28.4	5.51	30.2	5.97	31.9	6.44	32.6	6.46	33.3	6.52
29		20.9	3.94	24.7	4.91	28.4	5.88	30.2	6.38	31.9	6.87	32.6	6.89	33.3	6.96
31		20.9	4.20	24.7	5.24	28.4	6.27	30.2	6.80	31.9	7.33	32.6	7.35	33.3	7.42
33		20.9	4.48	24.7	5.58	28.4	6.68	30.2	7.24	31.9	7.81	32.6	7.83	33.3	7.91
35		20.9	4.76	24.7	5.93	28.4	7.10	30.2	7.71	31.9	8.31	32.6	8.33	33.3	8.41
37	20.9	5.06	24.7	6.31	28.4	7.56	30.2	8.20	31.9	8.83	32.6	8.86	33.3	8.95	
39	20.9	5.09	24.7	6.34	28.4	7.59	30.2	8.23	31.9	8.87	32.6	8.90	33.3	8.99	
41	20.6	5.11	24.4	6.37	28.0	7.62	29.9	8.27	31.6	8.91	32.2	8.94	33.0	9.03	
43	20.2	5.13	24.0	6.40	27.5	7.66	29.5	8.31	31.2	8.95	31.8	8.98	32.6	9.07	
46	19.4	5.16	23.4	6.43	26.8	7.69	28.7	8.34	30.3	9.00	31.0	9.02	31.8	9.11	
48	18.2	5.18	22.6	6.46	26.0	7.73	28.0	8.38	29.1	9.04	30.1	9.06	30.7	9.15	
50	17.1	5.20	21.2	6.48	25.2	7.76	26.9	8.42	27.8	9.08	28.9	9.11	29.4	9.19	
52	15.8	5.26	20.4	6.53	24.3	7.81	25.7	8.47	26.3	9.13	27.4	9.17	28.2	9.24	
80%	10	18.6	2.18	21.9	2.72	25.3	3.26	26.8	3.53	28.3	3.81	29.0	3.82	29.6	3.86
	12	18.6	2.22	21.9	2.77	25.3	3.32	26.8	3.60	28.3	3.88	29.0	3.89	29.6	3.93
	14	18.6	2.26	21.9	2.82	25.3	3.38	26.8	3.66	28.3	3.95	29.0	3.96	29.6	4.00

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	16	18.6	2.30	21.9	2.87	25.3	3.44	26.8	3.73	28.3	4.02	29.0	4.03	29.6	4.07
	18	18.6	2.35	21.9	2.92	25.3	3.50	26.8	3.80	28.3	4.09	29.0	4.10	29.6	4.14
	19	18.6	2.39	21.9	2.97	25.3	3.56	26.8	3.86	28.3	4.16	29.0	4.17	29.6	4.21
	21	18.6	2.56	21.9	3.19	25.3	3.82	26.8	4.14	28.3	4.46	29.0	4.48	29.6	4.52
	23	18.6	2.74	21.9	3.41	25.3	4.09	26.8	4.43	28.3	4.78	29.0	4.79	29.6	4.84
	25	18.6	2.93	21.9	3.65	25.3	4.37	26.8	4.74	28.3	5.11	29.0	5.13	29.6	5.18
	27	18.6	3.13	21.9	3.90	25.3	4.68	26.8	5.07	28.3	5.47	29.0	5.48	29.6	5.54
	29	18.6	3.35	21.9	4.17	25.3	4.99	26.8	5.41	28.3	5.84	29.0	5.85	29.6	5.91
	31	18.6	3.57	21.9	4.45	25.3	5.32	26.8	5.77	28.3	6.22	29.0	6.24	29.6	6.30
	33	18.6	3.80	21.9	4.74	25.3	5.67	26.8	6.15	28.3	6.63	29.0	6.65	29.6	6.72
	35	18.6	4.04	21.9	5.04	25.3	6.03	26.8	6.54	28.3	7.05	29.0	7.08	29.6	7.14
	37	18.6	4.30	21.9	5.36	25.3	6.42	26.8	6.96	28.3	7.50	29.0	7.53	29.6	7.60
	39	18.6	4.32	21.9	5.38	25.3	6.44	26.8	6.99	28.3	7.53	29.0	7.56	29.6	7.63
	41	18.2	4.34	21.5	5.41	25.0	6.47	26.5	7.02	28.0	7.57	28.7	7.59	29.4	7.67
	43	17.9	4.36	21.2	5.43	24.6	6.50	26.1	7.05	27.6	7.60	28.2	7.63	29.0	7.70
	46	17.0	4.38	20.4	5.46	23.8	6.53	25.0	7.09	26.7	7.64	27.1	7.66	28.0	7.74
	48	16.3	4.40	19.5	5.48	22.4	6.56	23.8	7.12	25.4	7.67	25.8	7.70	26.6	7.77
	50	14.9	4.42	18.1	5.51	21.2	6.59	22.5	7.15	24.2	7.71	24.5	7.73	25.3	7.81
	52	14.0	4.46	17.2	5.57	20.1	6.63	21.1	7.20	23.1	7.75	23.1	7.79	24.1	7.85
	70%	10	16.2	1.81	19.2	2.25	22.1	2.69	23.5	2.92	24.8	3.15	25.3	3.16	25.9
12		16.2	1.84	19.2	2.29	22.1	2.74	23.5	2.98	24.8	3.21	25.3	3.22	25.9	3.25
14		16.2	1.87	19.2	2.33	22.1	2.79	23.5	3.03	24.8	3.27	25.3	3.28	25.9	3.31
16		16.2	1.91	19.2	2.38	22.1	2.84	23.5	3.08	24.8	3.33	25.3	3.34	25.9	3.37
18		16.2	1.94	19.2	2.42	22.1	2.89	23.5	3.14	24.8	3.38	25.3	3.39	25.9	3.43
19		16.2	1.97	19.2	2.46	22.1	2.94	23.5	3.19	24.8	3.44	25.3	3.45	25.9	3.49
21		16.2	2.12	19.2	2.64	22.1	3.16	23.5	3.42	24.8	3.69	25.3	3.70	25.9	3.74
23		16.2	2.27	19.2	2.82	22.1	3.38	23.5	3.67	24.8	3.95	25.3	3.96	25.9	4.00
25		16.2	2.42	19.2	3.02	22.1	3.62	23.5	3.92	24.8	4.23	25.3	4.24	25.9	4.28
27		16.2	2.59	19.2	3.23	22.1	3.87	23.5	4.19	24.8	4.52	25.3	4.54	25.9	4.58
29		16.2	2.77	19.2	3.45	22.1	4.13	23.5	4.48	24.8	4.83	25.3	4.84	25.9	4.89
31		16.2	2.95	19.2	3.68	22.1	4.40	23.5	4.78	24.8	5.15	25.3	5.16	25.9	5.21
33		16.2	3.14	19.2	3.92	22.1	4.69	23.5	5.09	24.8	5.48	25.3	5.50	25.9	5.55
35		16.2	3.34	19.2	4.17	22.1	4.99	23.5	5.41	24.8	5.83	25.3	5.85	25.9	5.91
37		16.2	3.56	19.2	4.43	22.1	5.31	23.5	5.76	24.8	6.21	25.3	6.22	25.9	6.28
39		16.2	3.57	19.2	4.45	22.1	5.33	23.5	5.78	24.8	6.23	25.3	6.25	25.9	6.31
41	15.8	3.59	19.8	4.47	21.8	5.35	23.2	5.81	24.5	6.26	25.0	6.28	25.6	6.34	
43	15.0	3.61	19.3	4.49	21.4	5.38	22.8	5.83	24.1	6.29	24.6	6.31	25.2	6.37	
46	14.0	3.62	18.7	4.51	20.2	5.40	21.5	5.86	22.8	6.32	23.2	6.34	24.3	6.40	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
48	48	13.2	3.64	18.0	4.53	19.1	5.43	20.3	5.89	21.5	6.35	22.1	6.37	23.1	6.43
	50	12.1	3.66	16.8	4.55	18.0	5.45	19.1	5.92	20.3	6.38	20.8	6.40	21.9	6.46
	52	11.0	3.71	15.5	4.62	16.7	5.54	17.8	5.98	19.1	6.43	19.3	6.48	20.8	6.53
60%	10	13.9	1.47	16.4	1.84	18.9	2.20	20.1	2.38	21.3	2.57	21.7	2.58	22.2	2.60
	12	13.9	1.50	16.4	1.87	18.9	2.24	20.1	2.43	21.3	2.62	21.7	2.63	22.2	2.65
	14	13.9	1.53	16.4	1.90	18.9	2.28	20.1	2.47	21.3	2.66	21.7	2.67	22.2	2.70
	16	13.9	1.56	16.4	1.94	18.9	2.32	20.1	2.52	21.3	2.71	21.7	2.72	22.2	2.75
	18	13.9	1.58	16.4	1.97	18.9	2.36	20.1	2.56	21.3	2.76	21.7	2.77	22.2	2.80
	19	13.9	1.61	16.4	2.01	18.9	2.40	20.1	2.60	21.3	2.81	21.7	2.82	22.2	2.84
	21	13.9	1.73	16.4	2.15	18.9	2.57	20.1	2.79	21.3	3.01	21.7	3.02	22.2	3.05
	23	13.9	1.85	16.4	2.30	18.9	2.76	20.1	2.99	21.3	3.22	21.7	3.23	22.2	3.27
	25	13.9	1.98	16.4	2.46	18.9	2.95	20.1	3.20	21.3	3.45	21.7	3.46	22.2	3.49
	27	13.9	2.11	16.4	2.63	18.9	3.15	20.1	3.42	21.3	3.69	21.7	3.70	22.2	3.74
	29	13.9	2.26	16.4	2.81	18.9	3.37	20.1	3.65	21.3	3.94	21.7	3.95	22.2	3.99
	31	13.9	2.41	16.4	3.00	18.9	3.59	20.1	3.90	21.3	4.20	21.7	4.21	22.2	4.25
	33	13.9	2.56	16.4	3.20	18.9	3.83	20.1	4.15	21.3	4.47	21.7	4.49	22.2	4.53
	35	13.9	2.73	16.4	3.40	18.9	4.07	20.1	4.41	21.3	4.76	21.7	4.77	22.2	4.82
	37	13.9	2.90	16.4	3.62	18.9	4.33	20.1	4.70	21.3	5.06	21.7	5.08	22.2	5.13
	39	13.9	2.91	16.4	3.63	18.9	4.35	20.1	4.72	21.3	5.08	21.7	5.10	22.2	5.15
	41	13.6	2.93	16.1	3.65	18.5	4.37	19.8	4.74	21.0	5.11	21.4	5.12	21.9	5.17
	43	13.2	2.94	15.7	3.66	18.1	4.39	19.4	4.76	20.6	5.13	21.0	5.15	21.5	5.20
	46	12.1	2.95	14.3	3.68	17.0	4.41	18.2	4.78	19.3	5.15	19.8	5.17	20.3	5.22
	48	10.9	2.97	13.2	3.70	15.8	4.43	17.1	4.80	18.1	5.18	18.6	5.19	19.1	5.24
50	9.7	2.98	12.1	3.72	14.5	4.45	16.0	4.83	17.0	5.20	17.3	5.22	18.0	5.27	
52	8.6	3.03	11.0	3.76	13.2	4.50	14.8	4.87	15.8	5.24	16.1	5.27	16.8	5.33	
50%	10	11.6	1.17	13.7	1.46	15.8	1.75	16.8	1.90	17.7	2.05	18.1	2.05	18.5	2.07
	12	11.6	1.20	13.7	1.49	15.8	1.78	16.8	1.93	17.7	2.08	18.1	2.09	18.5	2.11
	14	11.6	1.22	13.7	1.52	15.8	1.82	16.8	1.97	17.7	2.12	18.1	2.13	18.5	2.15
	16	11.6	1.24	13.7	1.54	15.8	1.85	16.8	2.00	17.7	2.16	18.1	2.17	18.5	2.19
	18	11.6	1.26	13.7	1.57	15.8	1.88	16.8	2.04	17.7	2.20	18.1	2.21	18.5	2.23
	19	11.6	1.28	13.7	1.60	15.8	1.91	16.8	2.07	17.7	2.24	18.1	2.24	18.5	2.26
	21	11.6	1.37	13.7	1.71	15.8	2.05	16.8	2.22	17.7	2.40	18.1	2.40	18.5	2.43
	23	11.6	1.47	13.7	1.83	15.8	2.20	16.8	2.38	17.7	2.57	18.1	2.58	18.5	2.60
	25	11.6	1.58	13.7	1.96	15.8	2.35	16.8	2.55	17.7	2.75	18.1	2.76	18.5	2.78
	27	11.6	1.68	13.7	2.10	15.8	2.51	16.8	2.72	17.7	2.94	18.1	2.95	18.5	2.97
	29	11.6	1.80	13.7	2.24	15.8	2.68	16.8	2.91	17.7	3.14	18.1	3.15	18.5	3.18
	31	11.6	1.92	13.7	2.39	15.8	2.86	16.8	3.10	17.7	3.34	18.1	3.36	18.5	3.39
	33	11.6	2.04	13.7	2.54	15.8	3.05	16.8	3.30	17.7	3.56	18.1	3.57	18.5	3.61

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
35		11.6	2.17	13.7	2.71	15.8	3.24	16.8	3.52	17.7	3.79	18.1	3.80	18.5	3.84
37		11.6	2.31	13.7	2.88	15.8	3.45	16.8	3.74	17.7	4.03	18.1	4.04	18.5	4.08
39		11.6	2.32	13.7	2.89	15.8	3.46	16.8	3.76	17.7	4.05	18.1	4.06	18.5	4.10
41		11.3	2.33	13.4	2.90	15.5	3.48	16.5	3.77	17.3	4.07	17.8	4.08	18.2	4.12
43		11.0	2.34	13.0	2.92	15.2	3.49	16.2	3.79	17.0	4.09	17.4	4.10	17.8	4.14
46		10.1	2.35	11.9	2.93	14.1	3.51	15.1	3.81	15.8	4.10	16.0	4.12	16.4	4.16
48		9.2	2.36	10.7	2.95	13.0	3.53	14.0	3.83	14.6	4.12	14.8	4.14	15.2	4.18
50		8.1	2.37	9.4	2.96	11.8	3.54	12.8	3.84	13.2	4.14	13.6	4.16	14.0	4.20
52		7.0	2.42	8.2	3.02	10.5	3.60	11.5	3.89	12.0	4.18	12.5	4.21	12.8	4.25

14 HP

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	10	35.1	4.98	41.9	6.08	48.6	7.23	50.4	7.39	51.0	7.25	52.3	6.94	53.6	6.62
	12	35.1	5.06	41.9	6.20	48.6	7.38	49.7	7.35	50.4	7.20	51.6	6.88	52.9	6.78
	14	35.1	5.17	41.9	6.31	48.4	7.46	49.1	7.32	49.7	7.16	51.0	7.10	52.3	7.17
	16	35.1	5.25	41.9	6.45	47.9	7.44	48.4	7.38	49.0	7.41	50.3	7.48	51.6	7.55
	18	35.1	5.35	41.9	6.58	47.1	7.71	47.7	7.76	48.4	7.80	49.7	7.87	51.0	7.94
	19	35.1	5.47	41.9	7.00	46.4	8.09	47.1	8.13	47.7	8.18	49.0	8.25	50.3	8.34
	21	35.1	5.62	41.9	7.25	46.1	8.28	46.9	8.32	47.4	8.37	48.7	8.45	50.0	8.53
	23	35.1	6.02	41.9	7.77	45.6	8.66	46.1	8.70	46.7	8.74	48.0	8.83	49.3	8.92
	25	35.1	6.43	41.9	8.32	44.9	9.04	45.6	9.08	46.1	9.14	47.4	9.22	48.7	9.31
	27	35.1	6.87	41.9	8.90	44.3	7.96	44.9	9.47	45.4	9.52	46.7	9.62	48.0	9.72
	29	35.1	7.33	41.9	9.52	43.6	9.79	44.1	9.85	44.9	9.91	46.1	10.01	47.4	10.11
	31	35.1	7.83	41.7	10.07	42.9	10.19	43.6	10.51	44.1	10.29	45.4	10.40	46.7	10.52
	33	35.1	8.34	41.0	10.45	42.3	10.55	42.9	10.62	43.6	10.68	44.9	10.80	46.0	10.93
	35	35.1	8.89	40.3	10.83	41.6	10.96	42.3	11.01	42.9	11.07	44.1	11.20	45.4	11.32
	37	35.1	9.46	39.7	11.22	41.0	11.35	41.6	11.41	42.3	11.48	43.4	11.61	44.7	11.74
	39	35.1	10.07	39.0	11.60	40.3	11.73	41.0	11.80	41.6	11.84	42.9	12.00	44.1	12.15
	41	34.8	10.18	38.7	11.85	40.0	12.00	40.8	12.05	41.4	12.11	42.7	12.40	43.8	12.58
	43	34.6	10.26	38.5	12.09	39.4	12.29	40.5	12.36	41.1	12.45	42.5	12.85	43.5	12.96
46	33.3	10.37	38.2	12.35	38.2	12.58	39.3	12.73	40.3	12.84	41.3	13.21	42.4	13.37	
48	32.5	10.45	37.5	12.60	37.8	12.89	38.5	13.00	39.2	13.09	40.1	13.64	41.2	13.75	
50	31.3	10.59	36.3	12.89	36.9	13.05	37.2	13.36	38.1	13.32	39.0	14.01	40.0	14.09	
52	30.0	10.78	35.0	13.05	35.8	13.37	36.4	13.80	37.0	13.65	37.8	14.45	38.7	14.52	
120%	10	32.4	4.54	38.6	5.54	44.9	6.59	48.0	7.13	50.3	7.44	51.4	7.14	52.6	6.87
	12	32.4	4.63	38.6	5.65	44.9	6.72	48.0	7.26	49.6	7.39	50.7	7.11	51.9	6.82
	14	32.4	4.71	38.6	5.76	44.9	6.85	48.0	7.41	48.9	7.35	50.1	7.07	51.3	7.11
	16	32.4	4.80	38.6	5.88	44.9	6.98	47.7	7.46	48.3	7.36	49.4	7.44	50.6	7.49
	18	32.4	4.89	38.6	5.99	44.9	7.23	47.0	7.71	47.6	7.74	48.7	7.81	50.0	7.89
	19	32.4	4.99	38.6	6.23	44.9	7.77	46.4	8.09	47.0	8.12	48.1	8.19	49.3	8.26
	21	32.4	5.03	38.6	6.45	44.9	8.05	46.0	8.28	46.6	8.31	47.9	8.38	49.0	8.47
	23	32.4	5.38	38.6	6.91	44.9	8.61	45.4	8.64	46.0	8.69	47.1	8.77	48.3	8.85
	25	32.4	5.75	38.6	7.39	44.1	8.99	44.7	9.02	45.3	9.06	46.6	9.15	47.7	9.24
	27	32.4	6.14	38.6	7.90	43.6	9.36	44.1	9.41	44.7	9.46	45.9	9.54	47.0	9.63
	29	32.4	6.55	38.6	8.44	42.9	9.73	43.4	9.79	44.0	9.84	45.1	9.94	46.4	10.02
	31	32.4	6.98	38.6	9.01	42.3	10.13	42.9	10.17	43.4	10.23	44.6	10.33	45.7	10.43
	33	32.4	7.44	38.6	9.62	41.6	10.51	42.1	10.56	42.7	10.61	43.9	10.72	45.0	10.83
	35	32.4	7.92	38.6	10.24	40.9	10.88	41.4	10.94	42.1	11.00	43.3	11.12	44.4	11.23
37	32.4	8.42	38.6	10.91	40.3	11.28	40.9	11.33	41.4	11.39	42.6	11.51	43.7	11.64	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	39	32.4	8.96	38.4	11.52	39.6	11.65	40.1	11.73	40.7	11.79	42.0	11.92	43.1	12.03
	41	31.1	9.40	38.2	11.96	39.4	12.00	39.7	12.06	40.5	12.06	41.7	12.39	42.8	12.46
	43	30.0	9.76	37.9	12.38	39.0	12.39	39.5	12.50	40.0	12.49	41.3	12.85	42.3	12.92
	46	29.2	10.09	36.4	12.84	37.6	12.83	38.1	12.89	38.9	12.88	40.1	13.22	41.0	13.39
	48	28.1	10.45	35.3	13.26	36.8	13.19	37.0	13.30	38.0	13.33	39.0	13.65	39.9	13.85
	50	27.0	10.98	34.1	13.69	35.5	13.62	35.9	13.79	36.7	13.79	37.8	14.00	38.5	14.19
	52	25.8	11.39	33.0	14.05	34.2	14.00	34.5	14.18	35.4	14.12	36.2	14.45	37.1	14.55
	110%	10	29.7	4.12	35.4	5.02	41.1	5.97	44.0	6.45	46.9	6.94	50.4	7.36	51.6
12		29.7	4.20	35.4	5.12	41.1	6.08	44.0	6.58	46.9	7.07	49.9	7.33	50.9	7.07
14		29.7	4.28	35.4	5.21	41.1	6.20	44.0	6.69	46.9	7.20	49.1	7.33	50.3	7.06
16		29.7	4.35	35.4	5.31	41.1	6.31	44.0	6.82	46.9	7.35	48.6	7.38	49.6	7.45
18		29.7	4.44	35.4	5.41	41.1	6.45	44.0	7.01	46.9	7.70	47.9	7.76	49.0	7.83
19		29.7	4.53	35.4	5.53	41.1	6.82	44.0	7.54	46.1	8.08	47.3	8.13	48.3	8.21
21		29.7	4.57	35.4	5.69	41.1	7.07	44.0	7.81	45.9	8.26	46.9	8.32	48.0	8.40
23		29.7	4.79	35.4	6.10	41.1	7.58	44.0	8.38	45.1	8.63	46.3	8.72	47.3	8.79
25		29.7	5.09	35.4	6.52	41.1	8.10	44.0	8.98	44.6	9.01	45.6	9.09	46.7	9.17
27		29.7	5.44	35.4	6.97	41.1	8.67	43.3	9.36	43.9	9.38	45.0	9.47	46.0	9.56
29		29.7	5.81	35.4	7.44	41.1	9.27	42.7	9.73	43.3	9.78	44.3	9.86	45.4	9.95
31		29.7	6.18	35.4	7.93	41.1	9.89	42.0	10.11	42.6	10.16	43.7	10.24	44.7	10.35
33		29.7	6.58	35.4	8.45	40.9	10.43	41.4	10.49	42.0	10.53	43.0	10.64	44.1	10.74
35		29.7	7.00	35.4	9.01	40.3	10.81	40.7	10.87	41.3	10.93	42.3	11.03	43.4	11.13
37		29.7	7.45	35.4	9.59	39.6	11.20	40.1	11.25	40.6	11.31	41.7	11.42	42.7	11.52
39		29.7	7.92	35.4	10.21	38.9	11.58	39.4	11.64	40.0	11.70	41.0	11.81	42.1	11.93
41		29.5	8.34	35.0	10.65	38.5	11.92	39.0	11.98	39.7	12.00	40.8	12.09	41.8	12.35
43		29.1	8.76	34.6	11.00	38.0	12.29	38.7	12.39	39.5	12.45	40.5	12.52	41.3	12.86
46		28.0	9.05	33.2	11.45	37.0	12.67	37.4	12.78	38.3	12.93	39.3	13.01	40.1	13.21
48		26.8	9.48	32.1	11.92	35.8	13.00	37.2	13.05	37.2	13.34	37.8	13.45	39.0	13.62
50	25.4	9.97	31.0	12.37	34.6	13.36	36.0	13.48	36.0	13.75	36.5	13.98	37.8	14.00	
52	24.2	10.38	29.8	12.88	33.4	13.94	34.5	13.96	34.8	14.02	35.4	14.31	36.3	14.40	
100%	10	27.0	3.72	32.1	4.53	37.4	5.35	40.0	5.78	42.6	6.24	47.8	7.06	50.6	7.34
	12	27.0	3.77	32.1	4.59	37.4	5.42	40.0	5.86	42.6	6.36	47.8	7.19	49.8	7.28
	14	27.0	3.84	32.1	4.66	37.4	5.52	40.0	5.96	42.6	6.48	47.8	7.31	49.3	7.22
	16	27.0	3.93	32.1	4.77	37.4	5.64	40.0	6.10	42.6	6.62	47.7	7.47	48.6	7.39
	18	27.0	4.01	32.1	4.88	37.4	5.75	40.0	6.21	42.6	6.75	47.0	7.62	48.0	7.73
	19	27.0	4.08	32.1	4.95	37.4	5.94	40.0	6.54	42.6	7.18	46.3	8.02	47.3	8.14
	21	27.0	4.12	32.1	5.00	37.4	6.14	40.0	6.77	42.6	7.43	46.0	8.29	47.0	8.37
	23	27.0	4.22	32.1	5.34	37.4	6.61	40.0	7.27	42.6	7.99	45.4	8.78	46.3	8.85
	25	27.0	4.49	32.1	5.68	37.4	7.03	40.0	7.74	42.6	8.54	44.7	9.09	45.7	9.18

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)														
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24		
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	27	27.0	4.80	32.1	6.07	37.4	7.54	40.0	8.30	42.6	9.17	44.0	9.41	45.0	9.50	
	29	27.0	5.08	32.1	6.49	37.4	8.06	40.0	8.88	42.4	9.71	43.4	9.87	44.4	9.96	
	31	27.0	5.41	32.1	6.91	37.4	8.60	40.0	9.57	41.9	10.10	42.4	10.27	43.7	10.36	
	33	27.0	5.75	32.1	7.36	37.4	9.16	40.0	10.13	41.1	10.47	42.2	10.56	43.1	10.66	
	35	27.0	6.12	32.1	7.84	37.4	9.77	40.0	10.80	40.4	10.85	41.4	10.95	42.4	11.05	
	37	27.0	6.52	32.1	8.35	37.4	10.41	39.3	11.18	39.9	11.24	40.8	11.32	41.8	11.42	
	39	27.0	6.94	32.1	8.89	37.4	11.08	38.8	11.55	39.0	11.61	40.3	11.69	40.8	11.80	
	41	26.8	7.26	31.8	9.06	37.0	11.35	38.6	11.83	38.6	11.96	40.0	11.98	40.4	12.09	
	43	26.4	7.59	31.4	9.37	36.5	11.72	38.2	12.06	38.1	12.30	39.6	12.35	40.0	12.39	
	46	25.2	7.91	30.2	9.79	35.3	12.01	37.0	12.39	37.0	12.61	38.4	12.69	38.9	12.78	
	48	24.1	8.29	29.1	10.06	34.1	12.34	35.8	12.78	35.6	12.95	37.2	13.05	38.6	13.15	
	50	23.0	8.73	28.0	10.39	33.0	12.66	34.5	13.06	34.3	13.29	36.0	13.36	37.3	13.49	
	52	21.8	9.06	26.7	10.78	31.9	13.00	33.2	13.39	33.1	13.61	34.5	13.72	36.0	13.88	
	90%	10	24.3	3.25	28.9	3.90	33.7	4.57	36.0	5.15	38.3	5.48	43.1	6.28	47.7	7.12
		12	24.3	3.29	28.9	3.95	33.7	4.63	36.0	5.22	38.3	5.59	43.1	6.39	47.7	7.21
14		24.3	3.35	28.9	4.02	33.7	4.71	36.0	5.30	38.3	5.69	43.1	6.50	47.7	7.33	
16		24.3	3.42	28.9	4.11	33.7	4.82	36.0	5.42	38.3	5.81	43.1	6.65	47.6	7.47	
18		24.3	3.50	28.9	4.21	33.7	4.91	36.0	5.52	38.3	5.93	43.1	6.80	47.1	7.74	
19		24.3	3.56	28.9	4.27	33.7	5.07	36.0	5.63	38.3	6.17	43.1	7.31	46.3	8.06	
21		24.3	3.59	28.9	4.31	33.7	5.25	36.0	5.82	38.3	6.38	43.1	7.56	46.0	8.24	
23		24.3	3.68	28.9	4.61	33.7	5.64	36.0	6.26	38.3	6.83	43.1	8.12	45.3	8.67	
25		24.3	3.92	28.9	4.90	33.7	6.00	36.0	6.68	38.3	7.31	43.1	8.68	44.7	9.02	
27		24.3	4.19	28.9	5.24	33.7	6.44	36.0	7.13	38.3	7.83	43.1	9.26	44.0	9.42	
29		24.3	4.43	28.9	5.60	33.7	6.89	36.0	7.62	38.3	8.35	42.6	9.71	43.4	9.80	
31		24.3	4.72	28.9	5.96	33.7	7.34	36.0	8.13	38.3	8.91	41.9	10.06	42.7	10.20	
33		24.3	5.02	28.9	6.35	33.7	7.83	36.0	8.65	38.3	9.48	41.3	10.47	42.1	10.57	
35		24.3	5.34	28.9	6.76	33.7	8.34	36.0	9.22	38.3	10.14	40.6	10.85	41.4	10.95	
37		24.3	5.69	28.9	7.20	33.7	8.89	35.4	9.55	38.3	10.85	39.9	11.24	40.9	11.21	
39	24.3	6.06	28.9	7.67	33.7	9.46	34.9	9.87	38.3	11.50	39.3	11.66	40.1	11.63		
41	24.0	6.38	28.5	7.95	33.4	9.79	34.5	10.12	38.0	11.83	38.9	11.92	39.8	11.95		
43	23.6	6.75	28.2	8.21	33.2	10.01	34.2	10.49	37.8	12.15	38.5	12.30	39.4	12.36		
46	22.2	6.99	27.0	8.58	32.0	10.35	33.0	10.86	36.4	12.49	37.3	12.68	38.2	12.79		
48	21.0	7.31	25.6	8.93	31.6	10.78	31.8	11.25	35.2	12.92	36.1	13.00	37.1	13.01		
50	19.9	7.65	24.3	9.21	30.3	11.06	30.6	11.59	34.0	13.34	35.0	13.43	36.0	13.38		
52	18.6	7.97	23.1	9.56	29.1	11.40	29.4	11.93	32.8	13.69	33.8	13.82	34.6	12.84		
80%	10	21.6	2.95	25.7	3.54	29.9	4.16	32.0	4.48	34.1	4.80	38.3	5.49	42.4	6.37	
	12	21.6	3.00	25.7	3.59	29.9	4.23	32.0	4.57	34.1	4.89	38.3	5.58	42.4	6.32	
	14	21.6	3.06	25.7	3.67	29.9	4.31	32.0	4.64	34.1	4.98	38.3	5.67	42.4	6.46	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
16	21.6	3.10	25.7	3.72	29.9	4.39	32.0	4.73	34.1	5.06	38.3	5.80	42.4	6.69	
18	21.6	3.16	25.7	3.80	29.9	4.49	32.0	4.83	34.1	5.15	38.3	5.93	42.4	7.16	
19	21.6	3.22	25.7	3.87	29.9	4.57	32.0	4.92	34.1	5.27	38.3	6.15	42.4	7.42	
21	21.6	3.24	25.7	3.90	29.9	4.61	32.0	4.98	34.1	5.39	38.3	6.37	42.4	7.94	
23	21.6	3.30	25.7	3.99	29.9	4.83	32.0	5.30	34.1	5.76	38.3	6.81	42.4	8.49	
25	21.6	3.40	25.7	4.23	29.9	5.17	32.0	5.66	34.1	6.15	38.3	7.29	42.4	9.06	
27	21.6	3.62	25.7	4.51	29.9	5.50	32.0	6.04	34.1	6.60	38.3	7.78	42.4	9.38	
29	21.6	3.86	25.7	4.80	29.9	5.86	32.0	6.43	33.9	7.04	38.3	8.31	42.4	9.72	
31	21.6	4.09	25.7	5.11	29.9	6.24	32.0	6.85	33.9	7.50	38.3	8.87	41.7	10.08	
33	21.6	4.35	25.7	5.69	29.9	6.65	32.0	7.30	33.9	7.99	38.3	9.46	41.1	10.44	
35	21.6	4.61	25.7	5.69	29.9	7.07	32.0	7.78	33.9	8.51	38.3	10.10	40.4	10.82	
37	21.6	4.89	25.7	6.13	29.9	7.52	31.4	8.29	33.9	9.06	38.3	10.76	39.9	11.22	
39	21.6	5.18	25.7	6.50	29.9	8.00	31.0	8.83	33.9	9.65	38.3	11.45	39.1	11.64	
41	21.2	5.59	25.4	6.86	29.5	8.35	30.6	9.06	33.5	9.98	38.0	11.83	38.7	11.95	
43	21.0	5.93	25.0	7.29	29.1	8.74	30.2	9.42	33.1	10.34	37.6	12.06	38.2	12.29	
46	19.8	6.37	23.8	7.68	28.0	9.09	29.0	9.78	32.0	10.75	36.3	12.42	37.0	13.63	
48	18.4	6.79	24.4	8.00	26.7	9.45	27.9	10.06	30.8	11.08	35.1	12.76	35.6	13.99	
50	17.2	7.00	23.2	8.32	25.2	9.85	26.5	10.45	29.5	11.45	34.0	13.05	34.3	14.35	
52	16.0	7.36	23.0	8.53	24.0	10.16	24.3	10.86	28.3	11.82	32.6	13.40	33.1	14.73	
70%	10	18.9	2.60	22.5	3.08	26.2	3.59	28.0	3.87	29.8	4.15	33.5	4.71	37.1	5.30
	12	18.9	2.63	22.5	3.13	26.2	3.67	28.0	3.94	29.8	4.22	33.5	4.80	37.1	5.40
	14	18.9	2.68	22.5	3.19	26.2	3.72	28.0	4.00	29.8	4.29	33.5	4.89	37.1	5.50
	16	18.9	2.72	22.5	3.24	26.2	3.80	28.0	4.09	29.8	4.38	33.5	4.98	37.1	5.60
	18	18.9	2.76	22.5	3.30	26.2	3.87	28.0	4.16	29.8	4.45	33.5	5.08	37.1	5.72
	19	18.9	2.81	22.5	3.36	26.2	3.94	28.0	4.23	29.8	4.54	33.5	5.18	37.1	5.88
	21	18.9	2.84	22.5	3.39	26.2	3.97	28.0	4.28	29.8	4.58	33.5	5.24	37.1	6.08
	23	18.9	2.88	22.5	3.45	26.2	4.06	28.0	4.42	29.8	4.82	33.5	5.63	37.1	6.52
	25	18.9	2.94	22.5	3.59	26.2	4.32	28.0	4.73	29.8	5.14	33.5	6.02	37.1	6.97
	27	18.9	3.11	22.5	3.83	26.2	4.61	28.0	5.03	29.8	5.49	33.5	6.43	37.1	7.45
	29	18.9	3.30	22.5	4.06	26.2	4.90	28.0	5.37	29.8	5.83	33.5	6.85	37.1	7.96
	31	18.9	3.49	22.5	4.31	26.2	5.22	28.0	5.70	29.8	6.21	33.5	7.30	37.1	8.48
	33	18.9	3.71	22.5	4.58	26.2	5.56	28.0	6.07	29.8	6.62	33.5	7.78	37.1	9.05
	35	18.9	3.93	22.5	4.86	26.2	5.89	28.0	6.46	29.8	7.04	33.5	8.29	37.1	9.65
	37	18.9	4.15	22.5	5.15	26.2	6.27	27.5	6.87	29.8	7.49	33.5	8.83	37.1	10.27
39	18.9	4.39	22.5	5.46	26.2	6.65	27.1	7.29	29.8	7.96	33.5	9.38	37.1	10.94	
41	18.6	4.75	22.1	5.79	25.9	6.96	26.7	7.66	29.5	8.30	33.1	9.75	36.8	11.31	
43	18.2	5.06	21.8	6.05	25.5	7.30	26.2	7.98	29.1	8.67	32.8	10.06	36.4	11.68	
46	17.0	5.39	20.6	6.38	24.3	7.65	25.1	8.30	28.0	9.01	31.5	10.38	35.2	12.00	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
48	48	15.8	5.76	19.4	6.75	23.2	7.96	24.0	8.59	26.7	9.35	30.2	10.75	34.0	12.32
	50	14.6	6.05	18.2	7.06	22.0	8.31	22.8	8.90	25.4	9.74	29.0	11.06	32.8	12.65
	52	13.2	6.46	17.0	7.40	20.8	8.67	21.5	8.21	24.2	10.03	27.5	11.42	31.4	12.98
60%	10	16.2	2.26	19.3	2.65	22.5	3.07	24.0	3.29	25.5	3.51	28.7	3.97	31.9	4.45
	12	16.2	2.30	19.3	2.69	22.5	3.13	24.0	3.35	25.5	3.56	28.7	4.04	31.9	4.53
	14	16.2	2.33	19.3	2.74	22.5	3.17	24.0	3.40	25.5	3.64	28.7	4.12	31.9	4.61
	16	16.2	2.36	19.3	2.78	22.5	3.23	24.0	3.46	25.5	3.70	28.7	4.19	31.9	4.70
	18	16.2	2.40	19.3	2.82	22.5	3.29	24.0	3.52	25.5	3.77	28.7	4.26	31.9	4.79
	19	16.2	2.43	19.3	2.88	22.5	3.35	24.0	3.59	25.5	3.84	28.7	4.35	31.9	4.89
	21	16.2	2.46	19.3	2.90	22.5	3.38	24.0	3.62	25.5	3.87	28.7	4.39	31.9	4.93
	23	16.2	2.49	19.3	2.95	22.5	3.43	24.0	3.70	25.5	3.94	28.7	4.57	31.9	5.25
	25	16.2	2.53	19.3	3.01	22.5	3.56	24.0	3.87	25.5	4.19	28.7	4.87	31.9	5.60
	27	16.2	2.63	19.3	3.19	22.5	3.80	24.0	4.13	25.5	4.47	28.7	5.19	31.9	5.98
	29	16.2	2.78	19.3	3.38	22.5	4.04	24.0	4.39	25.5	4.76	28.7	5.54	31.9	6.39
	31	16.2	2.95	19.3	3.59	22.5	4.29	24.0	4.67	25.5	5.06	28.7	5.89	31.9	6.79
	33	16.2	3.11	19.3	3.80	22.5	4.55	24.0	4.96	25.5	5.38	28.7	6.27	31.9	7.25
	35	16.2	3.30	19.3	4.03	22.5	4.83	24.0	5.27	25.5	5.72	28.7	6.68	31.9	7.71
	37	16.2	3.49	19.3	4.26	22.5	5.12	23.6	5.59	25.5	6.07	28.7	7.10	31.9	8.21
	39	16.2	3.68	19.3	4.51	22.5	5.43	23.3	5.92	25.5	6.45	28.7	7.54	31.9	8.73
	41	15.9	4.00	19.0	4.85	22.2	5.75	23.0	6.34	25.2	6.78	28.4	7.83	31.5	9.05
	43	15.7	4.35	18.6	5.16	21.9	9.06	22.5	6.78	24.7	7.06	28.0	8.06	31.1	9.36
	46	14.5	4.72	17.4	5.45	20.5	9.38	21.3	7.09	23.2	7.45	26.7	8.39	30.0	9.73
	48	13.3	5.01	16.2	5.79	19.4	9.79	20.2	7.45	22.0	7.79	25.4	8.76	28.7	10.07
50	12.1	5.36	15.1	6.13	18.2	10.09	19.0	7.86	20.8	8.03	24.2	9.07	27.6	10.42	
52	11.0	5.78	14.0	6.48	17.0	10.42	17.9	8.19	19.6	8.39	23.0	9.39	26.4	10.75	
50%	10	13.5	1.95	16.1	2.26	18.7	2.58	20.0	2.75	21.3	2.91	23.9	3.27	26.6	3.65
	12	13.5	1.96	16.1	2.28	18.7	2.62	20.0	2.78	21.3	2.97	23.9	3.33	26.6	3.71
	14	13.5	1.99	16.1	2.31	18.7	2.65	20.0	2.84	21.3	3.01	23.9	3.39	26.6	3.78
	16	13.5	2.02	16.1	2.34	18.7	2.69	20.0	2.88	21.3	3.06	23.9	3.45	26.6	3.84
	18	13.5	2.05	16.1	2.39	18.7	2.74	20.0	2.92	21.3	3.11	23.9	3.51	26.6	3.91
	19	13.5	2.08	16.1	2.42	18.7	2.78	20.0	2.98	21.3	3.17	23.9	3.58	26.6	3.99
	21	13.5	2.10	16.1	2.44	18.7	2.81	20.0	3.00	21.3	3.20	23.9	3.61	26.6	4.03
	23	13.5	2.12	16.1	2.47	18.7	2.85	20.0	3.06	21.3	3.26	23.9	3.67	26.6	4.12
	25	13.5	2.15	16.1	2.52	18.7	2.91	20.0	3.11	21.3	3.36	23.9	3.86	26.6	4.39
	27	13.5	2.20	16.1	2.62	18.7	3.07	20.0	3.32	21.3	3.56	23.9	4.10	26.6	4.69
	29	13.5	2.31	16.1	2.76	18.7	3.26	20.0	3.52	21.2	3.80	23.9	4.37	26.6	4.99
	31	13.5	2.44	16.1	2.92	18.7	3.48	20.0	3.74	21.2	4.03	23.9	4.64	26.6	5.31
33	13.5	2.59	16.1	3.10	18.7	3.67	20.0	3.96	21.2	4.28	23.9	4.93	26.6	5.65	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
35	13.5	2.74	16.1	3.27	18.7	3.87	20.0	4.19	21.2	4.53	23.9	5.24	26.6	5.99	
37	13.5	2.88	16.1	3.46	18.7	4.10	19.6	4.44	21.2	4.80	23.9	5.56	26.6	6.37	
39	13.5	3.04	16.1	3.65	18.7	4.34	19.4	4.70	21.2	5.09	23.9	5.89	26.6	6.77	
41	13.3	3.42	15.8	3.95	18.3	4.67	19.0	5.02	20.8	5.39	23.5	6.10	26.2	7.06	
43	13.0	3.76	15.3	4.34	18.0	5.00	18.7	5.36	20.4	5.73	23.2	6.43	26.0	7.38	
46	11.8	4.05	14.1	4.69	16.9	5.31	16.5	5.75	19.2	6.08	22.1	6.75	24.5	7.79	
48	10.5	4.37	13.0	5.00	15.4	5.63	15.2	6.08	18.1	6.39	21.0	7.09	23.2	8.12	
50	9.3	4.76	11.8	5.32	14.2	5.99	14.0	6.39	17.0	6.78	19.8	7.42	22.0	8.46	
52	8.1	5.10	10.5	5.65	13.1	6.30	12.9	6.78	15.6	7.02	18.5	7.76	20.8	8.79	

16 HP

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	10	39.5	5.97	47.1	7.30	54.6	8.67	56.7	8.87	57.4	8.69	58.8	8.33	60.3	7.94
	12	39.5	6.07	47.1	7.43	54.6	8.85	55.9	8.81	56.7	8.64	58.0	8.26	59.5	8.13
	14	39.5	6.20	47.1	7.57	55.3	8.95	55.3	8.78	55.9	8.59	57.4	8.52	58.8	8.60
	16	39.5	6.30	47.1	7.73	54.5	9.92	54.5	8.85	55.1	8.88	56.6	8.97	58.0	9.06
	18	39.5	6.42	47.1	7.89	53.7	9.25	53.7	9.30	54.5	9.35	55.9	9.44	57.4	9.53
	19	39.5	6.56	47.1	8.39	53.0	9.70	53.0	9.76	53.7	9.81	55.1	9.90	56.6	10.00
	21	39.5	6.74	47.1	8.69	52.7	9.93	52.7	9.98	53.4	10.04	54.8	10.14	56.2	10.23
	23	39.5	7.23	47.1	9.32	51.9	10.38	51.9	10.44	52.6	10.49	54.0	10.59	55.4	10.70
	25	39.5	7.71	47.1	9.98	51.3	10.84	51.3	10.89	51.9	10.96	53.4	11.07	54.8	11.17
	27	39.5	8.24	47.1	10.68	50.5	11.35	50.5	11.36	51.1	11.41	52.6	11.54	54.0	11.66
	29	39.5	8.80	47.1	11.41	49.7	11.75	49.7	11.82	50.5	11.89	51.9	12.01	53.4	12.13
	31	39.5	9.39	46.9	12.08	49.0	12.22	49.0	12.22	49.7	12.34	51.1	12.48	52.6	12.62
	33	39.5	10.00	46.1	12.53	48.2	12.65	48.2	12.74	49.0	12.81	50.5	12.95	51.7	13.11
	35	39.5	10.66	45.3	12.99	47.6	13.14	47.6	13.21	48.2	13.28	49.7	13.44	51.1	13.58
	37	39.5	11.34	44.7	13.46	46.8	13.61	46.8	13.68	47.6	13.77	48.9	13.93	50.3	14.07
	39	39.5	12.08	43.9	13.91	46.1	14.07	46.1	14.15	46.8	14.24	48.2	14.40	49.7	14.57
	41	39.3	12.85	43.6	14.50	45.8	14.62	45.8	14.67	46.7	14.76	47.8	14.89	49.5	14.96
	43	39.0	13.67	43.2	14.98	45.4	15.13	45.6	15.20	46.4	15.34	47.4	15.53	49.2	15.63
46	37.7	14.50	42.0	15.36	44.2	15.56	44.4	15.67	45.2	15.76	46.3	15.86	48.0	15.98	
48	36.5	15.68	40.8	15.76	43.1	16.00	43.2	16.09	44.0	16.23	45.1	16.45	46.9	16.58	
50	35.2	15.93	39.5	16.12	42.0	16.45	42.1	16.64	42.7	16.79	44.0	16.97	45.7	17.06	
52	34.0	16.32	38.2	16.48	40.8	16.96	41.0	17.09	41.3	17.23	42.8	17.45	44.2	17.59	
120%	10	36.5	5.45	43.4	6.65	50.5	7.91	54.0	8.55	56.6	8.92	57.9	8.57	59.1	8.24
	12	36.5	5.55	43.4	6.77	50.5	8.06	54.0	8.71	55.8	8.87	57.1	8.53	58.3	8.19
	14	36.5	5.65	43.4	6.91	50.5	8.22	54.0	8.88	55.0	8.81	56.4	8.48	57.7	8.53
	16	36.5	5.76	43.4	7.05	50.5	8.38	53.7	8.95	54.3	8.83	55.6	8.92	56.9	8.99
	18	36.5	5.86	43.4	7.19	50.5	8.67	52.9	9.25	53.5	9.28	54.8	9.37	56.2	9.46
	19	36.5	5.99	43.4	7.47	50.5	9.32	52.2	9.70	52.9	9.74	54.2	9.83	55.4	9.91
	21	36.5	6.04	43.4	7.73	50.5	9.65	51.7	9.93	52.4	9.97	53.8	10.05	55.1	10.16
	23	36.5	6.46	43.4	8.29	50.5	10.33	51.1	10.37	51.7	10.42	53.0	10.52	54.3	10.61
	25	36.5	6.89	43.4	8.87	49.7	10.79	50.3	10.82	50.9	10.87	52.4	10.98	53.7	10.08
	27	36.5	7.37	43.4	9.48	49.0	11.22	49.7	11.29	50.3	11.34	51.6	11.45	52.9	11.55
	29	36.5	7.85	43.4	10.12	48.2	11.68	48.9	11.75	49.5	11.80	50.8	11.92	52.2	12.03
	31	36.5	8.38	43.4	10.80	47.6	12.15	48.2	12.20	48.9	12.27	50.1	13.39	51.4	12.51
	33	36.5	8.92	43.4	11.54	46.8	12.60	47.4	12.67	48.1	12.72	49.3	12.86	50.6	12.99
	35	36.5	9.49	43.4	12.29	46.0	13.05	46.6	13.12	47.4	13.19	48.7	13.33	50.0	13.47
37	36.5	10.11	43.4	13.09	45.3	13.53	46.0	13.60	46.6	13.67	47.9	13.81	49.2	13.96	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	39	36.5	10.75	43.2	13.82	44.5	13.98	45.2	14.07	45.8	14.14	47.2	14.29	48.5	14.43
	41	36.3	11.50	42.8	14.50	44.2	14.53	44.8	14.63	45.4	14.72	46.5	14.79	48.3	14.86
	43	36.0	12.10	42.5	15.01	44.0	15.12	44.4	15.20	45.2	15.28	46.1	15.32	48.0	15.46
	46	34.6	12.80	41.2	15.58	42.6	15.76	43.2	15.86	44.0	15.93	45.0	16.05	46.7	16.19
	48	33.3	13.40	40.0	16.10	41.3	16.43	42.0	16.52	42.7	16.65	43.7	16.72	45.3	16.85
	50	32.0	14.00	38.6	16.78	40.0	17.01	40.7	17.12	41.5	17.23	42.4	17.35	44.1	17.46
	52	30.3	14.60	37.2	17.35	38.8	17.59	39.5	17.69	40.3	17.82	41.2	17.96	43.0	18.05
	110%	10	33.4	4.94	39.9	6.02	46.3	7.16	49.5	7.73	52.7	8.33	56.7	8.83	58.0
12		33.4	5.04	39.9	6.14	46.3	7.30	49.5	7.89	52.7	8.48	56.1	8.80	57.2	8.48
14		33.4	5.13	39.9	6.25	46.3	7.43	49.5	8.03	52.7	8.64	55.3	8.81	56.6	8.46
16		33.4	5.22	39.9	6.37	46.3	7.57	49.5	8.19	52.7	8.81	54.6	8.85	55.8	8.94
18		33.4	5.32	39.9	6.49	46.3	7.73	49.5	8.41	52.7	9.23	53.8	9.30	55.1	9.39
19		33.4	5.43	39.9	6.63	46.3	8.19	49.5	9.04	51.9	9.69	53.2	9.76	54.3	9.84
21		33.4	5.48	39.9	6.82	46.3	8.48	49.5	9.37	51.6	9.91	52.7	9.98	54.0	10.07
23		33.4	5.74	39.9	7.31	46.3	9.09	49.5	10.05	50.8	10.35	52.1	10.45	53.2	10.54
25		33.4	6.11	39.9	7.82	46.3	9.72	49.5	10.77	50.1	10.80	51.3	10.91	52.6	11.00
27		33.4	6.53	39.9	8.36	46.3	10.40	48.7	11.22	49.3	11.26	50.6	11.36	51.7	11.47
29		33.4	6.96	39.9	8.92	46.3	11.12	48.1	11.68	48.7	11.73	49.8	11.83	51.1	11.94
31		33.4	7.42	39.9	9.51	46.3	11.87	47.2	12.13	47.9	12.18	49.2	12.29	50.3	12.41
33		33.4	7.89	39.9	10.14	46.0	12.51	46.6	12.58	47.2	12.64	48.4	12.76	49.7	12.88
35		33.4	8.39	39.9	10.80	45.3	12.97	45.8	13.04	46.4	13.11	47.6	13.23	48.9	13.35
37		33.4	8.94	39.9	11.50	44.5	13.44	45.2	13.49	45.6	13.56	46.9	13.70	48.1	13.82
39		33.4	9.49	39.9	12.25	43.7	13.89	44.4	13.96	45.0	14.03	46.1	14.17	47.4	14.31
41		33.2	9.97	39.5	12.89	43.5	14.23	44.2	14.46	44.6	14.53	45.7	14.63	47.0	14.78
43		33.0	10.51	39.2	13.45	43.1	14.65	43.9	14.95	44.3	15.06	45.5	15.19	46.5	15.34
46	31.8	11.06	38.0	14.06	42.0	15.03	42.6	15.43	43.1	15.62	44.3	15.78	45.3	15.97	
48	30.5	11.62	36.7	14.79	40.7	15.46	41.2	15.99	42.0	16.21	43.1	16.35	44.1	16.53	
50	29.2	12.18	35.3	15.53	39.5	15.99	40.0	16.42	40.8	16.67	42.0	16.84	43.0	16.97	
52	28.0	12.70	34.0	16.21	38.1	16.52	38.9	16.87	39.4	17.03	40.6	17.23	41.6	17.49	
100%	10	30.4	4.47	36.2	5.43	42.1	6.42	45.0	6.93	47.9	7.49	53.8	8.47	56.9	8.80
	12	30.4	4.53	36.2	5.50	42.1	6.50	45.0	7.02	47.9	7.63	53.8	8.62	56.1	8.74
	14	30.4	4.61	36.2	5.59	42.1	6.62	45.0	7.15	47.9	7.77	53.8	8.77	55.4	8.67
	16	30.4	4.71	36.2	5.72	42.1	6.77	45.0	7.31	47.9	7.95	53.6	8.97	54.6	8.86
	18	30.4	4.81	36.2	5.85	42.1	6.90	45.0	7.45	47.9	8.10	52.9	9.14	54.0	9.28
	19	30.4	4.89	36.2	5.94	42.1	7.13	45.0	7.85	47.9	8.62	52.1	9.62	53.2	9.77
	21	30.4	4.94	36.2	6.00	42.1	7.37	45.0	8.12	47.9	8.91	51.7	9.95	52.9	10.04
	23	30.4	5.06	36.2	6.41	42.1	7.92	45.0	8.73	47.9	9.58	51.1	10.53	52.1	10.62
	25	30.4	5.39	36.2	6.82	42.1	8.43	45.0	9.28	47.9	10.25	50.3	10.91	51.4	11.01

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	27	30.4	5.76	36.2	7.28	42.1	9.04	45.0	9.96	47.9	10.99	49.5	11.29	50.6	11.39
	29	30.4	6.10	36.2	7.78	42.1	9.67	45.0	10.65	47.9	11.65	48.8	11.84	49.9	11.94
	31	30.4	6.49	36.2	8.29	42.1	10.31	45.0	11.48	47.9	12.12	47.7	12.32	49.2	12.43
	33	30.4	6.90	36.2	8.83	42.1	10.99	45.0	12.15	47.9	12.56	47.5	12.67	48.5	12.79
	35	30.4	7.34	36.2	9.40	42.1	11.72	45.0	12.95	46.3	13.01	46.6	13.13	47.7	13.25
	37	30.4	7.82	36.2	10.01	42.1	12.48	45.0	13.42	46.3	13.48	45.9	13.58	47.0	13.70
	39	30.4	8.33	36.2	10.66	42.1	13.29	45.0	13.86	46.3	13.93	45.3	14.03	45.9	14.15
	41	30.2	8.80	36.0	11.13	41.7	13.89	44.6	14.23	46.3	14.49	45.0	14.56	45.6	14.68
	43	29.7	9.31	35.6	11.76	41.3	14.46	44.1	14.69	45.4	14.97	44.7	15.00	45.4	15.12
	46	28.5	9.85	34.3	12.43	40.0	15.19	42.6	15.29	44.2	15.46	43.6	15.53	44.2	15.65
	48	27.2	10.34	33.1	13.00	38.7	15.87	41.3	15.90	43.1	15.93	42.5	16.05	43.1	16.13
	50	26.0	10.86	32.0	13.58	37.4	16.52	40.0	16.61	42.0	16.73	41.3	16.83	42.0	16.96
	52	24.5	11.38	30.5	14.12	36.2	17.21	38.7	17.32	40.7	17.39	40.0	17.45	40.9	17.64
	90%	10	27.3	3.90	32.5	4.68	37.9	5.48	40.5	6.18	43.1	6.58	48.4	7.53	53.7
12		27.3	3.95	32.5	4.74	37.9	5.56	40.5	6.26	43.1	6.70	48.4	7.66	53.7	8.65
14		27.3	4.02	32.5	4.83	37.9	5.65	40.5	6.35	43.1	6.82	48.4	7.80	53.7	8.79
16		27.3	4.11	32.5	4.93	37.9	5.78	40.5	6.50	43.1	6.97	48.4	7.97	53.5	8.96
18		27.3	4.20	32.5	5.05	37.9	5.89	40.5	6.62	43.1	7.11	48.4	8.16	53.0	9.28
19		27.3	4.26	32.5	5.12	37.9	6.08	40.5	6.76	43.1	7.40	48.4	8.77	52.1	9.67
21		27.3	4.31	32.5	5.17	37.9	6.29	40.5	6.98	43.1	7.66	48.4	9.06	51.7	9.89
23		27.3	4.42	32.5	5.53	37.9	6.77	40.5	7.51	43.1	8.20	48.4	9.74	50.9	10.40
25		27.3	4.70	32.5	5.88	37.9	7.20	40.5	8.01	43.1	8.77	48.4	10.41	50.3	10.82
27		27.3	5.02	32.5	6.28	37.9	7.72	40.5	8.55	43.1	9.39	48.4	11.11	49.5	11.30
29		27.3	5.32	32.5	6.71	37.9	8.26	40.5	9.14	43.1	10.02	47.9	11.65	48.9	11.75
31		27.3	5.66	32.5	7.15	37.9	8.81	40.5	9.75	43.1	10.69	47.1	12.07	48.1	12.32
33		27.3	6.02	32.5	7.61	37.9	9.39	40.5	10.37	43.1	11.37	46.4	12.65	47.4	12.67
35		27.3	6.40	32.5	8.11	37.9	10.01	40.5	11.06	43.1	12.17	45.6	13.02	46.6	13.13
37		27.3	6.82	32.5	8.63	37.9	10.66	44.2	11.46	43.1	13.02	44.8	13.49	46.0	13.45
39		27.3	7.26	32.5	9.20	37.9	11.35	43.6	11.84	43.1	13.80	44.2	13.98	45.2	13.95
41		27.1	7.68	32.3	9.60	37.5	11.75	43.5	12.23	42.8	14.42	43.8	14.51	45.0	14.56
43		26.7	8.12	32.0	10.03	37.3	12.16	43.2	12.67	42.1	14.83	43.2	14.96	44.7	15.00
46	25.4	8.56	31.8	10.46	36.1	12.59	42.0	13.02	41.0	15.21	42.0	15.32	43.5	15.36	
48	24.2	9.00	30.5	10.89	35.0	13.05	40.8	13.46	39.7	15.67	41.1	15.79	42.1	15.83	
50	23.0	9.47	29.1	11.31	33.7	13.54	39.6	13.97	38.6	16.13	40.0	16.23	41.0	16.34	
52	21.7	9.97	28.0	11.78	32.3	13.96	38.2	14.45	37.2	16.54	38.9	16.64	39.7	16.75	
80%	10	24.3	3.54	28.9	4.24	33.7	4.99	36.0	5.38	38.3	5.76	43.1	6.58	47.7	7.64
	12	24.3	3.60	28.9	4.31	33.7	5.08	36.0	5.48	38.3	5.87	43.1	6.69	47.7	7.58
	14	24.3	3.67	28.9	4.40	33.7	5.17	36.0	5.57	38.3	5.97	43.1	6.81	47.7	7.75

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
16	24.3	3.72	28.9	4.47	33.7	5.27	36.0	5.67	38.3	6.07	43.1	6.96	47.7	8.03	
18	24.3	3.79	28.9	4.56	33.7	5.39	36.0	5.79	38.3	6.17	43.1	7.12	47.7	8.58	
19	24.3	3.86	28.9	4.64	33.7	5.48	36.0	5.90	38.3	6.32	43.1	7.37	47.7	8.90	
21	24.3	3.89	28.9	4.68	33.7	5.53	36.0	5.97	38.3	6.46	43.1	7.64	47.7	9.52	
23	24.3	3.96	28.9	4.78	33.7	5.79	36.0	6.35	38.3	6.91	43.1	8.17	47.7	10.19	
25	24.3	4.08	28.9	5.08	33.7	6.20	36.0	6.79	38.3	7.38	43.1	8.75	47.7	10.87	
27	24.3	4.35	28.9	5.41	33.7	6.60	36.0	7.24	38.3	7.92	43.1	9.34	47.7	11.25	
29	24.3	4.63	28.9	5.76	33.7	7.03	36.0	7.71	38.3	8.44	43.1	9.97	47.7	11.66	
31	24.3	4.90	28.9	6.13	33.7	7.49	36.0	8.22	38.3	9.00	43.1	10.64	46.9	12.09	
33	24.3	5.22	28.9	6.82	33.7	7.98	36.0	8.76	38.3	9.58	43.1	11.35	46.3	12.52	
35	24.3	5.53	28.9	6.99	33.7	8.48	36.0	9.34	38.3	10.21	43.1	12.11	45.5	12.98	
37	24.3	5.86	28.9	7.35	33.7	9.02	35.4	9.94	38.3	10.87	43.1	12.90	44.8	13.46	
39	24.3	6.21	28.9	7.80	33.7	9.60	34.9	10.59	38.3	11.58	43.1	13.74	44.0	13.96	
41	24.0	6.65	28.6	8.23	33.5	10.01	34.5	10.96	38.0	11.96	42.8	14.13	43.7	14.46	
43	23.7	7.03	28.1	8.65	33.4	10.43	34.1	11.43	37.6	12.54	42.4	14.56	43.5	14.98	
46	22.4	7.45	27.0	9.10	32.1	10.89	33.0	11.89	36.4	12.96	41.2	14.98	42.1	15.42	
48	21.2	7.94	25.6	9.53	31.0	11.23	31.5	12.23	35.2	13.49	40.0	15.52	41.0	15.86	
50	20.0	8.42	24.3	9.98	29.8	11.67	30.2	12.67	34.0	13.00	38.9	15.96	39.7	16.24	
52	18.7	8.89	23.1	10.32	27.3	12.12	29.1	13.01	32.6	13.45	37.5	16.49	38.5	16.76	
70%	10	21.3	3.12	25.3	3.70	29.5	4.31	31.5	4.64	33.5	4.97	37.7	5.65	41.8	6.35
	12	21.3	3.16	25.3	3.75	29.5	4.40	31.5	4.73	33.5	5.06	37.7	5.76	41.8	6.48
	14	21.3	3.21	25.3	3.82	29.5	4.47	31.5	4.80	33.5	5.15	37.7	5.86	41.8	6.60
	16	21.3	3.26	25.3	3.89	29.5	4.56	31.5	4.90	33.5	5.25	37.7	5.97	41.8	6.72
	18	21.3	3.32	25.3	3.96	29.5	4.64	31.5	4.99	33.5	5.34	37.7	6.09	41.8	6.86
	19	21.3	3.37	25.3	4.03	29.5	4.73	31.5	5.08	33.5	5.45	37.7	6.21	41.8	7.05
	21	21.3	3.40	25.3	4.07	29.5	4.76	31.5	5.13	33.5	5.50	37.7	6.28	41.8	7.30
	23	21.3	3.46	25.3	4.14	29.5	4.87	31.5	5.31	33.5	5.78	37.7	6.75	41.8	7.82
	25	21.3	3.53	25.3	4.31	29.5	5.18	31.5	5.67	33.5	6.16	37.7	7.23	41.8	8.36
	27	21.3	3.73	25.3	4.59	29.5	5.53	31.5	6.04	33.5	6.58	37.7	7.71	41.8	9.94
	29	21.3	3.96	25.3	4.87	29.5	5.88	31.5	6.44	33.5	7.00	37.7	8.22	41.8	9.55
	31	21.3	4.19	25.3	5.18	29.5	6.27	31.5	6.84	33.5	7.45	37.7	8.76	41.8	10.18
	33	21.3	4.45	25.3	5.53	29.5	6.67	31.5	7.28	33.5	7.94	37.7	9.34	41.8	10.86
	35	21.3	4.71	25.3	5.88	29.5	7.07	31.5	7.75	33.5	8.45	37.7	9.95	41.8	11.57
	37	21.3	4.97	25.3	6.27	29.5	7.52	31.5	8.24	33.5	8.99	37.7	10.59	41.8	12.32
	39	21.3	5.27	25.3	6.67	29.5	7.98	31.5	8.74	33.5	9.55	37.7	11.26	41.8	13.12
	41	21.0	5.62	25.0	7.03	29.2	8.43	31.2	9.23	33.2	10.01	37.5	11.64	41.5	13.56
43	20.6	5.96	24.6	7.45	29.0	8.89	31.0	9.65	32.9	10.49	37.2	12.00	41.1	14.00	
46	19.4	6.34	23.4	7.96	27.8	9.31	29.5	10.01	31.6	10.98	36.1	12.43	40.0	14.59	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
48	48	18.3	6.72	22.1	8.43	26.4	9.76	28.3	10.43	30.5	11.54	35.0	12.89	38.7	15.13
	50	17.1	7.03	21.0	8.87	25.2	10.15	27.1	10.76	29.3	12.03	33.7	13.42	37.5	15.76
	52	16.0	7.46	19.5	9.35	24.0	10.59	26.0	11.13	28.0	12.56	32.4	13.87	36.4	16.38
60%	10	18.2	2.71	21.7	3.18	25.3	3.68	27.0	3.94	28.7	4.21	32.3	4.76	35.8	5.34
	12	18.2	2.76	21.7	3.23	25.3	3.75	27.0	4.01	28.7	4.28	32.3	4.85	35.8	5.43
	14	18.2	2.79	21.7	3.28	25.3	3.80	27.0	4.08	28.7	4.36	32.3	4.94	35.8	5.53
	16	18.2	2.83	21.7	3.33	25.3	3.87	27.0	4.15	28.7	4.43	32.3	5.03	35.8	5.64
	18	18.2	2.88	21.7	3.39	25.3	3.94	27.0	4.22	28.7	4.52	32.3	5.11	35.8	5.74
	19	18.2	2.91	21.7	3.46	25.3	4.01	27.0	4.31	28.7	4.61	32.3	5.22	35.8	5.86
	21	18.2	2.95	21.7	3.47	25.3	4.05	27.0	4.35	28.7	4.64	32.3	5.27	35.8	5.92
	23	18.2	2.98	21.7	3.54	25.3	4.12	27.0	4.43	28.7	4.73	32.3	5.48	35.8	6.30
	25	18.2	3.04	21.7	3.61	25.3	4.28	27.0	4.64	28.7	5.03	32.3	5.85	35.8	6.72
	27	18.2	3.16	21.7	3.82	25.3	4.56	27.0	4.96	28.7	5.36	32.3	6.23	35.8	7.17
	29	18.2	3.33	21.7	4.05	25.3	4.85	27.0	5.27	28.7	5.71	32.3	6.65	35.8	7.66
	31	18.2	3.54	21.7	4.31	25.3	5.15	27.0	5.60	28.7	6.07	32.3	7.07	35.8	8.15
	33	18.2	3.73	21.7	4.56	25.3	5.46	27.0	5.95	28.7	6.46	32.3	7.52	35.8	8.69
	35	18.2	3.96	21.7	4.83	25.3	5.79	27.0	6.32	28.7	6.86	32.3	8.01	35.8	9.25
	37	18.2	4.19	21.7	5.11	25.3	6.14	27.0	6.70	28.7	7.28	32.3	8.52	35.8	9.84
	39	18.2	4.42	21.7	5.41	25.3	6.51	27.0	7.10	28.7	7.73	32.3	9.04	35.8	10.47
	41	18.0	4.73	21.5	5.73	25.0	6.92	26.4	7.56	28.5	8.03	32.0	9.49	35.4	10.87
	43	17.6	5.03	21.3	6.04	24.6	7.36	26.0	7.95	28.1	8.46	31.6	9.97	35.0	11.35
46	16.4	5.40	20.0	6.46	23.3	7.89	24.6	8.43	27.0	8.89	30.4	10.45	33.7	11.76	
48	15.2	5.76	18.7	6.79	22.1	8.34	23.4	8.87	25.6	9.21	29.8	10.89	32.4	12.21	
50	14.0	6.15	17.5	7.12	21.0	8.86	22.3	9.31	24.3	9.64	28.6	11.38	31.2	12.64	
52	12.6	6.52	16.3	7.46	19.7	9.24	21.1	9.76	23.1	10.03	27.3	11.87	30.0	12.95	
50%	10	15.2	2.34	18.1	2.71	21.1	3.09	22.5	3.30	23.9	3.49	26.9	3.93	29.9	4.38
	12	15.2	2.36	18.1	2.74	21.1	3.14	22.5	3.33	23.9	3.56	26.9	4.00	29.9	4.45
	14	15.2	2.39	18.1	2.78	21.1	3.18	22.5	3.40	23.9	3.61	26.9	4.07	29.9	4.54
	16	15.2	2.43	18.1	2.81	21.1	3.23	22.5	3.46	23.9	3.67	26.9	4.14	29.9	4.61
	18	15.2	2.46	18.1	2.86	21.1	3.28	22.5	3.51	23.9	3.73	26.9	4.21	29.9	4.69
	19	15.2	2.50	18.1	2.90	21.1	3.33	22.5	3.58	23.9	3.80	26.9	4.29	29.9	4.78
	21	15.2	2.51	18.1	2.93	21.1	3.37	22.5	3.60	23.9	3.84	26.9	4.33	29.9	4.83
	23	15.2	2.55	18.1	2.97	21.1	3.42	22.5	3.67	23.9	3.91	26.9	4.40	29.9	4.94
	25	15.2	2.58	18.1	3.02	21.1	3.49	22.5	3.73	23.9	4.03	26.9	4.63	29.9	5.27
	27	15.2	2.64	18.1	3.14	21.1	3.68	22.5	3.98	23.9	4.28	26.9	4.92	29.9	5.62
	29	15.2	2.78	18.1	3.32	21.1	3.91	22.5	4.22	23.9	4.56	26.9	5.24	29.9	5.99
	31	15.2	2.93	18.1	3.51	21.1	4.17	22.5	4.49	23.9	4.83	26.9	5.57	29.9	6.37
	33	15.2	3.11	18.1	3.72	21.1	4.40	22.5	4.75	23.9	5.13	26.9	5.92	29.9	6.77

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
35	15.2	3.28	18.1	3.93	21.1	4.64	22.5	5.03	23.9	5.43	26.9	6.28	29.9	7.19	
37	15.2	3.46	18.1	4.15	21.1	4.92	22.5	5.32	23.9	5.76	26.9	6.67	29.9	7.64	
39	15.2	3.65	18.1	4.38	21.1	5.20	22.5	5.64	23.9	6.11	26.9	7.07	29.9	8.12	
41	14.8	3.86	17.8	4.76	20.7	5.56	22.4	5.96	23.7	6.59	26.7	7.46	29.7	8.52	
43	14.4	4.00	17.4	5.02	20.4	5.89	22.1	6.34	23.3	7.03	26.2	7.86	29.5	8.89	
46	13.2	4.21	16.2	5.43	19.2	6.13	21.0	6.69	22.1	7.49	25.0	8.24	28.3	9.21	
48	12.1	4.56	15.1	5.83	18.0	6.45	19.8	7.01	21.0	7.98	23.8	8.69	27.1	9.69	
50	11.0	4.89	14.0	6.21	16.8	6.79	17.6	7.32	19.7	8.46	22.4	9.03	26.0	10.12	
52	10.1	5.03	12.8	6.64	15.4	7.06	16.3	7.68	18.5	9.01	21.0	9.46	24.5	10.54	

18 HP

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	10	44.2	5.88	52.7	7.20	61.3	8.57	63.5	8.75	64.3	8.57	65.9	8.21	67.5	7.84
	12	44.2	5.99	52.7	7.34	61.3	8.73	62.7	8.70	63.5	8.52	65.0	8.15	66.6	8.03
	14	44.2	6.11	52.7	7.48	61.0	8.84	61.8	8.66	62.6	8.47	64.2	8.41	65.8	8.48
	16	44.2	6.22	52.7	7.63	60.2	8.80	61.0	8.73	61.8	8.77	63.4	8.86	65.0	8.94
	18	44.2	6.35	52.7	7.78	59.4	9.13	60.2	9.18	61.0	9.22	62.6	9.31	64.2	9.40
	19	44.2	6.47	52.7	8.28	58.6	9.58	59.4	9.63	60.2	9.67	61.8	9.77	63.4	9.86
	21	44.2	6.65	52.7	8.58	58.2	9.80	59.0	9.85	59.8	9.90	61.4	10.00	63.0	10.10
	23	44.2	7.12	52.7	9.20	57.4	10.25	58.1	10.30	58.9	10.35	60.5	10.46	62.1	10.56
	25	44.2	7.62	52.7	9.85	56.5	10.70	57.3	10.75	58.1	10.81	59.7	10.92	61.3	11.03
	27	44.2	8.14	52.7	10.54	55.7	11.15	56.5	11.21	57.3	11.26	58.9	11.38	60.5	11.50
	29	44.2	8.69	52.7	11.26	54.9	11.60	55.7	11.66	56.5	11.72	58.1	11.85	59.7	11.97
	31	44.2	9.26	52.5	11.92	54.1	12.05	54.9	12.12	55.7	12.18	57.3	12.32	58.9	12.45
	33	44.2	9.87	51.7	12.37	53.3	12.51	54.0	12.58	54.8	12.65	56.4	12.79	58.0	12.93
	35	44.2	10.52	50.8	12.82	52.4	12.97	53.2	13.04	54.0	13.11	55.6	13.26	57.2	13.41
	37	44.2	11.20	50.0	13.27	51.6	13.43	52.4	13.50	53.2	13.58	54.8	13.74	56.4	13.89
	39	44.2	11.92	49.2	13.73	50.8	13.89	51.6	13.97	52.4	14.05	54.0	14.22	55.6	14.38
	41	43.8	12.26	48.7	14.05	50.4	14.15	51.4	14.30	52.2	14.36	53.6	14.53	55.2	14.76
	43	43.3	12.58	48.4	14.36	50.1	14.43	51.0	14.65	51.9	14.75	53.3	14.85	54.9	15.08
	46	42.0	12.79	47.2	14.78	49.0	14.75	49.8	15.00	50.7	15.06	52.1	15.19	53.5	15.39
	48	40.8	13.09	46.0	15.09	47.8	15.06	48.6	15.32	49.3	15.39	51.0	15.53	52.3	15.73
50	39.6	13.35	44.8	15.40	46.4	15.43	47.3	15.67	48.1	15.79	49.6	15.86	51.1	16.05	
52	38.3	13.74	43.5	15.75	45.1	15.78	46.0	15.98	47.0	16.09	48.2	16.18	50.0	16.39	
120%	10	40.8	5.38	48.7	6.57	56.5	7.81	60.5	8.44	63.3	8.79	64.7	8.46	66.2	8.13
	12	40.8	5.47	48.7	6.69	56.5	7.96	60.5	8.60	62.5	8.75	63.9	8.42	65.4	8.07
	14	40.8	5.58	48.7	6.82	56.5	8.11	60.5	8.77	61.6	8.71	63.1	8.36	64.6	8.42
	16	40.8	5.68	48.7	6.95	56.5	8.27	60.1	8.83	60.8	8.72	62.3	8.80	63.8	8.88
	18	40.8	5.79	48.7	7.09	56.5	8.55	59.3	9.13	60.0	9.17	61.5	9.25	62.9	9.33
	19	40.8	5.91	48.7	7.37	56.5	9.19	58.4	9.57	59.2	9.61	60.6	9.70	62.1	9.79
	21	40.8	5.97	48.7	7.63	56.5	9.52	58.0	9.79	58.8	9.84	60.2	9.93	61.7	10.02
	23	40.8	6.37	48.7	8.18	56.5	10.19	57.2	10.24	57.9	10.29	59.4	10.38	60.9	10.48
	25	40.8	6.81	48.7	8.75	55.6	10.64	56.4	10.69	57.1	10.74	58.6	10.84	60.1	10.94
	27	40.8	7.27	48.7	9.36	54.8	11.08	55.6	11.14	56.3	11.19	57.8	11.30	59.2	11.41
	29	40.8	7.75	48.7	9.99	54.0	11.53	54.7	11.59	55.5	11.65	57.0	11.76	58.4	11.88
	31	40.8	8.26	48.7	10.67	53.2	11.98	53.9	12.04	54.7	12.10	56.1	12.22	57.6	12.34
	33	40.8	8.80	48.7	11.38	52.4	12.43	53.1	12.50	53.8	12.56	55.3	12.69	56.8	12.82
	35	40.8	9.37	48.7	12.13	51.6	12.89	52.3	12.95	53.0	13.02	54.5	13.16	56.0	13.29
	37	40.8	9.97	48.7	12.93	50.7	13.34	51.5	13.41	52.2	13.48	53.7	13.63	55.1	13.77

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	39	40.8	10.61	48.7	13.65	49.9	13.80	50.6	13.88	51.4	13.95	52.9	14.10	54.3	14.25
	41	40.4	10.97	48.3	13.98	49.6	14.12	50.3	14.20	51.0	14.30	52.5	14.36	54.0	14.56
	43	40.1	11.29	47.1	14.30	49.1	14.45	49.9	14.53	50.5	14.79	52.3	14.85	53.6	14.89
	46	39.0	11.62	46.0	14.65	48.0	14.77	48.3	14.86	49.3	15.12	51.1	15.20	52.2	15.23
	48	38.8	11.98	44.6	14.97	46.7	15.09	47.1	15.17	48.0	15.46	50.0	15.59	51.0	15.63
	50	37.5	12.33	43.2	15.29	46.2	15.40	46.0	15.49	46.7	15.79	48.7	15.95	49.6	16.00
	52	36.1	12.69	42.0	15.63	45.0	15.76	44.8	15.86	45.3	16.12	47.2	16.28	48.3	16.42
	10	37.4	4.88	44.6	5.95	51.8	7.06	55.4	7.63	59.0	8.21	63.6	8.72	65.0	8.41
12	37.4	4.97	44.6	6.06	51.8	7.19	55.4	7.78	59.0	8.37	62.8	8.67	64.1	8.36	
14	37.4	5.06	44.6	6.17	51.8	7.33	55.4	7.93	59.0	8.53	62.0	8.63	63.3	8.36	
16	37.4	5.16	44.6	6.29	51.8	7.47	55.4	8.08	59.0	8.69	61.2	8.74	62.5	8.81	
18	37.4	5.25	44.6	6.41	51.8	7.62	55.4	8.30	59.0	9.11	60.3	9.19	61.7	9.26	
19	37.4	5.36	44.6	6.54	51.8	8.08	55.4	8.92	58.2	9.55	59.5	9.63	60.9	9.72	
21	37.4	5.41	44.6	6.74	51.8	8.37	55.4	9.25	57.8	9.78	59.1	9.86	60.5	9.94	
23	37.4	5.66	44.6	7.22	51.8	8.97	55.4	9.91	56.9	10.22	58.3	10.31	59.6	10.40	
25	37.4	6.05	44.6	7.72	51.8	9.60	55.4	10.62	56.1	10.67	57.5	10.76	58.8	10.86	
27	37.4	6.45	44.6	8.24	51.8	10.27	54.6	11.07	55.3	11.12	56.6	11.22	58.0	11.32	
29	37.4	6.87	44.6	8.80	51.8	10.97	53.8	11.51	54.5	11.57	55.8	11.67	57.2	11.78	
31	37.4	7.32	44.6	9.39	51.8	11.72	53.0	11.96	53.7	12.02	55.0	12.13	56.4	12.24	
33	37.4	7.79	44.6	10.01	51.5	12.36	52.2	12.41	52.8	12.47	54.2	12.59	55.5	12.71	
35	37.4	8.29	44.6	10.66	50.7	12.80	51.3	12.87	52.0	12.93	53.4	13.05	54.7	13.18	
37	37.4	8.81	44.6	11.35	49.8	13.26	50.5	13.32	51.2	13.39	52.5	13.52	53.9	13.65	
39	37.4	9.37	44.6	12.09	49.0	13.71	49.7	13.78	50.4	13.85	51.7	13.99	53.1	14.12	
41	37.0	9.69	44.2	12.36	48.6	14.05	49.3	14.09	50.0	14.19	51.5	14.35	52.8	14.48	
43	36.5	10.00	43.9	12.79	48.3	14.36	49.0	14.43	49.7	14.50	51.2	14.69	52.4	14.85	
46	35.3	10.32	42.5	13.12	47.1	14.77	47.8	14.80	48.5	14.82	50.0	15.02	51.0	15.19	
48	34.1	10.65	41.3	13.45	46.0	15.09	46.5	15.16	47.3	15.15	48.9	15.36	49.6	15.53	
50	33.0	10.99	40.0	13.79	44.6	15.42	44.2	15.53	46.2	15.60	47.6	15.75	48.3	15.90	
52	31.8	11.33	38.8	14.05	43.2	15.73	43.0	15.79	45.0	15.96	45.3	16.07	47.0	16.32	
110%	10	34.0	4.40	40.6	5.34	47.1	6.33	50.4	6.84	53.7	7.35	60.2	8.40	63.7	8.69
	12	34.0	4.48	40.6	5.44	47.1	6.45	50.4	6.96	53.7	7.49	60.2	8.56	62.9	8.65
	14	34.0	4.56	40.6	5.54	47.1	6.57	50.4	7.10	53.7	7.63	60.2	8.72	62.1	8.60
	16	34.0	4.64	40.6	5.64	47.1	6.70	50.4	7.24	53.7	7.78	60.0	8.84	61.3	8.75
	18	34.0	4.73	40.6	5.75	47.1	6.83	50.4	7.38	53.7	7.94	59.2	9.12	60.4	9.19
	19	34.0	4.82	40.6	5.87	47.1	7.03	50.4	7.75	53.7	8.50	58.4	9.57	59.6	9.64
	21	34.0	4.87	40.6	5.92	47.1	7.28	50.4	8.03	53.7	8.81	58.0	9.79	59.2	9.87
	23	34.0	4.99	40.6	6.32	47.1	7.80	50.4	8.60	53.7	9.45	57.2	10.24	58.4	10.32
	25	34.0	5.33	40.6	6.75	47.1	8.35	50.4	9.21	53.7	10.12	56.3	10.68	57.6	10.77
100%	10	34.0	4.40	40.6	5.34	47.1	6.33	50.4	6.84	53.7	7.35	60.2	8.40	63.7	8.69
	12	34.0	4.48	40.6	5.44	47.1	6.45	50.4	6.96	53.7	7.49	60.2	8.56	62.9	8.65
	14	34.0	4.56	40.6	5.54	47.1	6.57	50.4	7.10	53.7	7.63	60.2	8.72	62.1	8.60
	16	34.0	4.64	40.6	5.64	47.1	6.70	50.4	7.24	53.7	7.78	60.0	8.84	61.3	8.75
	18	34.0	4.73	40.6	5.75	47.1	6.83	50.4	7.38	53.7	7.94	59.2	9.12	60.4	9.19
	19	34.0	4.82	40.6	5.87	47.1	7.03	50.4	7.75	53.7	8.50	58.4	9.57	59.6	9.64
	21	34.0	4.87	40.6	5.92	47.1	7.28	50.4	8.03	53.7	8.81	58.0	9.79	59.2	9.87
	23	34.0	4.99	40.6	6.32	47.1	7.80	50.4	8.60	53.7	9.45	57.2	10.24	58.4	10.32
	25	34.0	5.33	40.6	6.75	47.1	8.35	50.4	9.21	53.7	10.12	56.3	10.68	57.6	10.77

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	27	34.0	5.68	40.6	7.21	47.1	8.92	50.4	9.85	53.7	10.82	55.5	11.13	56.7	11.22
	29	34.0	6.05	40.6	7.69	47.1	9.53	50.4	10.52	53.5	11.49	54.7	11.58	55.9	11.68
	31	34.0	6.44	40.6	8.19	47.1	10.16	50.4	11.23	52.7	11.94	53.9	12.04	55.1	12.14
	33	34.0	6.84	40.6	8.72	47.1	10.84	50.4	11.98	51.8	12.39	53.1	12.49	54.3	12.60
	35	34.0	7.27	40.6	9.29	47.1	11.55	50.4	12.78	51.0	12.84	52.2	12.95	53.5	13.06
	37	34.0	7.73	40.6	9.88	47.1	12.31	49.6	13.23	50.2	13.29	51.4	13.41	52.6	13.53
	39	34.0	8.21	40.6	10.51	47.1	13.11	48.8	13.68	49.4	13.74	50.6	13.87	51.8	14.00
	41	33.6	8.59	40.3	11.13	46.8	13.68	48.6	14.25	49.0	14.32	50.1	14.40	51.3	14.56
	43	33.4	9.06	40.0	11.68	46.4	14.35	48.2	14.80	48.7	14.96	49.7	14.99	51.1	15.07
	46	32.2	9.58	38.8	12.32	45.2	14.92	47.0	15.38	47.5	15.60	48.5	15.56	50.0	15.62
	48	31.1	10.10	37.6	12.85	44.0	15.53	45.8	16.00	46.3	16.23	47.2	16.10	48.8	16.05
	50	30.0	10.66	36.3	13.50	42.9	16.05	44.6	16.58	45.2	16.80	46.0	16.70	47.4	16.58
	52	28.8	11.23	25.2	14.06	41.7	16.59	43.2	17.09	44.0	17.43	44.5	17.23	46.2	17.09
	90%	10	30.6	3.90	36.5	4.71	42.4	5.56	45.4	6.00	48.3	6.45	54.2	7.36	60.1
12		30.6	3.97	36.5	4.79	42.4	5.66	45.4	6.11	48.3	6.57	54.2	7.50	60.1	8.46
14		30.6	4.04	36.5	4.88	42.4	5.77	45.4	6.22	48.3	6.69	54.2	7.65	60.1	8.62
16		30.6	4.11	36.5	4.97	42.4	5.88	45.4	6.34	48.3	6.82	54.2	7.80	60.0	8.76
18		30.6	4.18	36.5	5.06	42.4	5.99	45.4	6.47	48.3	6.96	54.2	7.95	59.2	9.03
19		30.6	4.26	36.5	5.16	42.4	6.11	45.4	6.60	48.3	7.22	54.2	8.54	58.4	9.47
21		30.6	4.30	36.5	5.21	42.4	6.22	45.4	6.83	48.3	7.47	54.2	8.85	58.0	9.69
23		30.6	4.38	36.5	5.43	42.4	6.65	45.4	7.31	48.3	8.01	54.2	9.49	57.1	10.13
25		30.6	4.61	36.5	5.79	42.4	7.11	45.4	7.82	48.3	8.57	54.2	10.17	56.3	10.58
27		30.6	4.91	36.5	6.18	42.4	7.59	45.4	8.36	48.3	9.16	54.2	10.88	55.5	11.02
29		30.6	5.23	36.5	6.58	42.4	8.10	45.4	8.92	48.3	9.78	53.6	11.38	54.7	11.47
31		30.6	5.56	36.5	7.01	42.4	8.64	45.4	9.52	48.3	10.44	52.8	11.83	53.9	11.92
33		30.6	5.90	36.5	7.46	42.4	9.20	45.4	10.15	48.3	11.14	51.9	12.27	53.0	12.37
35		30.6	6.27	36.5	7.93	42.4	9.80	45.4	10.81	48.3	11.87	51.1	12.72	52.2	12.82
37		30.6	6.65	36.5	8.43	42.4	10.43	45.4	11.51	48.3	12.65	50.3	13.17	51.4	13.27
39		30.6	7.06	36.5	8.96	42.4	11.10	45.4	12.26	48.3	13.48	49.5	13.62	50.6	13.73
41		30.3	7.52	36.4	9.40	42.2	11.52	45.2	12.68	48.0	13.95	49.3	14.06	50.3	14.20
43		30.0	7.96	36.0	9.84	41.9	11.96	45.0	12.13	46.8	14.40	49.0	14.49	50.0	14.65
46	28.7	8.43	34.6	10.35	40.5	12.40	43.7	12.58	45.4	14.86	47.6	14.95	48.7	15.09	
48	27.5	8.89	33.4	10.79	39.4	12.85	42.5	13.00	44.2	15.35	46.5	15.46	47.5	15.52	
50	26.4	9.40	32.2	11.23	38.2	13.26	41.3	13.45	43.0	15.79	45.3	15.98	46.4	15.98	
52	25.0	9.87	31.0	11.69	37.0	13.72	40.0	13.96	41.5	16.23	44.0	16.45	45.0	16.40	
80%	10	27.2	3.43	32.5	4.11	37.7	4.83	40.3	5.20	42.9	5.58	48.2	6.36	53.4	7.17
	12	27.2	3.49	32.5	4.18	37.7	4.91	40.3	5.29	42.9	5.68	48.2	6.48	53.4	7.31
	14	27.2	3.54	32.5	4.25	37.7	5.00	40.3	5.39	42.9	5.79	48.2	6.61	53.4	7.45

GREEN-GRV 4 Outdoor unit

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	16	27.2	3.60	32.5	4.33	37.7	5.10	40.3	5.50	42.9	5.90	48.2	6.74	53.4	7.59
	18	27.2	3.67	32.5	4.41	37.7	5.19	40.3	5.60	42.9	6.02	48.2	6.87	53.4	7.74
	19	27.2	3.73	32.5	4.49	37.7	5.30	40.3	5.71	42.9	6.14	48.2	7.12	53.4	8.28
	21	27.2	3.76	32.5	4.53	37.7	5.35	40.3	5.77	42.9	6.26	48.2	7.37	53.4	8.58
	23	27.2	3.83	32.5	4.62	37.7	5.61	40.3	6.14	42.9	6.70	48.2	7.90	53.4	9.20
	25	27.2	3.96	32.5	4.92	37.7	5.99	40.3	6.56	42.9	7.17	48.2	8.45	53.4	9.85
	27	27.2	4.21	32.5	5.24	37.7	6.39	40.3	7.01	42.9	7.65	48.2	9.04	53.4	10.54
	29	27.2	4.47	32.5	5.58	37.7	6.81	40.3	7.47	42.9	8.17	48.2	9.65	53.4	11.26
	31	27.2	4.75	32.5	5.93	37.7	7.25	40.3	7.96	42.9	8.71	48.2	10.30	52.6	11.70
	33	27.2	5.04	32.5	6.31	37.7	7.72	40.3	8.48	42.9	9.28	48.2	10.99	51.8	12.14
	35	27.2	5.35	32.5	6.70	37.7	8.21	40.3	9.03	42.9	9.88	48.2	11.71	51.0	12.58
	37	27.2	5.67	32.5	7.11	37.7	8.73	40.3	9.60	42.9	10.52	48.2	12.48	50.1	13.03
	39	27.2	6.01	32.5	7.55	37.7	9.28	40.3	10.22	42.9	11.20	48.2	13.29	49.3	13.47
	41	27.0	6.43	32.2	7.98	37.5	9.69	40.0	10.65	42.5	11.63	48.0	13.73	49.0	13.94
	43	26.6	6.90	31.9	8.45	37.1	10.12	39.6	11.10	42.2	12.04	47.6	14.16	48.6	14.43
	46	25.3	7.35	30.6	8.97	36.0	10.53	38.4	11.58	41.0	12.48	46.4	14.59	47.5	14.86
	48	24.2	7.76	29.3	9.40	34.8	10.97	37.2	12.03	39.6	12.97	45.3	15.00	46.3	15.32
	50	23.0	8.12	28.0	9.85	33.5	11.40	36.1	12.45	38.4	13.45	44.1	15.46	45.2	15.78
52	21.8	8.58	26.6	10.29	32.2	11.87	35.0	12.96	37.1	13.97	43.0	15.95	44.0	16.26	
70%	10	23.8	2.99	28.4	3.55	33.0	4.14	35.3	4.45	37.6	4.76	42.2	5.41	46.8	6.09
	12	23.8	3.03	28.4	3.60	33.0	4.21	35.3	4.53	37.6	4.85	42.2	5.51	46.8	6.20
	14	23.8	3.08	28.4	3.66	33.0	4.28	35.3	4.61	37.6	4.94	42.2	5.62	46.8	6.32
	16	23.8	3.13	28.4	3.73	33.0	4.36	35.3	4.69	37.6	5.03	42.2	5.72	46.8	6.44
	18	23.8	3.18	28.4	3.79	33.0	4.44	35.3	4.78	37.6	5.13	42.2	5.84	46.8	6.57
	19	23.8	3.23	28.4	3.86	33.0	4.53	35.3	4.87	37.6	5.22	42.2	5.95	46.8	6.75
	21	23.8	3.26	28.4	3.90	33.0	4.57	35.3	4.92	37.6	5.28	42.2	6.05	46.8	6.99
	23	23.8	3.32	28.4	3.97	33.0	4.66	35.3	5.09	37.6	5.53	42.2	6.47	46.8	7.49
	25	23.8	3.38	28.4	4.13	33.0	4.97	35.3	5.43	37.6	5.90	42.2	6.92	46.8	8.01
	27	23.8	3.57	28.4	4.39	33.0	5.30	35.3	5.79	37.6	6.30	42.2	7.39	46.8	8.56
	29	23.8	3.79	28.4	4.67	33.0	5.64	35.3	6.17	37.6	6.71	42.2	7.88	46.8	9.14
	31	23.8	4.02	28.4	4.96	33.0	6.00	35.3	6.56	37.6	7.15	42.2	8.40	46.8	9.75
	33	23.8	4.26	28.4	5.26	33.0	6.38	35.3	6.98	37.6	7.61	42.2	8.95	46.8	10.40
	35	23.8	4.51	28.4	5.58	33.0	6.78	35.3	7.42	37.6	8.09	42.2	9.53	46.8	11.09
	37	23.8	4.77	28.4	5.92	33.0	7.20	35.3	7.89	37.6	8.61	42.2	10.14	46.8	11.81
39	23.8	5.05	28.4	6.28	33.0	7.64	35.3	8.38	37.6	9.15	42.2	10.80	46.8	12.58	
41	23.6	5.36	28.1	6.69	32.7	8.03	35.0	8.85	37.4	9.56	41.9	11.24	46.5	12.97	
43	23.3	5.85	27.6	7.10	32.3	8.49	34.6	9.30	37.1	10.00	41.5	11.68	46.1	13.42	
46	22.1	6.29	26.4	7.53	31.2	8.96	33.5	9.75	36.0	10.45	40.2	12.10	45.0	13.86	

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
48	48	21.0	6.73	25.2	7.97	30.1	9.42	32.3	10.16	34.6	10.97	39.1	12.59	43.7	14.30
	50	19.8	7.16	24.1	8.41	29.0	9.87	31.0	10.59	33.3	11.38	38.0	13.02	42.5	14.72
	52	18.5	7.58	23.0	8.86	27.8	10.36	29.7	10.98	32.1	11.84	36.7	13.46	41.1	15.15
60%	10	20.4	2.57	24.3	3.02	28.3	3.50	30.2	3.74	32.2	4.00	36.1	4.52	40.1	5.07
	12	20.4	2.61	24.3	3.07	28.3	3.55	30.2	3.81	32.2	4.07	36.1	4.60	40.1	5.16
	14	20.4	2.65	24.3	3.12	28.3	3.61	30.2	3.87	32.2	4.14	36.1	4.68	40.1	5.25
	16	20.4	2.69	24.3	3.17	28.3	3.68	30.2	3.94	32.2	4.21	36.1	4.77	40.1	5.35
	18	20.4	2.73	24.3	3.22	28.3	3.74	30.2	4.01	32.2	4.29	36.1	4.86	40.1	5.46
	19	20.4	2.77	24.3	3.27	28.3	3.81	30.2	4.08	32.2	4.37	36.1	4.96	40.1	5.56
	21	20.4	2.79	24.3	3.30	28.3	3.84	30.2	4.12	32.2	4.41	36.1	5.00	40.1	5.62
	23	20.4	2.84	24.3	3.36	28.3	3.91	30.2	4.20	32.2	4.50	36.1	5.20	40.1	5.97
	25	20.4	2.89	24.3	3.42	28.3	4.07	30.2	4.41	32.2	4.78	36.1	5.55	40.1	6.38
	27	20.4	2.99	24.3	3.63	28.3	4.33	30.2	4.70	32.2	5.09	36.1	5.92	40.1	6.81
	29	20.4	3.17	24.3	3.85	28.3	4.60	30.2	5.00	32.2	5.42	36.1	6.31	40.1	7.27
	31	20.4	3.36	24.3	4.08	28.3	4.88	30.2	5.31	32.2	5.76	36.1	6.71	40.1	7.74
	33	20.4	3.55	24.3	4.33	28.3	5.19	30.2	5.64	32.2	6.12	36.1	7.14	40.1	8.25
	35	20.4	3.76	24.3	4.58	28.3	5.50	30.2	5.99	32.2	6.51	36.1	7.60	40.1	8.78
	37	20.4	3.97	24.3	4.85	28.3	5.83	30.2	6.36	32.2	6.91	36.1	8.08	40.1	9.34
	39	20.4	4.19	24.3	5.14	28.3	6.18	30.2	6.75	32.2	7.33	36.1	8.58	40.1	9.93
	41	20.2	4.64	24.0	5.58	28.0	6.59	30.0	7.19	31.8	7.76	35.8	9.00	39.7	10.35
	43	19.8	5.03	23.6	5.96	27.6	7.03	29.6	7.65	31.5	8.19	35.4	9.42	39.5	10.79
	46	18.5	5.47	22.4	6.41	26.4	7.48	28.4	8.09	30.3	8.65	34.2	9.86	38.3	10.23
	48	17.3	5.98	21.3	6.86	25.2	7.96	27.2	8.56	29.2	9.07	33.1	10.27	37.2	10.67
50	16.1	6.43	20.0	7.30	24.0	8.43	26.0	9.00	28.1	9.49	32.0	10.69	36.1	11.09	
52	15.0	6.89	18.7	7.72	22.6	8.89	24.6	9.42	27.0	9.96	30.8	11.10	35.0	11.52	
50%	10	17.0	2.19	20.3	2.54	23.6	2.90	25.2	3.09	26.8	3.29	30.1	3.69	33.4	4.11
	12	17.0	2.22	20.3	2.57	23.6	2.95	25.2	3.14	26.8	3.34	30.1	3.75	33.4	4.19
	14	17.0	2.25	20.3	2.61	23.6	2.99	25.2	3.19	26.8	3.40	30.1	3.82	33.4	4.26
	16	17.0	2.28	20.3	2.65	23.6	3.04	25.2	3.24	26.8	3.45	30.1	3.89	33.4	4.34
	18	17.0	2.31	20.3	2.69	23.6	3.09	25.2	3.30	26.8	3.51	30.1	3.96	33.4	4.42
	19	17.0	2.34	20.3	2.73	23.6	3.14	25.2	3.36	26.8	3.57	30.1	4.03	33.4	4.50
	21	17.0	2.36	20.3	2.75	23.6	3.17	25.2	3.38	26.8	3.61	30.1	4.07	33.4	4.54
	23	17.0	2.40	20.3	2.80	23.6	3.22	25.2	3.45	26.8	3.67	30.1	4.14	33.4	4.65
	25	17.0	2.43	20.3	2.84	23.6	3.28	25.2	3.52	26.8	3.78	30.1	4.35	33.4	4.96
	27	17.0	2.47	20.3	2.95	23.6	3.46	25.2	3.74	26.8	4.02	30.1	4.63	33.4	5.28
	29	17.0	2.62	20.3	3.12	23.6	3.67	25.2	3.97	26.8	4.28	30.1	4.93	33.4	5.62
	31	17.0	2.76	20.3	3.30	23.6	3.90	25.2	4.21	26.8	4.54	30.1	5.24	33.4	5.98
	33	17.0	2.92	20.3	3.50	23.6	4.13	25.2	4.47	26.8	4.82	30.1	5.56	33.4	6.36

Combination (%) (Capacity index)	Outdoor temp.(°C DB)	Indoor temperature(°C)													
		DB:20.8,WB:14		DB:23.3,WB:16		DB:25.8,WB:18		DB:27,WB:19		DB:28.2,WB:20		DB:30.7,WB:22		DB:32,WB:24	
		TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
		kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
35	17.0	3.08	20.3	3.70	23.6	4.37	25.2	4.73	26.8	5.11	30.1	5.90	33.4	6.76	
37	17.0	3.25	20.3	3.91	23.6	4.63	25.2	5.01	26.8	5.41	30.1	6.26	33.4	7.18	
39	17.0	3.42	20.3	4.13	23.6	4.90	25.2	5.31	26.8	5.74	30.1	6.65	33.4	7.63	
41	16.8	3.83	20.1	4.53	23.4	5.32	24.8	5.76	26.5	6.18	29.6	7.03	33.2	8.06	
43	16.5	4.26	19.8	4.97	23.1	5.75	24.3	6.19	26.1	6.63	29.2	7.48	32.8	8.48	
46	15.3	4.69	18.6	5.42	22.0	6.17	23.2	6.63	25.0	7.02	28.1	8.98	31.5	9.87	
48	14.2	5.12	17.4	5.86	20.8	6.59	22.0	7.05	23.8	7.45	27.0	9.45	30.3	10.32	
50	13.0	5.56	16.3	6.30	19.5	7.02	20.8	7.52	22.6	7.96	25.6	9.96	29.2	10.76	
52	12.2	6.00	15.1	6.75	18.2	7.46	19.7	7.96	21.2	8.35	24.3	10.43	28.0	11.21	

6.4 Heating Capacity table

8 HP

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	-14.7	-15	13.37	5.39	13.37	5.51	13.37	5.62	12.83	5.38	12.30	5.13	11.24	4.64
	-12.6	-13	13.96	5.48	13.96	5.60	13.96	5.72	13.41	5.47	12.85	5.21	11.74	4.71
	-10.5	-11	14.55	5.57	14.55	5.69	14.55	5.81	13.98	5.55	13.40	5.30	12.24	4.79
	-9.5	-10	16.34	5.61	16.34	5.73	16.34	5.85	15.69	5.60	15.04	5.34	13.74	4.83
	-8.5	-9.1	17.23	5.66	17.23	5.78	17.23	5.90	16.54	5.64	15.86	5.38	14.49	4.86
	-7	-7.6	17.82	5.72	17.82	5.84	17.82	5.96	17.11	5.70	16.41	5.44	14.99	4.92
	-5	-5.6	18.41	5.80	18.41	5.93	18.41	6.05	17.68	5.79	16.95	5.52	15.49	4.99
	-3	-3.7	20.79	5.89	20.79	6.01	20.79	6.14	19.97	5.87	19.14	5.60	17.49	5.06
	0	-0.7	22.87	6.02	22.87	6.14	22.87	6.27	21.96	6.00	21.05	5.72	19.24	5.17
	3	2.2	25.41	6.14	25.41	6.27	25.41	6.41	24.40	6.13	23.39	5.84	21.38	5.28
	5	4.1	28.70	6.23	28.70	6.36	28.70	6.49	27.56	6.21	26.42	5.93	24.15	5.36
	7	6	29.70	6.31	29.70	6.45	29.70	6.58	28.52	6.29	27.34	6.01	24.99	5.43
	9	7.9	29.70	6.10	29.70	6.23	29.70	6.36	28.52	6.08	27.34	5.80	24.99	5.25
	11	9.8	29.70	5.89	29.70	6.01	29.70	6.14	28.52	5.87	27.34	5.60	24.99	5.06
	13	11.8	29.70	5.68	29.70	5.80	29.70	5.92	28.52	5.66	27.34	5.40	24.99	4.88
15	13.7	29.70	5.47	29.70	5.58	29.70	5.70	28.52	5.45	27.34	5.20	24.99	4.70	
120%	-14.7	-15	13.37	5.55	13.37	5.67	13.37	5.79	12.83	5.53	12.30	5.28	11.24	4.77
	-12.6	-13	13.96	5.64	13.96	5.76	13.96	5.88	13.41	5.63	12.85	5.37	11.74	4.85
	-10.5	-11	14.55	5.73	14.55	5.86	14.55	5.98	13.98	5.72	13.40	5.46	12.24	4.93
	-9.5	-10	16.34	5.78	16.34	5.90	16.34	6.02	15.69	5.76	15.04	5.50	13.74	4.97
	-8.5	-9.1	17.23	5.82	17.23	5.95	17.23	6.07	16.54	5.80	15.86	5.54	14.49	5.01
	-7	-7.6	17.82	5.89	17.82	6.01	17.82	6.14	17.11	5.87	16.41	5.60	14.99	5.06
	-5	-5.6	18.41	5.97	18.41	6.10	18.41	6.23	17.68	5.96	16.95	5.68	15.49	5.14
	-3	-3.7	20.79	6.06	20.79	6.19	20.79	6.32	19.97	6.04	19.14	5.77	17.49	5.21
	0	-0.7	22.87	6.19	22.87	6.33	22.87	6.46	21.96	6.17	21.05	5.89	19.24	5.33
	3	2.2	25.41	6.32	25.41	6.46	25.41	6.59	24.40	6.31	23.39	6.02	21.38	5.44
	5	4.1	28.70	6.41	28.70	6.55	28.70	6.69	27.56	6.39	26.42	6.10	24.15	5.51
	7	6	29.70	6.50	29.70	6.64	29.70	6.78	28.52	6.48	27.34	6.18	24.99	5.59
	9	7.9	29.70	6.28	29.70	6.41	29.70	6.55	28.52	6.26	27.34	5.97	24.99	5.40
	11	9.8	29.70	6.06	29.70	6.19	29.70	6.32	28.52	6.04	27.34	5.77	24.99	5.21
	13	11.8	29.70	5.84	29.70	5.97	29.70	6.09	28.52	5.83	27.34	5.56	24.99	5.03
15	13.7	29.70	5.63	29.70	5.75	29.70	5.87	28.52	5.61	27.34	5.35	24.99	4.84	
110%	-14.7	-15	13.37	5.66	13.37	5.78	13.37	5.90	12.83	5.64	12.30	5.38	11.24	4.87
	-12.6	-13	13.96	5.75	13.96	5.88	13.96	6.00	13.41	5.74	12.85	5.47	11.74	4.95
	-10.5	-11	14.55	5.85	14.55	5.97	14.55	6.10	13.98	5.83	13.40	5.56	12.24	5.03
	-9.5	-10	16.34	5.89	16.34	6.02	16.34	6.14	15.69	5.87	15.04	5.60	13.74	5.07
	-8.5	-9.1	17.23	5.94	17.23	6.06	17.23	6.19	16.54	5.92	15.86	5.65	14.49	5.10
	-7	-7.6	17.82	6.00	17.82	6.13	17.82	6.26	17.11	5.98	16.41	5.71	14.99	5.16
	-5	-5.6	18.41	6.09	18.41	6.22	18.41	6.35	17.68	6.07	16.95	5.80	15.49	5.24
	-3	-3.7	20.79	6.18	20.79	6.31	20.79	6.44	19.97	6.16	19.14	5.88	17.49	5.32
	0	-0.7	22.87	6.31	22.87	6.45	22.87	6.58	21.96	6.30	21.05	6.01	19.24	5.43
	3	2.2	25.41	6.45	25.41	6.59	25.41	6.72	24.40	6.43	23.39	6.13	21.38	5.55
	5	4.1	28.70	6.54	28.70	6.68	28.70	6.82	27.56	6.52	26.42	6.22	24.15	5.62
	7	6	29.70	6.63	29.70	6.77	29.70	6.91	28.52	6.61	27.34	6.30	24.99	5.70
	9	7.9	29.70	6.40	29.70	6.54	29.70	6.68	28.52	6.38	27.34	6.09	24.99	5.51

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	11	9.8	29.70	6.18	29.70	6.31	29.70	6.44	28.52	6.16	27.34	5.88	24.99	5.32
	13	11.8	29.70	5.96	29.70	6.09	29.70	6.21	28.52	5.94	27.34	5.67	24.99	5.12
	15	13.7	29.70	5.74	29.70	5.86	29.70	5.98	28.52	5.72	27.34	5.46	24.99	4.93
100%	-14.7	-15	12.15	5.04	12.15	5.15	12.15	5.25	11.67	5.02	11.19	4.79	10.22	4.33
	-12.6	-13	12.69	5.12	12.69	5.23	12.69	5.34	12.19	5.11	11.68	4.87	10.68	4.40
	-10.5	-11	13.23	5.20	13.23	5.32	13.23	5.43	12.71	5.19	12.18	4.95	11.13	4.48
	-9.5	-10	14.85	5.24	14.85	5.36	14.85	5.47	14.26	5.23	13.67	4.99	12.49	4.51
	-8.5	-9.1	15.66	5.28	15.66	5.40	15.66	5.51	15.04	5.27	14.42	5.03	13.17	4.54
	-7	-7.6	16.20	5.34	16.20	5.46	16.20	5.57	15.56	5.33	14.91	5.08	13.63	4.60
	-5	-5.6	16.74	5.42	16.74	5.54	16.74	5.65	16.08	5.41	15.41	5.16	14.08	4.66
	-3	-3.7	18.90	5.50	18.90	5.62	18.90	5.74	18.15	5.49	17.40	5.23	15.90	4.73
	0	-0.7	20.79	5.62	20.79	5.74	20.79	5.86	19.97	5.60	19.14	5.35	17.49	4.83
	3	2.2	23.10	5.74	23.10	5.86	23.10	5.98	22.18	5.72	21.27	5.46	19.43	4.94
	5	4.1	26.09	5.82	26.09	5.94	26.09	6.07	25.06	5.80	24.02	5.54	21.95	5.00
	7	6	27.00	5.90	27.00	6.02	27.00	6.10	25.93	5.88	24.86	5.61	22.71	5.07
	9	7.9	27.00	5.70	27.00	5.82	27.00	5.94	25.93	5.68	24.86	5.42	22.71	4.90
	11	9.8	27.00	5.50	27.00	5.62	27.00	5.74	25.93	5.49	24.86	5.23	22.71	4.73
	13	11.8	27.00	5.30	27.00	5.42	27.00	5.53	25.93	5.29	24.86	5.05	22.71	4.56
15	13.7	27.00	5.11	27.00	5.22	27.00	5.32	25.93	5.09	24.86	4.86	22.71	4.39	
90%	-14.7	-15	10.94	4.45	10.94	4.54	10.94	4.64	10.50	4.44	10.07	4.23	9.20	3.83
	-12.6	-13	11.42	4.52	11.42	4.62	11.42	4.72	10.97	4.51	10.51	4.30	9.61	3.89
	-10.5	-11	11.91	4.60	11.91	4.69	11.91	4.79	11.43	4.58	10.96	4.37	10.02	3.95
	-9.5	-10	13.37	4.63	13.37	4.73	13.37	4.83	12.83	4.62	12.30	4.41	11.24	3.98
	-8.5	-9.1	14.09	4.67	14.09	4.77	14.09	4.87	13.53	4.65	12.98	4.44	11.86	4.01
	-7	-7.6	14.58	4.72	14.58	4.82	14.58	4.92	14.00	4.70	13.42	4.49	12.27	4.06
	-5	-5.6	15.07	4.79	15.07	4.89	15.07	4.99	14.47	4.77	13.87	4.56	12.67	4.12
	-3	-3.7	17.01	4.86	17.01	4.96	17.01	5.07	16.34	4.84	15.66	4.62	14.31	4.18
	0	-0.7	18.71	4.96	18.71	5.07	18.71	5.18	17.97	4.95	17.23	4.72	15.74	4.27
	3	2.2	20.79	5.07	20.79	5.18	20.79	5.29	19.96	5.05	19.14	4.82	17.49	4.36
	5	4.1	23.48	5.14	23.48	5.25	23.48	5.36	22.55	5.12	21.62	4.89	19.76	4.42
	7	6	24.30	5.21	24.30	5.32	24.30	5.43	23.34	5.19	22.37	4.96	20.44	4.48
	9	7.9	24.30	5.03	24.30	5.14	24.30	5.25	23.34	5.02	22.37	4.79	20.44	4.33
	11	9.8	24.30	4.86	24.30	4.96	24.30	5.07	23.34	4.84	22.37	4.62	20.44	4.18
	13	11.8	24.30	4.68	24.30	4.78	24.30	4.88	23.34	4.67	22.37	4.46	20.44	4.03
15	13.7	24.30	4.51	24.30	4.61	24.30	4.70	23.34	4.50	22.37	4.29	20.44	3.88	
80%	-14.7	-15	9.72	3.89	9.72	3.98	9.72	4.06	9.33	3.88	8.95	3.70	8.18	3.35
	-12.6	-13	10.15	3.96	10.15	4.04	10.15	4.13	9.75	3.95	9.35	3.76	8.54	3.40
	-10.5	-11	10.58	4.02	10.58	4.11	10.58	4.19	10.16	4.01	9.74	3.83	8.90	3.46
	-9.5	-10	11.88	4.05	11.88	4.14	11.88	4.23	11.41	4.04	10.94	3.86	9.99	3.48
	-8.5	-9.1	12.53	4.08	12.53	4.17	12.53	4.26	12.03	4.07	11.53	3.88	10.54	3.51
	-7	-7.6	12.96	4.13	12.96	4.22	12.96	4.31	12.45	4.12	11.93	3.93	10.90	3.55
	-5	-5.6	13.39	4.19	13.39	4.28	13.39	4.37	12.86	4.18	12.33	3.99	11.27	3.60
	-3	-3.7	15.12	4.25	15.12	4.34	15.12	4.43	14.52	4.24	13.92	4.04	12.72	3.66
	0	-0.7	16.63	4.34	16.63	4.44	16.63	4.53	15.97	4.33	15.31	4.13	13.99	3.74
	3	2.2	18.48	4.44	18.48	4.53	18.48	4.62	17.75	4.42	17.01	4.22	15.55	3.81
	5	4.1	20.87	4.50	20.87	4.59	20.87	4.69	20.04	4.48	19.22	4.28	17.56	3.87
	7	6	21.60	4.56	21.60	4.66	21.60	4.75	20.74	4.54	19.89	4.34	18.17	3.92
	9	7.9	21.60	4.40	21.60	4.50	21.60	4.59	20.74	4.39	19.89	4.19	18.17	3.79

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	11	9.8	21.60	4.25	21.60	4.34	21.60	4.43	20.74	4.24	19.89	4.04	18.17	3.66
	13	11.8	21.60	4.10	21.60	4.19	21.60	4.27	20.74	4.09	19.89	3.90	18.17	3.52
	15	13.7	21.60	3.95	21.60	4.03	21.60	4.11	20.74	3.93	19.89	3.75	18.17	3.39
	-14.7	-15	8.51	3.34	8.51	3.41	8.51	3.48	8.17	3.33	7.83	3.17	7.16	2.87
70%	-12.6	-13	8.88	3.39	8.88	3.46	8.88	3.54	8.53	3.38	8.18	3.23	7.47	2.92
	-10.5	-11	9.26	3.45	9.26	3.52	9.26	3.59	8.89	3.44	8.53	3.28	7.79	2.96
	-9.5	-10	10.40	3.47	10.40	3.55	10.40	3.62	9.98	3.46	9.57	3.30	8.75	2.99
	-8.5	-9.1	10.96	3.50	10.96	3.57	10.96	3.65	10.53	3.49	10.09	3.33	9.22	3.01
	-7	-7.6	11.34	3.54	11.34	3.61	11.34	3.69	10.89	3.53	10.44	3.37	9.54	3.04
	-5	-5.6	11.72	3.59	11.72	3.67	11.72	3.74	11.25	3.58	10.79	3.42	9.86	3.09
	-3	-3.7	13.23	3.64	13.23	3.72	13.23	3.80	12.71	3.63	12.18	3.47	11.13	3.13
	0	-0.7	14.55	3.72	14.55	3.80	14.55	3.88	13.98	3.71	13.40	3.54	12.24	3.20
	3	2.2	16.17	3.80	16.17	3.88	16.17	3.96	15.53	3.79	14.89	3.62	13.60	3.27
	5	4.1	18.26	3.85	18.26	3.94	18.26	4.02	17.54	3.84	16.81	3.67	15.37	3.31
	7	6	18.90	3.91	18.90	3.99	18.90	4.07	18.15	3.89	17.40	3.72	15.90	3.36
	9	7.9	18.90	3.78	18.90	3.86	18.90	3.94	18.15	3.76	17.40	3.59	15.90	3.25
	11	9.8	18.90	3.64	18.90	3.72	18.90	3.80	18.15	3.63	17.40	3.47	15.90	3.13
	13	11.8	18.90	3.51	18.90	3.59	18.90	3.66	18.15	3.50	17.40	3.34	15.90	3.02
	15	13.7	18.90	3.38	18.90	3.45	18.90	3.53	18.15	3.37	17.40	3.22	15.90	2.91
	60%	-14.7	-15	7.29	2.83	7.29	2.89	7.29	2.95	7.00	2.82	6.71	2.70	6.13
-12.6		-13	7.61	2.88	7.61	2.94	7.61	3.00	7.31	2.87	7.01	2.74	6.41	2.48
-10.5		-11	7.94	2.93	7.94	2.99	7.94	3.05	7.62	2.92	7.31	2.78	6.68	2.52
-9.5		-10	8.91	2.95	8.91	3.01	8.91	3.08	8.56	2.94	8.20	2.81	7.50	2.54
-8.5		-9.1	9.40	2.97	9.40	3.04	9.40	3.10	9.02	2.96	8.65	2.83	7.90	2.56
-7		-7.6	9.72	3.01	9.72	3.07	9.72	3.13	9.33	3.00	8.95	2.86	8.18	2.58
-5		-5.6	10.04	3.05	10.04	3.11	10.04	3.18	9.65	3.04	9.25	2.90	8.45	2.62
-3		-3.7	11.34	3.09	11.34	3.16	11.34	3.23	10.89	3.08	10.44	2.94	9.54	2.66
0		-0.7	12.47	3.16	12.47	3.23	12.47	3.30	11.98	3.15	11.48	3.01	10.49	2.72
3		2.2	13.86	3.23	13.86	3.30	13.86	3.37	13.31	3.22	12.76	3.07	11.66	2.78
5		4.1	15.65	3.27	15.65	3.34	15.65	3.41	15.03	3.26	14.41	3.11	13.17	2.81
7		6	16.20	3.32	16.20	3.39	16.20	3.46	15.56	3.31	14.91	3.16	13.63	2.85
9		7.9	16.20	3.21	16.20	3.27	16.20	3.34	15.56	3.20	14.91	3.05	13.63	2.76
11		9.8	16.20	3.09	16.20	3.16	16.20	3.23	15.56	3.09	14.91	2.94	13.63	2.66
13		11.8	16.20	2.98	16.20	3.05	16.20	3.11	15.56	2.97	14.91	2.84	13.63	2.57
15		13.7	16.20	2.87	16.20	2.93	16.20	2.99	15.56	2.86	14.91	2.73	13.63	2.47
50%	-14.7	-15	6.08	2.29	6.08	2.34	6.08	2.39	5.83	2.28	5.59	2.18	5.11	1.97
	-12.6	-13	6.35	2.33	6.35	2.38	6.35	2.43	6.09	2.32	5.84	2.21	5.34	2.00
	-10.5	-11	6.62	2.36	6.62	2.41	6.62	2.47	6.35	2.36	6.09	2.25	5.57	2.03
	-9.5	-10	7.43	2.38	7.43	2.43	7.43	2.48	7.13	2.38	6.84	2.27	6.25	2.05
	-8.5	-9.1	7.83	2.40	7.83	2.45	7.83	2.50	7.52	2.39	7.21	2.28	6.59	2.06
	-7	-7.6	8.10	2.43	8.10	2.48	8.10	2.53	7.78	2.42	7.46	2.31	6.81	2.09
	-5	-5.6	8.37	2.46	8.37	2.52	8.37	2.57	8.04	2.46	7.71	2.34	7.04	2.12
	-3	-3.7	9.45	2.50	9.45	2.55	9.45	2.61	9.08	2.49	8.70	2.38	7.95	2.15
	0	-0.7	10.40	2.55	10.40	2.61	10.40	2.66	9.98	2.55	9.57	2.43	8.75	2.20
	3	2.2	11.55	2.61	11.55	2.66	11.55	2.72	11.09	2.60	10.63	2.48	9.72	2.24
	5	4.1	13.05	2.64	13.05	2.70	13.05	2.76	12.53	2.64	12.01	2.51	10.98	2.27
	7	6	13.50	2.68	13.50	2.74	13.50	2.79	12.96	2.67	12.43	2.55	11.36	2.30
9	7.9	13.50	2.59	13.50	2.64	13.50	2.70	12.96	2.58	12.43	2.46	11.36	2.23	

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
11	9.8	13.50	2.50	13.50	2.55	13.50	2.61	12.96	2.49	12.43	2.38	11.36	2.15	
13	11.8	13.50	2.41	13.50	2.46	13.50	2.51	12.96	2.40	12.43	2.29	11.36	2.07	
15	13.7	13.50	2.32	13.50	2.37	13.50	2.42	12.96	2.31	12.43	2.21	11.36	1.99	

10 HP

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
130%	-14.7	-15	15.59	6.66	15.59	6.81	15.59	6.95	14.97	6.64	14.36	6.34	13.12	5.73
	-12.6	-13	16.29	6.77	16.29	6.92	16.29	7.06	15.64	6.75	14.99	6.44	13.70	5.83
	-10.5	-11	16.98	6.88	16.98	7.03	16.98	7.18	16.30	6.86	15.63	6.55	14.28	5.92
	-9.5	-10	19.06	6.94	19.06	7.08	19.06	7.23	18.30	6.92	17.55	6.60	16.03	5.97
	-8.5	-9.1	20.10	6.99	20.10	7.14	20.10	7.29	19.30	6.97	18.50	6.65	16.91	6.01
	-7	-7.6	20.79	7.07	20.79	7.22	20.79	7.37	19.97	7.05	19.14	6.72	17.49	6.08
	-5	-5.6	21.48	7.17	21.48	7.33	21.48	7.48	20.63	7.15	19.78	6.82	18.07	6.17
	-3	-3.7	24.26	7.28	24.26	7.43	24.26	7.59	23.29	7.26	22.33	6.92	20.41	6.26
	0	-0.7	26.68	7.43	26.68	7.59	26.68	7.75	25.62	7.41	24.56	7.07	22.45	6.39
	3	2.2	29.64	7.59	29.64	7.75	29.64	7.92	28.47	7.57	27.29	7.22	24.94	6.53
	5	4.1	33.48	7.70	33.48	7.86	33.48	8.03	32.16	7.67	30.83	7.32	28.17	6.62
	7	6	34.65	7.80	34.65	7.97	34.65	8.13	33.28	7.78	31.90	7.42	29.15	6.71
	9	7.9	34.65	7.54	34.65	7.70	34.65	7.86	33.28	7.52	31.90	7.17	29.15	6.48
	11	9.8	34.65	7.28	34.65	7.43	34.65	7.59	33.28	7.26	31.90	6.92	29.15	6.26
	13	11.8	34.65	7.02	34.65	7.17	34.65	7.32	33.28	6.99	31.90	6.67	29.15	6.03
15	13.7	34.65	6.75	34.65	6.90	34.65	7.04	33.28	6.73	31.90	6.42	29.15	5.81	
120%	-14.7	-15	15.59	6.86	15.59	7.01	15.59	7.15	14.97	6.84	14.36	6.53	13.12	5.90
	-12.6	-13	16.29	6.97	16.29	7.12	16.29	7.27	15.64	6.95	14.99	6.63	13.70	6.00
	-10.5	-11	16.98	7.09	16.98	7.24	16.98	7.39	16.30	7.07	15.63	6.74	14.28	6.09
	-9.5	-10	19.06	7.14	19.06	7.29	19.06	7.45	18.30	7.12	17.55	6.79	16.03	6.14
	-8.5	-9.1	20.10	7.19	20.10	7.35	20.10	7.50	19.30	7.17	18.50	6.84	16.91	6.19
	-7	-7.6	20.79	7.28	20.79	7.43	20.79	7.59	19.97	7.25	19.14	6.92	17.49	6.26
	-5	-5.6	21.48	7.38	21.48	7.54	21.48	7.70	20.63	7.36	19.78	7.02	18.07	6.35
	-3	-3.7	24.26	7.49	24.26	7.65	24.26	7.81	23.29	7.47	22.33	7.13	20.41	6.44
	0	-0.7	26.68	7.65	26.68	7.82	26.68	7.98	25.62	7.63	24.56	7.28	22.45	6.58
	3	2.2	29.64	7.82	29.64	7.98	29.64	8.15	28.47	7.79	27.29	7.43	24.94	6.72
	5	4.1	33.48	7.92	33.48	8.09	33.48	8.26	32.16	7.90	30.83	7.54	28.17	6.81
	7	6	34.65	8.03	34.65	8.20	34.65	8.37	33.28	8.01	31.90	7.64	29.15	6.91
	9	7.9	34.65	7.76	34.65	7.93	34.65	8.09	33.28	7.74	31.90	7.38	29.15	6.67
	11	9.8	34.65	7.49	34.65	7.65	34.65	7.81	33.28	7.47	31.90	7.13	29.15	6.44
	13	11.8	34.65	7.22	34.65	7.38	34.65	7.53	33.28	7.20	31.90	6.87	29.15	6.21
15	13.7	34.65	6.95	34.65	7.10	34.65	7.25	33.28	6.93	31.90	6.61	29.15	5.98	
110%	-14.7	-15	15.59	6.99	15.59	7.14	15.59	7.29	14.97	6.97	14.36	6.65	13.12	6.01
	-12.6	-13	16.29	7.11	16.29	7.26	16.29	7.41	15.64	7.09	14.99	6.76	13.70	6.11
	-10.5	-11	16.98	7.23	16.98	7.38	16.98	7.53	16.30	7.20	15.63	6.87	14.28	6.21
	-9.5	-10	19.06	7.28	19.06	7.44	19.06	7.59	18.30	7.26	17.55	6.93	16.03	6.26
	-8.5	-9.1	20.10	7.34	20.10	7.49	20.10	7.65	19.30	7.31	18.50	6.98	16.91	6.31
	-7	-7.6	20.79	7.42	20.79	7.58	20.79	7.73	19.97	7.40	19.14	7.06	17.49	6.38
	-5	-5.6	21.48	7.53	21.48	7.69	21.48	7.85	20.63	7.51	19.78	7.16	18.07	6.47
	-3	-3.7	24.26	7.64	24.26	7.80	24.26	7.96	23.29	7.62	22.33	7.27	20.41	6.57
	0	-0.7	26.68	7.80	26.68	7.97	26.68	8.14	25.62	7.78	24.56	7.42	22.45	6.71
	3	2.2	29.64	7.97	29.64	8.14	29.64	8.31	28.47	7.94	27.29	7.58	24.94	6.85
	5	4.1	33.48	8.08	33.48	8.25	33.48	8.42	32.16	8.05	30.83	7.69	28.17	6.95
	7	6	34.65	8.19	34.65	8.36	34.65	8.54	33.28	8.16	31.90	7.79	29.15	7.04
	9	7.9	34.65	7.91	34.65	8.08	34.65	8.25	33.28	7.89	31.90	7.53	29.15	6.81
	11	9.8	34.65	7.64	34.65	7.80	34.65	7.96	33.28	7.62	31.90	7.27	29.15	6.57
	13	11.8	34.65	7.36	34.65	7.52	34.65	7.68	33.28	7.34	31.90	7.01	29.15	6.33

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°C DB	°C WB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	15	13.7	34.65	7.09	34.65	7.24	34.65	7.39	33.28	7.07	31.90	6.74	29.15	6.10
100%	-14.7	-15	14.18	6.23	14.18	6.36	14.18	6.49	13.61	6.21	13.05	5.92	11.93	5.35
	-12.6	-13	14.81	6.33	14.81	6.46	14.81	6.60	14.22	6.31	13.63	6.02	12.46	5.44
	-10.5	-11	15.44	6.43	15.44	6.57	15.44	6.71	14.82	6.41	14.21	6.12	12.99	5.53
	-9.5	-10	17.33	6.48	17.33	6.62	17.33	6.76	16.64	6.46	15.95	6.17	14.58	5.57
	-8.5	-9.1	18.27	6.53	18.27	6.67	18.27	6.81	17.55	6.51	16.82	6.21	15.37	5.62
	-7	-7.6	18.90	6.60	18.90	6.74	18.90	6.88	18.15	6.58	17.40	6.28	15.90	5.68
	-5	-5.6	19.53	6.70	19.53	6.84	19.53	6.99	18.76	6.68	17.98	6.37	16.43	5.76
	-3	-3.7	22.05	6.80	22.05	6.94	22.05	7.09	21.18	6.78	20.30	6.47	18.55	5.85
	0	-0.7	24.26	6.95	24.26	7.09	24.26	7.24	23.29	6.93	22.33	6.61	20.41	5.97
	3	2.2	26.95	7.09	26.95	7.24	26.95	7.40	25.88	7.07	24.81	6.75	22.67	6.10
	5	4.1	30.44	7.19	30.44	7.34	30.44	7.50	29.23	7.17	28.02	6.84	25.61	6.18
	7	6	31.50	7.29	31.50	7.44	31.50	7.60	30.25	7.27	29.00	6.93	26.50	6.27
	9	7.9	31.50	7.04	31.50	7.19	31.50	7.34	30.25	7.02	29.00	6.70	26.50	6.06
	11	9.8	31.50	6.80	31.50	6.94	31.50	7.09	30.25	6.78	29.00	6.47	26.50	5.85
	13	11.8	31.50	6.55	31.50	6.69	31.50	6.83	30.25	6.54	29.00	6.24	26.50	5.64
15	13.7	31.50	6.31	31.50	6.44	31.50	6.58	30.25	6.29	29.00	6.00	26.50	5.43	
90%	-14.7	-15	12.76	5.50	12.76	5.62	12.76	5.73	12.25	5.48	11.75	5.23	10.73	4.73
	-12.6	-13	13.32	5.59	13.32	5.71	13.32	5.83	12.80	5.57	12.27	5.32	11.21	4.81
	-10.5	-11	13.89	5.68	13.89	5.80	13.89	5.92	13.34	5.66	12.79	5.40	11.69	4.88
	-9.5	-10	15.59	5.72	15.59	5.85	15.59	5.97	14.97	5.71	14.36	5.44	13.12	4.92
	-8.5	-9.1	16.44	5.77	16.44	5.89	16.44	6.01	15.79	5.75	15.14	5.49	13.83	4.96
	-7	-7.6	17.01	5.83	17.01	5.96	17.01	6.08	16.34	5.81	15.66	5.55	14.31	5.01
	-5	-5.6	17.58	5.92	17.58	6.04	17.58	6.17	16.88	5.90	16.18	5.63	14.79	5.09
	-3	-3.7	19.85	6.00	19.85	6.13	19.85	6.26	19.06	5.99	18.27	5.71	16.70	5.16
	0	-0.7	21.83	6.13	21.83	6.27	21.83	6.40	20.96	6.12	20.10	5.84	18.36	5.28
	3	2.2	24.25	6.26	24.25	6.40	24.25	6.53	23.29	6.25	22.33	5.96	20.40	5.39
	5	4.1	27.40	6.35	27.40	6.49	27.40	6.62	26.31	6.33	25.22	6.04	23.05	5.46
	7	6	28.35	6.44	28.35	6.57	28.35	6.71	27.23	6.42	26.10	6.12	23.85	5.54
	9	7.9	28.35	6.22	28.35	6.35	28.35	6.49	27.23	6.20	26.10	5.92	23.85	5.35
	11	9.8	28.35	6.00	28.35	6.13	28.35	6.26	27.23	5.99	26.10	5.71	23.85	5.16
	13	11.8	28.35	5.79	28.35	5.91	28.35	6.04	27.23	5.77	26.10	5.51	23.85	4.98
15	13.7	28.35	5.57	28.35	5.69	28.35	5.81	27.23	5.56	26.10	5.30	23.85	4.79	
80%	-14.7	-15	11.34	4.81	11.34	4.91	11.34	5.02	10.89	4.80	10.44	4.58	9.54	4.14
	-12.6	-13	11.84	4.89	11.84	4.99	11.84	5.10	11.37	4.88	10.90	4.65	9.96	4.21
	-10.5	-11	12.35	4.97	12.35	5.08	12.35	5.18	11.86	4.96	11.37	4.73	10.39	4.27
	-9.5	-10	13.86	5.01	13.86	5.11	13.86	5.22	13.31	4.99	12.76	4.76	11.66	4.31
	-8.5	-9.1	14.62	5.05	14.62	5.15	14.62	5.26	14.04	5.03	13.46	4.80	12.30	4.34
	-7	-7.6	15.12	5.10	15.12	5.21	15.12	5.32	14.52	5.09	13.92	4.85	12.72	4.39
	-5	-5.6	15.62	5.18	15.62	5.29	15.62	5.40	15.00	5.16	14.38	4.93	13.14	4.45
	-3	-3.7	17.64	5.25	17.64	5.37	17.64	5.48	16.94	5.24	16.24	5.00	14.84	4.52
	0	-0.7	19.40	5.37	19.40	5.48	19.40	5.60	18.63	5.35	17.86	5.11	16.32	4.62
	3	2.2	21.56	5.48	21.56	5.60	21.56	5.71	20.70	5.46	19.85	5.21	18.14	4.71
	5	4.1	24.35	5.56	24.35	5.68	24.35	5.79	23.39	5.54	22.42	5.29	20.49	4.78
	7	6	25.20	5.63	25.20	5.75	25.20	5.87	24.20	5.62	23.20	5.36	21.20	4.84
	9	7.9	25.20	5.44	25.20	5.56	25.20	5.68	24.20	5.43	23.20	5.18	21.20	4.68
	11	9.8	25.20	5.25	25.20	5.37	25.20	5.48	24.20	5.24	23.20	5.00	21.20	4.52
	13	11.8	25.20	5.07	25.20	5.17	25.20	5.28	24.20	5.05	23.20	4.82	21.20	4.36

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°C DB	°C WB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
	15	13.7	25.20	4.88	25.20	4.98	25.20	5.08	24.20	4.86	23.20	4.64	21.20	4.19
70%	-14.7	-15	9.92	4.12	9.92	4.21	9.92	4.30	9.53	4.11	9.14	3.92	8.35	3.55
	-12.6	-13	10.36	4.19	10.36	4.28	10.36	4.37	9.95	4.18	9.54	3.99	8.72	3.60
	-10.5	-11	10.80	4.26	10.80	4.35	10.80	4.44	10.38	4.25	9.95	4.05	9.09	3.66
	-9.5	-10	12.13	4.29	12.13	4.38	12.13	4.48	11.65	4.28	11.17	4.08	10.20	3.69
	-8.5	-9.1	12.79	4.32	12.79	4.42	12.79	4.51	12.28	4.31	11.77	4.11	10.76	3.72
	-7	-7.6	13.23	4.37	13.23	4.47	13.23	4.56	12.71	4.36	12.18	4.16	11.13	3.76
	-5	-5.6	13.67	4.44	13.67	4.53	13.67	4.63	13.13	4.42	12.59	4.22	11.50	3.82
	-3	-3.7	15.44	4.50	15.44	4.60	15.44	4.70	14.82	4.49	14.21	4.28	12.99	3.87
	0	-0.7	16.98	4.60	16.98	4.70	16.98	4.80	16.30	4.59	15.63	4.38	14.28	3.96
	3	2.2	18.86	4.70	18.86	4.80	18.86	4.90	18.12	4.68	17.37	4.47	15.87	4.04
	5	4.1	21.31	4.76	21.31	4.86	21.31	4.97	20.46	4.75	19.62	4.53	17.93	4.10
	7	6	22.05	4.83	22.05	4.93	22.05	5.03	21.18	4.81	20.30	4.59	18.55	4.15
	9	7.9	22.05	4.67	22.05	4.76	22.05	4.86	21.18	4.65	20.30	4.44	18.55	4.01
	11	9.8	22.05	4.50	22.05	4.60	22.05	4.70	21.18	4.49	20.30	4.28	18.55	3.87
	13	11.8	22.05	4.34	22.05	4.43	22.05	4.53	21.18	4.33	20.30	4.13	18.55	3.73
15	13.7	22.05	4.18	22.05	4.27	22.05	4.36	21.18	4.17	20.30	3.98	18.55	3.59	
60%	-14.7	-15	8.51	3.50	8.51	3.58	8.51	3.65	8.17	3.49	7.83	3.33	7.16	3.01
	-12.6	-13	8.88	3.56	8.88	3.64	8.88	3.71	8.53	3.55	8.18	3.39	7.47	3.06
	-10.5	-11	9.26	3.62	9.26	3.69	9.26	3.77	8.89	3.61	8.53	3.44	7.79	3.11
	-9.5	-10	10.40	3.64	10.40	3.72	10.40	3.80	9.98	3.63	9.57	3.47	8.75	3.13
	-8.5	-9.1	10.96	3.67	10.96	3.75	10.96	3.83	10.53	3.66	10.09	3.49	9.22	3.16
	-7	-7.6	11.34	3.71	11.34	3.79	11.34	3.87	10.89	3.70	10.44	3.53	9.54	3.19
	-5	-5.6	11.72	3.77	11.72	3.85	11.72	3.93	11.25	3.76	10.79	3.59	9.86	3.24
	-3	-3.7	13.23	3.82	13.23	3.91	13.23	3.99	12.71	3.81	12.18	3.64	11.13	3.29
	0	-0.7	14.55	3.91	14.55	3.99	14.55	4.07	13.98	3.89	13.40	3.72	12.24	3.36
	3	2.2	16.17	3.99	16.17	4.07	16.17	4.16	15.53	3.98	14.89	3.79	13.60	3.43
	5	4.1	18.26	4.04	18.26	4.13	18.26	4.22	17.54	4.03	16.81	3.85	15.37	3.48
	7	6	18.90	4.10	18.90	4.19	18.90	4.27	18.15	4.09	17.40	3.90	15.90	3.53
	9	7.9	18.90	3.96	18.90	4.05	18.90	4.13	18.15	3.95	17.40	3.77	15.90	3.41
	11	9.8	18.90	3.82	18.90	3.91	18.90	3.99	18.15	3.81	17.40	3.64	15.90	3.29
	13	11.8	18.90	3.69	18.90	3.77	18.90	3.84	18.15	3.68	17.40	3.51	15.90	3.17
15	13.7	18.90	3.55	18.90	3.62	18.90	3.70	18.15	3.54	17.40	3.38	15.90	3.05	
50%	-14.7	-15	7.09	2.83	7.09	2.89	7.09	2.95	6.81	2.82	6.53	2.69	5.96	2.43
	-12.6	-13	7.40	2.88	7.40	2.94	7.40	3.00	7.11	2.87	6.82	2.74	6.23	2.47
	-10.5	-11	7.72	2.92	7.72	2.98	7.72	3.05	7.41	2.91	7.11	2.78	6.49	2.51
	-9.5	-10	8.66	2.94	8.66	3.01	8.66	3.07	8.32	2.94	7.98	2.80	7.29	2.53
	-8.5	-9.1	9.14	2.97	9.14	3.03	9.14	3.09	8.77	2.96	8.41	2.82	7.69	2.55
	-7	-7.6	9.45	3.00	9.45	3.06	9.45	3.13	9.08	2.99	8.70	2.85	7.95	2.58
	-5	-5.6	9.77	3.04	9.77	3.11	9.77	3.17	9.38	3.04	8.99	2.90	8.22	2.62
	-3	-3.7	11.03	3.09	11.03	3.15	11.03	3.22	10.59	3.08	10.15	2.94	9.28	2.66
	0	-0.7	12.13	3.16	12.13	3.22	12.13	3.29	11.65	3.15	11.17	3.00	10.20	2.71
	3	2.2	13.47	3.22	13.47	3.29	13.47	3.36	12.94	3.21	12.41	3.07	11.34	2.77
	5	4.1	15.22	3.27	15.22	3.34	15.22	3.41	14.62	3.26	14.01	3.11	12.80	2.81
	7	6	15.75	3.31	15.75	3.38	15.75	3.45	15.13	3.30	14.50	3.15	13.25	2.85
	9	7.9	15.75	3.20	15.75	3.27	15.75	3.34	15.13	3.19	14.50	3.04	13.25	2.75
	11	9.8	15.75	3.09	15.75	3.15	15.75	3.22	15.13	3.08	14.50	2.94	13.25	2.66
	13	11.8	15.75	2.98	15.75	3.04	15.75	3.10	15.13	2.97	14.50	2.83	13.25	2.56

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	15	13.7	15.75	2.87	15.75	2.93	15.75	2.99	15.13	2.86	14.50	2.73	13.25	2.47

12 HP

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
130%	-14.7	-15	18.56	7.89	18.56	8.06	18.56	8.23	17.83	7.87	17.09	7.51	15.62	6.79
	-12.6	-13	19.39	8.02	19.39	8.19	19.39	8.36	18.62	8.00	17.85	7.63	16.31	6.90
	-10.5	-11	20.21	8.15	20.21	8.33	20.21	8.50	19.41	8.13	18.61	7.76	17.00	7.01
	-9.5	-10	22.69	8.21	22.69	8.39	22.69	8.56	21.79	8.19	20.89	7.81	19.09	7.06
	-8.5	-9.1	23.93	8.28	23.93	8.45	23.93	8.63	22.98	8.25	22.03	7.87	20.13	7.12
	-7	-7.6	24.75	8.37	24.75	8.55	24.75	8.73	23.77	8.34	22.79	7.96	20.82	7.20
	-5	-5.6	25.58	8.49	25.58	8.68	25.58	8.86	24.56	8.47	23.55	8.08	21.52	7.30
	-3	-3.7	28.88	8.62	28.88	8.80	28.88	8.99	27.73	8.59	26.58	8.20	24.29	7.41
	0	-0.7	31.76	8.80	31.76	8.99	31.76	9.18	30.50	8.78	29.24	8.38	26.72	7.57
	3	2.2	35.29	8.99	35.29	9.18	35.29	9.37	33.89	8.96	32.49	8.55	29.69	7.73
	5	4.1	39.86	9.11	39.86	9.31	39.86	9.50	38.28	9.09	36.70	8.67	33.53	7.84
	7	6	41.25	9.24	41.25	9.44	41.25	9.63	39.61	9.21	37.98	8.79	34.70	7.95
	9	7.9	41.25	8.93	41.25	9.12	41.25	9.31	39.61	8.90	37.98	8.49	34.70	7.68
	11	9.8	41.25	8.62	41.25	8.80	41.25	8.99	39.61	8.59	37.98	8.20	34.70	7.41
	13	11.8	41.25	8.31	41.25	8.49	41.25	8.66	39.61	8.28	37.98	7.90	34.70	7.14
15	13.7	41.25	8.00	41.25	8.17	41.25	8.34	39.61	7.97	37.98	7.61	34.70	6.88	
120%	-14.7	-15	18.56	8.12	18.56	8.30	18.56	8.47	17.83	8.10	17.09	7.73	15.62	6.99
	-12.6	-13	19.39	8.26	19.39	8.43	19.39	8.61	18.62	8.23	17.85	7.86	16.31	7.10
	-10.5	-11	20.21	8.39	20.21	8.57	20.21	8.75	19.41	8.37	18.61	7.98	17.00	7.22
	-9.5	-10	22.69	8.46	22.69	8.64	22.69	8.82	21.79	8.43	20.89	8.04	19.09	7.27
	-8.5	-9.1	23.93	8.52	23.93	8.70	23.93	8.88	22.98	8.49	22.03	8.11	20.13	7.33
	-7	-7.6	24.75	8.62	24.75	8.80	24.75	8.98	23.77	8.59	22.79	8.20	20.82	7.41
	-5	-5.6	25.58	8.74	25.58	8.93	25.58	9.12	24.56	8.72	23.55	8.32	21.52	7.52
	-3	-3.7	28.88	8.87	28.88	9.06	28.88	9.25	27.73	8.84	26.58	8.44	24.29	7.63
	0	-0.7	31.76	9.06	31.76	9.26	31.76	9.45	30.50	9.04	29.24	8.62	26.72	7.79
	3	2.2	35.29	9.25	35.29	9.45	35.29	9.65	33.89	9.23	32.49	8.80	29.69	7.96
	5	4.1	39.86	9.38	39.86	9.58	39.86	9.78	38.28	9.35	36.70	8.93	33.53	8.07
	7	6	41.25	9.51	41.25	9.71	41.25	9.92	39.61	9.48	37.98	9.05	34.70	8.18
	9	7.9	41.25	9.19	41.25	9.39	41.25	9.58	39.61	9.16	37.98	8.74	34.70	7.90
	11	9.8	41.25	8.87	41.25	9.06	41.25	9.25	39.61	8.85	37.98	8.44	34.70	7.63
	13	11.8	41.25	8.55	41.25	8.74	41.25	8.92	39.61	8.53	37.98	8.14	34.70	7.35
15	13.7	41.25	8.23	41.25	8.41	41.25	8.58	39.61	8.21	37.98	7.83	34.70	7.08	
110%	-14.7	-15	18.56	8.28	18.56	8.46	18.56	8.64	17.83	8.26	17.09	7.88	15.62	7.12
	-12.6	-13	19.39	8.42	19.39	8.60	19.39	8.78	18.62	8.39	17.85	8.01	16.31	7.24
	-10.5	-11	20.21	8.56	20.21	8.74	20.21	8.92	19.41	8.53	18.61	8.14	17.00	7.36
	-9.5	-10	22.69	8.62	22.69	8.81	22.69	8.99	21.79	8.60	20.89	8.20	19.09	7.41
	-8.5	-9.1	23.93	8.69	23.93	8.87	23.93	9.06	22.98	8.66	22.03	8.26	20.13	7.47
	-7	-7.6	24.75	8.78	24.75	8.97	24.75	9.16	23.77	8.76	22.79	8.36	20.82	7.55
	-5	-5.6	25.58	8.91	25.58	9.11	25.58	9.30	24.56	8.89	23.55	8.48	21.52	7.67
	-3	-3.7	28.88	9.05	28.88	9.24	28.88	9.43	27.73	9.02	26.58	8.60	24.29	7.78
	0	-0.7	31.76	9.24	31.76	9.44	31.76	9.63	30.50	9.21	29.24	8.79	26.72	7.95
	3	2.2	35.29	9.44	35.29	9.64	35.29	9.84	33.89	9.41	32.49	8.98	29.69	8.11
	5	4.1	39.86	9.57	39.86	9.77	39.86	9.97	38.28	9.54	36.70	9.10	33.53	8.23
	7	6	41.25	9.70	41.25	9.90	41.25	10.11	39.61	9.67	37.98	9.22	34.70	8.34
	9	7.9	41.25	9.37	41.25	9.57	41.25	9.77	39.61	9.34	37.98	8.91	34.70	8.06
	11	9.8	41.25	9.05	41.25	9.24	41.25	9.43	39.61	9.02	37.98	8.61	34.70	7.78
	13	11.8	41.25	8.72	41.25	8.91	41.25	9.09	39.61	8.69	37.98	8.30	34.70	7.50

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°C DB	°C WB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
	15	13.7	41.25	8.39	41.25	8.57	41.25	8.75	39.61	8.37	37.98	7.99	34.70	7.22
100%	-14.7	-15	16.88	7.37	16.88	7.53	16.88	7.69	16.21	7.35	15.54	7.01	14.20	6.34
	-12.6	-13	17.63	7.49	17.63	7.65	17.63	7.81	16.93	7.47	16.23	7.13	14.83	6.45
	-10.5	-11	18.38	7.62	18.38	7.78	18.38	7.94	17.65	7.59	16.92	7.25	15.46	6.55
	-9.5	-10	20.63	7.67	20.63	7.84	20.63	8.00	19.81	7.65	18.99	7.30	17.35	6.60
	-8.5	-9.1	21.75	7.73	21.75	7.90	21.75	8.06	20.89	7.71	20.02	7.36	18.30	6.65
	-7	-7.6	22.50	7.82	22.50	7.99	22.50	8.15	21.61	7.80	20.71	7.44	18.93	6.72
	-5	-5.6	23.25	7.94	23.25	8.10	23.25	8.27	22.33	7.91	21.40	7.55	19.56	6.82
	-3	-3.7	26.25	8.05	26.25	8.22	26.25	8.40	25.21	8.03	24.17	7.66	22.08	6.92
	0	-0.7	28.88	8.23	28.88	8.40	28.88	8.58	27.73	8.20	26.58	7.83	24.29	7.07
	3	2.2	32.08	8.40	32.08	8.58	32.08	8.76	30.81	8.37	29.54	7.99	26.99	7.22
	5	4.1	36.24	8.52	36.24	8.70	36.24	8.88	34.80	8.49	33.36	8.10	30.49	7.32
	7	6	37.50	8.63	37.50	8.82	37.50	9.10	36.01	8.61	34.52	8.21	31.55	7.42
	9	7.9	37.50	8.34	37.50	8.52	37.50	8.70	36.01	8.32	34.52	7.94	31.55	7.17
	11	9.8	37.50	8.05	37.50	8.22	37.50	8.40	36.01	8.03	34.52	7.66	31.55	6.92
	13	11.8	37.50	7.76	37.50	7.93	37.50	8.09	36.01	7.74	34.52	7.38	31.55	6.68
15	13.7	37.50	7.47	37.50	7.63	37.50	7.79	36.01	7.45	34.52	7.11	31.55	6.43	
90%	-14.7	-15	15.19	6.51	15.19	6.65	15.19	6.79	14.58	6.49	13.98	6.19	12.78	5.60
	-12.6	-13	15.86	6.62	15.86	6.76	15.86	6.90	15.23	6.60	14.60	6.30	13.34	5.69
	-10.5	-11	16.54	6.73	16.54	6.87	16.54	7.01	15.88	6.71	15.23	6.40	13.91	5.78
	-9.5	-10	18.56	6.78	18.56	6.92	18.56	7.07	17.83	6.76	17.09	6.45	15.62	5.83
	-8.5	-9.1	19.58	6.83	19.58	6.97	19.58	7.12	18.80	6.81	18.02	6.50	16.47	5.87
	-7	-7.6	20.25	6.91	20.25	7.05	20.25	7.20	19.45	6.88	18.64	6.57	17.04	5.94
	-5	-5.6	20.93	7.01	20.93	7.16	20.93	7.31	20.09	6.99	19.26	6.67	17.60	6.03
	-3	-3.7	23.63	7.11	23.63	7.26	23.63	7.41	22.69	7.09	21.75	6.76	19.88	6.11
	0	-0.7	25.99	7.26	25.99	7.42	25.99	7.57	24.96	7.24	23.93	6.91	21.86	6.25
	3	2.2	28.87	7.42	28.87	7.58	28.87	7.73	27.73	7.40	26.58	7.06	24.29	6.38
	5	4.1	32.61	7.52	32.61	7.68	32.61	7.84	31.32	7.50	30.03	7.15	27.44	6.47
	7	6	33.75	7.62	33.75	7.79	33.75	7.95	32.41	7.60	31.07	7.25	28.39	6.56
	9	7.9	33.75	7.37	33.75	7.52	33.75	7.68	32.41	7.34	31.07	7.01	28.39	6.34
	11	9.8	33.75	7.11	33.75	7.26	33.75	7.41	32.41	7.09	31.07	6.76	28.39	6.12
	13	11.8	33.75	6.85	33.75	7.00	33.75	7.15	32.41	6.83	31.07	6.52	28.39	5.89
15	13.7	33.75	6.60	33.75	6.74	33.75	6.88	32.41	6.58	31.07	6.28	28.39	5.67	
80%	-14.7	-15	13.50	5.70	13.50	5.82	13.50	5.94	12.96	5.68	12.43	5.42	11.36	4.90
	-12.6	-13	14.10	5.79	14.10	5.92	14.10	6.04	13.54	5.77	12.98	5.51	11.86	4.98
	-10.5	-11	14.70	5.89	14.70	6.01	14.70	6.14	14.12	5.87	13.53	5.60	12.37	5.06
	-9.5	-10	16.50	5.93	16.50	6.06	16.50	6.18	15.85	5.91	15.19	5.64	13.88	5.10
	-8.5	-9.1	17.40	5.98	17.40	6.10	17.40	6.23	16.71	5.96	16.02	5.68	14.64	5.14
	-7	-7.6	18.00	6.04	18.00	6.17	18.00	6.30	17.29	6.02	16.57	5.75	15.14	5.20
	-5	-5.6	18.60	6.13	18.60	6.26	18.60	6.39	17.86	6.11	17.12	5.83	15.65	5.27
	-3	-3.7	21.00	6.22	21.00	6.35	21.00	6.49	20.17	6.20	19.33	5.92	17.67	5.35
	0	-0.7	23.10	6.36	23.10	6.49	23.10	6.63	22.18	6.34	21.27	6.05	19.43	5.47
	3	2.2	25.67	6.49	25.67	6.63	25.67	6.77	24.65	6.47	23.63	6.17	21.59	5.58
	5	4.1	28.99	6.58	28.99	6.72	28.99	6.86	27.84	6.56	26.69	6.26	24.39	5.66
	7	6	30.00	6.67	30.00	6.81	30.00	6.95	28.81	6.65	27.62	6.35	25.24	5.74
	9	7.9	30.00	6.45	30.00	6.58	30.00	6.72	28.81	6.43	27.62	6.13	25.24	5.54
	11	9.8	30.00	6.22	30.00	6.35	30.00	6.49	28.81	6.20	27.62	5.92	25.24	5.35
	13	11.8	30.00	6.00	30.00	6.13	30.00	6.25	28.81	5.98	27.62	5.71	25.24	5.16

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°C DB	°C WB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
	15	13.7	30.00	5.77	30.00	5.90	30.00	6.02	28.81	5.76	27.62	5.49	25.24	4.97
70%	-14.7	-15	11.81	4.88	11.81	4.99	11.81	5.09	11.34	4.87	10.88	4.65	9.94	4.20
	-12.6	-13	12.34	4.96	12.34	5.07	12.34	5.18	11.85	4.95	11.36	4.72	10.38	4.27
	-10.5	-11	12.86	5.04	12.86	5.15	12.86	5.26	12.35	5.03	11.84	4.80	10.82	4.34
	-9.5	-10	14.44	5.08	14.44	5.19	14.44	5.30	13.86	5.07	13.29	4.84	12.15	4.37
	-8.5	-9.1	15.23	5.12	15.23	5.23	15.23	5.34	14.62	5.11	14.02	4.87	12.81	4.40
	-7	-7.6	15.75	5.18	15.75	5.29	15.75	5.40	15.13	5.16	14.50	4.93	13.25	4.45
	-5	-5.6	16.28	5.26	16.28	5.37	16.28	5.48	15.63	5.24	14.98	5.00	13.69	4.52
	-3	-3.7	18.38	5.33	18.38	5.45	18.38	5.56	17.65	5.32	16.92	5.07	15.46	4.59
	0	-0.7	20.21	5.45	20.21	5.56	20.21	5.68	19.41	5.43	18.61	5.18	17.00	4.68
	3	2.2	22.46	5.56	22.46	5.68	22.46	5.80	21.57	5.55	20.68	5.29	18.89	4.78
	5	4.1	25.37	5.64	25.37	5.76	25.37	5.88	24.36	5.62	23.35	5.37	21.34	4.85
	7	6	26.25	5.72	26.25	5.84	26.25	5.96	25.21	5.70	24.17	5.44	22.08	4.92
	9	7.9	26.25	5.52	26.25	5.64	26.25	5.76	25.21	5.51	24.17	5.26	22.08	4.75
	11	9.8	26.25	5.33	26.25	5.45	26.25	5.56	25.21	5.32	24.17	5.07	22.08	4.59
	13	11.8	26.25	5.14	26.25	5.25	26.25	5.36	25.21	5.13	24.17	4.89	22.08	4.42
15	13.7	26.25	4.95	26.25	5.05	26.25	5.16	25.21	4.93	24.17	4.71	22.08	4.26	
60%	-14.7	-15	10.13	4.15	10.13	4.24	10.13	4.32	9.72	4.13	9.32	3.94	8.52	3.57
	-12.6	-13	10.58	4.22	10.58	4.31	10.58	4.39	10.16	4.20	9.74	4.01	8.90	3.62
	-10.5	-11	11.03	4.28	11.03	4.37	11.03	4.47	10.59	4.27	10.15	4.08	9.28	3.68
	-9.5	-10	12.38	4.32	12.38	4.41	12.38	4.50	11.88	4.30	11.39	4.11	10.41	3.71
	-8.5	-9.1	13.05	4.35	13.05	4.44	13.05	4.53	12.53	4.34	12.01	4.14	10.98	3.74
	-7	-7.6	13.50	4.40	13.50	4.49	13.50	4.59	12.96	4.38	12.43	4.18	11.36	3.78
	-5	-5.6	13.95	4.46	13.95	4.56	13.95	4.65	13.40	4.45	12.84	4.25	11.74	3.84
	-3	-3.7	15.75	4.53	15.75	4.62	15.75	4.72	15.13	4.51	14.50	4.31	13.25	3.89
	0	-0.7	17.33	4.63	17.33	4.72	17.33	4.82	16.64	4.61	15.95	4.40	14.58	3.98
	3	2.2	19.25	4.72	19.25	4.82	19.25	4.93	18.49	4.71	17.72	4.49	16.19	4.06
	5	4.1	21.74	4.79	21.74	4.89	21.74	4.99	20.88	4.77	20.02	4.56	18.29	4.12
	7	6	22.50	4.85	22.50	4.96	22.50	5.06	21.61	4.84	20.71	4.62	18.93	4.17
	9	7.9	22.50	4.69	22.50	4.79	22.50	4.89	21.61	4.68	20.71	4.46	18.93	4.03
	11	9.8	22.50	4.53	22.50	4.63	22.50	4.72	21.61	4.51	20.71	4.31	18.93	3.89
	13	11.8	22.50	4.37	22.50	4.46	22.50	4.55	21.61	4.35	20.71	4.15	18.93	3.75
15	13.7	22.50	4.20	22.50	4.29	22.50	4.38	21.61	4.19	20.71	4.00	18.93	3.61	
50%	-14.7	-15	8.44	3.35	8.44	3.42	8.44	3.49	8.10	3.34	7.77	3.19	7.10	2.88
	-12.6	-13	8.81	3.40	8.81	3.48	8.81	3.55	8.46	3.39	8.11	3.24	7.41	2.93
	-10.5	-11	9.19	3.46	9.19	3.53	9.19	3.61	8.82	3.45	8.46	3.29	7.73	2.98
	-9.5	-10	10.31	3.49	10.31	3.56	10.31	3.64	9.90	3.48	9.49	3.32	8.68	3.00
	-8.5	-9.1	10.88	3.51	10.88	3.59	10.88	3.66	10.44	3.50	10.01	3.34	9.15	3.02
	-7	-7.6	11.25	3.55	11.25	3.63	11.25	3.70	10.80	3.54	10.36	3.38	9.46	3.06
	-5	-5.6	11.63	3.61	11.63	3.68	11.63	3.76	11.16	3.59	10.70	3.43	9.78	3.10
	-3	-3.7	13.13	3.66	13.13	3.74	13.13	3.81	12.60	3.65	12.08	3.48	11.04	3.15
	0	-0.7	14.44	3.74	14.44	3.82	14.44	3.90	13.86	3.73	13.29	3.56	12.15	3.21
	3	2.2	16.04	3.82	16.04	3.90	16.04	3.98	15.41	3.80	14.77	3.63	13.50	3.28
	5	4.1	18.12	3.87	18.12	3.95	18.12	4.03	17.40	3.86	16.68	3.68	15.24	3.33
	7	6	18.75	3.92	18.75	4.01	18.75	4.09	18.01	3.91	17.26	3.73	15.77	3.37
	9	7.9	18.75	3.79	18.75	3.87	18.75	3.95	18.01	3.78	17.26	3.61	15.77	3.26
	11	9.8	18.75	3.66	18.75	3.74	18.75	3.81	18.01	3.65	17.26	3.48	15.77	3.15
	13	11.8	18.75	3.53	18.75	3.60	18.75	3.68	18.01	3.52	17.26	3.35	15.77	3.03

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	15	13.7	18.75	3.39	18.75	3.47	18.75	3.54	18.01	3.38	17.26	3.23	15.77	2.92

14 HP

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW	TC kW	PI kW
130%	-14.7	-15	22.28	9.82	22.28	10.03	22.28	10.24	21.39	9.79	20.51	9.34	18.74	8.45
	-12.6	-13	23.27	9.98	23.27	10.20	23.27	10.41	22.34	9.95	21.42	9.50	19.57	8.58
	-10.5	-11	24.26	10.15	24.26	10.36	24.26	10.58	23.29	10.11	22.33	9.65	20.41	8.72
	-9.5	-10	27.23	10.22	27.23	10.44	27.23	10.66	26.14	10.19	25.06	9.72	22.90	8.79
	-8.5	-9.1	28.71	10.30	28.71	10.52	28.71	10.74	27.57	10.27	26.43	9.80	24.15	8.86
	-7	-7.6	29.70	10.42	29.70	10.64	29.70	10.86	28.52	10.38	27.34	9.91	24.99	8.96
	-5	-5.6	30.69	10.57	30.69	10.80	30.69	11.02	29.47	10.54	28.25	10.06	25.82	9.09
	-3	-3.7	34.65	10.72	34.65	10.95	34.65	11.18	33.28	10.69	31.90	10.20	29.15	9.22
	0	-0.7	38.12	10.96	38.12	11.19	38.12	11.42	36.60	10.92	35.09	10.42	32.07	9.42
	3	2.2	42.35	11.19	42.35	11.43	42.35	11.67	40.67	11.15	38.99	10.64	35.63	9.62
	5	4.1	47.83	11.34	47.83	11.58	47.83	11.83	45.94	11.31	44.04	10.79	40.24	9.75
	7	6	49.50	11.50	49.50	11.74	49.50	11.99	47.54	11.46	45.57	10.94	41.64	9.89
	9	7.9	49.50	11.11	49.50	11.35	49.50	11.59	47.54	11.08	45.57	10.57	41.64	9.56
	11	9.8	49.50	10.73	49.50	10.95	49.50	11.18	47.54	10.69	45.57	10.20	41.64	9.22
	13	11.8	49.50	10.34	49.50	10.56	49.50	10.78	47.54	10.31	45.57	9.84	41.64	8.89
15	13.7	49.50	9.95	49.50	10.17	49.50	10.38	47.54	9.92	45.57	9.47	41.64	8.56	
120%	-14.7	-15	22.28	10.11	22.28	10.33	22.28	10.54	21.39	10.08	20.51	9.62	18.74	8.69
	-12.6	-13	23.27	10.28	23.27	10.50	23.27	10.72	22.34	10.25	21.42	9.78	19.57	8.84
	-10.5	-11	24.26	10.44	24.26	10.67	24.26	10.89	23.29	10.41	22.33	9.94	20.41	8.98
	-9.5	-10	27.23	10.52	27.23	10.75	27.23	10.97	26.14	10.49	25.06	10.01	22.90	9.05
	-8.5	-9.1	28.71	10.60	28.71	10.83	28.71	11.06	27.57	10.57	26.43	10.09	24.15	9.12
	-7	-7.6	29.70	10.72	29.70	10.95	29.70	11.18	28.52	10.69	27.34	10.20	24.99	9.22
	-5	-5.6	30.69	10.88	30.69	11.11	30.69	11.35	29.47	10.85	28.25	10.35	25.82	9.36
	-3	-3.7	34.65	11.04	34.65	11.28	34.65	11.51	33.28	11.01	31.90	10.50	29.15	9.49
	0	-0.7	38.12	11.28	38.12	11.52	38.12	11.76	36.60	11.24	35.09	10.73	32.07	9.70
	3	2.2	42.35	11.52	42.35	11.76	42.35	12.01	40.67	11.48	38.99	10.96	35.63	9.90
	5	4.1	47.83	11.68	47.83	11.93	47.83	12.17	45.94	11.64	44.04	11.11	40.24	10.04
	7	6	49.50	11.84	49.50	12.09	49.50	12.34	47.54	11.80	45.57	11.26	41.64	10.18
	9	7.9	49.50	11.44	49.50	11.68	49.50	11.93	47.54	11.40	45.57	10.88	41.64	9.84
	11	9.8	49.50	11.04	49.50	11.28	49.50	11.51	47.54	11.01	45.57	10.50	41.64	9.49
	13	11.8	49.50	10.64	49.50	10.87	49.50	11.10	47.54	10.61	45.57	10.12	41.64	9.15
15	13.7	49.50	10.25	49.50	10.46	49.50	10.68	47.54	10.21	45.57	9.75	41.64	8.81	
110%	-14.7	-15	22.28	10.31	22.28	10.53	22.28	10.75	21.39	10.28	20.51	9.81	18.74	8.86
	-12.6	-13	23.27	10.48	23.27	10.70	23.27	10.92	22.34	10.45	21.42	9.97	19.57	9.01
	-10.5	-11	24.26	10.65	24.26	10.88	24.26	11.10	23.29	10.62	22.33	10.13	20.41	9.16
	-9.5	-10	27.23	10.73	27.23	10.96	27.23	11.19	26.14	10.70	25.06	10.21	22.90	9.23
	-8.5	-9.1	28.71	10.81	28.71	11.04	28.71	11.27	27.57	10.78	26.43	10.28	24.15	9.30
	-7	-7.6	29.70	10.93	29.70	11.17	29.70	11.40	28.52	10.90	27.34	10.40	24.99	9.40
	-5	-5.6	30.69	11.09	30.69	11.33	30.69	11.57	29.47	11.06	28.25	10.55	25.82	9.54
	-3	-3.7	34.65	11.26	34.65	11.50	34.65	11.74	33.28	11.22	31.90	10.71	29.15	9.68
	0	-0.7	38.12	11.50	38.12	11.74	38.12	11.99	36.60	11.46	35.09	10.94	32.07	9.89
	3	2.2	42.35	11.74	42.35	11.99	42.35	12.24	40.67	11.71	38.99	11.17	35.63	10.10
	5	4.1	47.83	11.91	47.83	12.16	47.83	12.41	45.94	11.87	44.04	11.33	40.24	10.24
	7	6	49.50	12.07	49.50	12.32	49.50	12.58	47.54	12.03	45.57	11.48	41.64	10.38
	9	7.9	49.50	11.66	49.50	11.91	49.50	12.16	47.54	11.63	45.57	11.09	41.64	10.03
	11	9.8	49.50	11.26	49.50	11.50	49.50	11.74	47.54	11.22	45.57	10.71	41.64	9.68
	13	11.8	49.50	10.85	49.50	11.08	49.50	11.31	47.54	10.82	45.57	10.32	41.64	9.33

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	15	13.7	49.50	10.45	49.50	10.67	49.50	10.89	47.54	10.41	45.57	9.94	41.64	8.98
100%	-14.7	-15	20.25	9.18	20.25	9.37	20.25	9.57	19.45	9.15	18.64	8.73	17.04	7.89
	-12.6	-13	21.15	9.33	21.15	9.53	21.15	9.72	20.31	9.30	19.47	8.87	17.79	8.02
	-10.5	-11	22.05	9.48	22.05	9.68	22.05	9.88	21.18	9.45	20.30	9.02	18.55	8.15
	-9.5	-10	24.75	9.55	24.75	9.75	24.75	9.96	23.77	9.52	22.79	9.09	20.82	8.21
	-8.5	-9.1	26.10	9.62	26.10	9.83	26.10	10.03	25.06	9.59	24.03	9.15	21.96	8.28
	-7	-7.6	27.00	9.73	27.00	9.94	27.00	10.15	25.93	9.70	24.86	9.26	22.71	8.37
	-5	-5.6	27.90	9.88	27.90	10.09	27.90	10.30	26.79	9.85	25.69	9.39	23.47	8.49
	-3	-3.7	31.50	10.02	31.50	10.23	31.50	10.45	30.25	9.99	29.00	9.53	26.50	8.62
	0	-0.7	34.65	10.24	34.65	10.45	34.65	10.67	33.28	10.21	31.90	9.74	29.15	8.80
	3	2.2	38.50	10.45	38.50	10.68	38.50	10.90	36.97	10.42	35.44	9.94	32.39	8.99
	5	4.1	43.49	10.60	43.49	10.82	43.49	11.05	41.76	10.57	40.03	10.08	36.58	9.11
	7	6	45.00	10.74	45.00	10.97	45.00	11.20	43.21	10.71	41.43	10.22	37.86	9.24
	9	7.9	45.00	10.38	45.00	10.60	45.00	10.82	43.21	10.35	41.43	9.88	37.86	8.93
	11	9.8	45.00	10.02	45.00	10.23	45.00	10.45	43.21	9.99	41.43	9.53	37.86	8.62
	13	11.8	45.00	9.66	45.00	9.87	45.00	10.07	43.21	9.63	41.43	9.19	37.86	8.31
15	13.7	45.00	9.30	45.00	9.50	45.00	9.70	43.21	9.27	41.43	8.85	37.86	8.00	
90%	-14.7	-15	18.23	8.10	18.23	8.28	18.23	8.45	17.50	8.08	16.78	7.71	15.33	6.97
	-12.6	-13	19.04	8.24	19.04	8.41	19.04	8.59	18.28	8.21	17.52	7.84	16.01	7.08
	-10.5	-11	19.85	8.37	19.85	8.55	19.85	8.73	19.06	8.35	18.27	7.96	16.70	7.20
	-9.5	-10	22.28	8.43	22.28	8.61	22.28	8.79	21.39	8.41	20.51	8.02	18.74	7.25
	-8.5	-9.1	23.49	8.50	23.49	8.68	23.49	8.86	22.56	8.47	21.63	8.08	19.76	7.31
	-7	-7.6	24.30	8.59	24.30	8.78	24.30	8.96	23.34	8.57	22.37	8.18	20.44	7.39
	-5	-5.6	25.11	8.72	25.11	8.91	25.11	9.09	24.11	8.69	23.12	8.30	21.12	7.50
	-3	-3.7	28.35	8.85	28.35	9.04	28.35	9.23	27.23	8.82	26.10	8.42	23.85	7.61
	0	-0.7	31.19	9.04	31.19	9.23	31.19	9.43	29.95	9.01	28.71	8.60	26.24	7.77
	3	2.2	34.65	9.23	34.65	9.43	34.65	9.63	33.27	9.20	31.90	8.78	29.15	7.94
	5	4.1	39.14	9.36	39.14	9.56	39.14	9.76	37.58	9.33	36.03	8.90	32.93	8.05
	7	6	40.50	9.49	40.50	9.69	40.50	9.89	38.89	9.46	37.29	9.02	34.07	8.16
	9	7.9	40.50	9.17	40.50	9.36	40.50	9.56	38.89	9.14	37.29	8.72	34.07	7.88
	11	9.8	40.50	8.85	40.50	9.04	40.50	9.23	38.89	8.82	37.29	8.42	34.07	7.61
	13	11.8	40.50	8.53	40.50	8.71	40.50	8.89	38.89	8.50	37.29	8.12	34.07	7.34
15	13.7	40.50	8.21	40.50	8.39	40.50	8.56	38.89	8.19	37.29	7.81	34.07	7.06	
80%	-14.7	-15	16.20	7.09	16.20	7.24	16.20	7.39	15.56	7.07	14.91	6.74	13.63	6.10
	-12.6	-13	16.92	7.21	16.92	7.36	16.92	7.51	16.25	7.19	15.58	6.86	14.23	6.20
	-10.5	-11	17.64	7.32	17.64	7.48	17.64	7.64	16.94	7.30	16.24	6.97	14.84	6.30
	-9.5	-10	19.80	7.38	19.80	7.54	19.80	7.69	19.01	7.36	18.23	7.02	16.66	6.35
	-8.5	-9.1	20.88	7.44	20.88	7.59	20.88	7.75	20.05	7.41	19.22	7.07	17.57	6.39
	-7	-7.6	21.60	7.52	21.60	7.68	21.60	7.84	20.74	7.50	19.89	7.15	18.17	6.47
	-5	-5.6	22.32	7.63	22.32	7.79	22.32	7.96	21.43	7.61	20.55	7.26	18.78	6.56
	-3	-3.7	25.20	7.74	25.20	7.91	25.20	8.07	24.20	7.72	23.20	7.37	21.20	6.66
	0	-0.7	27.72	7.91	27.72	8.08	27.72	8.25	26.62	7.89	25.52	7.52	23.32	6.80
	3	2.2	30.80	8.08	30.80	8.25	30.80	8.42	29.58	8.05	28.36	7.68	25.91	6.95
	5	4.1	34.79	8.19	34.79	8.36	34.79	8.54	33.41	8.16	32.03	7.79	29.27	7.04
	7	6	36.00	8.30	36.00	8.48	36.00	8.65	34.57	8.28	33.14	7.90	30.29	7.14
	9	7.9	36.00	8.02	36.00	8.19	36.00	8.36	34.57	8.00	33.14	7.63	30.29	6.90
	11	9.8	36.00	7.74	36.00	7.91	36.00	8.07	34.57	7.72	33.14	7.37	30.29	6.66
	13	11.8	36.00	7.46	36.00	7.62	36.00	7.78	34.57	7.44	33.14	7.10	30.29	6.42

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	15	13.7	36.00	7.19	36.00	7.34	36.00	7.49	34.57	7.16	33.14	6.84	30.29	6.18
70%	-14.7	-15	14.18	6.08	14.18	6.21	14.18	6.34	13.61	6.06	13.05	5.78	11.93	5.23
	-12.6	-13	14.81	6.18	14.81	6.31	14.81	6.44	14.22	6.16	13.63	5.88	12.46	5.31
	-10.5	-11	15.44	6.28	15.44	6.41	15.44	6.55	14.82	6.26	14.21	5.97	12.99	5.40
	-9.5	-10	17.33	6.33	17.33	6.46	17.33	6.60	16.64	6.31	15.95	6.02	14.58	5.44
	-8.5	-9.1	18.27	6.37	18.27	6.51	18.27	6.65	17.55	6.35	16.82	6.06	15.37	5.48
	-7	-7.6	18.90	6.44	18.90	6.58	18.90	6.72	18.15	6.43	17.40	6.13	15.90	5.54
	-5	-5.6	19.53	6.54	19.53	6.68	19.53	6.82	18.76	6.52	17.98	6.22	16.43	5.62
	-3	-3.7	22.05	6.64	22.05	6.78	22.05	6.92	21.18	6.62	20.30	6.31	18.55	5.71
	0	-0.7	24.26	6.78	24.26	6.92	24.26	7.07	23.29	6.76	22.33	6.45	20.41	5.83
	3	2.2	26.95	6.92	26.95	7.07	26.95	7.22	25.88	6.90	24.81	6.59	22.67	5.95
	5	4.1	30.44	7.02	30.44	7.17	30.44	7.32	29.23	7.00	28.02	6.68	25.61	6.04
	7	6	31.50	7.11	31.50	7.27	31.50	7.42	30.25	7.09	29.00	6.77	26.50	6.12
	9	7.9	31.50	6.88	31.50	7.02	31.50	7.17	30.25	6.85	29.00	6.54	26.50	5.91
	11	9.8	31.50	6.64	31.50	6.78	31.50	6.92	30.25	6.62	29.00	6.31	26.50	5.71
	13	11.8	31.50	6.40	31.50	6.53	31.50	6.67	30.25	6.38	29.00	6.09	26.50	5.50
15	13.7	31.50	6.16	31.50	6.29	31.50	6.42	30.25	6.14	29.00	5.86	26.50	5.30	
60%	-14.7	-15	12.15	5.16	12.15	5.27	12.15	5.38	11.67	5.14	11.19	4.91	10.22	4.44
	-12.6	-13	12.69	5.25	12.69	5.36	12.69	5.47	12.19	5.23	11.68	4.99	10.68	4.51
	-10.5	-11	13.23	5.33	13.23	5.44	13.23	5.56	12.71	5.31	12.18	5.07	11.13	4.58
	-9.5	-10	14.85	5.37	14.85	5.49	14.85	5.60	14.26	5.36	13.67	5.11	12.49	4.62
	-8.5	-9.1	15.66	5.41	15.66	5.53	15.66	5.64	15.04	5.40	14.42	5.15	13.17	4.65
	-7	-7.6	16.20	5.47	16.20	5.59	16.20	5.71	15.56	5.46	14.91	5.21	13.63	4.71
	-5	-5.6	16.74	5.55	16.74	5.67	16.74	5.79	16.08	5.54	15.41	5.28	14.08	4.78
	-3	-3.7	18.90	5.64	18.90	5.76	18.90	5.88	18.15	5.62	17.40	5.36	15.90	4.85
	0	-0.7	20.79	5.76	20.79	5.88	20.79	6.00	19.97	5.74	19.14	5.48	17.49	4.95
	3	2.2	23.10	5.88	23.10	6.00	23.10	6.13	22.18	5.86	21.27	5.59	19.43	5.06
	5	4.1	26.09	5.96	26.09	6.09	26.09	6.21	25.06	5.94	24.02	5.67	21.95	5.13
	7	6	27.00	6.04	27.00	6.17	27.00	6.30	25.93	6.02	24.86	5.75	22.71	5.20
	9	7.9	27.00	5.84	27.00	5.96	27.00	6.09	25.93	5.82	24.86	5.55	22.71	5.02
	11	9.8	27.00	5.64	27.00	5.76	27.00	5.88	25.93	5.62	24.86	5.36	22.71	4.85
	13	11.8	27.00	5.43	27.00	5.55	27.00	5.66	25.93	5.42	24.86	5.17	22.71	4.67
15	13.7	27.00	5.23	27.00	5.34	27.00	5.45	25.93	5.21	24.86	4.98	22.71	4.50	
50%	-14.7	-15	10.13	4.17	10.13	4.26	10.13	4.35	9.72	4.16	9.32	3.97	8.52	3.58
	-12.6	-13	10.58	4.24	10.58	4.33	10.58	4.42	10.16	4.22	9.74	4.03	8.90	3.64
	-10.5	-11	11.03	4.31	11.03	4.40	11.03	4.49	10.59	4.29	10.15	4.10	9.28	3.70
	-9.5	-10	12.38	4.34	12.38	4.43	12.38	4.52	11.88	4.33	11.39	4.13	10.41	3.73
	-8.5	-9.1	13.05	4.37	13.05	4.47	13.05	4.56	12.53	4.36	12.01	4.16	10.98	3.76
	-7	-7.6	13.50	4.42	13.50	4.52	13.50	4.61	12.96	4.41	12.43	4.21	11.36	3.80
	-5	-5.6	13.95	4.49	13.95	4.58	13.95	4.68	13.40	4.47	12.84	4.27	11.74	3.86
	-3	-3.7	15.75	4.55	15.75	4.65	15.75	4.75	15.13	4.54	14.50	4.33	13.25	3.91
	0	-0.7	17.33	4.65	17.33	4.75	17.33	4.85	16.64	4.64	15.95	4.42	14.58	4.00
	3	2.2	19.25	4.75	19.25	4.85	19.25	4.95	18.49	4.73	17.72	4.52	16.19	4.08
	5	4.1	21.74	4.81	21.74	4.92	21.74	5.02	20.88	4.80	20.02	4.58	18.29	4.14
	7	6	22.50	4.88	22.50	4.98	22.50	5.09	21.61	4.87	20.71	4.64	18.93	4.20
	9	7.9	22.50	4.72	22.50	4.82	22.50	4.92	21.61	4.70	20.71	4.49	18.93	4.06
	11	9.8	22.50	4.55	22.50	4.65	22.50	4.75	21.61	4.54	20.71	4.33	18.93	3.91
	13	11.8	22.50	4.39	22.50	4.48	22.50	4.58	21.61	4.38	20.71	4.17	18.93	3.77

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	15	13.7	22.50	4.22	22.50	4.31	22.50	4.40	21.61	4.21	20.71	4.02	18.93	3.63

16 HP

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°C DB	°C WB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
130%	-14.7	-15	24.75	11.22	24.75	11.46	24.75	11.70	23.77	11.19	22.79	10.68	20.82	9.65
	-12.6	-13	25.85	11.41	25.85	11.65	25.85	11.90	24.82	11.37	23.80	10.85	21.75	9.81
	-10.5	-11	26.95	11.59	26.95	11.84	26.95	12.09	25.88	11.56	24.81	11.03	22.67	9.97
	-9.5	-10	30.25	11.68	30.25	11.93	30.25	12.18	29.05	11.65	27.85	11.11	25.45	10.05
	-8.5	-9.1	31.90	11.77	31.90	12.02	31.90	12.27	30.63	11.74	29.37	11.20	26.84	10.12
	-7	-7.6	33.00	11.90	33.00	12.16	33.00	12.41	31.69	11.87	30.38	11.32	27.76	10.24
	-5	-5.6	34.10	12.08	34.10	12.34	34.10	12.60	32.75	12.04	31.39	11.49	28.69	10.39
	-3	-3.7	38.50	12.26	38.50	12.52	38.50	12.78	36.97	12.22	35.44	11.66	32.39	10.54
	0	-0.7	42.35	12.52	42.35	12.79	42.35	13.06	40.67	12.48	38.99	11.91	35.63	10.77
	3	2.2	47.06	12.79	47.06	13.06	47.06	13.33	45.19	12.75	43.32	12.16	39.59	11.00
	5	4.1	53.15	12.96	53.15	13.24	53.15	13.52	51.04	12.92	48.93	12.33	44.71	11.15
	7	6	55.00	13.14	55.00	13.42	55.00	13.70	52.82	13.10	50.63	12.50	46.27	11.30
	9	7.9	55.00	12.70	55.00	12.97	55.00	13.24	52.82	12.66	50.63	12.08	46.27	10.92
	11	9.8	55.00	12.26	55.00	12.52	55.00	12.78	52.82	12.22	50.63	11.66	46.27	10.54
	13	11.8	55.00	11.82	55.00	12.07	55.00	12.32	52.82	11.78	50.63	11.24	46.27	10.16
15	13.7	55.00	11.37	55.00	11.62	55.00	11.86	52.82	11.34	50.63	10.82	46.27	9.78	
120%	-14.7	-15	24.75	11.55	24.75	11.80	24.75	12.05	23.77	11.52	22.79	10.99	20.82	9.94
	-12.6	-13	25.85	11.74	25.85	12.00	25.85	12.25	24.82	11.71	23.80	11.17	21.75	10.10
	-10.5	-11	26.95	11.94	26.95	12.19	26.95	12.44	25.88	11.90	24.81	11.35	22.67	10.26
	-9.5	-10	30.25	12.03	30.25	12.28	30.25	12.54	29.05	11.99	27.85	11.44	25.45	10.34
	-8.5	-9.1	31.90	12.12	31.90	12.38	31.90	12.63	30.63	12.08	29.37	11.53	26.84	10.42
	-7	-7.6	33.00	12.25	33.00	12.52	33.00	12.78	31.69	12.22	30.38	11.66	27.76	10.54
	-5	-5.6	34.10	12.44	34.10	12.70	34.10	12.97	32.75	12.40	31.39	11.83	28.69	10.69
	-3	-3.7	38.50	12.62	38.50	12.89	38.50	13.16	36.97	12.58	35.44	12.00	32.39	10.85
	0	-0.7	42.35	12.89	42.35	13.16	42.35	13.44	40.67	12.85	38.99	12.26	35.63	11.08
	3	2.2	47.06	13.16	47.06	13.44	47.06	13.72	45.19	13.12	43.32	12.52	39.59	11.32
	5	4.1	53.15	13.34	53.15	13.63	53.15	13.91	51.04	13.30	48.93	12.69	44.71	11.48
	7	6	55.00	13.53	55.00	13.81	55.00	14.10	52.82	13.49	50.63	12.87	46.27	11.63
	9	7.9	55.00	13.07	55.00	13.35	55.00	13.63	52.82	13.03	50.63	12.44	46.27	11.24
	11	9.8	55.00	12.62	55.00	12.89	55.00	13.16	52.82	12.58	50.63	12.00	46.27	10.85
	13	11.8	55.00	12.16	55.00	12.42	55.00	12.68	52.82	12.13	50.63	11.57	46.27	10.46
15	13.7	55.00	11.71	55.00	11.96	55.00	12.21	52.82	11.67	50.63	11.14	46.27	10.07	
110%	-14.7	-15	24.75	11.78	24.75	12.03	24.75	12.28	23.77	11.74	22.79	11.21	20.82	10.13
	-12.6	-13	25.85	11.97	25.85	12.23	25.85	12.49	24.82	11.94	23.80	11.39	21.75	10.30
	-10.5	-11	26.95	12.17	26.95	12.43	26.95	12.69	25.88	12.13	24.81	11.58	22.67	10.47
	-9.5	-10	30.25	12.26	30.25	12.52	30.25	12.79	29.05	12.23	27.85	11.66	25.45	10.54
	-8.5	-9.1	31.90	12.35	31.90	12.62	31.90	12.88	30.63	12.32	29.37	11.75	26.84	10.62
	-7	-7.6	33.00	12.49	33.00	12.76	33.00	13.03	31.69	12.46	30.38	11.89	27.76	10.74
	-5	-5.6	34.10	12.68	34.10	12.95	34.10	13.22	32.75	12.64	31.39	12.06	28.69	10.90
	-3	-3.7	38.50	12.86	38.50	13.14	38.50	13.41	36.97	12.83	35.44	12.24	32.39	11.06
	0	-0.7	42.35	13.14	42.35	13.42	42.35	13.70	40.67	13.10	38.99	12.50	35.63	11.30
	3	2.2	47.06	13.42	47.06	13.71	47.06	13.99	45.19	13.38	43.32	12.77	39.59	11.54
	5	4.1	53.15	13.61	53.15	13.90	53.15	14.19	51.04	13.56	48.93	12.94	44.71	11.70
	7	6	55.00	13.79	55.00	14.09	55.00	14.38	52.82	13.75	50.63	13.12	46.27	11.86
	9	7.9	55.00	13.33	55.00	13.61	55.00	13.90	52.82	13.29	50.63	12.68	46.27	11.46
	11	9.8	55.00	12.86	55.00	13.14	55.00	13.41	52.82	12.83	50.63	12.24	46.27	11.06
	13	11.8	55.00	12.40	55.00	12.67	55.00	12.93	52.82	12.36	50.63	11.80	46.27	10.67

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
			TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	°C DB	°C WB	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	
	15	13.7	55.00	11.94	55.00	12.19	55.00	12.45	52.82	11.90	50.63	11.36	46.27	10.27
100%	-14.7	-15	22.50	10.49	22.50	10.71	22.50	10.93	21.61	10.45	20.71	9.98	18.93	9.02
	-12.6	-13	23.50	10.66	23.50	10.89	23.50	11.11	22.57	10.63	21.63	10.14	19.77	9.17
	-10.5	-11	24.50	10.83	24.50	11.06	24.50	11.29	23.53	10.80	22.56	10.31	20.61	9.32
	-9.5	-10	27.50	10.92	27.50	11.15	27.50	11.38	26.41	10.88	25.32	10.38	23.13	9.39
	-8.5	-9.1	29.00	11.00	29.00	11.23	29.00	11.47	27.85	10.96	26.70	10.46	24.40	9.46
	-7	-7.6	30.00	11.12	30.00	11.36	30.00	11.60	28.81	11.09	27.62	10.58	25.24	9.56
	-5	-5.6	31.00	11.29	31.00	11.53	31.00	11.77	29.77	11.25	28.54	10.74	26.08	9.71
	-3	-3.7	35.00	11.45	35.00	11.70	35.00	11.94	33.61	11.42	32.22	10.89	29.44	9.85
	0	-0.7	38.50	11.70	38.50	11.95	38.50	12.20	36.97	11.66	35.44	11.13	32.39	10.06
	3	2.2	42.78	11.95	42.78	12.20	42.78	12.46	41.08	11.91	39.38	11.36	35.99	10.27
	5	4.1	48.32	12.11	48.32	12.37	48.32	12.63	46.40	12.07	44.48	11.52	40.65	10.42
	7	6	50.00	12.28	50.00	12.54	50.00	12.80	48.02	12.24	46.03	11.68	42.06	10.56
	9	7.9	50.00	11.86	50.00	12.12	50.00	12.37	48.02	11.83	46.03	11.29	42.06	10.20
	11	9.8	50.00	11.45	50.00	11.70	50.00	11.94	48.02	11.42	46.03	10.89	42.06	9.85
	13	11.8	50.00	11.04	50.00	11.28	50.00	11.51	48.02	11.01	46.03	10.50	42.06	9.49
15	13.7	50.00	10.63	50.00	10.85	50.00	11.08	48.02	10.60	46.03	10.11	42.06	9.14	
90%	-14.7	-15	20.25	9.26	20.25	9.46	20.25	9.66	19.45	9.23	18.64	8.81	17.04	7.96
	-12.6	-13	21.15	9.41	21.15	9.61	21.15	9.82	20.31	9.39	19.47	8.96	17.79	8.10
	-10.5	-11	22.05	9.57	22.05	9.77	22.05	9.97	21.18	9.54	20.30	9.10	18.55	8.23
	-9.5	-10	24.75	9.64	24.75	9.84	24.75	10.05	23.77	9.61	22.79	9.17	20.82	8.29
	-8.5	-9.1	26.10	9.71	26.10	9.92	26.10	10.13	25.06	9.68	24.03	9.24	21.96	8.35
	-7	-7.6	27.00	9.82	27.00	10.03	27.00	10.24	25.93	9.79	24.86	9.34	22.71	8.45
	-5	-5.6	27.90	9.97	27.90	10.18	27.90	10.39	26.79	9.94	25.69	9.48	23.47	8.57
	-3	-3.7	31.50	10.11	31.50	10.33	31.50	10.54	30.25	10.08	29.00	9.62	26.50	8.70
	0	-0.7	34.65	10.33	34.65	10.55	34.65	10.77	33.28	10.30	31.90	9.83	29.15	8.88
	3	2.2	38.50	10.55	38.50	10.78	38.50	11.00	36.97	10.52	35.44	10.04	32.39	9.07
	5	4.1	43.49	10.70	43.49	10.92	43.49	11.15	41.76	10.66	40.03	10.17	36.58	9.20
	7	6	45.00	10.84	45.00	11.07	45.00	11.30	43.21	10.81	41.43	10.31	37.86	9.32
	9	7.9	45.00	10.48	45.00	10.70	45.00	10.92	43.21	10.45	41.43	9.97	37.86	9.01
	11	9.8	45.00	10.11	45.00	10.33	45.00	10.54	43.21	10.08	41.43	9.62	37.86	8.70
	13	11.8	45.00	9.75	45.00	9.96	45.00	10.17	43.21	9.72	41.43	9.27	37.86	8.38
15	13.7	45.00	9.39	45.00	9.59	45.00	9.79	43.21	9.36	41.43	8.93	37.86	8.07	
80%	-14.7	-15	18.00	8.10	18.00	8.28	18.00	8.45	17.29	8.08	16.57	7.71	15.14	6.97
	-12.6	-13	18.80	8.24	18.80	8.41	18.80	8.59	18.05	8.21	17.31	7.84	15.82	7.08
	-10.5	-11	19.60	8.37	19.60	8.55	19.60	8.73	18.82	8.35	18.04	7.96	16.49	7.20
	-9.5	-10	22.00	8.43	22.00	8.61	22.00	8.79	21.13	8.41	20.25	8.02	18.51	7.25
	-8.5	-9.1	23.20	8.50	23.20	8.68	23.20	8.86	22.28	8.47	21.36	8.08	19.52	7.31
	-7	-7.6	24.00	8.59	24.00	8.78	24.00	8.96	23.05	8.57	22.10	8.18	20.19	7.39
	-5	-5.6	24.80	8.72	24.80	8.91	24.80	9.09	23.82	8.69	22.83	8.30	20.86	7.50
	-3	-3.7	28.00	8.85	28.00	9.04	28.00	9.23	26.89	8.82	25.78	8.42	23.56	7.61
	0	-0.7	30.80	9.04	30.80	9.23	30.80	9.43	29.58	9.01	28.36	8.60	25.91	7.77
	3	2.2	34.22	9.23	34.22	9.43	34.22	9.63	32.86	9.20	31.51	8.78	28.79	7.94
	5	4.1	38.65	9.36	38.65	9.56	38.65	9.76	37.12	9.33	35.59	8.90	32.52	8.05
	7	6	40.00	9.49	40.00	9.69	40.00	9.89	38.41	9.46	36.83	9.02	33.65	8.16
	9	7.9	40.00	9.17	40.00	9.36	40.00	9.56	38.41	9.14	36.83	8.72	33.65	7.88
	11	9.8	40.00	8.85	40.00	9.04	40.00	9.23	38.41	8.82	36.83	8.42	33.65	7.61
	13	11.8	40.00	8.53	40.00	8.71	40.00	8.89	38.41	8.50	36.83	8.12	33.65	7.34

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	15	13.7	40.00	8.21	40.00	8.39	40.00	8.56	38.41	8.19	36.83	7.81	33.65	7.06
70%	-14.7	-15	15.75	6.94	15.75	7.09	15.75	7.24	15.13	6.92	14.50	6.61	13.25	5.97
	-12.6	-13	16.45	7.06	16.45	7.21	16.45	7.36	15.80	7.04	15.14	6.72	13.84	6.07
	-10.5	-11	17.15	7.17	17.15	7.33	17.15	7.48	16.47	7.15	15.79	6.83	14.43	6.17
	-9.5	-10	19.25	7.23	19.25	7.38	19.25	7.54	18.49	7.21	17.72	6.88	16.19	6.22
	-8.5	-9.1	20.30	7.28	20.30	7.44	20.30	7.59	19.49	7.26	18.69	6.93	17.08	6.26
	-7	-7.6	21.00	7.37	21.00	7.52	21.00	7.68	20.17	7.34	19.33	7.01	17.67	6.33
	-5	-5.6	21.70	7.47	21.70	7.63	21.70	7.79	20.84	7.45	19.98	7.11	18.26	6.43
	-3	-3.7	24.50	7.58	24.50	7.75	24.50	7.91	23.53	7.56	22.56	7.21	20.61	6.52
	0	-0.7	26.95	7.75	26.95	7.91	26.95	8.08	25.88	7.72	24.81	7.37	22.67	6.66
	3	2.2	29.94	7.91	29.94	8.08	29.94	8.25	28.76	7.89	27.57	7.53	25.19	6.80
	5	4.1	33.82	8.02	33.82	8.19	33.82	8.36	32.48	8.00	31.14	7.63	28.45	6.90
	7	6	35.00	8.13	35.00	8.30	35.00	8.48	33.61	8.11	32.22	7.73	29.44	6.99
	9	7.9	35.00	7.86	35.00	8.03	35.00	8.19	33.61	7.83	32.22	7.47	29.44	6.76
	11	9.8	35.00	7.58	35.00	7.75	35.00	7.91	33.61	7.56	32.22	7.22	29.44	6.52
	13	11.8	35.00	7.31	35.00	7.47	35.00	7.62	33.61	7.29	32.22	6.96	29.44	6.29
15	13.7	35.00	7.04	35.00	7.19	35.00	7.34	33.61	7.02	32.22	6.70	29.44	6.05	
60%	-14.7	-15	13.50	5.90	13.50	6.02	13.50	6.15	12.96	5.88	12.43	5.61	11.36	5.07
	-12.6	-13	14.10	5.99	14.10	6.12	14.10	6.25	13.54	5.98	12.98	5.70	11.86	5.16
	-10.5	-11	14.70	6.09	14.70	6.22	14.70	6.35	14.12	6.07	13.53	5.80	12.37	5.24
	-9.5	-10	16.50	6.14	16.50	6.27	16.50	6.40	15.85	6.12	15.19	5.84	13.88	5.28
	-8.5	-9.1	17.40	6.19	17.40	6.32	17.40	6.45	16.71	6.17	16.02	5.88	14.64	5.32
	-7	-7.6	18.00	6.25	18.00	6.39	18.00	6.52	17.29	6.24	16.57	5.95	15.14	5.38
	-5	-5.6	18.60	6.35	18.60	6.48	18.60	6.62	17.86	6.33	17.12	6.04	15.65	5.46
	-3	-3.7	21.00	6.44	21.00	6.58	21.00	6.71	20.17	6.42	19.33	6.13	17.67	5.54
	0	-0.7	23.10	6.58	23.10	6.72	23.10	6.86	22.18	6.56	21.27	6.26	19.43	5.66
	3	2.2	25.67	6.72	25.67	6.86	25.67	7.01	24.65	6.70	23.63	6.39	21.59	5.78
	5	4.1	28.99	6.81	28.99	6.96	28.99	7.10	27.84	6.79	26.69	6.48	24.39	5.86
	7	6	30.00	6.90	30.00	7.05	30.00	7.20	28.81	6.88	27.62	6.57	25.24	5.94
	9	7.9	30.00	6.67	30.00	6.81	30.00	6.96	28.81	6.65	27.62	6.35	25.24	5.74
	11	9.8	30.00	6.44	30.00	6.58	30.00	6.72	28.81	6.42	27.62	6.13	25.24	5.54
	13	11.8	30.00	6.21	30.00	6.34	30.00	6.47	28.81	6.19	27.62	5.91	25.24	5.34
15	13.7	30.00	5.98	30.00	6.10	30.00	6.23	28.81	5.96	27.62	5.69	25.24	5.14	
50%	-14.7	-15	11.25	4.76	11.25	4.87	11.25	4.97	10.80	4.75	10.36	4.53	9.46	4.10
	-12.6	-13	11.75	4.84	11.75	4.95	11.75	5.05	11.28	4.83	10.82	4.61	9.88	4.16
	-10.5	-11	12.25	4.92	12.25	5.03	12.25	5.13	11.76	4.91	11.28	4.68	10.31	4.23
	-9.5	-10	13.75	4.96	13.75	5.06	13.75	5.17	13.20	4.94	12.66	4.72	11.57	4.26
	-8.5	-9.1	14.50	5.00	14.50	5.10	14.50	5.21	13.92	4.98	13.35	4.75	12.20	4.30
	-7	-7.6	15.00	5.05	15.00	5.16	15.00	5.27	14.40	5.04	13.81	4.81	12.62	4.34
	-5	-5.6	15.50	5.13	15.50	5.24	15.50	5.35	14.88	5.11	14.27	4.88	13.04	4.41
	-3	-3.7	17.50	5.20	17.50	5.31	17.50	5.42	16.81	5.19	16.11	4.95	14.72	4.47
	0	-0.7	19.25	5.31	19.25	5.43	19.25	5.54	18.49	5.30	17.72	5.06	16.19	4.57
	3	2.2	21.39	5.43	21.39	5.54	21.39	5.66	20.54	5.41	19.69	5.16	17.99	4.67
	5	4.1	24.16	5.50	24.16	5.62	24.16	5.74	23.20	5.49	22.24	5.23	20.32	4.73
	7	6	25.00	5.58	25.00	5.70	25.00	5.82	24.01	5.56	23.02	5.31	21.03	4.80
	9	7.9	25.00	5.39	25.00	5.50	25.00	5.62	24.01	5.37	23.02	5.13	21.03	4.64
	11	9.8	25.00	5.20	25.00	5.31	25.00	5.42	24.01	5.19	23.02	4.95	21.03	4.47
	13	11.8	25.00	5.02	25.00	5.12	25.00	5.23	24.01	5.00	23.02	4.77	21.03	4.31

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	15	13.7	25.00	4.83	25.00	4.93	25.00	5.03	24.01	4.81	23.02	4.59	21.03	4.15

18 HP

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
130%	-14.7	-15	41.0	10.63	40.9	11.21	40.8	11.80	40.7	12.10	40.6	12.40	40.5	13.00
	-12.6	-13	42.9	11.12	42.8	11.70	42.7	12.20	42.6	12.50	42.6	12.80	42.4	13.40
	-10.5	-11	45.0	11.60	44.9	12.10	44.7	12.70	44.7	12.90	44.6	13.20	44.5	13.70
	-9.5	-10	46.0	11.80	45.9	12.30	45.8	12.90	45.7	13.10	45.6	13.40	45.5	13.90
	-8.5	-9.1	47.0	12.00	46.9	12.50	46.7	13.00	46.7	13.30	46.6	13.60	46.5	14.10
	-7	-7.6	48.7	12.40	48.5	12.80	48.4	13.30	48.3	13.60	48.3	13.80	48.1	14.30
	-5	-5.6	50.9	12.80	50.8	13.20	50.7	13.70	50.6	13.90	50.6	14.20	50.4	14.60
	-3	-3.7	53.2	13.10	53.1	13.60	53.0	14.00	52.9	14.30	52.8	14.50	52.7	14.90
	0	-0.7	57.0	13.70	56.8	14.10	56.7	14.50	56.6	14.70	56.6	14.90	56.5	15.40
	3	2.2	60.8	14.20	60.7	14.60	60.5	15.00	60.5	15.20	60.4	15.40	60.3	15.80
	5	4.1	63.4	14.50	63.3	14.90	63.2	15.20	63.1	15.40	63.0	15.60	62.9	16.00
	7	6	66.1	14.80	66.0	15.10	65.9	15.50	65.8	15.70	65.8	15.90	64.0	15.60
	9	7.9	68.9	15.10	68.8	15.40	68.7	15.70	68.6	15.90	68.6	16.10	64.0	14.80
	11	9.8	71.8	15.30	71.7	15.70	71.6	16.00	71.1	16.00	68.7	15.30	64.0	14.10
	13	11.8	75.0	15.60	74.8	15.90	73.5	15.20	71.1	15.20	68.7	14.60	64.0	13.40
15	13.7	78.0	15.80	77.9	16.10	73.5	14.40	71.1	14.40	68.7	13.90	64.0	12.70	
120%	-14.7	-15	40.8	11.40	40.7	12.00	40.6	12.50	40.5	12.80	40.5	13.00	40.4	13.60
	-12.6	-13	42.8	11.90	42.7	12.40	42.5	12.90	42.5	13.20	42.4	13.40	42.3	13.90
	-10.5	-11	44.8	12.30	44.7	12.80	44.6	13.30	44.5	13.50	44.4	13.80	44.3	14.30
	-9.5	-10	45.9	12.50	45.7	13.00	45.6	13.50	45.6	13.70	45.5	14.00	45.4	14.40
	-8.5	-9.1	46.8	12.70	46.7	13.20	46.6	13.70	46.5	13.90	46.5	14.10	46.3	14.60
	-7	-7.6	48.5	13.00	48.4	13.50	48.2	13.90	48.2	14.10	48.1	14.40	48.0	14.80
	-5	-5.6	50.8	13.40	50.7	13.80	50.5	14.30	50.5	14.50	50.4	14.70	50.3	15.10
	-3	-3.7	53.0	13.70	52.9	14.20	52.8	14.60	52.7	14.80	52.7	15.00	52.6	15.40
	0	-0.7	56.8	14.30	56.7	14.60	56.6	15.00	56.5	15.20	56.4	15.40	56.3	15.80
	3	2.2	60.6	14.70	60.5	15.10	60.4	15.40	60.3	15.60	60.3	15.80	59.1	15.70
	5	4.1	63.3	15.00	63.1	15.30	63.0	15.70	63.0	15.90	62.9	16.00	59.1	14.90
	7	6	66.0	15.30	65.8	15.60	65.7	15.90	65.6	16.10	63.4	15.40	59.1	14.10
	9	7.9	68.8	15.50	68.6	15.80	67.8	15.90	65.6	15.30	63.4	14.60	59.1	13.40
	11	9.8	71.6	15.80	71.5	16.10	67.8	15.10	65.6	14.50	63.4	13.90	59.1	12.80
	13	11.8	74.8	16.00	72.2	15.40	67.8	14.30	65.6	13.80	63.4	13.20	59.1	12.20
15	13.7	76.5	15.80	72.2	14.70	67.8	13.60	65.6	13.10	63.4	12.60	59.1	11.60	
110%	-14.7	-15	40.7	12.20	40.6	12.70	40.4	13.20	40.4	13.40	40.3	13.70	40.2	14.20
	-12.6	-13	42.6	12.60	42.5	13.10	42.4	13.60	42.3	13.80	42.3	14.00	42.2	14.50
	-10.5	-11	44.6	13.00	44.5	13.50	44.4	13.90	44.4	14.20	44.3	14.40	44.2	14.80
	-9.5	-10	45.7	13.20	45.6	13.70	45.5	14.10	45.4	14.30	45.4	14.50	45.2	15.00
	-8.5	-9.1	46.7	13.40	46.5	13.80	46.4	14.30	46.4	14.50	46.3	14.70	46.2	15.10
	-7	-7.6	48.3	13.70	48.2	14.10	48.1	14.50	48.0	14.70	48.0	14.90	47.9	15.30
	-5	-5.6	50.6	14.00	50.5	14.40	50.4	14.80	50.3	15.00	50.3	15.20	50.2	15.60
	-3	-3.7	52.9	14.40	52.8	14.70	52.6	15.10	52.6	15.30	52.5	15.50	52.4	15.90
	0	-0.7	56.6	14.80	56.5	15.20	56.4	15.50	56.3	15.70	56.3	15.90	54.2	15.30
	3	2.2	60.5	15.20	60.3	15.60	60.2	15.90	60.2	16.10	58.2	15.40	54.2	14.10
	5	4.1	63.1	15.50	63.0	15.80	62.2	15.80	60.2	15.20	58.2	14.60	54.2	13.40
	7	6	65.8	15.80	65.7	16.10	62.2	15.00	60.2	14.40	58.2	13.90	54.2	12.70
	9	7.9	68.6	16.00	66.1	15.40	62.2	14.30	60.2	13.70	58.2	13.20	54.2	12.10
	11	9.8	70.1	15.70	66.1	14.60	62.2	13.60	60.2	13.10	58.2	12.60	54.2	11.60
	13	11.8	70.1	14.90	66.1	13.90	62.2	12.90	60.2	12.40	58.2	11.90	54.2	11.00

GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
	15	13.7	70.1	14.20	66.1	13.20	62.2	12.30	60.2	11.80	58.2	11.40	54.2	10.50
100%	-14.7	-15	40.5	13.00	40.4	13.40	40.3	13.90	40.2	14.10	40.2	14.30	40.1	14.80
	-12.6	-13	42.4	13.40	42.3	13.80	42.2	14.20	42.2	14.50	42.1	14.70	42.0	15.10
	-10.5	-11	44.5	13.80	44.4	14.20	44.3	14.60	44.2	14.80	44.2	15.00	44.1	15.40
	-9.5	-10	45.5	13.90	45.4	14.30	45.3	14.70	45.3	14.90	45.2	15.10	45.1	15.50
	-8.5	-9.1	46.5	14.10	46.4	14.50	46.3	14.90	46.2	15.10	46.2	15.30	46.1	15.60
	-7	-7.6	48.1	14.30	48.0	14.70	47.9	15.10	47.9	15.30	47.8	15.50	47.7	15.80
	-5	-5.6	50.4	14.70	50.3	15.00	50.2	15.40	50.2	15.60	50.1	15.70	49.2	15.70
	-3	-3.7	52.7	15.00	52.6	15.30	52.5	15.60	52.4	15.80	52.4	16.00	49.2	14.90
	0	-0.7	56.4	15.40	56.3	15.70	56.2	16.00	54.7	15.50	52.9	14.90	49.2	13.60
	3	2.2	60.3	15.80	60.1	16.00	56.5	14.90	54.7	14.30	52.9	13.70	49.2	12.60
	5	4.1	62.9	16.00	60.1	15.20	56.5	14.10	54.7	13.60	52.9	13.00	49.2	12.00
	7	6	63.8	15.50	60.1	14.40	56.5	13.40	54.7	12.90	52.9	12.40	49.2	11.40
	9	7.9	63.8	14.70	60.1	13.70	56.5	12.70	54.7	12.30	52.9	11.80	49.2	10.90
	11	9.8	63.8	14.00	60.1	13.10	56.5	12.10	54.7	11.70	52.9	11.20	49.2	10.40
	13	11.8	63.8	13.30	60.1	12.40	56.5	11.50	54.7	11.10	52.9	10.70	49.2	9.90
15	13.7	63.8	12.70	60.1	11.80	56.5	11.00	54.7	10.60	52.9	10.20	49.2	9.40	
90%	-14.7	-15	40.3	13.80	40.2	14.20	40.1	14.60	40.1	14.80	40.0	15.00	40.0	15.40
	-12.6	-13	42.3	14.10	42.2	14.50	42.1	14.90	42.0	15.10	42.0	15.30	41.9	15.70
	-10.5	-11	44.3	14.50	44.2	14.80	44.1	15.20	44.1	15.40	44.0	15.60	43.9	15.90
	-9.5	-10	45.3	14.60	45.2	15.00	45.2	15.30	45.1	15.50	45.1	15.70	44.3	15.70
	-8.5	-9.1	46.3	14.80	46.2	15.10	46.1	15.50	46.1	15.60	46.0	15.80	44.3	15.30
	-7	-7.6	48.0	15.00	47.9	15.30	47.8	15.70	47.7	15.80	47.6	16.00	44.3	14.60
	-5	-5.6	50.3	15.30	50.2	15.60	50.1	15.90	49.2	15.70	47.6	15.10	44.3	13.80
	-3	-3.7	52.5	15.60	52.4	15.90	50.9	15.50	49.2	14.80	47.6	14.30	44.3	13.10
	0	-0.7	56.3	15.90	54.1	15.30	50.9	14.20	49.2	13.60	47.6	13.10	44.3	12.00
	3	2.2	57.4	15.20	54.1	14.10	50.9	13.10	49.2	12.60	47.6	12.10	44.3	11.10
	5	4.1	57.4	14.40	54.1	13.40	50.9	12.40	49.2	12.00	47.6	11.50	44.3	10.60
	7	6	57.4	13.70	54.1	12.70	50.9	11.80	49.2	11.40	47.6	11.00	44.3	10.10
	9	7.9	57.4	13.00	54.1	12.10	50.9	11.30	49.2	10.90	47.6	10.40	44.3	9.60
	11	9.8	57.4	12.40	54.1	11.50	50.9	10.70	49.2	10.40	47.6	10.00	44.3	9.20
	13	11.8	57.4	11.70	54.1	11.00	50.9	10.20	49.2	9.90	47.6	9.50	44.3	8.80
15	13.7	57.4	11.20	54.1	10.50	50.9	9.80	49.2	9.40	47.6	9.40	44.3	8.41	
80%	-14.7	-15	40.1	14.60	40.1	14.90	40.0	15.30	39.9	15.50	39.9	15.70	39.4	15.70
	-12.6	-13	42.1	14.90	42.0	15.20	41.9	15.60	41.9	15.70	41.8	15.90	39.4	14.80
	-10.5	-11	44.1	15.20	44.0	15.50	43.9	15.80	43.7	15.90	42.3	15.30	39.4	14.00
	-9.5	-10	45.2	15.30	45.1	15.60	45.0	16.00	43.7	15.40	42.3	14.80	39.4	13.60
	-8.5	-9.1	46.1	15.50	46.0	15.80	45.2	15.70	43.7	15.00	42.3	14.40	39.4	13.20
	-7	-7.6	47.8	15.70	47.7	16.00	45.2	15.00	43.7	14.40	42.3	13.80	39.4	12.70
	-5	-5.6	50.1	15.90	48.1	15.30	45.2	14.10	43.7	13.60	42.3	13.10	39.4	12.00
	-3	-3.7	51.1	15.50	48.1	14.40	45.2	13.40	43.7	12.90	42.3	12.40	39.4	11.40
	0	-0.7	51.1	14.20	48.1	13.30	45.2	12.30	43.7	11.90	42.3	11.40	39.4	10.50
	3	2.2	51.1	13.10	48.1	12.30	45.2	11.40	43.7	11.00	42.3	10.60	39.4	9.80
	5	4.1	51.1	12.50	48.1	11.70	45.2	10.90	43.7	10.50	42.3	10.10	39.4	9.30
	7	6	51.1	11.90	48.1	11.10	45.2	10.30	43.7	10.00	42.3	9.60	39.4	8.90
	9	7.9	51.1	11.30	48.1	10.60	45.2	9.90	43.7	9.50	42.3	9.20	39.4	8.48
	11	9.8	51.1	10.80	48.1	10.10	45.2	9.40	43.7	9.10	42.3	8.80	39.4	8.11
	13	11.8	51.1	10.30	48.1	9.60	45.2	9.00	43.7	8.70	42.3	8.35	39.4	7.75


GREEN-GRV 4 Outdoor unit

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	15	13.7	51.1	9.80	48.1	9.20	45.2	8.60	43.7	8.29	42.3	8.00	39.4	7.42
70%	-14.7	-15	40.0	15.40	39.9	15.70	39.6	15.80	38.3	15.20	37.0	14.60	34.5	13.40
	-12.6	-13	41.9	15.60	41.8	15.90	39.6	14.90	38.3	14.30	37.0	13.80	34.5	12.60
	-10.5	-11	43.9	15.90	42.1	15.20	39.6	14.10	38.3	13.50	37.0	13.00	34.5	11.90
	-9.5	-10	44.6	15.80	42.1	14.70	39.6	13.70	38.3	13.10	37.0	12.60	34.5	11.60
	-8.5	-9.1	44.6	15.40	42.1	14.30	39.6	13.30	38.3	12.80	37.0	12.30	34.5	11.30
	-7	-7.6	44.6	14.80	42.1	13.70	39.6	12.80	38.3	12.30	37.0	11.80	34.5	10.90
	-5	-5.6	44.6	13.90	42.1	13.00	39.6	12.10	38.3	11.60	37.0	11.20	34.5	10.30
	-3	-3.7	44.6	13.20	42.1	12.30	39.6	11.40	38.3	11.00	37.0	10.60	34.5	9.80
	0	-0.7	44.6	12.10	42.1	11.30	39.6	10.60	38.3	10.20	37.0	9.80	34.5	9.06
	3	2.2	44.6	11.20	42.1	10.50	39.6	9.80	38.3	9.50	37.0	9.10	34.5	8.43
	5	4.1	44.6	10.70	42.1	10.00	39.6	9.30	38.3	9.00	37.0	8.69	34.5	8.05
	7	6	44.6	10.20	42.1	9.50	39.6	8.90	38.3	8.60	37.0	8.30	34.5	7.69
	9	7.9	44.6	9.70	42.1	9.10	39.6	8.52	38.3	8.22	37.0	7.93	34.5	7.36
	11	9.8	44.6	9.30	42.1	8.70	39.6	8.14	38.3	7.87	37.0	7.59	34.5	7.05
	13	11.8	44.6	8.90	42.1	8.31	39.6	7.78	38.3	7.52	37.0	7.26	34.5	6.75
15	13.7	44.6	8.50	42.1	7.96	39.6	7.46	38.3	7.21	37.0	6.96	34.5	6.48	
60%	-14.7	-15	32.7	14.40	31.9	14.20	30.0	13.20	29.0	12.70	28.1	12.20	26.1	11.20
	-12.6	-13	33.9	14.40	31.9	13.40	30.0	12.50	29.0	12.00	28.1	11.50	26.1	10.60
	-10.5	-11	33.9	13.40	31.9	12.70	30.0	11.80	29.0	11.40	28.1	10.90	26.1	10.08
	-9.5	-10	33.9	13.20	31.9	12.40	30.0	11.50	29.0	11.10	28.1	10.60	26.1	9.81
	-8.5	-9.1	33.9	12.90	31.9	12.00	30.0	11.20	29.0	10.80	28.1	10.40	26.1	9.57
	-7	-7.6	33.9	12.30	31.9	11.50	30.0	10.70	29.0	10.32	28.1	9.94	26.1	9.18
	-5	-5.6	33.9	11.60	31.9	9.00	30.0	10.12	29.0	9.75	28.1	9.39	26.1	8.68
	-3	-3.7	33.9	11.00	31.9	10.27	30.0	9.58	29.0	9.23	28.1	8.89	26.1	8.23
	0	-0.7	33.9	10.05	31.9	0.41	30.0	8.78	29.0	8.47	28.1	8.17	26.1	7.57
	3	2.2	33.9	9.23	31.9	8.65	30.0	8.09	29.0	7.81	28.1	7.54	26.1	7.00
	5	4.1	33.9	8.74	31.9	8.20	30.0	7.67	29.0	7.41	28.1	7.15	26.1	6.65
	7	6	33.9	8.28	31.9	7.77	30.0	7.28	29.0	7.04	28.1	6.79	26.1	6.32
	9	7.9	33.9	7.85	31.9	7.38	30.0	6.91	29.0	6.69	28.1	6.46	26.1	6.02
	11	9.8	33.9	7.45	31.9	7.01	30.0	6.58	29.0	6.36	28.1	6.15	26.1	5.73
	13	11.8	33.9	7.06	31.9	6.65	30.0	6.24	29.0	6.04	28.1	5.85	26.1	5.45
15	13.7	33.9	6.72	31.9	6.33	30.0	5.95	29.0	5.76	28.1	5.58	26.1	5.21	
50%	-14.7	-15	28.2	12.20	26.6	11.40	25.0	10.60	24.2	10.20	23.4	9.86	21.8	9.11
	-12.6	-13	28.2	11.60	26.6	10.80	25.0	10.10	24.2	9.74	23.4	9.38	21.8	8.67
	-10.5	-11	28.2	11.00	26.6	10.30	25.0	9.58	24.2	9.24	23.4	8.90	21.8	8.24
	-9.5	-10	28.2	10.70	26.6	10.00	25.0	9.33	24.2	8.99	23.4	8.67	21.8	8.02
	-8.5	-9.1	28.2	10.40	26.6	9.76	25.0	9.10	24.2	8.78	23.4	8.46	21.8	7.84
	-7	-7.6	28.2	9.99	26.6	9.36	25.0	8.73	24.2	8.43	23.4	8.13	21.8	7.53
	-5	-5.6	28.2	9.44	26.6	8.85	25.0	8.27	24.2	7.98	23.4	7.70	21.8	7.14
	-3	-3.7	28.2	8.94	26.6	8.39	25.0	7.84	24.2	7.58	23.4	7.31	21.8	6.79
	0	-0.7	28.2	8.21	26.6	7.72	25.0	7.23	24.2	6.98	23.4	6.75	21.8	6.28
	3	2.2	28.2	7.58	26.6	7.12	25.0	6.68	24.2	6.46	23.4	6.25	21.8	5.82
	5	4.1	28.2	7.19	26.6	6.77	25.0	6.35	24.2	6.15	23.4	5.94	21.8	5.54
	7	6	28.2	6.83	26.6	6.43	25.0	6.04	24.2	5.85	23.4	5.66	21.8	5.29
	9	7.9	28.2	6.49	26.6	6.12	25.0	5.76	24.2	5.58	23.4	5.40	21.8	5.05
	11	9.8	28.2	6.18	26.6	5.83	25.0	5.49	24.2	5.32	23.4	5.15	21.8	4.82
	13	11.8	28.2	5.87	26.6	5.55	25.0	5.23	24.2	5.07	23.4	4.91	21.8	4.60

Combination (Capacity index)	Outdoor air temp.		Indoor temperature(°C DB)											
			16		18		20		21		22		24	
	°C DB	°C WB	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI	TC	PI
			kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW
	15	13.7	28.2	5.60	26.6	5.30	25.0	4.99	24.2	4.84	23.4	4.70	21.8	4.40

6.5 Length Correction Coefficient “K3” of Indoor/Outdoor Unit Connecting Tube.


High head(m)



Rate of change in cooling capacity

Equivalent pipe length(m)

High head(m)





Rate of change in heating capacity

Equivalent pipe length(m)

Positive side of high head means installation height of outdoor unit should be higher than indoor unit; negative side of high head means installation height of outdoor unit should be lower than indoor unit; (change ratio of basic capacity)

6.6 Heating Capacity Correction Coefficient “K4” under Frosting of Outdoor Heat Exchanger



6.7 Capacity Correction

Under cooling mode: actual cooling capacity = nominal cooling capacity×K3;

Under heating mode: actual Heating capacity = nominal cooling capacity×K3×K4。

6.8 Units selection example (Selection procedure for cooling and heating are the same)

(1) Given condition

a. temperature condition

Cooling: Indoor 21°C (WB), Outdoor 35°C (DB)

b. Cooling load

	Room A	Room B	Room C	RoomD
Load (kW)	2.0	9.1	5.2	6.5

c. Piping equivalent length: 30m

d. Height difference: 10m (Outdoor unit is lower than indoor units)

(1) Indoor unit selection

Select the suitable capacity for condition of ‘Indoor 21°C (WB), Outdoor 35°C (DB)’ using indoor unit capacity table. Because of the long pipelines and large height difference between indoor and outdoor unit, we consider to choose indoor unit of a largernominal cooling capacity.

The selected result is as follow:

	Room A	Room B	Room C	Room D
Cooling load (kW)	2.0	9.1	5.2	6.5
Unit specification	2.2	10.0	5.6	7.1
Capacity (kW)	2.2	10.0	5.6	7.1

(3) Outdoor unit selection

Calculate the total nominal cooling capacity of indoor units in the combination according to the above table:

$$2.2 \times 1 + 10.0 \times 1 + 5.6 \times 1 + 7.1 \times 1 = 24.9 \text{ kW}$$

Select outdoor unit: GRV08P3T3, which has nominal cooling capacity: 25.2kW.

The combination ratio between indoor units and outdoor unit: $24.9/25.2=99\%$

Result : Because the ratio is within 50~130%, we can go to next step.

(4) Outdoor unit capacity correction

a. Assuming the combination of indoor and outdoor units is as follow:

Outdoor unit: GRV08P3T3

Indoor unit: IDGRV09P1/IDGRV34P1/M, IDGRV18P1/IDGRV24P1

b. For the 99% combination, calculate the cooling capacity of outdoor unit (GRV08P3T3).

24.3kW 90% (Indoor temperature: WB 21°C, Outdoor temperature: DB 35°C)

27.0kW 100% (Indoor temperature: WB 21°C, Outdoor temperature: DB 35°C)

Then calculate the outdoor capacity in 99% combination index:

Therefore: $24.3 + \{(27.0-24.3)/10\} \times 9 = 26.7$;

c. The capacity modification coefficient with pipe length (30m) and height difference (10m) (Outdoor unit is lower than indoor units): 0.88.

Then calculated the outdoor capacity: $26.7 \times 0.88 = 23.5 \text{ kW}$

(5) Indoor unit capacity correction

The individual indoor unit capacity (power input) can be calculated as follows.

$$\text{IUC} = \text{OUC} \times \text{INX} / \text{TNX}$$

IUC: Each indoor unit capacity

OUC: Outdoors unit capacity

INX: Each indoor unit capacity index

TNX: Total capacity index

$$\text{IDGRV09P1: } 23.5 \times 2.2 / 24.9 = 2.08 \text{ kW}$$

$$\text{IDGRV34P1/M: } 23.5 \times 10.0 / 24.9 = 9.44 \text{ kW}$$

$$\text{IDGRV18P1: } 23.5 \times 5.6 / 24.9 = 5.29 \text{ kW}$$

$$\text{IDGRV24P1: } 23.5 \times 7.1 / 24.9 = 6.70 \text{ kW}$$

7.Control discipline

7.1Explanation of symbols

HPS	high pressure switch
LPS	low pressure switch
Pd sensor	high pressure sensor
Ps sensor	low pressure sensor
Tao	out door ambient temperature
Tdi	discharge temperature of inverter compressor
Td1	discharge temperature of fix speed compressor
Ts	total suction temperature
Tdef	defrost temperature
Tci	total liquid pipe temperature
SV0	4 way valve
SV1	unload valve
SVA	oil return valve of inverter compressor
SVB	oil return valve of fix speed compressor
PMV1	heating mode EXV
PMV2	heating mode EXV (only in the 14\16\18 HP)
PMV3	Sub-cooling valve

7.2 Basic control logic description

(1)master outdoor unit

Communication between outdoor units and indoor units, outdoor and outdoor units, the operation sequence of the outdoor unit.

Coordinate the operation of the master outdoor unit and the slave outdoor unit in one group.

Detect the operation data and the error code.

Count the capacity requirement and the operation frequency of each module

(2)slave outdoor unit

receive the signal from the master outdoor unit, control the component of the slave outdoor unit.

(3)relations between outdoor unit and indoor unit

series	Control item	master	slave	signal(master slave)	notes
1	Capacity requirement of indoor unit counting	○	/	No	Master count
2	Frequency of compressor	○* send signal	○* control by itself after receiving signal	Yes	
3	Balance the pressure before starting	○* send signal	○* control by itself after receiving signal	Yes	
4	Starting up	○* send signal	○* control by itself after receiving signal	Yes	
5	Operation of four way valve	○* send signal	○* control by itself after receiving signal		
6	Shut down	○* send signal	○* control by itself after receiving signal	No	
7	PMV1	○	○	No	
9	PMV2	○	○	No	
10	Fan motor	○	○	No	
11	Solenoid valve	○	○	No	
12	Electric heater	○	○	No	
13	Defrosting operation	○* send signal	○* send signal	Yes	
14	Oil reclaim	○* send signal	○* send signal	Yes	
15	Oil balance	○* send signal	○* send signal	Yes	
16	Residual control operation	○* send signal	○* send signal	Yes	
17	Testing mode	○* send signal	○* send signal	Yes	
18	Silent operation	○* send signal	○* send signal	Yes	
19	Back up function	○	○	No	
20	Anti snow function	○	○	No	
21	Wiring error	○* send signal	○* send signal	Yes	
22	Refrigerant Auto charging	○* send signal	○* send signal	Yes	
23	Relay start up protection	○	○	No	
24	Temp. Sensor protection	○	○	No	
25	Pressure switch protection	○	○	No	
26	Lack of refrigerant protection	○* send signal	○* send signal	Yes	
27	Phase protection	○	○	No	
28	IPM protection	○	○	No	
29	Communication malfunction	○	○	No	
30	Over capacity protection	○* send signal	○* send signal	Yes	

○ control singly

○* control together

7.3 Activity of main components

(1)master outdoor unit

Items	Master (ON)	Slave 1 (ON)	Slave 2 (OFF)
DC compressor	ON	ON	OFF
Fixed compressor 1	Auto	Auto	OFF
Fixed compressor 2	Auto	Auto	OFF
Four way valve (SV0)	OFF	OFF	OFF
Expansion valve(PMV1)	open	open	5pulse
Expansion valve(PMV2)	Auto	Auto	5pulse
Sub-cooling expansion valve(PMV3)	Auto	Auto	5pulse
By pass valve(SV1)	Auto	Auto	OFF
Oil reclaim valve (SVA)	Auto	Auto	OFF
Oil reclaim valve(SVB)	Auto	Auto	OFF
Fan motor	Auto	Auto	OFF

(2)slave outdoor unit

Items	Master (ON)	Slave 1 (ON)	Slave 2 (OFF)
DC compressor	ON	ON	OFF
Fixed compressor 1	auto	auto	OFF
Fixed compressor 2	ON	ON	ON
Four way valve (SV0)	OFF	OFF	OFF
Expansion valve(PMV1)	auto	auto	5pulse
Expansion valve(PMV2)	auto	auto	5pulse
Sub-cooling expansion valve(PMV3)	auto	auto	OFF
By pass valve(SV1)	auto	auto	OFF
Oil reclaim valve (SVA)	auto	auto	OFF
Oil reclaim valve(SVB)	auto	auto	OFF

7.4 calculation of indoor capacity requirement

Outdoor controller calculate the requirement ration of indoor units by PI method, detect the deviation of the temperature every 5 seconds, calculate the capacity requirement every 40 seconds.

7.5 start up control discipline

7.5.1 start up of outdoor unit

cooling mode

- (1) the compressor operate at 45Hz or 53Hz for 3 minutes, then come to the automatic adjustment.
- (2) solenoid valve SV1 opens for 20 seconds.
- (3) outdoor and indoor units adjust automatically.

heating mode

- (1) the compressor operate at 45Hz or 53Hz for 3 minutes, then come to the automatic adjustment.
- (2) solenoid valve SV1 opens for 20 seconds.
- (3) outdoor and indoor units adjust automatically.

7.5.2 start up of compressor

- (1) relay protection of compressor :

The compressor can start up until the compressor has stopped for 3 minutes.

- (2) equalize the high and low pressure:

the master outdoor unit receives the signal of start up, and distribute the capacity requirement of indoor units to the outdoor units. Equalize the system pressure before DC inverter compressor start up.

- (3) interval of the compressor start up :

In one group, the next DC inverter compressor start up 3 seconds later than the compressor start up before. the interval of the fixed compressor start up is 10 seconds.

- (4) compressors start up procedure in combination group :

Heating mode:

When the running frequency of the DC inverter compressor up to 75Hz, start up the fixed compressor in this module; when the running frequency of the DC inverter compressor low to 25Hz, shut down the fixed compressor in this module. The interval of compressor start up between modules is 3 seconds.

Cooling mode:

When the running frequency of the DC inverter compressor up to 75Hz, start up the fixed compressor in this module; when the running frequency of the DC inverter compressor low to 25Hz, shut down the fixed compressor in this module. The interval of compressor start up between modules is 3 seconds.

7.6 protection and error detection during start up

7.6.1 effective protection

Compressor restart protection, discharge temp. protection, over current protection, high pressure protection, phase sequence protection, IPM protection, communication protection, temp. sensor malfunction protection, over heating protection.

7.6.2 ineffective protection

Anti cold protection, low pressure protection, low pressure protection is ineffective during defrosting, oil reclaim , first 10 minutes after start up.

7.7 stop control discipline

7.7.1 cooling、dehumidify mode

(1)definition: fshut=48Hz,

The fixed compressor stop immediately when receives the signal of stopping ; when the running frequency of the DC inverter compressor higher than the fshut, firstly reduce the frequency lower than fshut, then come to stop.

(2) outdoor fan stop 1 minute later.

7.7.2 heating mode

(1)definition: fshut=48Hz,

The fixed compressor stop immediately when receives the signal of stopping ; when the running frequency of the DC inverter compressor higher than the fshut, firstly reduce the frequency lower than fshut, then come to stop.

(2) outdoor fan stop 1 minute later.

(3) when the indoor unit OFF., the four way valve still ON.

7.8 expansion valve PMV1、PMV2

(1) cooling mode: expansion open to 480pls;

(2) heating mode: after resetting, firstly close expansion valve -----then 96 pls-----than auto adjust.

(3) the open degree should more than the min. open pulse and less than the max. open pulse.

Min. open degree is 3 pls during heating mode:

Min. open degree is 60 pls when the supper heating is less than 25°C.

Min. open degree is 126 pls when the discharge temp. is more than 90°C.

Min. open degree is 96 pls during mormal operation.

Max. open degree is 480pls.

7.9 sub-cooling expansion valve PMV3

(1)cooling mode:

Max. open degree is 350pls according to the sub-cooling temp.

When then discharge temp is more than 100°C, the max. open degree is 480pls, and min. open degree is100 pls.

(1) heating mode:

When then discharge temp is more than 100°C, the max. open degree is 480pls, and min. open degree is 100 pls.

7.10 outdoor fan motor

cooling mode

Data based: high pressure Pd

- (1) Starting condition

The group start cooling operation

- (2) relation between master and slave outdoor unit

The outdoor unit control individually

heating mode

Data based: high pressure Pd

- (1) Starting condition

The group start cooling operation

- (2) relation between master and slave outdoor unit

The outdoor unit control individually

7.11 solenoid valve control

7.11.1 SVI

During the normal operation, the solenoid valve opens when the low pressure lower than 2 bar, the valve closes when the low pressure more than 2.5 bar in cooling mode , or low pressure more than 3 bar in heating mode.

7.11.2oil return valve SVA, SVB

The valves are closed when the outdoor unit is closed; when the compressor is ON, the corresponding valve is open; and the corresponding valve is closed when the compressor is OFF.

7.12 crankcase heating control

The ON/OFF status of the crankcase heating is depending on the discharge temp.

7.13 defrosting in heating mode

7.13.1 starting condition

In heating mode, the outdoor unit detect the temp. (Tdef) of the heat exchanger through defrosting temp. sensor, and the defrosting control based on the temp. Tdef.

Any one reach the defrosting condition in one combined group, the master outdoor unit will send the defrosting signal to the modules in the group, then the outdoor control individually.

7.13.2 exiting defrosting

In heating mode, the temperature of Tdef is higher than 10°Cfor 1 minute, or the temp. of Tdef is higher than 15 °C for 10 seconds.

7.13.3 defrosting cycle

- (1) interval time limit: max.120 minutes ,min. 48 minutes ;
- (2) the first defrosting happens after running 33 minutes in heating mode.

7.13.4 defrosting procedure

- (1) running frequency is 80 Hz
- (2) four-way OFF
- (3) indoor fan motor OFF
- (4) outdoor fan motor OFF
- (5) EXV of indoor units open to 125 pls.
- (6) EXV of outdoor units open to 250 pls.

7.13.5 relation between defrosting progress and other progress

Defrosting is prior , except the protections.

Low pressure protection is not activated during defrosting.

Control priority : 1、protections; 2、defrosting; 3、oil return

7.14 oil return control

During low frequency operation, the outdoor will come to the oil return program every 2-4 hours to reclaim the oil accumulated in the indoor units. The EXV of the indoor units are open with fixed degree, and the oil return program lasts for 6 minutes.


7.15 protection function

(1) compressor restart protection

The compressor can start up until 3 minutes later after the last stop.


(2) discharge temp. protection

When the discharge temp. is too high, the compressor will reduce the running frequency to control the discharge temp.



(3)IPM protection

The sensor detects the temp. of IMP, and send the data to the main PCB.3 minutes later the machine can start up after stop, if the protection happens 3 times in one hour, the outdoor unit should be powered on again to start up.



(4) high pressure protection

When the discharge pressure is too high, the compressor will reduce the running frequency. When pressure is more than 38bar, compressor can reduce the running frequency, and when the pressure is less than 37bar, the compressor can increase the frequency.


(5) over current protection:

①protection current:

OULD HP	DC com.X	Fixed com.Y
8-12	28A	/
14-16	28A	13A
18	28A	15A

②DC inverter compressor

I=24A



③fixed compressor:

When the current is more than Y in the table , the compressor stops immediately.

NOTES: 3-time protection in 60 minutes, should reset the outdoor.

(6) Temp. sensor protection

If some malfunctions happen to discharge temp. sensor , indoor coil temp. sensor, outdoor coil temp. sensor, suction temp. sensor, ambient temp. sensor, the system will stop and display the error code.

In heating mode, if the defrosting temp. sensor is broken, and when it is time to defrost, it will directly come to defrosting ,and last for 5 minutes. It will display the error coed when operate in cooling mode.

(7) high pressure protection

When the switch is OFF for 2 seconds, the system stop, and 3 minutes later can start up. 3-time protection in 60 minutes, should reset the outdoor.

(8) low pressure protection

When the switch is OFF for 2 seconds, the system stop, and 3 minutes later can start up. 3-time protection in 60 minutes, should reset the outdoor.

During the first 10 minutes , defrosting progress, oil return progress, the low pressure switch will not active.

(9) sequence protection

PCB detects whether the power supply is phase reversed or phase lost. IPM detects the power of DC inverter compressor.

(10) communication protection

①when signal missing for 4 minutes between outdoor unit and indoor unit,the system will display the communication error code.

②communication malfunction between outdoor units.

Cooling mode: when the master can not receive signal from the slave ones, the master one will re-distribute the capacity and responded controlling, and the slave ones display the error code and stops.

Heating mode: when the master can not receive signal from the slave ones, the master one and the slave ones display the error code and stops.

8. Electric Characteristic

Unit			Power		OFM	
Model	Hz	Voltage	MCA	Breaker (A)	Output power (W)	FLA
8 HP	50	380-415	28.8	32	750	23
10 HP	50	380-415	28.8	32	750	23
12 HP	50	380-415	28.8	32	750	23
14 HP	50	380-415	44.5	50	450+370	35.6
16 HP	50	380-415	44.5	50	450+370	35.6
18 HP	50	380-415	46.1	50	450+370	36.9

Symbols:

MCA: Min. Circuit Amps (A)

OFM: Outdoor fan motor

FLA: Full load AMPS (A)

Notice:

1 Voltage range


Units are suitable for use on electrical systems where voltage supplied to unit terminals is not below or above listed range limit.

2 Maximum allowable voltage unbalance between phase is 2%

$MCA = 1.25 * FLA$

3 Select wire size base on the MCA

9.Sound level




Note:


1. The operating condition are assumed to be atandard(JIS Condition).
2. These operating values were obtained in a dead room (conversion values).
Sound level will vary depending on a range of factors such as the construction (acoustic absorption coefficient) of the particular room in which the equipments installed.
3. The result is the biggest one of four testing device.
4. Test height (Unit height +1)/2m, horizontal distance : 1m.

Model	Sound (dB)
8 HP	60
10 HP	60
12 HP	60
14 HP	62
16 HP	62
18 HP	62


10.Explode View
8/10 HP



No.	GREEN code	Part name	Part name	Quantity	Unit
1	16321002000060	DLR-280W5/DCM3 底盘组件	Classis components	1	Set
2	16421031000134	DLR-450W5/DCM3 前右立柱	Front right side support cylinder	2	Pc
3	16421015000043	DLR-450W5/DCM3 冷凝器护板	Condenser plate	2	Pc
4	16421036000069	DLR-450W5-DCM-3A 侧钢丝网罩	Side steel net cover	2	Pc
5	16421036000070	DLR-280W5-DCM-3A 后钢丝网罩	Back steel net cover	1	Pc
6	16324002000031	DLR-280W5/DCM3 冷凝器总成	Condenser assembly	1	Set
7	16421001000491	DLR-450W5/DCM3 上侧板	Upper side panel	2	Pc
8	16421004000230	DLR-280W5/DCM3 后上面板	Back upper panel	1	Pc
9	16421012000111	DLR-280W5/DCM3 横梁	Beam	2	Pc
10	16444008000017	轴流风叶 700x206.6	Axial flow fan 560x86	1	Pc
11	16421036000017	LSQWRF65MX/D 风叶网罩 I	Net cover	1	Pc
12	16421025000007/ 16421025000006	DLR-280W/DCM 导风圈/导风板(铆接)	Guide ring (plating)	1	Pc
13	16430001000478	室外电机 DMSB-750W-8P	Fan motor	1	Pc
14	16421026000202	DLR-450W5/DCM3 电机支架	Motor bracket	2	Pc
15	16421022000235	DLR-450W5/DCM3 横梁(短)	Beam (short)	2	Pc
16	16421004000219	DLR-280W5/DCM3 上面板	Upper panel	1	Pc
17	16421004000220	DLR-280W5/DCM3 前面板(上)	Front panel	1	Pc
18	16421005000410	DLR-280W5-DCM-3A 电控箱盖	Electric box cover	1	Pc
19	16321002000063	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
20	16421014000056	DLR-280W5/DCM-AVR3 阀板	Valve board	2	Pc
21	16421026000216	DLR-280W5-DCM-3A 电控箱支架	Electric box bracket	1	Pc
22	16421031000133	DLR-450W5/DCM3 前左立柱	Front left side support cylinder	2	Pc




No.	GREEN code	Part name	Part name	Quantity	Unit
1	16441004000062	(ROHS)截止阀组件 7/8in(双焊接)	Stop valve assembly	1	Set
2	16441004000061	(ROHS)截止阀组件 1/2in(双焊接)	Stop valve assembly	1	Set
3	16439003000012	板式换热器 B3-014-4.5-H 2×3/8in+2×1/2in	Plate heat exchanger	1	Pc
4	16442001000019	过滤器 φ12.7×φ12.7-100	Filter	2	Pc
5	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV	1	Pc
6	16441014000026	(ROHS)电子膨胀阀阀 UKV-32D61	EXV	1	Pc
7	/	(ROHS)截止阀 1/4in(直管)(R410a)	Stop valve	1	Pc
8	16441008000001	四通换向阀阀体 SHF-H35672-003	4-way valve	1	Pc
9	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	Pc
10	16442024000006	高压开关 H20PS D 4.2/3.3(弯管)	High pressure switch	1	Pc
11	16442001000021	过滤器 φ22.2×φ22.2-185	Filter	1	Pc
12	16441003000035	单向阀 22.2×22.2-160	One-way valve	1	Pc
13	/	压力传感 NSK-S783-1(0~3.0)MPa	Pressure sensor	1	Pc
14	16442024000006	压力传感 NSK-S784-1(0~5.0)MPa	Pressure sensor	1	Pc
15	16442023000039	气液分离器 QFQ-15L(22)(立)	Gas-liquid separator	1	Pc
16	16442021000036	油分离器 DA 16P(R410a)	Oil separator 16P(R410a)	1	Pc
17	16441012000001	电磁阀阀体 FDF2A	EXV FDF2A	1	Pc
18	16438003000018	压缩机 E655DHD-65D2YG(变频并 联)	Compressor E655DHD-65D2YG	1	Pc
19	16441012000038	电磁阀阀体 FDF2AK01	EXV FDF2AK01	1	Pc




No.	GREEN code	Part name	Part name	Quantity	Unit
1	16430013000007	(ROHS)电抗器 DK-5mH-30A(L=400)	(ROHS)Electric reactor	1	Pc
2	16422007000005	滤波板 ZLBP3D-SWLB-XESE1	Filter board	1	Pc
3	16422012000009	模块板 ZLBP3D-SWMK-XESE1	Moudle board 1	1	Pc
4	16422012000016	模块板 BPFJ-SW-XSE1	Moudle board 2	1	Pc
5	16321002000063	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
6	16421026000211	DLR-450W5-DCM-3A 电控元器件固定板支架	Electric components fixed plate bracket	2	Pc
7	16422005000008	(ROHS)变压器 TDB-16-B2B	Transformer	1	Pc
8	16422006000001	电容板 ZLBP3D-SWDR-XESE1	Capacitor board	1	Pc
9	16422001000079	控制板 ZLBP-SW3C-SYE1(ZK)	Main PC board	1	Pc
10	16427014000005	线槽 25×45	Trunking	2	Pc
11	16427001000054	端子板 5位(600V 16mm ²)	Terminal board 5 bits	1	Pc
12	16421002000264	DLR-450W5-DCM-3A 电控元器件固定板上	Electric components fixed plate	1	Pc
13	16427022000002	接地铜排 7位	Earthing copper row	1	Pc

12 HP




No.	GREEN code	Part name	Part name	Quantity	Unit
1	16321002000060	DLR-280W5/DCM3 底盘组件	Classis components	1	Set
2	16421031000134	DLR-450W5/DCM3 前右立柱	Front right side support cylinder	2	Pc
3	16421015000043	DLR-450W5/DCM3 冷凝器护板	Condenser plate	2	Pc
4	16421036000069	DLR-450W5-DCM-3A 侧钢丝网罩	Side steel net cover	2	Pc
5	16421036000070	DLR-280W5-DCM-3A 后钢丝网罩	Back steel net cover	1	Pc
6	16324002000035	DLR-335W5/DCM3 冷凝器总成	Condenser assembly	1	Set
7	16421001000491	DLR-450W5/DCM3 上侧板	Upper side panel	2	Pc
8	16421004000230	DLR-280W5/DCM3 后上面板	Back upper panel	1	Pc
9	16421012000111	DLR-280W5/DCM3 横梁	Beam	2	Pc
10	16444008000017	轴流风叶 φ700×206.6	Axial flow fanφ700×206.6	1	Pc
11	16430001000478	LSQWRF65MX/D 风叶网罩 I	Net cover	1	Pc
12	16421026000202	DLR-280W/DCM 导风圈/导风板(铆接)	Guide ring (plating)	1	Pc
13	16421022000235	室外电机 DMSB-750W-8P	Fan motor	1	Pc
14	16421004000219	DLR-450W5/DCM3 电机支架	Motor bracket	2	Pc
15	16421004000220	DLR-450W5/DCM3 横梁(短)	Beam (short)	2	Pc
16	16421005000410	DLR-280W5/DCM3 上面板	Upper panel	1	Pc
17	16321002000063	DLR-280W5/DCM3 前面板(上)	Front panel	1	Pc

No.	GREEN code	Part name	Part name	Quantity	Unit
18	16421014000056	DLR-280W5-DCM-3A 电控箱盖	Electric box cover	1	Pc
19	16421026000216	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
20	16421031000133	DLR-280W5/DCM-AVR3 阀板	Valve board	2	Pc
21	16430001000478	DLR-280W5-DCM-3A 电控箱支架	Electric box bracket	1	Pc
22	16421026000202	DLR-450W5/DCM3 前左立柱	Front left side support cylinder	2	Pc




No.	GREEN code	Part name	Part name	Quantity	Unit
1	16441004000062	(ROHS)截止阀组件 7/8in(双焊接)	Stop valve assembly	1	Set
2	16441004000061	(ROHS)截止阀组件 1/2in(双焊接)	Stop valve assembly	1	Set
3	16439003000012	板式换热器 B3-014-4.5-H 2×3/8in+2×1/2in	Plate heat exchanger	1	Pc
4	16442001000019	过滤器 φ12.7×φ12.7-100	Filter	2	Pc
5	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV	1	Pc
6	16441014000026	(ROHS)电子膨胀阀 UKV-32D61	EXV	1	Pc
7	/	(ROHS)截止阀 1/4in(直管)(R410a)	Stop valve	1	Pc
8	16441008000001	四通换向阀阀体 SHF-H35672-003	4-way valve	1	Pc
9	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	Pc
10	16442024000006	高压开关 H20PS D 4.2/3.3(弯管)	High pressure switch	1	Pc
11	16442001000021	过滤器 φ22.2×φ22.2-185	Filter	1	Pc
12	16441003000035	单向阀 22.2×22.2-160	One-way valve	1	Pc
13	/	压力传感 NSK-S783-1(0~3.0)MPa	Pressure sensor	1	Pc
14	16442024000006	压力传感 NSK-S784-1(0~5.0)MPa	Pressure sensor	1	Pc
15	16442023000039	气液分离器 QFQ-15L(22)(立)	Gas-liquid separator	1	Pc
16	16442021000036	油分离器 DA 16P(R410a)	Oil separator	1	Pc
17	16441012000001	电磁阀阀体 FDF2A	EXV	1	Pc
18	16438003000018	压缩机 E655DHD-65D2YG(变频并联)	Compressor	1	Pc
19	16441012000038	电磁阀阀体 FDF2AK01	EXV	1	Pc




No.	GREEN code	Part name	Part name	Quantity	Unit
1	16430013000007	(ROHS)电抗 DK-5mH-30A(L=400)	(ROHS)Electric reactor	1	Pc
2	16422007000005	滤波板 ZLBP3D-SWLБ-XESE1	Filter board	1	Pc
3	16422012000009	模块板 ZLBP3D-SWMK-XESE1	Mouldle board 1	1	Pc
4	16422012000016	模块板 BPFJ-SW-XSE1	Mouldle board 2	1	Pc
5	16321002000063	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
6	16421026000211	DLR-450W5-DCM-3A 电控元器件 固定板支架	Electric components fixed plate bracket	2	Pc
7	16422005000008	(ROHS)变压器 TDB-16-B2B	Transformer	1	Pc
8	16422006000001	电容板 ZLBP3D-SWDR-XESE1	Capacitor board	1	Pc
9	16422001000079	控制板 ZLBP-SW3C-SYE1(ZK)	Main PC board	1	Pc
10	16427014000005	线槽 25×45	Trunking	2	Pc
11	16427001000054	端子板 5位(600V 16mm ²)	Terminal board 5 bits	1	Pc
12	16421002000264	DLR-450W5-DCM-3A 电控元器件 固定板上	Electric components fixed plate	1	Pc
13	16427022000002	接地铜排 7位	Earthing copper row	1	Pc


14/16 HP



No.	GREEN code	Part name	Part name	Quantity	Unit
1	16321002000059	DLR-450W5/DCM3 底盘组件	Classis components	1	Set
2	16421031000134	DLR-450W5/DCM3 前右立柱	Front right side support cylinder	2	Pcs
3	16421015000043	DLR-450W5/DCM3 冷凝器护板	Condenser plate	2	Pc
4	16421036000069	DLR-450W5-DCM-3A 侧钢丝网罩	Side steel net cover	2	Pc
5	16421036000071	DLR-450W5-DCM-3A 后钢丝网罩	Back steel net cover	1	Pc
6	16324002000030	DLR-450W5/DCM3 冷凝器总成	Condenser assembly	1	Set
7	16421001000491	DLR-450W5/DCM3 上侧板	Upper side panel	2	Pc
8	16421004000231	DLR-450W5/DCM3 后上面板	Back upper panel	1	Pc
9	16421022000236	DLR-450W5/DCM3 横梁(长)	Beam	2	Pc
10	16421026000203	DLR-450W5/DCM3 顶盖板支撑条	Top cover plate support	2	Pc
11	16430001000479	室外电机 DMSB-450W-8P	Fan motor	1	Pc
12	16421005000402/ 16421025000022	DLR-450W5/DCM3 顶盖板/导风圈(铆接)	Guide ring (plating)	2	Pc
13	16421036000049	DLR-450W5-DCM-3A 风叶网罩	Net cover	2	Pc
14	16430001000500	室外电机(三速) YDK370-6	Fan motor	1	Pc
15	16444008000042	轴流风叶 φ600×178	Axial flow fan Φ560×86	2	Pc
16	16421022000235	DLR-450W5/DCM3 横梁(短)	Beam (short)	2	Pc
17	16421026000202	DLR-450W5/DCM3 电机支架	Motor bracket	4	Pc
18	16421004000217	DLR-450W5/DCM3 上面板	Upper panel	1	Pc
19	16421004000218	DLR-450W5/DCM3 前面板	Front panel	2	Pc
20	16421014000056	DLR-280W5-DCM-3A 电控箱盖	Electric box cover	1	Pc
21	16421026000216	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
22	16421014000053	DLR-450W5/DCM3 阀板(右)	Valve board(right)	2	Pc
23	16421014000051	DLR-450W5/DCM3 阀板(左)	Valve board(left)	1	Pc
24	16421022000243	DLR-450W5/DCM3 电控横梁	Electric box bracket	1	Pc
25	16421031000133	DLR-450W5/DCM3 前左立柱	Front left side support cylinder	2	Pc




No.	GREEN code	Part name	Part name	Quantity	Unit
1	16441004000063	(ROHS)截止阀组件 9/8in(双焊接)	Stop valve assembly	1	Set
2	16441004000061	(ROHS)截止阀组件 1/2in(双焊接)	Stop valve assembly	1	Set
3	16442001000019	板式换热器 B3-014-4.5-H 2×3/8in+2×1/2in	Plate heat exchanger	1	Pc
4	16441014000013	过滤器 φ12.7×φ12.7-100	Filter	2	Pc
5	16441014000026	电子膨胀阀 CAM-BD22FKS-1	EXV	2	Pc
6	16442001000019	(ROHS)电子膨胀阀 UKV-32D61	EXV	1	Pc
7	/	(ROHS)截止阀 1/4in(直管)(R410a)	Stop valve	1	Pc
8	16441008000030	四通换向阀阀体 SHF-H35792-007	4-way valve	1	Pc
9	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	Pc
10	/	压力传感 NSK-S783-1(0~3.0)MPa	Pressure sensor	1	Pc
11	16442001000020	过滤器 φ28.6×φ28.6-185	Filter	1	Pc
12	16442023000040	气液分离器 QFQ-23L(双出管)	Gas-liquid separator	1	Pc
13	6441012000001	电磁阀阀体 FDF2A	EXV	1	Pc
14	6441003000035	单向阀 22.2×22.2-160	One-way valve	1	Pc
15	16442024000006	压力传感器 NSK-S784-1(0~5.0)MPa	Pressure sensor	1	Pc
16	16442021000036	油分离器 DA 16P(R410a)	Oil separator	1	Pc
17	16442024000006	高压开关 H2OPS D 4.2/3.3(弯管)	High pressure switch	2	Pc
18	16438003000002	压缩机 E605DH-59D2YG(定频并联)	Compressor	1	Pc
19	16438003000018	压缩机 E655DHD-65D2YG(变频并联)	Compressor	1	Pc
20	16441012000038	电磁阀阀体 FDF2AK01	EXV	2	Pc



No.	GREEN code	Part name	Part name	Quantity	Unit
1	16430013000007	(ROHS)电抗器 DK-5mH-30A(L=400)	(ROHS)Electric reactor	1	Pc
2	16422007000005	滤波板 ZLBP3D-SWLB-XESE1	Filter board	1	Pc
3	16422012000009	模块板 ZLBP3D-SWMK-XESE1	Moudle board 1	1	Pc
4	16422012000016	模块板 ZLBP3D-SW-XESE1	Moudle board 2	1	Pc
5	16321002000063	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
6	16421026000211	DLR-450W5-DCM-3A 电控元器件固定板支架	Electric components fixed plate bracket	2	Pc
7	16422005000008	(ROHS)变压器 TDB-16-B2B	Transformer	1	Pc
8	16422006000001	电容板 ZLBP3D-SWDR-XESE1	Capacitor board	1	Pc
9	16422001000079	控制板 ZLBP-SW3C-SYE1(ZK)	Main PC board	1	Pc
10	16427014000005	线槽 25×45	Trunking	2	Pc
11	16427001000054	端子板 5位(660V 25mm ²)	Terminal board 5 bits	1	Pc
12	16421002000264	DLR-450W5-DCM-3A 电控元器件固定板上	Electric components fixed plate	1	Pc
13	16427022000002	接地铜排 7位	Earthing copper row	1	Pc
14	16430009000003	交流接触器 GC4-18/01KK	AC contactor	1	Pc
15	16422001000079	控制板 FAN(AC)-3F-SYE1	PC board	1	Pc
16	16430015000027	(ROHS)电容 15μF/450V a.c	Capacitor	1	Pc


18 HP



No.	GREEN code	Part name	Part name	Quantity	Unit
1	16321002000059	DLR-450W5/DCM3 底盘组件	Classis components	1	Set
2	16421031000134	DLR-450W5/DCM3 前右立柱	Front right side support cylinder	2	Pcs
3	16421015000043	DLR-450W5/DCM3 冷凝器护板	Condenser plate	2	Pc
4	16421036000069	DLR-450W5-DCM-3A 侧钢丝网罩	Side steel net cover	2	Pc
5	16421036000071	DLR-450W5-DCM-3A 后钢丝网罩	Back steel net cover	1	Pc
6	16324002000038	DLR-500W5/DCM-3A 冷凝器总成	Condenser assembly	1	Set
7	16421001000491	DLR-450W5/DCM3 上侧板	Upper side panel	2	Pc
8	16421004000231	DLR-450W5/DCM3 后上面板	Back upper panel	1	Pc
9	16421022000236	DLR-450W5/DCM3 横梁(长)	Beam	2	Pc
10	16421026000203	DLR-450W5/DCM3 顶盖板支撑条	Top cover plate support	2	Pc
11	16430001000479	室外电机 DMSB-450W-8P	Fan motor	1	Pc
12	16421005000402/ 16421025000022	DLR-450W5/DCM3 顶盖板/导风圈(铆接)	Guide ring (plating)	2	Pc
13	16421036000049	DLR-450W5-DCM-3A 风叶网罩	Net cover	2	Pc
14	16430001000500	室外电机(三速) YDK370-6	Fan motor	1	Pc


GEEN GRV Four Way Cassette Type

No.	GREEN code	Part name	Part name	Quantity	Unit
15	16444008000042	轴流风叶 φ600×178	Axial flow fan Φ560×86	2	Pc
16	16421022000235	DLR-450W5/DCM3 横梁(短)	Beam (short)	2	Pc
17	16421026000202	DLR-450W5/DCM3 电机支架	Motor bracket	4	Pc
18	16421004000217	DLR-450W5/DCM3 上面板	Upper panel	1	Pc
19	16421004000218	DLR-450W5/DCM3 前面板	Front panel	2	Pc
20	16421014000056	DLR-280W5-DCM-3A 电控箱盖	Electric box cover	1	Pc
21	16421026000216	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
22	16421014000053	DLR-450W5/DCM3 阀板(右)	Valve board(right)	2	Pc
23	16421014000051	DLR-450W5/DCM3 阀板(左)	Valve board(left)	1	Pc
24	16421022000243	DLR-450W5/DCM3 电控横梁	Electric box bracket	1	Pc
25	16421031000133	DLR-450W5/DCM3 前左立柱	Front left side support cylinder	2	Pc



No.	GREEN code	Part name	Part name	Quantity	Unit
1	16441004000063	(ROHS)截止阀组件 9/8in(双焊接)	Stop valve assembly	1	Set
2	16441004000061	(ROHS)截止阀组件 1/2in(双焊接)	Stop valve assembly	1	Set
3	16442001000019	板式换热器 B3-014-4.5-H 2×3/8in+2×1/2in	Plate heat exchanger	1	Pc
4	16441014000013	过滤器 φ12.7×φ12.7-100	Filter	2	Pc
5	16441014000026	电子膨胀阀阀体 CAM-BD22FKS-1	EXV	2	Pc
6	16442001000019	(ROHS)电子膨胀阀阀体 UKV-32D61	EXV	1	Pc
7	/	(ROHS)截止阀 1/4in(直管)(R410a)	Stop valve	1	Pc
8	16441008000030	四通换向阀阀体 VH61100	4-way valve	1	Pc
9	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	Pc
10	/	压力传感器 NSK-S783-1(0~3.0)MPa	Pressure sensor	1	Pc

No.	GREEN code	Part name	Part name	Quantity	Unit
11	16442001000020	过滤器 φ28.6×φ28.6-185	Filter	1	Pc
12	16442023000040	气液分离器 QFQ-23L(双出管)	Gas-liquid separator	1	Pc
13	6441012000001	电磁阀阀体 FDF2A	EXV	1	Pc
14	6441003000035	单向阀 22.2×22.2-160	One-way valve	1	Pc
15	16442024000006	压力传感器 NSK-S784-1(0~5.0)MPa	Pressure sensor	1	Pc
16	16442021000036	油分离器 16P(R410a)	Oil separator	1	Pc
17	16442024000006	高压开关 H2OPS D 4.2/3.3(弯管)	High pressure switch	2	Pc
18	6438003000028	压缩机 E655DH-65D2YG(定频并联)	Compressor	1	Pc
19	16438003000018	压缩机 E655DHD-65D2YG(变频并联)	Compressor	1	Pc
20	16441012000038	电磁阀阀体 FDF2AK01	EXV	2	Pc



No.	GREEN code	Part name	Part name	Quantity	Unit
1	16430013000007	(ROHS)电抗器 DK-5mH-30A(L=400)	(ROHS)Electric reactor	1	Pc
2	16422007000005	滤波板 ZLBP3D-SWLB-XESE1	Filter board	1	Pc

GEEN GRV Four Way Cassette Type

3	16422012000009	模块板 ZLBP3D-SWMK-XESE1	Moudle board 1	1	Pc
4	16422012000016	模块板 BPFJ-SW-XSE1	Moudle board 2	1	Pc
5	16321002000063	DLR-280W5-DCM-3A 电控箱组件	Electric box components	1	Set
6	16421026000211	DLR-450W5-DCM-3A 电控元器件固定板支架	Electric components fixed plate bracket	2	Pc
7	16422005000008	(ROHS)变压器 TDB-16-B2B	Transformer	1	Pc
8	16422006000001	电容板 ZLBP3D-SWDR-XESE1	Capacitor board	1	Pc
9	16422001000079	控制板 ZLBP-SW3C-SYE1(ZK)	Main PC board	1	Pc
10	16427014000005	线槽 25×45	Trunking	2	Pc
11	16427001000054	端子板 5 位(600V 16mm ²)	Terminal board 5 bits	1	Pc
12	16421002000264	DLR-450W5-DCM-3A 电控元器件固定板上	Electric components fixed plate	1	Pc
13	16427022000002	接地铜排 7 位	Earthing copper row	1	Pc
14	16430009000003	交流接触器 GC4-18/01KK	AC contactor	1	Pc
15	16422001000079	控制板 FAN(AC)-3F-SYE1	PC board	1	Pc
16	16430015000027	(ROHS)电容 15μF/450V a.c	Capacitor	1	Pc

11.Spare parts lists

8/10 HP

series	items	Part name	Part name	Qty.	unit
1	16445999000081	压缩机冷冻油 FVC68D	Crankcase oil	3.5	L
2	16430001000478	室外电机 DMSB-750W-8P	Fan motor	1	PC
3	16441008000001	四通换向阀阀体 SHF-H35672-003	Four way valve	1	PC
4	16441009000001	四通换向阀线圈 RANCO L=1500	Four way valve wiring	1	PC
5	16441012000038	电磁阀阀体 FDF2AK01	Solenoid valve FDF2AK01	1	PC
6	16441012000001	电磁阀阀体 FDF2A	Solenoid valve FDF2A	1	PC
7	16441011000011	电磁阀线圈 FQ-679-RK L=1500	Solenoid valve wiring	1	PC
8	16441011000001	电磁阀线圈 FDF2A L=1800	Solenoid valve wiring	1	PC
9	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV	1	PC
10	16441014000026	(ROHS)电子膨胀阀阀体 UKV-32D61	EXV	1	PC
11	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	EXV wiring	1	PC
12	16441015000011	(ROHS)电子膨胀阀线圈 UKV-254	EXV wiring	1	PC
13	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	PC
14	16442024000006	高压开关 H2OPS D 4.2/3.3(弯管)	High pressure switch	1	PC
15	16430007000161	传感器 ZLBP-4SW1C(组件)		1	PC
16	16442023000001	压力传感器 NSK-S784-1(0~5.0)MPa L=2000	High pressure sensor	1	PC
17	16442023000002	压力传感器 NSK-S783-1(0~3.0)MPa L=2000	Low pressure sensor	1	PC
18	16322002000025	DLR-280W5/DCM3 电控箱总成	Electric box assembly	1	set
19	16422008000046	(ROHS)通讯线 4 芯 0.3m(XH4Y-XH4Y)白	Communication wire	1	set
20	16422008000047	(ROHS)通讯线 4 芯 0.35m(XH4Y-XH4Y)红	Communication wire	1	set
21	16430022000003	油温加热带 220V/33W, 485mm/1600mm	Crankcase heater	1	PC
22	16444008000017	轴流风叶 700×206.6	Axial fan blade	1	PC
23	16441003000035	单向阀 22.2×22.2-160	Check valve	1	PC
24	16441003000019	单向阀 9.52×9.52-100	Check valve	1	PC
25	16441004000062	截止阀组件 7/8in(双焊接)	Stop valve assembly	1	PC
26	16441004000061	截止阀组件 1/2in(双焊接)	Stop valve assembly	1	PC
27	16442001000021	过滤器 22.2× 22.2-185	filter	1	PC
28	16442001000019	过滤器 12.7× 12.7-100	filter	2	PC
29	16442001000005	过滤器 6× 8-66	filter	2	PC
30	16442023000039	气液分离器 QFQ-15L(22)(立)	Gas-liquid separator	1	PC
31	16442021000035	油分离器 16P(R410a)	Oil separator	1	PC
32	16438003000018	压缩机 E655DHD-65D2YG (变频并联)	DC compressor	1	PC

12 HP

series	items	Part name	Part name	Qty.	unit
1	16445999000081	压缩机冷冻油 FVC68D	Crankcase oil	3.5	L
2	16430001000478	室外电机 DMSB-750W-8P	Fan motor	1	PC
3	16441008000001	四通换向阀阀体 SHF-H35672-003	Four way valve	1	PC
4	16441009000001	四通换向阀线圈 RANCO L=1500	Four way valve wiring	1	PC
5	16441012000038	电磁阀阀体 FDF2AK01	Solenoid valve FDF2AK01	1	PC
6	16441012000001	电磁阀阀体 FDF2A	Solenoid valve FDF2A	1	PC
7	16441011000011	电磁阀线圈 FQ-679-RK L=1500	Solenoid valve wiring	1	PC
8	16441011000001	电磁阀线圈 FDF2A L=1800	Solenoid valve wiring	1	PC
9	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV	1	PC
10	16441014000026	(ROHS)电子膨胀阀阀体 UKV-32D61	EXV	1	PC
11	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	EXV wiring	1	PC
12	16441015000011	(ROHS)电子膨胀阀线圈 UKV-254	EXV wiring	1	PC
13	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	PC
14	16442024000006	高压开关 H2OPS D 4.2/3.3(弯管)	High pressure switch	1	PC
15	16430007000161	传感器 ZLBP-4SW1C(组件)		1	PC
16	16442023000001	压力传感器 NSK-S784-1(0~5.0)MPa L=2000	High pressure sensor	1	PC
17	16442023000002	压力传感器 NSK-S783-1(0~3.0)MPa L=2000	Low pressure sensor	1	PC
18	16322002000025	DLR-280W5/DCM3 电控箱总成	Electric box assembly	1	set
19	16422008000046	(ROHS)通讯线 4芯0.3m(XH4Y-XH4Y) 白	Communication wire	1	set
20	16422008000047	(ROHS)通讯线 4芯 0.35m(XH4Y-XH4Y)红	Communication wire	1	set
21	16430022000003	油温加热带 220V/33W, 485mm/1600mm	Crankcase heater	1	PC
22	16444008000017	轴流风叶 700x206.6	Axial fan blade	1	PC
23	16441003000035	单向阀 22.2x22.2-160	Check valve	1	PC
24	16441003000019	单向阀 9.52x9.52-100	Check valve	1	PC
25	16441004000062	截止阀组件 7/8in(双焊接)	Stop valve assembly	1	PC
26	16441004000061	截止阀组件 1/2in(双焊接)	Stop valve assembly	1	PC
27	16442001000021	过滤器 $\phi 22.2 \times \phi 22.2$ -185	filter	1	PC
28	16442001000019	过滤器 12.7x 12.7-100	filter	2	PC
29	16442001000005	过滤器 6x 8-66	filter	2	PC
30	16442023000039	气液分离器 QFQ-15L(22)(立)	Gas-liquid separator	1	PC
31	16442021000035	油分离器 16P(R410a)	Oil separator	1	PC
32	16438003000018	压缩机 E655DHD-65D2YG (变频并联)	DC compressor	1	PC

14/16 HP

series	items	Part name	Part name	Qty.	unit
1	16445999000081	压缩机冷冻油 FVC68D	Crankcase oil	4.5	L
2	16430001000480	室外电机(三速) YDK370-6	Fixed Fan motor	1	PC
3	16430001000479	室外电机 DMSB-450W-8	DC fan motor	1	PC
4	11225509000061	四通换向阀阀体 VH61100	Four way valve	1	PC
5	11330011000039	四通换向阀线圈 RANCO 系列 L=1900	Four way valve wiring	1	PC
6	16441012000038	电磁阀阀体 FDF2AK01	Solenoid valve FDF2AK01	2	PC
7	16441012000001	电磁阀阀体 FDF2A	Solenoid valve FDF2A	1	PC
8	16441011000011	电磁阀线圈 FQ-679-RK L=1500	Solenoid valve wiring	2	PC
9	16441011000001	电磁阀线圈 FDF2A L=1800	Solenoid valve wiring	1	PC
10	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV	1	PC
11	16441014000026	(ROHS)电子膨胀阀阀体 UKV-32D61	EXV	2	PC
12	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	EXV wiring	1	PC
13	16441015000011	(ROHS)电子膨胀阀线圈 UKV-254	EXV wiring	2	PC
14	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	PC
15	16442024000006	高压开关 H20PS D 4.2/3.3(弯管)	High pressure switch	2	PC
16	16430007000162	温度传感器	Temp. sensor	1	PC
17	16430007000161	温度传感器 ZLBP-SW1C(组件)	Temp. sensor	1	PC
18	16422008000046	(ROHS)通讯线 4 芯 0.3m(XH4Y-XH4Y)白	Communication wire	1	set
19	16422008000047	(ROHS)通讯线 4 芯 0.35m(XH4Y-XH4Y)红	Communication wire	1	set
20	16442023000001	压力传感器 NSK-S784-1(0~5.0)MPa L=2000	High pressure sensor	1	PC
21	16442023000002	压力传感器 NSK-S783-1(0~3.0)MPa L=2000	Low pressure sensor	1	PC
22	16322002000024	DLR-450W5/DCM3 电控箱总成	Electric box assembly	1	set
23	16430015000027	电容 15 μ F/450V a.c	Capacitor	1	PC
24	16430022000003	油温加热带 220V/33W, 485mm/1600mm	Crankcase heater	2	PC
25	16444008000042	轴流风叶 600 \times 178	Axial fan blade	2	PC
26	16441003000035	单向阀 22.2 \times 22.2-160	Check valve	1	PC
27	16441003000019	单向阀 9.52 \times 9.52-100	Check valve	1	PC
28	16441004000062	截止阀组件 9/8in(双焊接)	Stop valve assembly	1	PC
29	16441004000061	截止阀组件 1/2in(双焊接)	Stop valve assembly	1	PC
30	16442001000020	过滤器 28.6 \times 28.6-185	filter	1	PC
31	16442001000019	过滤器 12.7 \times 12.7-100	filter	2	PC
32	16442001000005	过滤器 6 \times 8-66	filter	2	PC
33	16442023000040	气液分离器 QFQ-23L(双出管)	Gas-liquid separator	1	PC
34	16442021000035	油分离器 16P(R410a)	Oil separator	1	PC
35	16438003000018	压缩机 E655DHD-65D2YG(变频并 联)	DC compressor	1	PC
36	16438003000002	压缩机 E605DH-59D2YG(定频并联)	Fixed compressor	1	PC

18 HP

series	items	Part name	Part name	Part name	Qty.
1	16445999000081	压缩机冷冻油 FVC68D	Crankcase oil	4.5	L
2	16430001000480	室外电机(三速) YDK370-6	Fixed Fan motor	1	pc
3	16430001000479	室外电机 DMSB-450W-8	DC fan motor	1	pc
4	11225509000061	四通换向阀阀体 VH61100	Four way valve	1	pc
5	11330011000039	四通换向阀线圈 RANCO 系列 L=1900	Four way valve wiring	1	pc
6	16441012000038	电磁阀阀体 FDF2AK01	Solenoid valve FDF2AK01	2	pc
7	16441012000001	电磁阀阀体 FDF2A	Solenoid valve FDF2A	1	pc
8	16441011000011	电磁阀线圈 FQ-679-RK L=1500	Solenoid valve wiring	2	pc
9	16441011000001	电磁阀线圈 FDF2A L=1800	Solenoid valve wiring	1	pc
10	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV	1	pc
11	16441014000026	(ROHS)电子膨胀阀阀体 UKV-32D61	EXV	2	pc
12	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	EXV wiring	1	pc
13	16441015000011	(ROHS)电子膨胀阀线圈 UKV-254	EXV wiring	2	pc
14	16442024000005	低压开关 H20PS C 0.3/0.1(弯管)	Low pressure switch	1	pc
15	16442024000006	高压开关 H20PS D 4.2/3.3(弯管)	High pressure switch	1	pc
16	16430007000162	温度传感器	Temp. sensor	1	pc
17	16430007000161	温度传感器 ZLBP-SW1C(组件)	Temp. sensor	1	pc
18	16422008000046	(ROHS)通讯线 4 芯 0.3m(XH4Y-XH4Y)白	Communication wire	1	Set
19	16422008000047	(ROHS)通讯线 4 芯 0.35m(XH4Y-XH4Y)红	Communication wire	1	Set
20	16442023000001	压力传感器 NSK-S784-1(0~5.0)MPa L=2000	High pressure sensor	1	pc
21	16442023000002	压力传感器 NSK-S783-1(0~3.0)MPa L=2000	Low pressure sensor	1	pc
22	16322002000024	DLR-450W5/DCM3 电控箱总成	Electric box assembly	1	set
23	16430015000027	电容 15 μ F/450V a.c	Capacitor	1	pc
24	16430022000003	油温加热带 220V/33W, 485mm/1600mm	Crankcase heater	2	pc
25	16444008000042	轴流风叶 600 \times 178	Axial fan blade	2	pc
26	16441003000035	单向阀 22.2 \times 22.2-160	Check valve	1	pc
27	16441003000019	单向阀 9.52 \times 9.52-100	Check valve	1	pc
28	16441004000062	截止阀组件 9/8in(双焊接)	Stop valve assembly	1	pc
29	16441004000061	截止阀组件 1/2in(双焊接)	Stop valve assembly	1	pc
30	16442001000020	过滤器 28.6 \times 28.6-185	filter	1	pc
31	16442001000019	过滤器 12.7 \times 12.7-100	filter	2	pc
32	16442001000005	过滤器 6 \times 8-66	filter	2	pc
33	16442023000040	气液分离器 QFQ-23L(双出管)	Gas-liquid separator	1	pc
34	16442021000035	油分离器 16P(R410a)	Oil separator	1	pc
35	16438003000018	压缩机 E655DHD-65D2YG(变频 并联)	DC compressor	1	pc
36	16438003000028	压缩机 E655DH-59D2YG(定频并 联)	Fixed compressor	1	pc

Part 3 Indoor unit

Four-way cassette.....	138
Ceiling&floor Type	171
Wall-mounted Type	200
Slim Duct	226
Low Static Pressure Duct.....	251
Middle static pressure duct	274
High Static Pressure Duct Type	307
Fresh Air Processing Unit.....	337

Four-way cassette

1. Features	139
2. Specifications	141
3. Dimensions	147
4. Piping Diagrams	149
5. Wiring Diagram	150
6. Electric characteristics	151
7. Capacity Tables	152
8. Sound levels	154
9. Installation	155
10. Exploded View	160
11. Spare parts list	164

1. Features


(1) Concealed design

—Ceiling installation, saving room space, very suitable for family or office occasion.

(2) With Setting or Auto two operation modes

—Fourway blowing, strong circulating wind, multi wind speed

—The cooling or heating capacity can reach to each corner of the room.



(3) One-step formed shell by mold


The appearance is elegant

(4) Special insulation design

—achieves high heat insulation efficiency, and no condensation water on shell

(5) Built-in drain pump

—Drain-head height is up to 1.2 meters, creating the ideal solution for perfect water drainage, also construction and installation is much easier and more convenient;



(6) Long term air filter

—Wash period is two times longer than normal filter, and maintenance is free

(7) 3D helix air blade ensures the air flow sufficiently

—reduces the unit thickness

—reduces the operation noise greatly



(8) Plastic drip tray adopts innovative foam combined with plastic technical

—The thickness of plastic reaches 1mm, avoid any leakage;

(9) Ingenious hook design

—the panel is convenient to install or remove

(10) Fresh air intake design

—Leading in fresh air to improve indoor air quality anytime



(11) All the units have low ambient temperature cooling function

—makes the unit can run normally on the condition that the ambient temperature falls down to -5°C;




(12) Failure automatic detection

—The indicator will flash and the error code will display on the display board or remote controller, the failure code is easier to be found and make the malfunction checking easier. (C7 panel)



(13) Reserve spaces for air side-outlet

—Air duct can be connected from the four sides to nearby rooms



(14) Slimmer body

—The exposed height only has 18mm for small panel

(15) Two panels for choose: C5, C7



2. Specifications

Model	Indoor		9000	12000	16000
	Panel		MB13	MB13	MB13
Code	Indoor		16104001000006	16104002000010	16104003000010
	Panel		16108004000004	16108004000004	16108004000004
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	2.8	3.6	4.5
	Heating	kW	3.0	4.3	5.0
Fan Motor	Model		YDK30-6E1	YDK30-6E1	YDK30-6E1
	Brand		SINJUN	SINJUN	SINJUN
	Output Power	W	30	30	30
	Capacitor	uF	2.5	2.5	2.5
	Speed (Hi/Mi/Lo)	r/min	870/830/785	870/830/785	870/830/785
Coil	Number Of Row		2	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.5	1.5	1.5
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	1160x164x25.4	1160x164x25.4	1160x164x25.4
	Heat Exchanging Area	m ²	4.34	4.34	5.76
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	620/496/434	620/496/434	850/680/595
	Noise Level(Hi/Mi/Lo)	dB(A)	38/35/32	38/35/32	39/36/33
	Net Dimension (WxDxH)	mm	615x615x263	615x615x263	615x615x263
	Packing Dimension (WxDxH)	mm	700x700x330	700x700x330	700x700x330
	Net Weight	Kg	20	20	20
	Gross Weight	Kg	25	25	25
Panel	Net Dimension (WxDxH)	mm	650x650x55	650x650x55	650x650x55
	Packing Dimension (WxDxH)	mm	710x710x80	710x710x80	710x710x80
	Net Weight	Kg	3	3	3
	Gross Weight	Kg	5	5	5
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	6.35
	Gas Side	mm	12.7	12.7	12.7
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		℃	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		℃	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	10~25	15~30	20~35
Stuffing Quantity	20/40/40H	Unit	140/299/345	140/299/345	140/299/345

GEEN GRV Four Way Cassette Type

Notes:

1. Cooling Capacity: Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m, level difference: 0 m.
2. Heating Capacity: Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m, level difference: 0 m.
3. Anechoic chamber conversion value, measured in test room. During actual operation. These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

Model	Indoor		18000	24000	28000
	Panel		MB13	MB12	MB12
Code	Indoor		16104005000010	16104007000013	16104008000014
	Panel		16108004000004	16108002000007	16108002000007
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	5.6	7.1	8.0
	Heating	kW	6.3	8.0	10.0
Fan Motor	Model		YDK30-6E1	YDK30-6 Q	YDK35-6 Q
	Brand		SINJUN	HUATE	HUATE
	Output Power	W	30	30	35
	Capacitor	uF	2.5	3	4
	Speed (Hi/Mi/Lo)	r/min	870/830/785	500/400/320	570/480/400
Coil	Number Of Row		2	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.5	1.6	1.4
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	1160x164x25.4	2142x205x25.4	2142x205x25.4
	Heat Exchanging Area	m ²	5.76	10.02	10.02
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	850/680/595	1100/880/770	1500/1200/1050
	Noise Level(Hi/Mi/Lo)	dB(A)	39/36/33	40/37/33	41/38/35
	Net Dimension (WxDxH)	mm	615x615x263	835x835x240	835x835x240
	Packing Dimension (WxDxH)	mm	700x700x330	910x910x320	910x910x320
	Net Weight	Kg	20	27	27
	Gross Weight	Kg	25	34	34
Panel	Net Dimension (WxDxH)	mm	650x650x55	950x950x55	950x950x55
	Packing Dimension (WxDxH)	mm	710x710x80	1000x1000x100	1000x1000x100
	Net Weight	Kg	3	5	5
	Gross Weight	Kg	5	7	7
Refrigerant	Liquid Side	mm	6.35	9.52	9.52

GEEN GRV Four Way Cassette Type

Pipe	Gas Side	mm	12.7	15.88	15.88
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		℃	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		℃	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	25~45	30~50	35~55
Stuffing Quantity	20/40/40H	Unit	140/299/345	77/164/175	77/164/175

Notes:

1. Cooling Capacity: Indoor temp.27℃DB,19℃WB,outdoor temp.35℃DB,24℃WB /Equivalent piping length :7.5m, level difference: 0 m.
2. Heating Capacity: Indoor temp.20℃DB, outdoor temp.7℃DB,6℃WB /Equivalent piping length :7.5m, level difference: 0 m.
3. Anechoic chamber conversion value, measured in test room. During actual operation. These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

Model	Indoor		30000	34000	38000
	Panel		MB12	MB12	MB12
Code	Indoor		16104009000010	16104010000009	16104011000012
	Panel		16108002000007	16108002000007	16108002000007
Power Supply		V~,Hz,P h	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	9.0	10.0	11.2
	Heating	kW	11.0	12.0	12.8
Fan Motor	Model		YDK45-6 Q	YDK45-6 Q	YDK80-6-50 Q
	Brand		HUATE	HUATE	HUATE
	Output Power	W	45	45	80
	Capacitor	uF	4	4	6
	Speed (Hi/Mi/Lo)	r/min	650/520/450	650/520/450	685/540/450
Coil	Number Of Row		2	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.4	1.4	1.4
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	2142x205x25.4	2142x205x25.4	2142x205x25.4
	Heat Exchanging Area	m ²	10.02	12.76	15.60
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	1500/1200/1050	1500/1200/1050	1800/1440/1260
	Noise Level(Hi/Mi/Lo)	dB(A)	41/38/35	41/38/35	41/38/35
	Net Dimension (WxDxH)	mm	835x835x240	835x835x240	835x835x280
	Packing Dimension (WxDxH)	mm	910x910x320	910x910x320	910x910x360

GEEN GRV Four Way Cassette Type

	Net Weight	Kg	27	27	30
	Gross Weight	Kg	34	34	37
Panel	Net Dimension (WxDxH)	mm	950x950x55	950x950x55	950x950x55
	Packing Dimension (WxDxH)	mm	1000x1000x100	1000x1000x100	1000x1000x100
	Net Weight	Kg	5	5	5
	Gross Weight	Kg	7	7	7
Refrigerant Pipe	Liquid Side	mm	9.52	9.52	9.52
	Gas Side	mm	15.88	15.88	19.05
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	40~60	45~65	50~75
Stuffing Quantity	20/40/40H	Unit	77/164/175	77/164/175	77/164/175

Notes:

1. Cooling Capacity: Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m, level difference: 0 m.
2. Heating Capacity: Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value, measured in test room. During actual operation. These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

Model	Indoor		42000	48000
	Panel		MB12	MB12
Factory Model	Indoor		ALCa-H42A4/R1DICA	ALCa-H48A4/R1DICA
	Panel		MB12	MB12
Code	Indoor		16104012000010	16104013000010
	Panel		16108002000007	16108002000007
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	12.5	14.0
	Heating	kW	13.3	15.0
Fan Motor	Model		YDK80-6-50 Q	YDK80-6-50 Q
	Brand		HUATE	HUATE
	Output Power	W	80	80
	Capacitor	uF	6	6
	Speed (Hi/Mi/Lo)	r/min	685/540/450	685/540/450
Coil	Number Of Row		2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7

GEEN GRV Four Way Cassette Type

	Fin Pitch	mm	1.4	1.4
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	2142x246x25.4	2142x246x25.4
	Heat Exchanging Area	m ²	15.60	15.60
	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	1800/1440/1260	1800/1440/1260
	Noise Level(Hi/Mi/Lo)	dB(A)	41/38/35	41/38/35
	Net Dimension (WxDxH)	mm	835x835x280	835x835x280
	Packing Dimension (WxDxH)	mm	910x910x360	910x910x360
	Net Weight	Kg	30	30
Code	Indoor		16104022000051	
	Panel		16108002000007	
Power Supply		V~,Hz,Ph	220~240,50,1	
Capacity	Cooling	kW	14.0	
	Heating	kW	15.0	
Fan Motor	Model		XD80A	
	Brand		SINJUN	
	Output Power	W	80	
	Capacitor	uF	6	
	Speed (Hi/Mi/Lo)	r/min	695/585/495	
Coil	Number Of Row		2	
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	
	Fin Pitch	mm	1.4	
	Fin Material		Hydrophilic aluminum fin	
	Tube Outside Dia.and Material	mm	7,Inner grooved	
	Coil Length x Height x Width	mm	2142x246x25.4	
	Heat Exchanging Area	m ²	15.60	
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	1800/1440/1260	
	Noise Level(Hi/Mi/Lo)	dB(A)	41/38/35	
	Net Dimension (WxDxH)	mm	835x835x250	
	Packing Dimension (WxDxH)	mm	900x900x330	
	Net Weight	Kg	30	
	Gross Weight	Kg	37	
Panel	Net Dimension (WxDxH)	mm	950x950x55	
	Packing Dimension (WxDxH)	mm	1000x1000x100	
	Net Weight	Kg	5	
	Gross Weight	Kg	7	
Refrigerant Pipe	Liquid Side	mm	9.52	
	Gas Side	mm	15.88	
	Drainage	mm	R1in(DN25)	
Operation Temperature Range		℃	145	16~32
Ambient Temperature Range(Cooling/Heating)		℃		-5~-52/-20~24
Application Area		m ²		60~100
Stuffing Quantity	20/40/40H	Unit		77/164/175

GEEN GRV Four Way Cassette Type

Unit	Gross Weight	Kg	37	37
Panel	Net Dimension (WxDxH)	mm	950x950x55	950x950x55
	Packing Dimension (WxDxH)	mm	1000x1000x100	1000x1000x100
	Net Weight	Kg	5	5
	Gross Weight	Kg	7	7
Refrigerant Pipe	Liquid Side	mm	9.52	9.52
	Gas Side	mm	19.05	19.05
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	50~90	60~100
Stuffing Quantity	20/40/40H	Unit	77/164/175	77/164/175

Notes:

1. Cooling Capacity: Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m, level difference: 0 m.
2. Heating Capacity: Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m, level difference: 0 m.
3. Anechoic chamber conversion value, measured in test room. During actual operation. These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.


Notes:

1. Cooling Capacity: Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m, level difference: 0 m.
2. Heating Capacity: Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m, level difference: 0 m.
3. Anechoic chamber conversion value, measured in test room. During actual operation. These values are normally somewhat higher as a result of ambient conditions.


All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

3. Dimensions


9000/12000/16000/18000




24000/28000/30000/34000/38000



42000/48000



4. Piping Diagrams




Refrigerant pipe connection port diameters

(mm)

Model	Gas	Liquid
9000/12000/16000/18000	12.7	6.35
24000/28000/30000/34000	15.88	9.52
38000/42000/48000	19.05	9.52

5. Wiring Diagram



6. Electric characteristics

Model	Indoor Unit				Power supply		IFM	
	Hz	Voltage	Min.	Max.	MCA	MFA	KW	FLA
9000	50	220-240	198	264	0.34	10	0.03	0.27
12000	50	220-240	198	264	0.34	10	0.03	0.27
16000	50	220-240	198	264	0.34	10	0.03	0.27
18000	50	220-240	198	264	0.34	10	0.03	0,27
24000	50	220-240	198	264	0.35	10	0.03	0.28
28000	50	220-240	198	264	0.4	10	0.035	0.32
30000	50	220-240	198	264	0.53	16	0.045	0.42
34000	50	220-240	198	264	0.53	16	0.045	0.42
38000	50	220-240	198	264	1.16	16	0.08	0.93
42000	50	220-240	198	264	1.16	16	0.08	0.93
48000	50	220-240	198	264	1,16	16	0.08	0.93

Symbols:

MCA: Min. Circuit Amps(A)
 MFA: Max. Circuit BreakerAmps
 KW: Fan Motor Rated Output(kW)
 FLA: Full Load Amps(A)
 IFM:Indoor Fan Motor

Note:

1. Min. and Max. Voltage:Units are suitable for use on electrical system where voltage supplied to unit terminals is not below or above listed rang limits.
2. Maximum allowable voltage unbalance between phases is 2%.
3. $MCA = 1.25 \times FLA$
4. Select wire size based on the MCA.

7. Capacity Tables

Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient



Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature[°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.1	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1	1.06	1.13
	Power	0.96	0.97	1	1.01	1.03
40	Cooling capacity	0.96	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.9	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.8	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32

Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb[°C]	capacity/power correction coefficient	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.7
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1	0.96
	Power	0.94	1	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07
	Power	1.05	1.11	1.17


15-24	Heating capacity	0.85 – 1.05 of nominal
	Power	0.80 – 1.20 of nominal

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube



Positive side of high head means installation height of outdoor unit should be higher than indoor unit;
 negative side of high head means installation height of outdoor unit should be lower than indoor unit;
 (change ratio of basic capacity)

8. Sound levels



Model	220~240V 50Hz		
	H	M	L
9000	38	35	32
12000	38	35	32
16000	39	36	33
18000	39	36	33
24000	40	37	33
28000	41	38	35
30000	41	38	35
34000	41	38	35
38000	41	38	35
42000	41	38	35
48000	41	38	35

Note:

1. The operating condition is assumed to be standard(JIS Condition).
2. These operating values were obtained in a dead room (conversion values).Sound level will vary depending on a range of factors such as the construction (acoustic absorption coefficient) of the particular room in which the equipments installed.

9. Installation

9.1 Preparation and Tools before Installation

◇ Please buy the following parts from the market before installation


Hanging bolt (4 per unit)
PVC drain pipe
Some cable ties
Connecting copper tube
Branch manifold (choose according to actual installation situation)
Thermal insulation materials for connecting copper tube (PEF foaming materials with thickness above 8mm)
Power cord and power connection line (it's required to wire according to requirement for line diameter in wiring diagram)

Note:

Due to the difference between the characteristics of R410A and R22 refrigerant, it's necessary to use dedicated tools of R410A for some tools during installation.


- ◇ The selected position hanging indoor unit should be able to support the weight of unit without noise and additional vibration. It's necessary to reinforce before installation if reinforcement is required;
- ◇ The space of selected ceiling should be enough for holding indoor unit;
- ◇ The installation location should be easy for drainage;
- ◇ It shouldn't be installed in places (such as kitchen, laundry and mechanical workshop, etc.) of heat source, vapor source and more oil mist to prevent degradation of heat exchanger, electric shock and unit damage caused by plastic parts corrosion;
- ◇ Install in the place at least one meter away from TV and radio to prevent interfering TV and radio.
- ◇ There is no barrier blocking ventilation nearby and cold air should be able to evenly distribute to each indoor corner;
- ◇ There should be certain spacing between the surrounding and barrier of indoor unit to ease maintenance;
- ◇ The unit uses R410A environment-friendly refrigerant that is a kind of nonflammable and nontoxic gas. Since the refrigerant has larger specific gravity than air, it will suffuse on the ground in case of leakage. Therefore, the unit must be well ventilated if installed in closed room to prevent suffocation. In case of refrigerant leakage, immediately stop unit operation, timely contact maintenance personnel and avoid any open fire on site because refrigerant will decompose hazardous gas when exposed to open fire.

9.2 Space to be reserved between the Surrounding of Indoor Unit and Barrie




9.3 Hoisting of indoor unit

- ◇ Selection of hanging foundation: the foundation must be wooden frame and reinforced concrete structure, which is firm and reliable, able to stand a weight four times of the unit's weight and stand a certain vibration for a long time.
- ◇ Fixing of hanging foundation: fix hanging bolt as shown in the diagram or fix it with iron bracket and wooden bracket.




- ◇ If the unit body is installed on oblique ceiling, it's necessary to put cushion block between ceiling and air outlet panel to ensure the unit body is installed on horizontal position.




- ◇ Dual nuts should be adopted to fix the indoor unit under the ceiling.
- ◇ Adjust the relative position of hook on hanging bolt to keep the main unit horizontal in each direction. Check with level meter after installation to ensure horizontal indoor main unit and prevent possible failures such as water leakage and air leakage.
- ◇ Tighten nut to ensure tight contact among nut, washer and four mounting hooks without loose hanging;
- ◇ Ensure there is no loose positioning such as shaking of main unit after installation;
- ◇ Ensure rough alignment between the center of indoor main unit and the opening of ceiling;

9.4 Schematic Diagram of Hanging




9.5 Installation of drain pipe


- ◇ Drain pipe must be wrapped with thermal insulation material as follows to prevent condensation or dripping.



- ◇ Thermal insulation material should be rubber & plastic thermal insulation pipe with thickness above 8mm.
- ◇ Drain pipe should incline downwards with gradient of 1/50-1/100, which will subject to failure such as back flow or water leakage in case of up-and-down fluctuation or upward inclination.



- ◇ Although draining pump of unit has a lift of 1200mm, considering the protective shutdown of float switch will be caused due to the back flow of condensed water after shutdown, please arrange drain pipe according to the following diagram where possible.



- ◇ When install drain pipes for multiple units, it's necessary to install utility piping at 100mm under the drainage outlet of each unit as shown in the following diagram.




- ◇ After installation, conduct drainage test to determine if water correctly flows through pipeline and carefully observe the connection to ensure there is no leakage. If the unit is installed in new house, it's recommended to test before decorating ceiling. Conduct drainage test for the unit used for heating only.

9.6 Installation of Panel

- ◇ Installation of Panel:

Refer to the following diagram for MB06, buckle four hooks of panel on corresponding hooks of main unit and tighten adjusting bolt.



Note:


Please ensure the position of air-ducting motor of panel corresponds to the auxiliary pipe side of main unit

9.7 Connection of Air Duct and Ventilation of Fresh Air

Note:

- 1) It's allowed to connect air duct only under special installation environment and he length shouldn't be over five meters;
- 2) Please use air duct that can prevent condensation and absorb sound.
- 3) Wrap air duct and the connection between air duct and main unit for thermal insulation and sealing.


To meet user's different using requirements and environments, reserve an interface for ventilating fresh air and four air duct interfaces for indoor unit of 3HP and 5HP or connect air duct on unit.



- ◇ Ventilation of fresh air: a round interface for ventilating fresh air is reserved at edge angle of unit. User can cut off the round sheet metal and lead it to outdoors after connecting air duct if user needs this function. Interface for ventilating fresh air is connected with air return inlet of indoor unit, which can introduce fresh air from outdoors due to the action of negative pressure during unit operation.
- ◇ Connection of air duct: four square interfaces are reserved on four sides of unit, among which, air outlet on the side for connecting air duct can be blocked. Cut off sheet metal of square interface.

10. Exploded View

9000 TO 18000




9000 TO 18000

N0.	GREEN Code	Part Name (Chinese)	Part Name	Quantity	Unit
1	16108004000004	面板 MB13	Panel MB13	1	Pc
1.1	16420014000019	面板 MB13 围框	Panel cover board	1	Set
1.2	16420010000015	面板 MB13 回风格栅	Return air grille assembly	1	Set
1.3	16420012000004	面板 MB13 过滤网	Air filter net	1	Pc
1.4	16420007000023	面板 MB13 导风叶片	guide wind vane	4	Pcs
1.5	16430001000133	步进电机 24BYJ48-2	Step motor	4	Pcs
1.6	16422015000007	显示灯板 SX-DISP-01	Display board	1	Set
2	16420016000005	电控盒盖	Cover for electric components	1	Pc
3	16322001000038	电控总成	Electric assembly	1	Set
3.1	16422001000092	控制板 DCZ-SN3F-SYE2 (R8C)	PCB board	1	Pc
3.2	16422005000009	变压器 TDB-14-B2B	Transformer	1	Pc
3.3	16427001000008	端子板 7 位 (600V 2.5mm2) AB	Terminal board	1	Pc
3.4	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	Sensor 1 White 15K	1	Pc
3.5	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	Sensor 2 Blue 20K	1	Pc
3.6	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	Sensor 3 Yellow 20K	1	Pc
3.7	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	Sensor 4 Green 20K	1	Pc
4	16432016000037	橡胶塞 ALCa-H18A4/C7	Rubber plug	1	Pc
5	16320005000018	接水盘组件(涂胶)	Water pan	1	Set
6	16324001000063	蒸发器总成	Evaporator assembly	1	Set
6.1	16324005000025	蒸发器组件	Evaporator part	1	Set
6.2	16325005000033	蒸发器出气管组件	Evaporator outlet tube assembly	1	Set
6.3	16325001000103	蒸发器进液管组件(内置)	Evaporator inlet tube assembly	1	Set
7	16421040000020	蒸发器挂钩	Evaporator Pothook	2	Pcs
8	16421007000035	蒸发器连接板	Evaporator connect board	1	Pc
9.1	16440001000004	排水泵 PLD-700	Drain pump	1	Pc
9.2	16445034000003	浮子开关 AKS5	Bodder switch	1	Pc
9.3	16421026000129	水泵支架	Drain pump support	1	Pc
10	16444001000006	风轮 $\phi 283 \times 166$	Wind wheel 283x166	1	Pc
11	16430001000045	电机 YDK30-6-60E1	Fan motor YSK30-6E1	1	Pc
12	16421035000014	电机支架	motor holder	1	Pc
13	16421999000052	风道	Air passage	1	Pc
14	16421002000192	接水盘固定板	Water pan holder	4	Pcs
15	16421040000019	挂钩	Pothook	4	Pcs
16	16421010000022	围板 A	Boarding A	1	Pc

GREEN GRV Ceiling&floor Type

16.1	16421010000023	围板 B	Boarding B	1	Pc
17	16421014000037	阀板 A	Valve board A	1	Pc
17.1	16421014000038	阀板 B	Valve board B	1	Pc
18	16321005000011	底盘组件	Chassis	1	Pc
19	16432019000008	塑料排水软管 QR-50N/C3	Plastic drainage pipe	1	Set
20.1	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	EXV body	1	Pc
20.2	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	EXV coil	1	Pc

24000 TO 48000



11. Spare parts list

9000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm ²)AB	1
Capacitor	11330010000054	R 风机电容 2.5μF/450VAC/70/2000h	1
Fan motor	16430001000135	电机 YDK30-6E1	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000004	温度传感器 15K3950 XH2 白 0.7m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000006	风轮 283×166	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000004	面板 MB13 过滤网	1
Filter	16442001000005	过滤器 6× 8-66	2
Air guide blades	16420007000023	(ROHS)面板 MB13 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000004	排水泵 PLD-700	1
Dobber switch	16445034000003	(ROHS)浮子开关 AKS5	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

12000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm ²)AB	1
Capacitor	11330010000054	R 风机电容 2.5μF/450VAC/70/2000h	1
Fan motor	16430001000135	电机 YDK30-6E1	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000004	温度传感器 15K3950 XH2 白 0.7m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000006	风轮 283×166	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000004	面板 MB13 过滤网	1

GREEN GRV Ceiling&floor Type

Filter	16442001000005	过滤器 6× 8-66	2
Air guide blades	16420007000023	(ROHS)面板 MB13 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000004	排水泵 PLD-700	1
Dobber switch	16445034000003	(ROHS)浮子开关 AKS5	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

16000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm2)AB	1
Capacitor	11330010000054	R 风机电容 2.5μF/450VAC/70/2000h	1
Fan motor	16430001000135	电机 YDK30-6E1	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000004	温度传感器 15K3950 XH2 白 0.7m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000006	风轮 283×166	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000004	面板 MB13 过滤网	1
Filter	16442001000005	过滤器 6× 8-66	2
Air guide blades	16420007000023	(ROHS)面板 MB13 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000004	排水泵 PLD-700	1
Dobber switch	16445034000003	(ROHS)浮子开关 AKS5	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

18000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm2)AB	1
Capacitor	11330010000055	R 风机电容 3.0μF/450VAC/70/2000h	1

GREEN GRV Ceiling&floor Type

Fan motor	16430001000234	电机(三速) YDK30-6	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000027	风轮 470×147(ABS 新料)(白色)(3PC7 款)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2
Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

24000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7 位(600V 2.5mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000490	电机(长轴) YDK35-6Q	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000027	风轮 470×147(ABS 新料)(白色)(3PC7 款)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2
Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1

GREEN GRV Ceiling&floor Type

expansion valve			
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

28000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000490	电机(长轴) YDK35-6Q	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000027	风轮 470×147(ABS 新料)(白色)(3PC7 款)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2
Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

30000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000491	电机(长轴) YDK45-6Q	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1

GREEN GRV Ceiling&floor Type

temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000027	风轮 470×147(ABS 新料)(白色)(3PC7 款)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2
Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

34000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7 位(600V 2.5mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000491	电机(长轴) YDK45-6Q	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000027	风轮 470×147(ABS 新料)(白色)(3PC7 款)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2
Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

38000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm ²)AB	1
Capacitor	11330010000059	R 风机电容 6.0μF/450VAC/70/2000h	1
Fan motor	16430001000209	(ROHS)电机(三速) YDK80-6-50Q	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000028	风轮 470×170(ABS 新料)(白色)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2
Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

42000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm ²)AB	1
Capacitor	11330010000059	R 风机电容 6.0μF/450VAC/70/2000h	1
Fan motor	16430001000209	(ROHS)电机(三速) YDK80-6-50Q	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000028	风轮 470×170(ABS 新料)(白色)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2

GREEN GRV Ceiling&floor Type

Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

48000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000008	(ROHS)端子板 7位(600V 2.5mm2)AB	1
Capacitor	11330010000059	R 风机电容 6.0μF/450VAC/70/2000h	1
Fan motor	16430001000209	(ROHS)电机(三速) YDK80-6-50Q	1
Step motor	16430001000133	步进电机 24BYJ48-2	4
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000028	风轮 470×170(ABS 新料)(白色)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000001	面板 MB06 过滤网	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	2
Air guide blades	16420007000009	(ROHS)面板 MB12 导风叶片	4
Display board	16422015000007	(ROHS)显示灯板 SX-DISP-01	1
Drain pump	16440001000009	(ROHS)排水泵 PLD-1200(惠而浦)	1
Dobber switch	16445034000001	(ROHS)浮子开关 GMF-31	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

Ceiling&floor Type

1. Feature	172
2. Specifications	173
3. Dimension	176
4. Piping Diagram	177
5. Wiring Diagram	178
6. Electric Characteristics.....	179
7. Capacity Tables	180
8. Sound Levels	182
9. Installation	183
10.Exploded View.....	185
11.Spare parts list.....	193


1.Feature

(1) Dual-direction swing,wide swing angle

Vertical and horizontal swing function makes it possible to blow air to every corner of the room.




every



(2) Ultra slim design

Thinner and lighter, the unit is only 205mm.



(3) Adjustable fan speed

All units are equipped with 3 speed controlled fan mode,adjust the air flow rate in accordance with the ceiling height.

(4) Flexible installation

Can be vertically installed against the wall or horizontally installed under the ceiling.



2.Specifications

Model			IFGRV16P1	IFGRV18P1	IFGRV24P1
Code			16104086000007	16104088000006	16104090000007
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	4.5	3.6	5.6
	Heating	kW	5.0	4.3	6.0
Fan Motor	Model		YSK-40W-4	YSK-40W-4	YSK-40W-4
	Brand		HUATE	HUATE	HUATE
	Output Power	W	40	40	40
	Capacitor	uF	2.5	2.5	2.5
	Speed (Hi/Mi/Lo)	r/min	1250/1010/900	1250/1010/900	1250/1010/900
Coil	Number Of Row		3	3	3
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.6	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	570x246x38.1	570x246x38.1	570x246x38.1
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	850/680/595	630/504/441	850/680/595
	Noise Level(Hi/Mi/Lo)	dB(A)	42/39/36	39/36/33	42/39/36
	Net Dimension (WxDxH)	mm	929x660x205	929x660x205	929x660x205
	Packing Dimension (WxDxH)	mm	1010x720x290	1010x720x290	1010x720x290
	Net Weight	Kg	25	24	26
	Gross Weight	Kg	29	28	29
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	6.35
	Gas Side	mm	12.7	12.7	12.7
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	20~35	15~30	25~45
Stuffing Quantity	20/40/40H	Unit	149/300/350	149/300/350	104/222/246

Note:

1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference: 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

GREEN GRV Ceiling&floor Type

Model			IFGRV28P1	IFGRV30P1	IFGRV34P1
Code			16104091000006	16104092000006	16104093000005
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	8.0	9.0	10.0
	Heating	kW	10.0	11.0	12.0
Fan Motor	Model		YSK-70W-4	YSK-70W-4	YSK-70W-4
	Brand		HUATE	HUATE	HUATE
	Output Power	W	70	70	70
	Capacitor	uF	4	4	4
	Speed (Hi/Mi/Lo)	r/min	1386/1100/970	1386/1100/970	1386/1100/970
Coil	Number Of Row		3	3	3
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	22x19.05	22x19.05
	Fin Pitch	mm	1.6	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7.94 , Inner grooved	7.94 , Inner grooved
	Coil Length x Height x Width	mm	950*246*38.1	950X264X57.15	950X264X57.15
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	1200/960/840	1500/1200/1050	1500/1200/1050
	Noise Level(Hi/Mi/Lo)	dB(A)	47/44/41	47/44/41	47/44/41
	Net Dimension (WxDxH)	mm	1280x660x205	1280x660x205	1280x660x205
	Packing Dimension (WxDxH)	mm	1360x720x290	1360x720x290	1360x720x290
	Net Weight	Kg	35	35	35
	Gross Weight	Kg	39	39	39
Refrigerant Pipe	Liquid Side	mm	9.52	9.52	9.52
	Gas Side	mm	15.88	15.88	15.88
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	35~55	40~60	45~65
Stuffing Quantity	20/40/40H	Unit	104/222/246	104/222/246	104/222/246

Note:

1. Cooling Capacity:Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m,level difference: 0 m.
2. Heating Capacity:Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.
- 5.

GREEN GRV Ceiling&floor Type


Model			IFGRV38P1	IFGRV42P1	IFGRV48P1
Code			16104094000005	16104095000006	16104096000005
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	11.2	12.5	14.0
	Heating	kW	12.8	13.3	15.0
Fan Motor	Model		YSK-105W-4	YSK-105W-4	YSK-105W-4
	Brand		HUATE	HUATE	HUATE
	Output Power	W	105	105	105
	Capacitor	uF	5	5	5
	Speed (Hi/Mi/Lo)	r/min	1386/1100/970	1386/1100/970	1386/1100/970
Coil	Number Of Row		3	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	22×19.05	20.5×12.7	20.5×12.7
	Fin Pitch	mm	1.6	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7.94 , Inner grooved	7.94 , Inner grooved	7.94 , Inner grooved
	Coil Length x Height x Width	mm	1300×242×57.15	1300×242×57.15	1300×242×57.15
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	1800/1440/1260	1800/1440/1260	1800/1440/1260
	Noise Level(Hi/Mi/Lo)	dB(A)	48/45/42	48/45/42	48/45/42
	Net Dimension (WxDxH)	mm	1631×660×205	1631×660×205	1631×660×205
	Packing Dimension (WxDxH)	mm	1710×720×290	1710×720×290	1710×720×290
	Net Weight	Kg	45	45	45
	Gross Weight	Kg	51	51	51
Refrigerant Pipe	Liquid Side	mm	9.52	9.52	9.52
	Gas Side	mm	19.05	19.05	19.05
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	50~75	50~90	60~100
Stuffing Quantity	20/40/40H	Unit	86/173/202	86/173/202	86/173/202

Note:


1. Cooling Capacity:Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m,level difference: 0 m.
2. Heating Capacity:Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m,level difference : 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

3.Dimension


16000/18000




24000/28000/30000/34000



38000/42000/48000



4.Piping Diagram




Refrigerant pipe connection port diameters

(mm)

Model	Gas	Liquid
16000	12.7	6.35
18000		
24000		
28000	15.88	9.52
30000		
34000		
38000	19.05	9.52
42000		
48000		

5.Wiring Diagram



6.Electric Characteristics

Model	Indoor Unit				Supply Power		IFW	
	Hz	Voltage	Min.	Max.	MCA	MFA	KW	FLA
16000	50	220-240	198	264	0.51	10	0.04	0.41
18000	50	220-240	198	264	0.51	10	0.04	0.41
24000	50	220-240	198	264	1.13	10	0.07	0.90
28000	50	220-240	198	264	1.13	10	0.07	0.90
30000	50	220-240	198	264	1.13	16	0.07	0.90
34000	50	220-240	198	264	1.13	16	0.07	0.90
38000	50	220-240	198	264	1.50	16	0.105	1.20
42000	50	220-240	198	264	1.50	16	0.105	1.20
48000	50	220-240	198	264	1.50	16	0.105	1.20

Symbols:

MCA: Min. Circuit Amps(A)
 MFA: Max.CircuitBreakerAmps
 KW: Fan Motor Rated Output(kW)
 FLA: Full Load Amps(A)
 IFM:Indoor Fan Motor

Note:

- 1.Min. and Max. Voltage:Units are suitable for use on electrical system where voltage supplied to unitterminals is not below or above listed rang limits.
- 2.Maximum allowable voltage unbalance between phases is 2%.
- 3.MCA/MFA
 $MCA = 1.25 \times FLA$
- 4.Select wire size based on the MCA.

7.Capacity Tables

Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient



Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature [°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.10	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1.0	1.06	1.13
	Power	0.96	0.97	1.0	1.01	1.03
40	Cooling capacity	0.96	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.90	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.80	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32

Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb [°C]	capacity/power correction coefficient	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.70
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1.0	0.96
	Power	0.94	1.0	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07


	Power	1.05	1.11	1.17
15-24	Heating capacity	0.85 – 1.05 of nominal		
	Power	0.80 – 1.20 of nominal		

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube



Positive side of high head means installation height of outdoor unit should be higher than indoor unit;
 negative side of high head means installation height of outdoor unit should be lower than indoor unit;
 (change ratio of basic capacity)

8.Sound Levels



Note:


1. The operating condition is assumed to be standard(JIS Condition).
2. These operating values were obtained in a dead room (conversion values).
3. Sound level will vary depending on a range of factors such as the construction (acoustic absorption coefficient) of the particular room in which the equipments installed.

Model	220-240V 50Hz		
	High (dB)	Medium (dB)	Low (dB)
16000	42	39	36
18000			
24000	45	42	39
28000	47	44	41
30000			
34000			
38000	48	45	42
42000			
48000			


9. Installation

9.1 Service Space

- ◇ Hoisting Installation




- ◇ Floor-standing Installation




9.2 Hoisting of Indoor Unit

- ◇ Selection of hanging foundation: the foundation must be wooden frame and reinforced concrete structure, which is firm and reliable, able to stand a weight four times of the unit's weight and stand a certain vibration for a long time.



- ◇ Fixing of hanging foundation: fix hanging bolt as shown in the diagram or fix it with iron bracket and wooden bracket.


- ◇ Adjust the relative position of hook on hanging bolt to keep the main unit horizontal in each direction. Check with level meter after installation to ensure horizontal indoor main unit and prevent possible failures such as water leakage and air leakage.




- ◇ Tighten nut to ensure tight contact among nut, washer and four mounting hooks without loose hanging;
- ◇ Ensure there is no loose positioning such as shaking of main unit after installation;

Installation of Drain Pipe

◇ Drain pipe must be wrapped with thermal insulation material as follows to prevent condensation or dripping. Thermal insulation material should be rubber & plastic thermal insulation pipe with thickness above 8mm.




- ◇ Drain pipe should incline downwards with gradient of 1/50-1/100, which will subject to failure such as back flow or water leakage in case of up-and-down fluctuation or upward inclination.



- ◇ After installation, conduct drainage test to determine if water correctly flows through pipeline and carefully observe the connection to ensure there is no leakage. If the unit is installed in new house, it's recommended to test before decorating ceiling. Conduct drainage test for the unit used for heating only.

10.Exploded View


16000/18000



16000/18000

NO.	BOM Number	Chinese name	Part Name	Quantity	Unit
1	16420012000002	ALCe-H24B4/C5 滤网	Filter net	2	PCS
2	16420010000002	ALCe-H24B4/C5 格栅	Grille	2	PCS
3	16420015000002	ALCe-H24B4/C5 左装饰板	Left decorative plate	1	PC
4	16421038000009	ALCe-H24B4/C5 电控盒	Electrical assembly	1	PC
5	16421005000205	ALCe-H24B4/C5 电控盒盖	Electrical control box	1	PC
6	11220544000008	R51L/C(5)双联压线座组件	Double line pressing seat assembly	1	Set
7	16427001000010	端子板 5 位(600V 4mm2)AB	Terminal board	1	PC
8	16422005000009	变压器 TDB-14-B2B	Transformer	1	PC
9	11330010000090	风 机 电 容 2.5μF/450VAC/70/2000h/P2	Capacitor 2.5μF/450V a.c	1	PC
10	16422001000092	控制板 DCZ-SN3F-SYE2 (R8C)	PCB board	1	PC
11,33,34	16430001000196	电机 YSK-40W-4	Motor YSK-40W-4	1	PC
12	16420014000007	ALCe-H24B4/C5 左盖板	Left covers plate	1	PC
13	16421001000029	ALCe-H24B4/C5 左挂架	Left suspend plate	1	PC
14	16321006000005	ALCe-H24B4/C5 左侧板组件	Left side plate assembly	1	Set
15	16428001000017	ALCe-H24B4/C5 左泡沫	Left foam	1	PC
16	16421018000004	ALCe-H18A4/C5 背板	Back plate assembly	1	Set
17	16324001000093	蒸发器总成	Evaporator assembly	1	Set
40	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	EXV body CAM-BD18FKS-1	1	PC
18	16420005000005	ALCe-H18A4/C5 导风门	Guide throttle	1	PC
19	16420014000016	ALCe-H18A4/C5 顶盖板	Top covers plate	1	PC
20	16428001000023	ALCe-H18A4/C5 顶泡沫	Top foam	1	PC
21	16420006000007	ALCe-H18A4/C5 导风架	Guide wind frame	1	PC
22	16430001000018	步进电机 35BYJ46-QC120	Step motor 35BYJ46-QC120	1	PC
23	16430001000022	步进电机 35BYJ46-QC50	Step motor 35BYJ46-QC50	1	PC
24	16420008000003	ALCe-H24B4/C5 垂直叶片连杆 A	Vertical blade connecting rod A	1	PC
25	16420007000008	ALCe-H24B4/C5 垂直叶片	Vertical blade	9	PCS
26	16428001000018	ALCe-H24B4/C5 右泡沫	Right foam	1	PC
27	16321006000006	ALCe-H24B4/C5 右侧板组件	Right side plate assembly	1	Set
28	16421001000030	ALCe-H24B4/C5 右挂架	Right suspend plate	1	PC
29	16420014000008	ALCe-H24B4/C5 右盖板	Right covers plate	1	PC
30	16321006000008	ALCe-H18A4/C5 集水盘组件	Draining tray assembly	1	Set
31	16432019000004	塑料排水软管	Drainage insulation tube	1	PC
32	16421002000190	ALCe-H18A4/C5 电机固定板	Motor fixed plate	1	PC
35	16444001000013	风轮 φ 145×190×φ 12	Wind wheel	2	PCS
36	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	Top plastics	2	PCS
	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	Under plastics	2	PCS
37	11222023000333	显示灯板 SX-DISP(ZDJ)-02-SYE1	Display board	1	PC
38	16420017000002	ALCe-H24B4/C5 显示盒	Display board cover	1	PC
39	16420013000019	ALCe-H18A4/C5 面板	Front panel	1	PC

24000 TO 34000



24000/28000

N0.	BOM Number	Chinese name	Part Name	Quantity	Unit
1	16420012000002	ALCe-H24B4/C5 滤网	Filter net	2	PCS
2	16420010000002	ALCe-H24B4/C5 格栅	Grille	2	PCS
3	16420012000003	ALCe-H24B4/C5 中滤网	Middle filter net	1	PC
4	16420010000003	ALCe-H24B4/C5 中格栅	Middle grille	1	PC
5	16420015000002	ALCe-H24B4/C5 左装饰板	Left decorative plate	1	PC
6	16421038000009	ALCe-H24B4/C5 电控盒	Electrical assembly	1	PC
7	16421005000205	ALCe-H24B4/C5 电控盒盖	Electrical control box	1	PC
8	11220544000008	R51L/C(5)双联压线座组件	Double line pressing seat assembly	1	Set

GREEN GRV Ceiling&floor Type

9	16427001000010	端子板 5 位 (600V 4mm ²) AB	Terminal board	1	PC
10	16422005000009	变压器 TDB-14-B2B	Transformer	1	PC
11	11330010000093	风机电容 4.0μF/450VAC/70/2000h/P2	Capacitor 4μF/450V a.c	1	PC
12	16422001000092	控制板 DCZ-SN3F-SYE2 (R8C)	PCB board	1	PC
13	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	Top plastics	3	PCS
	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	Under plastics	3	PCS
14	16444001000025	风轮 φ 145×190×φ 15(白色)	Wind wheel	3	PCS
15	16420014000007	ALCe-H24B4/C5 左盖板	Left covers plate	1	PC
16	16421001000029	ALCe-H24B4/C5 左挂架	Left suspend plate	1	PC
17	16321006000005	ALCe-H24B4/C5 左侧板组件	Left side plate assembly	1	Set
18	16428001000017	ALCe-H24B4/C5 左泡沫	Left foam	1	PC
19	16321006000003	ALCe-H24B4/C5 背板组件	Back plate assembly	1	Set
20	16324001000094	蒸发器总成	Evaporator assembly	1	Set
47	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV body CAM-BD22FKS-1	1	PC
21	16420005000003	ALCe-H24B4/C5 导风门	Guide throttle	1	PC
22	16420014000009	ALCe-H24B4/C5 顶盖板	Top covers plate	1	PC
23	16428001000019	ALCe-H24B4/C5 顶泡沫	Top foam	1	PC
24	16420006000004	ALCe-H24B4/C5 导风架	Guide wind frame	1	PC
25	16430001000018	步进电机 35BYJ46-QC120	Step motor 35BYJ46-QC120	1	PC
26	16430001000022	步进电机 35BYJ46-QC50	(ROHS)Step motor 35BYJ46-QC50	1	PC
27	16420008000003	ALCe-H24B4/C5 垂直叶片连杆 A	Vertical blade connecting rod A	1	PC
	16420008000004	ALCe-H24B4/C5 垂直叶片连杆 B	Vertical blade connecting rod B	1	PC
28	16420007000008	ALCe-H24B4/C5 垂直叶片	Vertical blade	15	PCS
29	16428001000018	ALCe-H24B4/C5 右泡沫	Right foam	1	PC
30	16321006000006	ALCe-H24B4/C5 右侧板组件	Right side plate assembly	1	Set
31	16421001000030	ALCe-H24B4/C5 右挂架	Right suspend plate	1	PC
32	16420014000008	ALCe-H24B4/C5 右盖板	Right covers plate	1	PC
33	16321006000002	ALCe-H24B4/C5 集水盘组件	Draining tray assembly	1	Set
34	16432019000004	塑料排水软管	Drainage insulation tube	1	PC
35	16421002000185	ALCe-H24B4/C5 电机固定板	Motor fixed plate	1	PC
36,37,46	16430001000019	电机 YSK-70W-4	Motor YSK-70W-4	1	PC
38	16444007000001	联轴器 15	Coupling	1	PC
39	16444007000003	加长轴 15×565	Lengthening shaft	1	PC
40	16421002000011	ALCe-H24B4/C5 轴承固定座	Bearing permanent seat	1	PC
41	16421002000219	GR-50D/DC2 橡胶轴承压板	Rubber bearing holder	1	PC
42	16432016000033	GR-50D/DC2 橡胶轴承	Rubber bearing	1	PC
43	11222023000333	显示灯板 SX-DISP(ZDJ)-02-SYE1	Display board	1	PC
44	16420017000002	ALCe-H24B4/C5 显示盒	Display board cover	1	PC
45	16420013000016	ALCe-H24B4/C5 面板	Panel	1	PC


30000/34000

NO.	BOM Number	Chinese name	Part Name	Quantity	Unit
1	16420012000002	ALCe-H24B4/C5 滤网	Filter net	2	PCS
2	16420010000002	ALCe-H24B4/C5 格栅	Grille	2	PCS
3	16420012000003	ALCe-H24B4/C5 中滤网	Middle filter net	1	PC
4	16420010000003	ALCe-H24B4/C5 中格栅	Middle grille	1	PC
5	16420015000002	ALCe-H24B4/C5 左装饰板	Left decorative plate	1	PC
6	16421038000009	ALCe-H24B4/C5 电控盒	Electrical assembly	1	PC
7	16421005000205	ALCe-H24B4/C5 电控盒盖	Electrical control box	1	PC
8	11220544000008	R51L/C(5)双联压线座组件	Double line pressing seat assembly	1	Set
9	16427001000010	端子板 5位(600V 4mm ²)AB	Terminal board	1	PC
10	16422005000009	变压器 TDB-14-B2B	Transformer	1	PC
11	11330010000093	风机电容 4.0μF/450VAC/70/2000h/P2	Capacitor 4μF/450V a.c	1	PC
12	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	PCB board	1	PC
13	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	Top plastics	3	PCS
	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	Under plastics	3	PCS
14	16444001000025	风轮 φ145×190×φ15(白色)	Wind wheel	3	PCS
15	16420014000007	ALCe-H24B4/C5 左盖板	Left covers plate	1	PC
16	16421001000029	ALCe-H24B4/C5 左挂架	Left suspend plate	1	PC
17	16321006000005	ALCe-H24B4/C5 左侧板组件	Left side plate assembly	1	Set
18	16428001000017	ALCe-H24B4/C5 左泡沫	Left foam	1	PC
19	16321006000003	ALCe-H24B4/C5 背板组件	Back plate assembly	1	Set
20	16324001000095	DLR-90D/C5-A 蒸发器总成	Evaporator assembly	1	Set
47	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV body CAM-BD22FKS-1	1	PC
21	16420005000003	ALCe-H24B4/C5 导风门	Guide throttle	1	PC
22	16420014000009	ALCe-H24B4/C5 顶盖板	Top covers plate	1	PC
23	16428001000019	ALCe-H24B4/C5 顶泡沫	Top foam	1	PC
24	16420006000004	ALCe-H24B4/C5 导风架	Guide wind frame	1	PC
25	16430001000018	步进电机 35BYJ46-QC120	Step motor 35BYJ46-QC120	1	PC
26	16430001000022	步进电机 35BYJ46-QC50	(ROHS)Step motor 35BYJ46-QC50	1	PC
27	16420008000003	ALCe-H24B4/C5 垂直叶片连杆 A	Vertical blade connecting rod A	1	PC
	16420008000004	ALCe-H24B4/C5 垂直叶片连杆 B	Vertical blade connecting rod B	1	PC
28	16420007000008	ALCe-H24B4/C5 垂直叶片	Vertical blade	15	PCS
29	16428001000018	ALCe-H24B4/C5 右泡沫	Right foam	1	PC
30	16321006000006	ALCe-H24B4/C5 右侧板组件	Right side plate assembly	1	Set
31	16421001000030	ALCe-H24B4/C5 右挂架	Right suspend plate	1	PC
32	16420014000008	ALCe-H24B4/C5 右盖板	Right covers plate	1	PC
33	16321006000002	ALCe-H24B4/C5 集水盘组件	Draining tray assembly	1	Set
34	16432019000004	塑料排水软管	Drainage insulation tube	1	PC
35	16421002000185	ALCe-H24B4/C5 电机固定板	Motor fixed plate	1	PC
36,37,46	16430001000019	电机 YSK-70W-4	Motor YSK-70W-4	1	PC

GREEN GRV Ceiling&floor Type

38	16444007000001	联轴器 15	Coupling	1	PC
39	16444007000003	加长轴 15×565	Lengthening shaft	1	PC
40	16421002000011	ALCe-H24B4/C5 轴承固定座	Bearing permanent seat	1	PC
41	164210020000219	GR-50D/DC2 橡胶轴承压板	Rubber bearing holder	1	PC
42	16432016000033	GR-50D/DC2 橡胶轴承	Rubber bearing	1	PC
43	11222023000333	显示灯板 SX-DISP(ZDJ)-02-SYE1	Display board	1	PC
44	16420017000002	ALCe-H24B4/C5 显示盒	Display board cover	1	PC
45	16420013000016	ALCe-H24B4/C5 面板	Panel	1	PC

38000/42000/48000



38000/42000/48000

NO.	BOM Number	Chinese name	Part Name	Quantity	Unit
1	16420012000002	ALCe-H24B4/C5 滤网	Filter net	2	PCS
2	16420010000002	ALCe-H24B4/C5 格栅	Grille	2	PCS
3	16420012000003	ALCe-H24B4/C5 中滤网	Middle filter net	2	PCS
4	16420010000003	ALCe-H24B4/C5 中格栅	Middle grille	2	PCS
5	16420015000002	ALCe-H24B4/C5 左装饰板	Left decorative plate	1	PC
6	16421038000009	ALCe-H24B4/C5 电控盒	Electrical assembly	1	PC
7	16421005000205	ALCe-H24B4/C5 电控盒盖	Electrical control box	1	PC
8	11220544000008	R51L/C(5)双联压线座组件	Double line pressing seat assembly	1	Set
9	16427001000010	端子板 5 位(600V 4mm ²)AB	Terminal board	1	PC
10	16422005000009	变压器 TDB-14-B2B	Transformer	1	PC
11	11330010000095	风 机 电 容 5.0μF/450VAC/70/2000h/P2	Capacitor 5μF/450V a.c	1	PC

GREEN GRV Ceiling&floor Type

12	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	PCB board	1	PC
13	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	Top plastics	4	PCS
	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	Under plastics	4	PCS
14	16444001000025	风轮 $\phi 145 \times 190 \times \phi 15$ (白色)	Wind wheel	4	PCS
15	16420014000007	ALCe-H24B4/C5 左盖板	Left covers plate	1	PC
16	16421001000029	ALCe-H24B4/C5 左挂架	Left suspend plate	1	PC
17	16321006000005	ALCe-H24B4/C5 左侧板组件	Left side plate assembly	1	Set
18	16428001000017	ALCe-H24B4/C5 左泡沫	Left foam	1	PC
19	16321006000020	ALCe-H42A5/C5 背板组件	Back plate assembly	1	Set
20	16324001000112	DLR-112D/C5-A1 蒸发器总成	Evaporator assembly	1	Set
47	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	EXV body CAM-BD24FKS-1	1	PC
21	16420005000004	ALCe-H42A5/C5 导风门	Guide throttle	1	PC
22	16420014000015	ALCe-H42A5/C5 顶盖板	Top covers plate	1	PC
23	16428001000022	ALCe-H42A5/C5 顶泡沫	Top foam	1	PC
24	16420006000006	ALCe-H42A5/C5 导风架	Guide wind frame	1	PC
25	16430001000018	步进电机 35BYJ46-QC120	Step motor 35BYJ46-QC120	1	PC
26	16430001000022	步进电机 35BYJ46-QC50	Step motor 35BYJ46-QC50	1	PC
27	16420008000003	ALCe-H24B4/C5 垂直叶片连杆 A	Vertical blade connecting rod A	1	PC
	16420008000005	ALCe-H42A5/C5 垂直叶片连杆	Vertical blade connecting rod B	1	PC
28	16420007000008	ALCe-H24B4/C5 垂直叶片	Vertical blade	21	PCS
29	16428001000018	ALCe-H24B4/C5 右泡沫	Right foam	1	PC
30	16321006000006	ALCe-H24B4/C5 右侧板组件	Right side plate assembly	1	Set
31	16421001000030	ALCe-H24B4/C5 右挂架	Right suspend plate	1	PC
32	16420014000008	ALCe-H24B4/C5 右盖板	Right covers plate	1	PC
33	16321006000007	ALCe-H42A5/C5 集水盘组件	Draining tray assembly	1	Set
34	16432019000004	塑料排水软管	Drainage insulation tube	1	PC
35	16421002000187	ALCe-H42A5/C5 电机固定板	Motor fixed plate	1	PC
36,37,46	16430001000026	电机 YSK-105W-4	Motor YSK-70W-4	1	PC
38	16444007000001	联轴器 15	Coupling	2	PCS
39	16444007000003	加长轴 15x565	Lengthening shaft	2	PCS
40	16421002000011	ALCe-H24B4/C5 轴承固定座	Bearing permanent seat	1	PC
41	16421002000219	GR-50D/DC2 橡胶轴承压板	Rubber bearing holder	2	PCS
42	16432016000033	GR-50D/DC2 橡胶轴承	Rubber bearing	2	PCS
43	11222023000333	显示灯板 SX-DISP(ZDJ)-02-SYE1	Display board	1	PC
44	16420017000002	ALCe-H24B4/C5 显示盒	Display board cover	1	PC
45	16420013000017	ALCe-H42A5/C5 面板	Panel	1	PC
47	16421002000189	ALCe-H42A5/C5 轴承固定座	Display board cover	1	PC

11.Spare parts list

16000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000054	R 风机电容 2.5 μ F/450VAC/70/2000h	1
Fan motor	16430001000196	电机 YSK-40W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	2
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	2
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000013	风轮 145 \times 190 \times 12	2
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Filter	16442001000013	过滤器 9.52 \times 9.52-70	1
Filter	16442001000010	过滤器 8 \times 9.52-66(R410a)	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

18000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000054	R 风机电容 2.5 μ F/450VAC/70/2000h	1
Fan motor	16430001000196	电机 YSK-40W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	2
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	2
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1

GREEN GRV Ceiling&floor Type

temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
Fan wheel	16444001000013	风轮 145×190× 12	2
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Filter	16442001000013	过滤器 9.52× 9.52-70	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

24000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5 位(600V 4mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000019	电机 YSK-70W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	3
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	3
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000073	温度传感器 20K3950 XH2 蓝 1.5m 铜壳 2	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000075	温度传感器 20K3950 XH2 绿 1.5m 铜壳 4	1
Fan wheel	16444001000004	风轮 145×190× 15	3
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Filter	16442001000013	过滤器 9.52× 9.52-70	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000003	加长轴 15×565	1
Shaft coupling	16444007000001	联轴器 15	1

28000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000019	电机 YSK-70W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	3
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	3
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000073	温度传感器 20K3950 XH2 蓝 1.5m 铜壳 2	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000075	温度传感器 20K3950 XH2 绿 1.5m 铜壳 4	1
Fan wheel	16444001000004	风轮 145×190× 15	3
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Middle Air Filter	16420012000003	ALCe-H24B4/C5 中滤网	1
Filter	16442001000013	过滤器 9.52× 9.52-70	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000003	加长轴 15×565	1
Shaft coupling	16444007000001	联轴器 15	1

30000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000019	电机 YSK-70W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	3
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	3

GREEN GRV Ceiling&floor Type

temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000073	温度传感器 20K3950 XH2 蓝 1.5m 铜壳 2	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000075	温度传感器 20K3950 XH2 绿 1.5m 铜壳 4	1
Fan wheel	16444001000004	风轮 145×190× 15	3
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Middle Air Filter	16420012000003	ALCe-H24B4/C5 中滤网	1
Filter	16442001000013	过滤器 9.52× 9.52-70	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000003	加长轴 15×565	1
Shaft coupling	16444007000001	联轴器 15	1

34000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5 位(600V 4mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	16430001000019	电机 YSK-70W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	3
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	3
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000073	温度传感器 20K3950 XH2 蓝 1.5m 铜壳 2	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000075	温度传感器 20K3950 XH2 绿 1.5m 铜壳 4	1
Fan wheel	16444001000004	风轮 145×190× 15	3
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Middle Air Filter	16420012000003	ALCe-H24B4/C5 中滤网	1
Filter	16442001000013	过滤器 9.52× 9.52-70	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	1

GREEN GRV Ceiling&floor Type

Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000003	加长轴 15x565	1
Shaft coupling	16444007000001	联轴器 15	1

38000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000058	R 风机电容 5.0μF/450VAC/70/2000h	1
Fan motor	16430001000026	电机 YSK-105W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	3
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	3
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000073	温度传感器 20K3950 XH2 蓝 1.5m 铜壳 2	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000075	温度传感器 20K3950 XH2 绿 1.5m 铜壳 4	1
Fan wheel	16444001000004	风轮 145x190x 15	3
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Middle Air Filter	16420012000003	ALCe-H24B4/C5 中滤网	2
Filter	16442001000013	过滤器 9.52x 9.52-70	1
Filter	16442001000010	过滤器 8x 9.52-66(R410a)	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000003	加长轴 15x565	1
Shaft coupling	16444007000001	联轴器 15	1

42000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm ²)AB	1
Capacitor	11330010000058	R 风机电容 5.0μF/450VAC/70/2000h	1
Fan motor	16430001000026	电机 YSK-105W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1
Upper shell	16444002000014	上涡壳 ALCe-H24B4/C5(白色)	4
Lower shell	16444002000015	下涡壳 ALCe-H24B4/C5(白色)	4
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000073	温度传感器 20K3950 XH2 蓝 1.5m 铜壳 2	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000075	温度传感器 20K3950 XH2 绿 1.5m 铜壳 4	1
Fan wheel	16444001000004	风轮 145×190× 15	4
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Middle Air Filter	16420012000003	ALCe-H24B4/C5 中滤网	2
Filter	16442001000013	过滤器 9.52× 9.52-70	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000003	加长轴 15×565	1
Shaft coupling	16444007000001	联轴器 15	1

48000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm ²)AB	1
Capacitor	11330010000058	R 风机电容 5.0μF/450VAC/70/2000h	1
Fan motor	16430001000026	电机 YSK-105W-4	1
Step motor	16430001000022	(ROHS)步进电机 35BYJ46-QC50	1
Step motor	16430001000018	步进电机 35BYJ46-QC120	1

GREEN GRV Ceiling&floor Type

Upper shell	16444002000014	上涡壳 ALCe-H24B2/C5(白色)	4
Lower shell	16444002000015	下涡壳 ALCe-H24B2/C5(白色)	4
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000073	温度传感器 20K3950 XH2 蓝 1.5m 铜壳 2	1
temperature Sensor	16430007000074	温度传感器 20K3950 XH2 黄 1.5m 铜壳 3	1
temperature Sensor	16430007000075	温度传感器 20K3950 XH2 绿 1.5m 铜壳 4	1
Fan wheel	16444001000013	风轮 145x190x 12	4
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Air Filter	16420012000002	ALCe-H24B4/C5 滤网	2
Middle Air Filter	16420012000003	ALCe-H24B4/C5 中滤网	2
Filter	16442001000013	过滤器 $\phi 9.52 \times \phi 9.52-70$	1
Filter	16442001000010	过滤器 $\phi 8 \times \phi 9.52-66(R410a)$	1
Display board	11222023000333	R 显示灯板 SX-DISP(ZDJ)-02-SYE1	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000003	加长轴 15x565	1
Shaft coupling	16444007000001	联轴器 15	1

Wall-mounted Type

1. Features	201
2. Specifications	203
3. Dimensions	206
4. Piping Diagrams	207
5. Wiring Diagrams	208
6. Electrical Characteristics.....	211
7. Capacity Tables	212
8. Sound levels	214
9. Installation	215
10. Explode view	217
11. Spare parts list	223

1.Features



Anti-cold-air (Heat pump only)

When starting the heating operation, the fan speed is regulated automatically from the lowest grade to the preset level, according to the temperature rising of evaporator. The function can prevent cold air blowing out at the beginning of the operation, which avoids the discomfort to the user.



Self-diagnosis function

Monitoring some abnormal operations or parts failures, which happens microcomputer of the air conditioner which switch off and protect the system automatically. Meanwhile, the error or protection code will be displayed on the indoor unit.



24-hour timer

User can set on the timer to turn on or off the air conditioner any time within 24 hours.



Force cooling

This function is convenient when user can't find the remote controller.



Low ambient cooling

The air conditioner with a special built-in low ambient cooling component can be used in temperature as low as -15C for cooling operation.



Auto restart

If the machine is suddenly shut down during operation, the unit will record the operating



Sleep Mode


User can select mode after pressing time-off button, this function will adjust temperature automatically, which makes a comfortable sleep environment and save energy.



Intelligent defrosting

Normal defrost function can only be operated in certain time, but GREEN commercial air conditioner's intelligent defrost can start automatically according to the surrounding condition.

- ◇ EXV inside type have two kind panels choose :
- ◇ Easy and flexible installation, which can satisfy the different space demands
- ◇ Low noise, creates quite and comfortable environment.
- ◇ Adopt cross fan and optimization wind path design, supply air is strong and quiet.



2.Specifications

Model Model	Indoor		IWGRV07P1	IWGRV09P1	IWGRV12P1
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	2.2	2.8	3.6
	Heating	kW	2.5	3.0	4.3
Fan Motor	Model		YYK19-4	YYK19-4	YYK19-4
	Brand		Dongfang Motor	Dongfang Motor	Dongfang Motor
	Output Power	W	19	19	19
	Capacitor	uF	1.5	1.5	1.5
	Speed (Hi/Mi/Lo)	r/min	1130/900/850	1130/900/850	1130/900/850
Coil	Number Of Row		2	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.5	1.5	1.5
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	639x266x25.4	639x266x25.4	639x266x25.4
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	620/496/434	620/496/434	620/496/434
	Noise Level(Hi/Mi/Lo)	dB(A)	38/35/31	38/35/31	38/35/31
	External Static Pressure	Pa	0	0	0
	Net Dimension (WxDxH)	mm	880x286x203	880x286x203	880x286x203
	Packing Dimension (WxDxH)	mm	950x350x270	950x350x270	950x350x270
	Net Weight	Kg	12	12	12
	Gross Weight	Kg	14	14	14
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	6.35
	Gas Side	mm	9.52	9.52	9.52
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	10~20	10~25	15~30
Stuffing Quantity	20/40/40H	Unit	320/656/732	320/656/732	320/656/732

Notes:

1. Cooling Capacity:Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m,level difference:

GREEN GRV Wall-mounted Type

0 m.

2. Heating Capacity:Indoor temp.20℃DB, outdoor temp.7℃DB,6℃WB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value, measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

Model	Indoor		IWGRV16P1	IWGRV18P1	IWGRV24P1
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	4.5	5.6	7.1
	Heating	kW	5.0	6.0	8.0
Fan Motor	Model		YYS20-4-5A	YYS20-4-5A	YYS60-4
	Brand		Dongfang Motor	Dongfang Motor	Dongfang Motor
	Output Power	W	20	20	60
	Capacitor	uF	2	2	2
	Speed (Hi/Mi/Lo)	r/min	1150/1050/950	1150/1050/950	1350/1250/1150
Coil	Number Of Row		2	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.5	1.5	1.5
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	800x267x25.4	800x267x25.4	1130.5x411x25.4
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	950/760/665	950/760/665	1100/880/770
	Noise Level(Hi/Mi/Lo)	dB(A)	41/38/34	41/38/34	45/42/37
	External Static Pressure	Pa	0	0	0
	Net Dimension (WxDxH)	mm	1095x312x215	1095x312x215	1310x322x235
	Packing Dimension (WxDxH)	mm	1175x375x275	1175x375x275	1420x440x380
	Net Weight	Kg	14	14	20
	Gross Weight	Kg	17	17	23
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	9.52
	Gas Side	mm	12.7	12.7	15.88
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		℃	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		℃	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24


GREEN GRV Wall-mounted Type

Application Area		m ²	20~35	25~45	30~50
Stuffing Quantity	20/40/40H	Unit	240/496/558	240/496/558	240/496/558

Notes:

1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference: 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value, measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

3.Dimensions




Physical Dimension		7000	9000	12000
Length	mm	880	880	880
Height	mm	286	286	286
Width	mm	203	203	203


Physical Dimension		16000	18000	24000
Length	mm	1095	1095	1310
Height	mm	312	312	322
Width	mm	215	215	235

4.Piping Diagrams

EXV Built-in type



EXV separate type




Refrigerant pipe connection port diameters


Model	(mm)	
	Gas	Liquid
7000 TO 12000	9.52	6.35
16000/18000	12.7	6.35
24000	15.88	6.35

5.Wiring Diagrams


7000/9000/12000



16000/18000



24000



6. Electrical Characteristics

Model	Indoor Unit				Power Supply		IFM	
	Hz	Voltage	Min.	Max.	MCA	MFA	KW	FLA
7000	50	220-240V	198	254	0.25	10	0.019	0.20
9000	50	220-240V	198	254	0.25	10	0.019	0.20
12000	50	220-240V	198	254	0.25	10	0.019	0.20
16000	50	220-240V	198	254	0.28	10	0.02	0.22
18000	50	220-240V	198	254	0.28	16	0.02	0.22
24000	50	220-240V	198	254	0.58	16	0.06	0.46

Symbols:

MCA: Min. Circuit Amps (A)

MFA: Max. Circuit Breaker Amps

KW: Fan Motor Rated Output(kW)

FLA: Full Load Amps (A)

IFM: Indoor Fan Motor

Note:

1. Min. and Max. Voltage: Units are suitable for use on electrical system where voltage supplied to unit terminals is not below or above listed range limits.
2. Maximum allowable voltage unbalance between phases is 2%.
3. $MCA = 1.25 \times FLA$
4. Select wire size based on the MCA.

7.Capacity Tables

Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient


Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature [°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.10	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1.0	1.06	1.13
	Power	0.96	0.97	1.0	1.01	1.03
40	Cooling capacity	0.96	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.90	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.80	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32

Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb [°C]	capacity/power correction coefficient	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.70
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1.0	0.96
	Power	0.94	1.0	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07
	Power	1.05	1.11	1.17


15-24	Heating capacity	0.85 – 1.05 of nominal
	Power	0.80 – 1.20 of nominal

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube



Positive side of high head means installation height of outdoor unit should be higher than indoor unit;
 negative side of high head means installation height of outdoor unit should be lower than indoor unit;
 (change ratio of basic capacity)


8.Sound levels




Model (EXV Built-in)	Noise level under three speeds of fan (dB(A))		
	H	M	L
7000	37	34	29
9000	37	34	29
12000	38	35	31
16000	41	38	34
18000	41	38	34
24000	45	42	37

9. Installation

9.1 Spacing Reserved Between the Surrounding of Indoor Unit and Barrier




9.2 Hoisting of Indoor Unit



- ◇ The wall for installing indoor unit should be firm to prevent vibration. Horizontally install hanging plate on the wall with four cruciform *screws* to keep laterally horizontal and longitudinally vertical.
- ◇ Drill a $\Phi 70$ Auxiliary pipeline hole on lower left side or lower right side of hanging plate. The position of hole should slightly incline downwards.
- ◇ Hang indoor unit on hanging plate and move the unit to left or right to ensure hanging hook is correctly positioned on the hanging plate.

9.3 Installation of Sterilization Net


- ◇ Uplift panel of indoor unit, pull out the bulge in the middle of air filter downwards after uplifting;
- ◇ Completely snap sterilization net inside accessory bag into sterilization mounting support on air filter;
- ◇ Put back air filter in the original way, close the panel of indoor unit and tightly clamp;
- ◇ Push the lower left side and lower right side of indoor unit towards hanging plate until hanging hook inserts into groove and sends click sound.




9.4 Drainage Checking

In case of maintenance, remove grille from casing of the unit according to the following procedures:

- ◇ As shown in right diagram, remove two screw caps on both sides of the front grille and then screw down two fixing screws.
- ◇ Pull the lower end of grille cover towards oneself to remove it.
- ◇ Reinstall grille cover, then install the grille cover to proper position according to the reverse sequence of the above.
- ◇ Pour a glass of water into plastic drainage groove;
- ◇ Confirm if the water flows through the drainage outlet of indoor unit.




Pull the lower end of front grille towards oneself to remove the front grille



10. Explode view

7000 TO 12000




7000 TO 12000

NO	GREEN code	Components description	Components description	Quantity	Unit
1	11220502000935	ASW-H12A4/SA1 面板组件	Panel assembly	1	Set
2	11220508000008	R25G/SA 过滤网组件(三折黑色)	Air filter assembly (triple fold, black)	2	Sets
3	1500R000251A	ASW-H12A4/SAR2 中框组件(二折)	Middle of frame assembly	1	Set
4	11220503000032	R32G/SA(2)导风架组件	Wind guide frame assembly	1	Set
5	16324001000054	DLR-36G/DCZDSA 蒸发器组件(内置)	Evaporator assembly (built-in)	1	Set
6	11320015000045	R32G/SA(2)蒸发器左支架	Evaporator left bracket	1	PC
7	11320105000002	R32G/SA(2)风叶轴承座	Fan bearing	1	PC
8	11220513000033	R32G/H 室内风叶(贯流)(ROHS)	Cross-flow fan	1	Set
9	11220500000045	R32G/SA(2)底座组件	Bottom assembly	1	Set
10	11221500000013	R32G/SA 挂板组件	Cladding assembly	1	Set
11	11320084000010	R25G/H1 管路压攀 A(ROHS)	Pipe cover (ROHS)	1	PC
12	11230003000056	室内电机(塑封)(YYK19-4)(出口)	Fan motor YYK19-4	1	PC
13	11320052000011	R32G/SA 电机压盖	Fan motor cover	1	PC
14	16421001000378	蒸发器侧板(内置)	Evaporator sideboard (built-in)	1	PC
15	16322001000025	电控总成	Electrical assembly	1	Set
15.1	11320057000037	R32G/SA 电控盒	Electrical box	1	PC
15.2	11320087000013	R35W/E6 电源连接线压板(ROHS)	Power connection terminal cover	1	PC

GREEN GRV Wall-mounted Type

15.3	16422001000076	控制板 DCZDSA-28G-SN1F-SYE1	Electrical PCB	1	PC
15.4	16430007000058	传感器 15K3950 XH2(白) (塑封)1	Sensor 15K3950 XH2 (White 0.5m)	1	PC
15.5	16430007000059	传感器 20K3950 XH2(蓝) (铜)2	Sensor 20K3950 XH2 (Blue 0.5m)	1	PC
15.6	16430007000060	传感器 20K3950 XH2(黄) (铜)3	Sensor 20K3950 XH2 (Yellow 0.5m)	1	PC
15.7	16430007000061	传感器 20K3950 XH2(绿) (铜)4	Sensor 20K3950 XH2 (Green 0.5m)	1	PC
15.8	16427001000027	端子板 5位(600V 4MM2)挂机	5 terminal board (600V 4MM2)	1	PC
15.9	16430019000281	(ROHS)连接线 6芯 0.4m I	Connect wire 6 core 0.4m	1	PC
15.1	16430019000125	接地线 1.5×300	Earth connection wire 1.5mm×300mm	1	PC
15.11	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	TransformerTDB-14-B2B(PTC)	1	PC
15.12	16422008000025	通讯线 2芯 0.3m(XH3Y-U)	Signal wire (Two core 0.3mXH3Y-U)	1	PC
16	16325001000078	蒸发器出气管组件(内置)	Evaporator outlet pipe assembly (built-in)	1	Set
16.1	16442007000011	三通接头 9.52/7×7-40	Tee union 9.52/7×7-40	1	PC
17	16325001000101	蒸发器进液管组件	Evaporator inlet pipe assembly (built-in)	1	Set
17.1	16441015000002	EXV 线圈 CAM-MD12FKS-5 L=1500	EXV coil (CAM-MD12FKS-5 L=1500)	1	PC
17.2	16441014000002	电子膨胀阀阀体 CAM-BD15FKS-2	EXV (CAM-BD15FKS-2)	1	PC
17.3	16442001000005	过滤器 DLR-25F/BPZ 冻结	Filter DLR-25F/BPZ	1	PC
18	11230002000019	R 步进电机 24BYJ48*150*EH	Step motor 24BYJ48*150*EH	1	PC
19	11320020000005	R32G/H 保温排水软管	Insulation drain hose	1	Set
20	18430000503	R25G/H1 导风叶片 A(PP/黑色)	Wind guide blade (Black)	2	PCS
21	11220534000019	R32G/SA(2)导风门组件	Wind guide assembly	1	Set

16000/18000




16000/18000

NO	GREEN code	Components description	Components description	Quantity	Unit
1	11220502000937	ASW-H18B4/SA1 面板组件	Panel assembly	1	Set
2	1843R000178	ASW-H18B4/ET 过滤网(ROHS)	Air filter assembly (ROHS)	2	PCS
3	11220501000106	ASW-H18B4/ET 中框组件(ROHS)	Middle of frame assembly	1	Set
4	11220503000045	导风架组件(ROHS)	Wind guide frame assembly	1	Set
5	11320015000055	ASW-H24B4/EN 蒸发器左支架	Evaporator left bracket	1	PC
6	16324001000044	A 蒸发器组件(内置)	Evaporator assembly (built-in)	1	Set
7	11220551000003	70G 贯流风叶轴承组合件	Cross-flow fan bearing assembly	1	PC
8	11220513000013	室内风叶组件(贯流)	Cross-flow fan (ROHS)	1	Set
9	11220500000065	R53G/ET 底座组件(新)	Bottom assembly	1	Set
10	11221500000020	ASW-H18B4/ET(RoHS)挂板组件	Cladding assembly	1	PC
11	11320087000012	管路压板(ROHS)	Pipe cover (ROHS)	1	PC
12	11230003000052	电机(YYS20-4-5A)ROHS	Fan motor (YYS20-4-5A) ROHS	1	PC
13	16322001000024	DLR-45G/DCZDSA 电控总成	Electrical assembly	1	Set
13.1	11320057000006	ASW-H18B4/ET 电控盒(ROHS)	Electrical control box	1	PC
13.2	16422001000089	辅 PCB 板接线板 ROHS	Assistance connection board (ROHS)	1	PC
13.3	16422001000075	控制板 DCZDSA-45G-SN3F-SYE1	Electrical PCB	1	PC

GREEN GRV Wall-mounted Type

13.4	16430007000058	传感器 15K3950 XH2(白)(塑封)1	Sensor 15K3950 XH2(White 0.5m)	1	PC
13.5	16430007000059	传感器 20K3950 XH2(蓝)(铜)2	Sensor 20K3950 XH2(Blue 0.5m)	1	PC
13.6	16430007000060	传感器 20K3950 XH2(黄)(铜)3	Sensor 20K3950 XH2(Yellow 0.5m)	1	PC
13.7	16430007000061	传感器 20K3950 XH2(绿)(铜)4	Sensor 20K3950 XH2(Green 0.5m)	1	PC
13.8	11320087000013	R35W/E6 电源连接线压板 (ROHS)	Power supply terminal protection board	1	PC
13.9	16430019000281	(ROHS)连接线 6 芯 0.4m I	Connect wire 6 core 0.4m	1	PC
13.1	16430019000125	接地线 1.5x300	Earth connection wire 1.5mmx300mm	1	PC
13.11	16427001000022	端子板 7 位(600V 4mm2) II	7 terminal board (600V 4MM2)	1	PC
13.12	16427018000003	压线板 (R)53E	Wire protection board	1	PC
13.13	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	TransformerTDB-14-B2B(PTC)	1	PC
13.14	16422008000025	通讯线 2 芯 0.3m(XH3Y-U)	Signal wire (Two core 0.3mXH3Y-U)	1	PC
14	16325001000064	蒸发器出气管组件(内置)	Evaporator outlet pipeassembly(built-in)	1	Set
14.1	11325011000093	ASW-H18B4/EN 出气集管(翻边孔)	Outlet collecting pipe (ROHS)	1	PC
15	16325001000079	蒸发器进液管组件_(内置)	Evaporator inlet pipe assembly(built-in)	1	Set
15.1	16441015000002	EXV 线圈 CAM-MD12FKS-5 L=1500	EXV coil(CAM-MD12FKS-5 L=1500)	1	PC
15.2	16441014000012	EXV 阀体 CAM-BD18FKS-1	EXV (CAM-BD15FKS-2)	1	PC
15.3	16442013000005	分路接头 9.52/4x3.5 四路删	Branch union	1	PC
15.4	16442001000016	过滤器 6x 6.35-70(R410A)	Filter 6x 6.35-70(R410A)	1	PC
16	16421001000377	蒸发器侧板(内置)	Evaporator sideboard (built-in)	1	PC
17	11320020000005	R32G/H 保温排水软管	Insulation drain hose	1	Set
18	11230002000017	R 步进电机 28BYJ48*280*EH	Step motor 28BYJ48*280*EH	1	PC
19	18320000178	ASW-H18B4/ET 导风门 A	Wind guide entrance board	2	PCS
20	1800R000018A	ASW-H18B4/ET 导风架(配分体叶片)	Wind guide frame	2	PCS

24000



24000

NO	GREEN code	Components description	Components description	Quantity	Unit
1	13220502000023	ASW-H30A4/SA-5 面板组件(未喷涂)	Panel assembly	1	Set
2	1843R000033	ASW-H30A4/SA-5 左过滤网(ROHS)	Left air filter(ROHS)	2	PCS
3	11220501000108	ASW-H30A4/SA-5 中框组件(ROHS)	Middle of frame assembly	1	PC
4	1832R000058	ASW-H30A4/SA-5 导风门 A (ROHS)	Wind guide entrance board	2	PCS
5	11230002000023	R 步进电机 24BYJ48*300*XH 双电机	Step motor 24BYJ48*300*XH	3	PCS
6	11220503000047	ASW-H30A4/SA-5 导风架组件(双电机)	Wind guide frame assembly	1	Set
7	11320015000080	蒸发器左支架 (HIPS)	Evaporator left bracket	1	PC
8	11224005000227	ASW-H30A4/SA-5 蒸发器组(ROHS)	Evaporator assembly (built-in)	1	Set
9	11220551000003	70G 贯流风叶轴承组合件	Cross-flow fan bearing assembly	1	PC
10	11220513000003	80G 贯流风叶组件(ROHS)	Cross-flow fan (ROHS)	1	Set
11	11220500000049	ASW-H30A4/SA-5 底座组件(ROHS)	Bottom assembly (ROHS)	1	Set
12	11221500000010	ASW-H30A4/SA-5 挂板组件(ROHS)	Cladding assembly (ROHS)	1	Set
13	11320062000016	ASW-H30A4/SA-5 电机固定(ROHS)	Fan motor foundation	1	PC
14	11230003000079	塑封电机 YYS60-4 220-240V/50Hz	Fan motor (YYS60-4)	1	PC
15	11320052000024	ASW-H30A4/SA-5 电机压盖(ROHS)	Fan motor cover board	1	PC
16	11320104000005	ASW-H30A4/SA-5 底座镶块(ROHS)	Fan motor foundation insert	1	PC

GREEN GRV Low Static Pressure Duct Type

			component		
17	16322001000036	DLR-71G/DCZSA+电控总成	Electrical assembly	1	Set
17.1	11221512000006	ASW-H30A4/SA-5 电控盒组件 (ROHS)	Electrical control box	1	Set
17.2	16422001000084	控制板 DCZD-71G-SN3F-SYE1	Electrical PCB	1	PC
17.3	16430007000058	传感器 15K3950 XH2(白)(塑封)1	Sensor 15K3950 XH2 (White 0.5m)	1	PC
17.4	16430007000059	传感器 20K3950 XH2(蓝)(铜)2	Sensor 20K3950 XH2 (Blue 0.5m)	1	PC
17.5	16430007000060	传感器 20K3950 XH2(黄)(铜)3	Sensor 20K3950 XH2 (Yellow 0.5m)	1	PC
17.6	16430007000061	传感器 20K3950 XH2(绿)(铜)4	Sensor 20K3950 XH2 (Green 0.5m)	1	PC
17.7	16430019000125	接地线 1.5×300 mm	Earth connection wire1.5*300mm	1	PC
17.8	16427001000027	端子板 5位(600V 4MM2)挂机	5 terminal board (600V 4MM2)	1	PC
17.9	16427018000003	压线板 (R)53E	Wire cover board	1	PC
17.1	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	TransformerTDB-14-B2B(PTC)	1	PC
17.1 1	16422008000026	(ROHS)通讯线 2芯0.35m(XH3Y-U)	Signal wire (Two core 0.35mXH3Y-U)	1	PC
17.1 2	11320129000001	PCB 板固定盒(ROHS)	PCB fix frame	1	PC
17.1 3	11320074000002	ASW-H30A4/SA-5 电控盒固定座 ROHS	Electrical box foundation ROHS	1	PC
17.1 4	11320012000001	ASW-H30A4/SA-5 遥控接收座 ROHS	Signal receiver foundation ROHS	1	PC
17.1 5	16427007000006	尼龙扎带 L100	Nylon cable ties L=100mm	1	PC
17.1 7	11320087000013	R35W/E6 电源连接线压板(ROHS)	Power wire protection board	1	PC
17.1 8	11320010000032	ASW-12B3/EV 压线板	Wire protection board	1	PC
18	16325001000081	DLR-71G/DCZSA+进液管组件(内置)	Evaporator inlet pipe assembly (built-in)	1	Set
18.1	16441015000002	EXV 线圈 CAM-MD12FKS-5 L=1500	EXV coil (CAM-MD12FKS-5 L=1500)	1	PC
18.2	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV (CAM-BD22FKS-1)	1	PC
18.3	16442013000036	分路接头 12/7×4 七路	Branch union	1	PC
18.4	16442001000013	过滤器 9.52×9.52-70	Filter 9.52×9.52-70	1	PC
19	16325001000080	DLR-71G/DCZSA+出气管组件	Evaporator outlet pipe assembly	1	Set
20	1843R000032	ASW-H30A4/SA-5 导风叶片(ROHS)	Wind guide fan (ROHS)	2	PCS

11. Spare parts list

7000

PCB board	16422001000081	控制板 DCZDSA-28G-SN1F-SYE2	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000027	端子板 5位(600V 4mm ²)挂机	1
Fan motor	11230003000056	室内电机(塑封)(YYK19-4)(出口)ROHS	1
Step motor	11230002000019	R 步进电机 24BYJ48*150*EH	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	11220513000033	R32G/H 室内风叶(贯流)(ROHS)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Filter	16442001000005	过滤器 6× 8-66	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

9000

PCB board	16422001000081	控制板 DCZDSA-28G-SN1F-SYE2	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000027	端子板 5位(600V 4mm ²)挂机	1
Fan motor	11230003000056	室内电机(塑封)(YYK19-4)(出口)ROHS	1
Step motor	11230002000019	R 步进电机 24BYJ48*150*EH	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	11220513000033	R32G/H 室内风叶(贯流)(ROHS)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Filter	16442001000005	过滤器 6× 8-66	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

12000

PCB board	16422001000081	控制板 DCZDSA-28G-SN1F-SYE2	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000027	端子板 5 位(600V 4mm ²)挂机	1
Fan motor	11230003000056	室内电机(塑封)(YYK19-4)(出口)ROHS	1
Step motor	11230002000019	R 步进电机 24BYJ48*150*EH	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	11220513000033	R32G/H 室内风叶(贯流)(ROHS)	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Filter	16442001000005	过滤器 6× 8-66	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

16000

PCB board	16422001000082	控制板 DCZDSA-45G-SN3F-SYE2	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	11330037000017	内机端子板 7 位黑白地 1245NL/插片(3*0+4*2)	1
Fan motor	11230003000052	电机 (YYS20-4-5A) ROHS	1
Step motor	11230002000017	R 步进电机 28BYJ48*220*EH-5 端子(白)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	11220513000013	R53G/ET 贯流风叶组件(ROHS) 102*850	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Filter	16442001000016	过滤器 6× 6.35-70(R410a)	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

18000

PCB board	16422001000082	控制板 DCZDSA-45G-SN3F-SYE2	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	11330037000017	内机端子板 7 位黑白地 1245NL/插片(3*0+4*2)	1
Fan motor	11230003000052	电机 (YYS20-4-5A) ROHS	1
Step motor	11230002000017	R 步进电机 28BYJ48*220*EH-5 端子(白)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	11220513000013	R53G/ET 贯流风叶组件(ROHS) 102*850	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Filter	16442001000016	过滤器 6x 6.35-70(R410a)	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

24000

PCB board	16422001000080	控制板 DCZDSA-71G-SN3F-SYE2	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000027	端子板 5 位(600V 4mm ²)挂机	1
Fan motor	11230003000079	塑封电机 YYS60-4 220-240V/50Hz	1
Step motor	11230002000023	R 步进电机 24BYJ48*300*XH*双电机	1
Step motor	11230002000033	R 步进电机 24BYJ48*1550*EH	1
Step motor	11230002000034	R 步进电机 24BYJ48*500*EH	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	11220513000003	R85G/SA 贯流风叶组件(ROHS) 107*1013.8	1
Remote controller	11222001000139	遥控器 YKR-K/001E(按键荧光, 背光源)	1
Filter	16442001000013	过滤器 9.52x 9.52-70	1
The body of Electronic expansion valve	11222018000115	R 接收板组件(H)30SA/QB-J	1
The coil of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
Display board	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

Slim Duct

1. Features


- **Compact unit body**

Duct body designed thin and compact. The EXV is fixed inside of the indoor unit, Compact unit body. Concealed installation, combined with indoor decoration perfectly



- **Air inlet from back standard and from bottom optional.**

The size of the plate from bottom is the same as the flange from back, which makes it convenient to change installation style due to different



- **Built-in infrared receiver wire controller and remote controller**

2. Specifications

Model			IDGRV07P1	IDGRV09P1	IDGRV12P1
Code			16104022000034	16104022000035	16104022000036
Power Supply		V~,Hz,P h	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	2.2	2.8	3.6
	Heating	kW	2.5	3.0	4.3
Fan motor	Model		YSK-20W-4(AG57)	YSK-20W-4(AG57)	YSK-25W-4(AG58)
	Brand		SINJUN	SINJUN	SINJUN
	Output Power	W	20	20	25
	Capacitor	uF	1.5	1.5	2.0
	Speed (Hi/Mi/Lo)	r/min	1060/790/610	11060/790/610	1060/890/800
Coil	Number Of Row		2	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Spacing	mm	1.4	1.4	1.4
	Fin Material		Hydrophilic	Hydrophilic	Hydrophilic
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	640*205*25.4	640*205*25.4	640*205*25.4
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	420/336/294	420/336/294	630/504/441
	Noise Level(Hi/Mi/Lo)	dB(A)	30/26/23	30/26/23	32/28/25
	External Static Pressure	Pa	10/30	10/30	10/30
	Unit Dimension (W*H*D)	mm	840x440x185	840x440x185	840x440x185
	Packing (W*H*D)	mm	1030x525x250	1030x525x250	1030x525x250
	Net Weight	Kg	17.5	17.5	18.5
	Gross Weight	Kg	21	21	22
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	6.35
	Gas Side	mm	9.52	9.52	12.7
	Drainage	mm	R1in(DN25)	R1in(DN25)	R1in(DN25)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	10~20	10~25	10~35
Qty'per 20'& 40'&40HQ(Only For Reference)		Set	168/344/387	168/344/387	168/344/387

Notes:

- Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference: 0 m.

GREEN GRV Low Static Pressure Duct Type

2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

Model			IDGRV16P1	IDGRV189P1	IDGRV24P1
Code			16104022000037	16104022000038	16104022000039
Power Supply		V~,Hz,P h	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	4.5	5.6	7.1
	Heating	kW	5.0	6.0	8.0
Fan motor	Model		YSK-40W-4(AG59)	YSK-40W-4(AG59)	YSK-60W-4(AG60)
	Brand		SINJUN	SINJUN	SINJUN
	Output Power	W	40	40	60
	Capacitor	uF	2.0	2.0	4.0
	Speed (Hi/Mi/Lo)	r/min	1160/1070/940	1160/1070/940	1300/1060/940
Coil	Number Of Row		2	2	3
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Spacing	mm	1.4	1.4	1.4
	Fin Material		Hydrophilic	Hydrophilic	Hydrophilic
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	960*205*25.4	960*205*25.4	960*226*38.1
Unit	Indoor Air Flow (Hi/Mi/Lo)	m3/h	860/688/602	860/688/602	1200/960/840
	Noise Level(Hi/Mi/Lo)	dB(A)	38/35/32	38/35/32	39/36/32
	External Static Pressure	Pa	10/30	10/30	10/30
	Unit Dimension (W*H*D)	mm	1160x440x185	1160x440x185	1160x440x185
	Packing (W*H*D)	mm	1350x525x250	1350x525x250	1350x525x250
	Net Weight	Kg	22	22	24
	Gross Weight	Kg	26	26	28
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	9.52
	Gas Side	mm	12.7	12.7	15.88
	Drainage	mm	R1in(DN25)	R1in(DN25)	R1in(DN25)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	20~50	30~60	40~70

GREEN GRV Low Static Pressure Duct Type


Qty'per 20' & 40'&40HQ(Only For Reference)	Set	104/224/252	104/224/252	104/216/243
--	-----	-------------	-------------	-------------

Notes:


1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference: 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

3. Dimensions


7000 TO 12000



16000 TO 24000



4. Piping Diagrams




Refrigerant pipe connection port diameters

Model	Gas	Liquid
7000/9000	9.52	6.35
12000/16000/18000	12.7	6.35
24000	15.88	9.52

5. Wiring Diagrams

7000 TO 24000



6. Electrical Characteristics

Model	Indoor Unit				Power Supply		IFM	
	Hz	Voltage	Min.	Max.	MCA	MFA	KW	FLA
7000	50	220-240V	198	254	0.40	10	0.02	0.32
9000	50	220-240V	198	254	0.40	10	0.02	0.32
12000	50	220-240V	198	254	0.45	10	0.025	0.36
16000	50	220-240V	198	254	0.60	10	0.04	0.48
18000	50	220-240V	198	254	0.60	10	0.04	0.48
24000	50	220-240V	198	254	0.73	10	0.06	0.58

Symbols:

MCA: Min. Circuit Amps (A)

MFA: Max. Circuit Breaker Amps

KW: Fan Motor Rated Output(kW)

FLA: Full Load Amps (A)

IFM: Indoor Fan Motor

Note:

1. Min. and Max. Voltage: Units are suitable for use on electrical system where voltage supplied to unit terminals is not below or above listed range limits.
2. Maximum allowable voltage unbalance between phases is 2%.
3. $MCA = 1.25 \times FLA$
4. Select wire size based on the MCA.

7. Capacity Tables

Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient



Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature [°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.10	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1.0	1.06	1.13
	Power	0.96	0.97	1.0	1.01	1.03
40	Cooling capacity	0.96	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.90	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.80	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32

Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb [°C]	capacity/power correction coefficient	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.70
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1.0	0.96
	Power	0.94	1.0	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07
	Power	1.05	1.11	1.17


15-24	Heating capacity	0.85 – 1.05 of nominal
	Power	0.80 – 1.20 of nominal

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube




Positive side of high head means installation height of outdoor unit should be higher than indoor unit;
 negative side of high head means installation height of outdoor unit should be lower than indoor unit;
 (change ratio of basic capacity)

8. Sound levels




Model	Noise level under three speeds of fan (dB(A))		
	H	M	L
7000	30	26	23
9000	32	28	25
12000	32	28	25
16000	38	35	32
18000	38	35	32
24000	39	36	32


9. Fan performance




7000/9000			
Static (Pa)	Air volume m3/h		
	High speed	Middle speed	Low speed
0	570	480	380
10	550	460	370
20	500	410	330
30	420	330	250
40	350	240	150
50	240	120	/
60	100	/	/



12000			
Static (Pa)	Air volume m3/h		
	High speed	Middle speed	Low speed
0	700	600	515
10	680	580	490
20	640	540	445
30	580	485	390
40	500	410	320
50	412	305	215
60	300	200	/
70	165	/	/




16000/18000			
Static (Pa)	Air volume m3/h		
	High speed	Middle speed	Low speed
0	930	820	725
10	920	812	710
20	900	795	690
30	860	755	650
40	800	700	595
50	720	620	520
60	600	500	405
70	450	350	265
80	250	150	/
90	/	/	/
100	/	/	/



24000			
Static (Pa)	Air volume m ³ /h		
	High speed	Middle speed	Low speed
0	1300	1200	1085
10	1280	1170	1060
20	1250	1140	1025
30	1200	1080	960
40	1120	1000	890
50	1020	910	800
60	900	795	690
70	760	665	545
80	600	495	395
90	420	320	215
100	220	115	/

10. Installation

10.1 Spacing Reserved Between the Surrounding of Indoor Unit and Barrier




10.2 Hoisting of Indoor Unit

- ◇ Selection of hanging foundation: the foundation must be wooden frame and reinforced concrete structure, which is firm and reliable, able to stand a weight four times of the unit's weight and stand a certain vibration for a long time.
- ◇ Fixing of hanging foundation: fix hanging with bolt or iron frame or wooden frame as shown in the diagram.
- ◇ Adjust the relative position of hook on hanging bolt to make the main unit incline towards drainage outlet to facilitate draining.
- ◇ Tighten nut to ensure tight contact among nut, washer and four mounting hooks without loose hanging;
- ◇ Ensure there is no loose positioning such as shaking of main unit after installation.


10.3 Installation of Ducting

- ◇ Connect indoor unit and ducting with canvas to reduce unnecessary vibration;
- ◇ Ducting installation includes two methods such as backward air return and downward air return as shown in the following diagram:




10.6 Installation of Drain Pipe

- ◇ Drain pipe must be wrapped with thermal insulation material as follows to prevent condensation or dripping.



Thermal insulation material should be rubber & plastic thermal insulation pipe with thickness above 8mm.


- ◇ Drain pipe should incline downwards with gradient of 1/50-1/100, which will subject to failure such as back flow or water leakage in case of up-and-down fluctuation or upward inclination.



- ◇ After installation, conduct drainage test to determine if water correctly flows through pipeline and carefully observe the connection to ensure there is no leakage. If the unit is installed in new house, it's recommended to test before decorating ceiling. Conduct drainage test for the unit used for heating only.


11. Explode view

7000/9000




N0.	GREEN code	Component description	Component description	Quantity	Unit
1	16321001000035	缝制过滤网组件	Air filter	1	
2	16421028000133	底盘B	Chassis B	1	
3	16421028000132	底盘A	Chassis A	1	
4	16421001000555	左侧板	Left cover board	1	
5	16421007000082	蒸发器左连接板	Left connecting board of evaporator	1	
6	16440001000008	排水泵组件	Drainage pump components	1	
7	16421040000042	挂耳	Peg	4	
8	16321001000042	蜗壳固定板总成	The fixed plate assembly	1	
9	16321009000187	顶盖板组件	Top cover board assembly	1	
10	16322001000076	电控总成	Controller assembly	1	
11	16421038000242	电控盒盖	Electric cover	1	
12	16420011000010	旋钮	Knob	1	
13	16421014000060	阀板	Valve board	1	
14	16320009000001	接水盘组件	Drip tray assembly	1	
15	16421001000554	右侧板	Right cover board	1	
16	16421007000083	蒸发器右连接板	Right connecting board of evaporator	1	
17	16324001000129	蒸发器总成	The evaporator assembly		

12000




N0.	GREEN code	Component description	Component description	Quantity	Unit
1	16321001000035	缝制过滤网组件	Air filter	1	
2	16421028000133	底盘B	Chassis B	1	
3	16421028000132	底盘A	Chassis A	1	
4	16421001000555	左侧板	Left cover board	1	
5	16421007000082	蒸发器左连接板	Left connecting board of evaporator	1	
6	16440001000008	排水泵组件	Drainage pump components	1	
7	16421040000042	挂耳	Peg	4	
8	16321001000042	蜗壳固定板总成	The fixed plate assembly	1	
9	16321009000187	顶盖板组件	Top cover board assembly	1	
10	16322001000076	电控总成	Controller assembly	1	
11	16421038000242	电控盒盖	Electric cover	1	
12	16420011000010	旋钮	Knob	1	
13	16421014000060	阀板	Valve board	1	
14	16320009000001	接水盘组件	Drip tray assembly	1	
15	16421001000554	右侧板	Right cover board	1	
16	16421007000083	蒸发器右连接板	Right connecting board of evaporator	1	
17	16324001000128	蒸发器总成	The evaporator assembly		

16000/18000



N0.	GREEN code	Component description	Component description	Quantity	Unit
1	16321001000036	缝制过滤网组件	Air filter	1	
2	16421028000135	底盘B	Chassis B	1	
3	16421001000555	左侧板	Left cover board	1	
4	16421007000082	蒸发器左连接板	Left connecting board of evaporator	1	
5	16440001000008	排水泵组件	Drainage pump components	1	
6	16321001000044	蜗壳固定板总成	The fixed plate assembly	1	
7	16321009000188	顶盖板组件	Top cover board assembly	1	
8	16421040000042	挂耳	Peg	4	
9	16421038000242	电控盒盖	Electric cover	1	
10	16322001000076	电控总成	Controller assembly	1	
11	16420011000010	旋钮	Knob	1	
12	16421014000060	阀板	Valve board	1	
13	16324001000127	蒸发器总成	The evaporator assembly	1	
14	16421007000083	蒸发器右连接板	Right connecting board of evaporator	1	
15	16320009000002	接水盘组件	Drip tray assembly	1	
16	16421001000554	右侧板	Right cover board	1	
17	16421028000134	底盘A	Chassis A	1	

24000



N0.	GREEN code	Component description	Component description	Quantity	Unit
1	16321001000036	缝制过滤网组件	Air filter	1	
2	16421028000135	底盘B	Chassis B	1	
3	16421001000055	左侧板	Left cover board	1	
4	16440001000008	排水泵组件	Drainage pump components	1	
5	16421007000082	蒸发器左连接板	Left connecting board of evaporator	1	
6	16321001000044	蜗壳固定板总成	The fixed plate assembly	1	
7	16321009000188	顶盖板组件	Top cover board assembly	1	
8	16421040000042	挂耳	Peg	4	
9	16322001000076	电控总成	Controller assembly	1	
10	16421038000242	电控盒盖	Electric cover	1	
11	16420011000010	旋钮	Knob	1	
12	16421014000060	阀板	Valve board	1	
13	16324001000126	蒸发器总成	The evaporator assembly	1	
14	16421001000054	右侧板	Right cover board	1	
15	16421007000083	蒸发器右连接板	Right connecting board of evaporator	1	
16	16320009000002	接水盘组件	Drip tray assembly	1	
17	16421028000134	底盘A	Chassis A	1	

12. Spare parts list

7000

Component description	Code	Description(Chinese)	Quantity
PCB board	11222542000002	CJ 控制板 DCZ-SN3F(R8C)-SYE2(三热)	1
Transformer	16422005000032	(ROHS)变压器 TDB-14-B3B(PTC)	1
Terminal board	16427001000062	端子板 4 位(600V 4mm ²)LNAB(45 度)	1
Capacitor	11330010000052	R 风机电容 1.5μF/450VAC/70/2000h	1
Fan motor	16430001000510	电机(四速) FP20A	1
Upper shell	16444002000016	上涡壳 175/219(白色)	1
Lower shell	16444002000017	下涡壳 175/219(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000033	风轮 136×193(ABS 新料)(蓝色)	1
Remote controller	11222001000586	遥控器 YKR-H/009(普通按键无背光源)	1
Air Filter	16444013000099	缝制过滤网 742×145×4	1
Filter	16442001000024	过滤器 6× 8-50	1
Filter	16442001000023	过滤器 6× 6.35-50	1
Drain Pan/Condensate pan/Drain pump	16440001000017	(ROHS)排水泵 PLD-700(L=350)	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000017	电子膨胀阀线圈 CAM-MD12HRSZ-105 L=700	1

9000

Component description	Code	Description(Chinese)	Quantity
PCB board	11222542000002	CJ 控制板 DCZ-SN3F(R8C)-SYE2(三热)	1
Transformer	16422005000032	(ROHS)变压器 TDB-14-B3B(PTC)	1
Terminal board	16427001000062	端子板 4 位(600V 4mm ²)LNAB(45 度)	1
Capacitor	11330010000052	R 风机电容 1.5μF/450VAC/70/2000h	1
Fan motor	16430001000510	电机(四速) FP20A	1
Upper shell	16444002000016	上涡壳 175/219(白色)	1
Lower shell	16444002000017	下涡壳 175/219(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000033	风轮 136×193(ABS 新料)(蓝色)	1
Remote controller	11222001000586	遥控器 YKR-H/009(普通按键无背光源)	1

GREEN GRV Low Static Pressure Duct Type

Air Filter	16444013000099	缝制过滤网 742x145x4	1
Filter	16442001000024	过滤器 6x 8-50	1
Filter	16442001000023	过滤器 6x 6.35-50	1
Drain Pan/Condensate pan/Drain pump	16440001000017	(ROHS)排水泵 PLD-700(L=350)	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000017	电子膨胀阀线圈 CAM-MD12HRSZ-105 L=700	1

12000

Component description	Code	Description(Chinese)	Quantity
PCB board	11222542000002	CJ 控制板 DCZ-SN3F(R8C)-SYE2(三热)	1
Transformer	16422005000032	(ROHS)变压器 TDB-14-B3B(PTC)	1
Terminal board	16427001000062	端子板 4位(600V 4mm2)LNAB(45度)	1
Capacitor	11330010000053	R 风机电容 2.0μF/450VAC/70/2000h	1
Fan motor	16430001000510	电机(四速) FP25A	1
Upper shell	16444002000016	上涡壳 175/219(白色)	1
Lower shell	16444002000017	下涡壳 175/219(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000033	风轮 136x193(ABS 新料)(蓝色)	1
Remote controller	11222001000586	遥控器 YKR-H/009(普通按键无背光源)	1
Air Filter	16444013000099	缝制过滤网 742x145x4	1
Filter	16442001000024	过滤器 6x 8-50	1
Filter	16442001000023	过滤器 6x 6.35-50	1
Drain Pan/Condensate pan/Drain pump	16440001000017	(ROHS)排水泵 PLD-700(L=350)	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000017	电子膨胀阀线圈 CAM-MD12HRSZ-105 L=700	1

16000

Component description	Code	Description(Chinese)	Quantity
PCB board	11222542000002	CJ 控制板 DCZ-SN3F(R8C)-SYE2(三热)	1
Transformer	16422005000032	(ROHS)变压器 TDB-14-B3B(PTC)	1
Terminal board	16427001000062	端子板 4位(600V 4mm2)LNAB(45度)	1
Capacitor	11330010000053	R 风机电容 2.0μF/450VAC/70/2000h	1
Fan motor	16430001000511	电机(四速) FP40A	1
Upper shell	16444002000016	上涡壳 175/219(白色)	1
Lower shell	16444002000017	下涡壳 175/219(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1

GREEN GRV Low Static Pressure Duct Type

temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000033	风轮 136x193(ABS 新料)(蓝色)	1
Remote controller	11222001000586	遥控器 YKR-H/009(普通按键无背光源)	1
Air Filter	16444013000100	缝制过滤网 1066x145x4	1
Filter	16442001000024	过滤器 6x 8-50	1
Filter	16442001000023	过滤器 6x 6.35-50	1
Drain Pan/Condensate pan/Drain pump	16440001000017	(ROHS)排水泵 PLD-700(L=350)	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000017	电子膨胀阀线圈 CAM-MD12HRSZ-105 L=700	1
Longer shaft	16444007000015	加长轴(空心) 15x590	
Shaft coupling	16444007000001	联轴器 15	1

18000

Component description	Code	Description(Chinese)	Quantity
PCB board	11222542000002	CJ 控制板 DCZ-SN3F(R8C)-SYE2(三热)	1
Transformer	16422005000032	(ROHS)变压器 TDB-14-B3B(PTC)	1
Terminal board	16427001000062	端子板 4位(600V 4mm2)LNAB(45度)	1
Capacitor	11330010000053	R 风机电容 2.0μF/450VAC/70/2000h	1
Fan motor	16430001000511	电机(四速) FP40A	1
Upper shell	16444002000016	上涡壳 175/219(白色)	1
Lower shell	16444002000017	下涡壳 175/219(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000033	风轮 136x193(ABS 新料)(蓝色)	1
Remote controller	11222001000586	遥控器 YKR-H/009(普通按键无背光源)	1
Air Filter	16444013000100	缝制过滤网 1066x145x4	1
Filter	16442001000024	过滤器 6x 8-50	1
Filter	16442001000023	过滤器 6x 6.35-50	1
Drain Pan/Condensate pan/Drain pump	16440001000017	(ROHS)排水泵 PLD-700(L=350)	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000017	电子膨胀阀线圈 CAM-MD12HRSZ-105 L=700	1
Longer shaft	16444007000015	加长轴(空心) 15x590	
Shaft coupling	16444007000001	联轴器 15	1

24000

Component description	Code	Description(Chinese)	Quantity
PCB board	11222542000002	CJ 控制板 DCZ-SN3F(R8C)-SYE2(三热)	1
Transformer	16422005000032	(ROHS)变压器 TDB-14-B3B(PTC)	1
Terminal board	16427001000062	端子板 4位(600V 4mm2)LNAB(45度)	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Fan motor	164300010000512	电机(四速) FP60A	1
Upper shell	16444002000016	上涡壳 175/219(白色)	1
Lower shell	16444002000017	下涡壳 175/219(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000033	风轮 136x193(ABS 新料)(蓝色)	1
Remote controller	112220010000586	遥控器 YKR-H/009(普通按键无背光源)	1
Air Filter	16444013000100	缝制过滤网 1066x145x4	1
Filter	16442001000024	过滤器 6x 8-50	1
Filter	16442001000023	过滤器 6x 6.35-50	1
Drain Pan/Condensate pan/Drain pump	16440001000017	(ROHS)排水泵 PLD-700(L=350)	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000017	电子膨胀阀线圈 CAM-MD12HRSZ-105 L=700	1
Longer shaft	16444007000015	加长轴(空心) 15x590	
Shaft coupling	16444007000001	联轴器 15	1

Low Static Pressure Duct

1.Features


- **Compact unit body**

Duct body designed thin and compact. The EXV is fixed inside of the indoor unit, Compact unit body. Concealed installation, combined with indoor decoration perfectly




- **Air inlet from back standard and from bottom optional.**

The size of the plate from bottom is the same as the flange from back, which makes it convenient to change installation style due to different



- **Built-in infrared receiver wire controller and remote controller**



2.Specifications

Model			IDGRV07P1	IDGRV09P1	IDGRV12P1
Power Supply		V~,Hz,P h	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	2.2	2.8	3.6
	Heating	kW	2.5	3.0	4.3
Fan motor	Model		YSK15-4	YSK15-4	YSK22-4(12)
	Brand		HUATE	HUATE	AIMUTE
	Output Power	W	15	15	22.0
	Capacitor	uF	1.5	1.5	1.5
	Speed (Hi/Mi/Lo)	r/min	870/820/800	870/820/800	973/910/873
Coil	Number Of Row		2	2	2
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Spacing	mm	1.4	1.4	1.4
	Fin Material		Hydrophilic	Hydrophilic	Hydrophilic
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	685*205*25.4	685*205*25.4	685*205*25.4
Unit	Indoor Air Flow (Hi/Mi/Lo)	m3/h	420/336/294	420/336/294	630/504/441
	Noise Level(Hi/Mi/Lo)	dB(A)	36/33/30	36/33/30	38/35/32
	External Static Pressure	Pa	12/30	12/30	12/30
	Unit Dimension (W*H*D)	mm	880x547x240	880x547x240	880x547x240
	Packing (W*H*D)	mm	980x620x280	980x620x280	980x620x280
	Net Weight	Kg	22.5	22.5	22.5
	Gross Weight	Kg	26	26	26
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	6.35
	Gas Side	mm	9.52	9.52	12.7
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24

GREEN GRV Low Static Pressure Duct Type

Range(Cooling/Heating)				
Application Area	m ²	10~20	10~25	10~35
Qty'per 20' & 40'&40HQ(Only For Reference)	Set	168/344/387	168/344/387	168/344/387

Notes:

1. Cooling Capacity:Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m,level difference: 0 m.
2. Heating Capacity:Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate

Model			IDGRV16P1	IDGRV18P1	IDGRV24P1
Power Supply		V~,Hz,P h	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	4.5	5.6	7.1
	Heating	kW	5.0	6.0	8.0
Fan motor	Model		YSK30-4(12)	YSK30-4(12)	YSK50-4
	Brand		HUATE	HUATE	HUATE
	Output Power	W	30	30	50
	Capacitor	uF	1.5	1.5	3
	Speed (Hi/Mi/Lo)	r/min	950/865/835	950/865/835	1070/960/800
Coil	Number Of Row		3	3	3
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Spacing	mm	1.6	1.6	1.6
	Fin Material		Hydrophilic	Hydrophilic	Hydrophilic
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	920*205*38.1	920*205*38.1	1110*205*38.1
Unit	Indoor Air Flow (Hi/Mi/Lo)	m3/h	860/688/602	860/688/602	1200/960/840
	Noise Level(Hi/Mi/Lo)	dB(A)	40/37/34	40/37/34	42/39/36
	External Static Pressure	Pa	12/30	12/30	12/30
	Unit Dimension (W*H*D)	mm	1110x547x240	1110x547x240	1305x547x240
	Packing (W*H*D)	mm	1210x620x280	1210x620x280	1400x620x280
	Net Weight	Kg	31	31	35.5
	Gross Weight	Kg	35	35	40.5
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	9.52
	Gas Side	mm	12.7	12.7	15.88
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)

GREEN GRV Low Static Pressure Duct Type


Operation Temperature Range	°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)	°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area	m ²	20~50	30~60	40~70
Qty'per 20'& 40'&40HQ(Only For Reference)	Set	104/224/252	104/224/252	104/216/243

Notes:


1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference: 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference: 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

3.Dimensions


9000 TO 12000




16000/18000



24000




4.Piping Diagrams



Refrigerant pipe connection port diameters

Model	Gas	Liquid
7000/9000	9.52	6.35
12000/16000/18000	12.7	6.35
24000	15.88	6.35

5.Wiring Diagrams



6. Electrical Characteristics

Model	Indoor Unit				Power Supply		IFM	
	Hz	Voltage	Min.	Max.	MCA	MFA	KW	FLA
7000	50	220-240V	198	254	0.25	10	0.015	0.20
9000	50	220-240V	198	254	0.25	10	0.015	0.20
12000	50	220-240V	198	254	0.34	10	0.022	0.27
16000	50	220-240V	198	254	0.60	10	0.03	0.48
18000	50	220-240V	198	254	0.60	10	0.03	0.48
24000	50	220-240V	198	254	0.73	10	0.05	0.58

Symbols:

MCA: Min. Circuit Amps (A)

MFA: Max. Circuit Breaker Amps

KW: Fan Motor Rated Output(kW)

FLA: Full Load Amps (A)

IFM: Indoor Fan Motor

Note:

5. Min. and Max. Voltage: Units are suitable for use on electrical system where voltage supplied to unit terminals is not below or above listed range limits.
6. Maximum allowable voltage unbalance between phases is 2%.
7. $MCA = 1.25 \times FLA$
8. Select wire size based on the MCA.

7.Capacity Tables

Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient



Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature [°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.10	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1.0	1.06	1.13
	Power	0.96	0.97	1.0	1.01	1.03
40	Cooling capacity	0.96	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.90	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.80	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32

Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb [°C]	capacity/power correction coefficient	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.70
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1.0	0.96
	Power	0.94	1.0	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07
	Power	1.05	1.11	1.17


15-24	Heating capacity	0.85 – 1.05 of nominal
	Power	0.80 – 1.20 of nominal

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube



Positive side of high head means installation height of outdoor unit should be higher than indoor unit;
 negative side of high head means installation height of outdoor unit should be lower than indoor unit;
 (change ratio of basic capacity)

8.Sound levels



Model	Noise level under three speeds of fan (dB(A))		
	H	M	L
7000	36	33	30
9000	36	33	30
12000	38	35	32
16000	40	37	34
18000	40	37	34
24000	42	39	36

9.Fan performance

7000/9000			
Static (Pa)	Air volume m3/h		
	High speed	Middle speed	Low speed
0	570	480	380
10	550	460	370
20	500	410	330
30	420	330	250
40	350	240	150
50	240	120	/
60	100	/	/


12000			
Static (Pa)	Air volume m3/h		
	High speed	Middle speed	Low speed
0	700	600	515
10	680	580	490
20	640	540	445
30	580	485	390
40	500	410	320
50	412	305	215
60	300	200	/
70	165	/	/

16000/18000			
Static (Pa)	Air volume m3/h		
	High speed	Middle speed	Low speed
0	930	820	725
10	920	812	710
20	900	795	690
30	860	755	650
40	800	700	595
50	720	620	520
60	600	500	405
70	450	350	265
80	250	150	/
90	/	/	/
100	/	/	/

24000			
Static (Pa)	Air volume m3/h		
	High speed	Middle speed	Low speed
0	1300	1200	1085
10	1280	1170	1060
20	1250	1140	1025
30	1200	1080	960
40	1120	1000	890
50	1020	910	800
60	900	795	690
70	760	665	545
80	600	495	395
90	420	320	215
100	220	115	/

10. Installation

10.1 Spacing Reserved Between the Surrounding of Indoor Unit and Barrier




10.2 Hoisting of Indoor Unit

- ◇ Selection of hanging foundation: the foundation must be wooden frame and reinforced concrete structure, which is firm and reliable, able to stand a weight four times of the unit's weight and stand a certain vibration for a long time.
- ◇ Fixing of hanging foundation: fix hanging with bolt or iron frame or wooden frame as shown in the diagram.
- ◇ Adjust the relative position of hook on hanging bolt to make the main unit incline towards drainage outlet to facilitate draining.
- ◇ Tighten nut to ensure tight contact among nut, washer and four mounting hooks without loose hanging;
- ◇ Ensure there is no loose positioning such as shaking of main unit after installation.


10.3 Installation of Ducting

- ◇ Connect indoor unit and ducting with canvas to reduce unnecessary vibration;
- ◇ Ducting installation includes two methods such as backward air return and downward air return as shown in the following diagram:




10.6 Installation of Drain Pipe

- ◇ Drain pipe must be wrapped with thermal insulation material as follows to prevent condensation or dripping.



Thermal insulation material should be rubber & plastic thermal insulation pipe with thickness above 8mm.


- ◇ Drain pipe should incline downwards with gradient of 1/50-1/100, which will subject to failure such as back flow or water leakage in case of up-and-down fluctuation or upward inclination.



- ◇ After installation, conduct drainage test to determine if water correctly flows through pipeline and carefully observe the connection to ensure there is no leakage. If the unit is installed in new house, it's recommended to test before decorating ceiling. Conduct drainage test for the unit used for heating only.

11. Explode view

7000 TO 18000




N0.	GREEN code	Component description	Component description	Quantity	Unit
1	16421005000013	顶盖板	Top cover board	1	Pc
2	16421030000002	出风法兰短条	Air outlet flange part	2	Pcs
3	16421028000009	底盘	Chassis	1	Pc
4	16432014000016	接水盘	Drip tray	1	Pc
5	16421014000004	阀板	Valve board	1	Pc
6	16432020000006	管夹 9.52	Pipe Clamp 9.52	1	Pc
7	16432020000007	管夹 12	Pipe Clamp 12	1	Pc
8	16324009000006	蒸发器组件	Evaporator assembly	1	Set
8.1	16325009000018	蒸发器出气管组件	Evaporator gas outlet pipe assembly	1	Set
9	16325001000022	蒸发器进液管组件	Evaporator liquid inlet pipe assembly	1	Set
10	16421002000056	蜗壳固定板	Volute fixing board	1	Pc
11	16421038000028	电控盒总成	Electric assembly	1	Set
11.1	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	PCB board DCZ-SN3F-SYE2(R8C)	1	Pc
11.2	16422005000009	变压器 TDB-14-B2B(PTC)	Transformer TDB-14-B2B(PTC)	1	Pc
11.3	16430007000003	传感器 XH2(白)15K3950 0.5M(塑封)	Sensor 15K3950 0.5M white	1	Pc
11.3	16430007000010	传感器 XH2(蓝)20K3950 0.5M(铜)	Sensor 20K3950 0.5M blue	1	Pc
11.4	16430007000008	传感器 XH2(黄)20K3950 0.5M(铜)	Sensor 20K3950 0.5M yellow	1	Pc

GREEN GRV Low Static Pressure Duct Type

11.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Sensor 20K3950 0.5M green	1	Pc
11.5	16427001000010	端子板 5 位	Terminal board	1	Pc
11.6	16421038000028	电控盒	Electric components box	1	Set
12	16421005000104	电控盒盖	Cover for electric box	1	Pc
13	16444005000001	离心风轮组件 150/175(H115)	Centrifugal fan motor	2	Sets
14	16321012000014	回风箱下后板组件	Return-air box underside board	1	Set
15	16421001000420	回风箱右侧板	Return-air box right board	1	Pc
16	16421030000006	回风箱导风短条	Return-air box wind-guiding part	2	Pcs
17	16321012000009	回风箱滑道组件	Return-air box slide way assembly	1	Set
18	16421005000276	回风箱顶板	Return-air box top cover board	1	Pc
19	16444013000016	缝制过滤网	Air filter	1	Pc
20	16430001000023	室内风扇电机 YSK15-4 用于	Indoor fan motor YSK15-4 for	1	Pc
	16430001000194	YSK22-4	YSK22-4 for		Pc
	16430001000042				Pc
21	16421038000034	电控盒支撑板	Electric box bracket	1	Pc
22	16421001000419	回风箱左侧板	Return-air box left board	1	Pc
23	16441015000002	电子膨胀阀	EXV	1	Pc

24000



24000

GREEN GRV Medium Static Pressure Duct Type

NO.	GREEN code	Component description	Component description	Quantity	Unit
1	16421005000015	FP-136WA/B 顶盖板斜 47°	Top cover board	1	Pc
2	16421030000002	出风法兰短条	Air outlet flange part	2	Pcs
3	16324009000005	GR-72D/DS3 蒸发器组件(片距 1.6)	Evaporator assembly	1	Set
4	16421028000007	底盘	Chassis	1	Pc
5	16432014000017	接水盘 GR-72D/DS3 242x1305	Drip tray	1	Pc
6	16421014000004	GR-26D/DS2 阀板	Valve board	1	Pc
7	16432020000006	管夹 9.52	Pipe Clamp 9.52	1	Pc
8	16432020000008	管夹 16	Pipe Clamp 16	1	Pc
9	16325009000007	蒸发器出气管组件	Evaporator liquid inlet pipe assembly	1	Set
10	16325001000025	蒸发器进液管组件	Evaporator gas outlet pipe assembly	1	Set
11	16321009000003	蜗壳固定板总成	Volute fixing board assembly	1	Set
11.1	16421002000058	FP-136WAZ/C 蜗壳固定板	Volute fixing board	1	Pc
11.2	16444007000001	联轴器 15	Motor coupling	1	Pc
11.3	16444005000001	离心风轮组件 150/175(H115)	Centrifugal fan motor	2	Set
11.4	16421002000219	橡胶轴承压板	Rubber bearing clamp	1	Pc
11.5	16432016000033	橡胶轴承	Rubber bearing	1	Pc
11.6	16421026000006	风机支撑架	Fan motor bracket	1	Set
11.7	16444007000002	加长轴 15	Motor lengthen axes	1	Pc
11.8	16430001000017	室内风扇电机 YSK50-4 适用于 GRVLD-H071/4R1A	Fan motor YSK50-4 for GRVLD-H071/4R1)	1	Pc
12	16421038000034	GR-25D/S2 电控盒支撑板	Electric box bracket	1	Pc
13	16322001000009	DLR-71F/DCZDS3 控制器总成	Electric box assembly	1	Set
13.1	16422001000170	R 室内主控板 DCZ-SN3F-SYE1(R8C)	PCB board	1	Pc
13.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer (ROHS)	1	Pc
13.3	16430007000003	传感器 XH2(白)15K3950 0.5M(塑封)	Sensor 15K3950 0.5M white	1	Pc
13.3	16430007000010	传感器 XH2(蓝)20K3950 0.5M(铜)	Sensor 20K3950 0.5M blue	1	Pc
13.4	16430007000008	传感器 XH2(黄)20K3950 0.5M(铜)	Sensor 20K3950 0.5M yellow	1	Pc
13.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Sensor 20K3950 0.5M green	1	Pc
13.5	16427001000010	端子板 5 位(600V 4mm2)AB	Terminal board	1	Pc
13.6	16421038000028	GR-26D/DS3 电控盒	Electric components box	1	Set
14	16421005000104	GR-26D/DS3 电控盒盖	Cover for electric components	1	Pc
15	16321012000005	FP-136WA 回风箱下后板组件 A	Return-air box underside board	1	Set
16	16421001000420	风机盘管回风箱右侧板	Return-air box right board	1	Pc
17	16421030000006	风机盘管回风箱导风短条 A	Return-air box flange	2	Pcs
18	16321012000004	FP-136WA 回风箱过滤滑道组件	Return-air box slideway assembly	1	Set
19	16421005000278	FP-136WA/B 回风箱顶板	Return-air box top cover board	1	Pc
20	16444013000002	缝制过滤网 545x204x6mm	Air filter	2	Pcs
21	16421001000419	风机盘管回风箱左侧板	Return-air box left board	1	Pc
22	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	EXV	1	Pc

12. Spare parts list

7000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000052	R 风机电容 1.5μF/450VAC/70/2000h	1
Fan motor	16430001000023	电机(三速) YSK15-4	1
Upper shell	16444002000002	上涡壳 150/175(白色)	1
Lower shell	16444002000001	下涡壳 150/175(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000032	风轮 150×175× 15(ABS 新料)(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000016	缝制过滤网 665×204×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	1
Filter	16442001000005	过滤器 6× 8-66	1
Drain Pan/Condensate pan/Drain pump	16432014000016	接水盘 242×880	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

9000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000052	R 风机电容 1.5μF/450VAC/70/2000h	1
Fan motor	16430001000023	电机(三速) YSK15-4	1
Upper shell	16444002000002	上涡壳 150/175(白色)	1
Lower shell	16444002000001	下涡壳 150/175(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000032	风轮 150×175× 15(ABS 新料)(白色)	1

GREEN GRV Medium Static Pressure Duct Type

Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000016	缝制过滤网 665×204×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	1
Filter	16442001000005	过滤器 6× 8-66	1
Drain Pan/Condensate pan/Drain pump	16432014000016	接水盘 242×880	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

12000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm ²)AB	1
Capacitor	11330010000052	R 风机电容 1.5μF/450VAC/70/2000h	1
Fan motor	16430001000194	电机 YSK22-4(12)	1
Upper shell	16444002000002	上涡壳 150/175(白色)	1
Lower shell	16444002000001	下涡壳 150/175(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000031	风轮 150×175× 12(ABS 新料)(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000016	缝制过滤网 665×204×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	1
Filter	16442001000005	过滤器 6× 8-66	1
Drain Pan/Condensate pan/Drain pump	16432014000016	接水盘 242×880	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

16000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm ²)AB	1
Capacitor	11330010000052	R 风机电容 1.5μF/450VAC/70/2000h	1
Fan motor	16430001000042	电机 YSK30-4(12)	1
Upper shell	16444002000002	上涡壳 150/175(白色)	1
Lower shell	16444002000001	下涡壳 150/175(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳4(组件)	1
Fan wheel	16444001000031	风轮 150×175× 12(ABS 新料)(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000001	缝制过滤网 900×204×6	1
Filter	16442001000005	过滤器 6× 8-66	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	1
Drain Pan/Condensate pan/Drain pump	16432014000019	接水盘 GR-51D/DS3 242×1115	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

18000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm ²)AB	1
Capacitor	11330010000052	R 风机电容 1.5μF/450VAC/70/2000h	1
Fan motor	16430001000042	电机 YSK30-4(12)	1
Upper shell	16444002000002	上涡壳 150/175(白色)	1
Lower shell	16444002000001	下涡壳 150/175(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳4(组件)	1

GREEN GRV Medium Static Pressure Duct Type

Fan wheel	16444001000031	风轮 150×175× 12(ABS 新料)(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000001	缝制过滤网 900×204×6	1
Filter	16442001000005	过滤器 6× 8-66	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	1
Drain Pan/Condensate pan/Drain pump	16432014000019	接水盘 GR-51D/DS3 242×1115	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

24000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5 位(600V 4mm ²)AB	1
Capacitor	11330010000055	R 风机电容 3.0μF/450VAC/70/2000h	1
Fan motor	16430001000017	电机(三速) YSK50-4	1
Upper shell	16444002000002	上涡壳 150/175(白色)	1
Lower shell	16444002000001	下涡壳 150/175(白色)	1
temperature Sensor	16430007000003	温度传感器 15K3950 XH2 白 0.5m 塑封 1(组件)	1
temperature Sensor	16430007000010	温度传感器 20K3950 XH2 蓝 0.5m 铜壳 2(组件)	1
temperature Sensor	16430007000008	温度传感器 20K3950 XH2 黄 0.5m 铜壳 3(组件)	1
temperature Sensor	16430007000011	温度传感器 20K3950 XH2 绿 0.5m 铜壳 4(组件)	1
Fan wheel	16444001000032	风轮 150×175× 15(ABS 新料)(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000002	缝制过滤网 1090×204×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	1
Filter	16442001000010	过滤器 8× 9.52-66(R410a)	1
Drain Pan/Condensate pan/Drain pump	16432014000017	接水盘 GR-72D/DS3 242×1305	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000002	加长轴(空心) 15×584	1
Shaft coupling	16444007000001	联轴器 15	1

Middle static pressure duct

1.Feature	275
2.Specification	276
3.Dimension	280
4.Piping Diagram	281
5.Wiring Diagram	282
6.Electric Characteristics.....	283
7.Capacity Tables	284
8.Fan Performance	286
9.Sound Levels	287
10.Installation Manual.....	288
11.Exploded View	290
12.Spare parts list.....	300


1.Feature

Mid static pressure allows for flexible duct design




- **Fresh air intake**

Reversed fresh air intake hole, It's convenient to connect with air duct.




- **Ultra slim design**

Thinner and Lighter, Only 290mm.



- **Built-in water drainage pump(Optional)**


The built-in pump can lift condensing water up 800mm high from the drainage pan.



- **Flexible air intake options**

Air intake from rear as standard, from bottom as optional.

The size of the plate from bottom is the same as the flange from back, which makes it convenient to change installation style due to different decoration requirement.



2.Specification

Model			IDGRV16P1/M	IDGRV18P1/M	IDGRV24P1/M
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	4.5	5.6	7.1
	Heating	kW	5.0	6.0	8.0
Fan Motor	Model		YSK100-4	YSK100-4	YSK160-4
	Brand		KANGBAO	KANGBAO	KANGBAO
	Output Power	W	100	100	160
	Capacitor	uF	4	4	3.5
	Speed (Hi/Mi/Lo)	r/min	960/860/840	960/860/840	1050/1000/910
Coil	Number Of Row		2	2	3
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.5	1.5	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	625x369x25.4	625x369x25.4	625x369x38.1
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	950/760/665	950/760/665	1200/960/840
	Noise Level(Hi/Mi/Lo)	dB(A)	42/39/37	42/59/37	45/42/39
	External Static Pressure	Pa	50/80	50/80	50/80
	Net Dimension (WxDxH)	mm	890x785x290	890x785x290	890x785x290
	Packing Dimension (WxDxH)	mm	1100x870x360	1100x870x360	1100x870x360
	Net Weight	Kg	35	35	37
	Gross Weight	Kg	41	41	43
Refrigerant Pipe	Liquid Side	mm	6.35	6.35	9.52
	Gas Side	mm	12.7	12.7	15.88
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	20~35	25~45	30~50
Stuffing Quantity	20/40/40H	Unit	83/175/204	83/175/204	83/175/204

Note:

1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference : 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference : 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

GREEN GRV Medium Static Pressure Duct Type

Model			IDGRV28P1/M	IDGRV30P1/M	IDGRV34P1/M
Power Supply		V~,Hz, Ph	220~240,50,1	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	8.0	9.0	10.0
	Heating	kW	10.0	11.0	12.0
Fan Motor	Model		YSK160-4	YSK180-4	YSK180-4
	Brand		KANGBAO	KANGBAO	KANGBAO
	Output Power	W	160	180	180
	Capacitor	uF	8	8	8
	Speed (Hi/Mi/Lo)	r/min	1050/1000/910	1100/990/920	1100/990/920
Coil	Number Of Row		3	3	3
	Tube Pitch(a)x Row Pitch(b))	mm	20.5x12.7	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.6	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	625x369x38.1	625x369x38.1	625x369x38.1
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	1500/1200/1050	1500/1200/1050	1500/1200/1050
	Noise Level(Hi/Mi/Lo)	dB(A)	48/45/42	48/45/42	48/52/42
	External Static Pressure	Pa	50/80	50/80	50/80
	Net Dimension (WxDxH)	mm	890x785x290	890x785x290	890x785x290
	Packing Dimension (WxDxH)	mm	1100x870x360	1100x870x360	1100x870x360
	Net Weight	Kg	37	37	37
	Gross Weight	Kg	43	43	43
Refrigerant Pipe	Liquid Side	mm	9.52	9.52	9.52
	Gas Side	mm	15.88	15.88	15.88
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	35~55	40~60	45~65
Stuffing Quantity	20/40/40H	Unit	83/175/204	83/175/204	83/175/204

Note:

1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference : 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference : 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

GREEN GRV Medium Static Pressure Duct Type

Model			IDGRV38P1/M	IDGRV42P1/M
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	11.2	12.5
	Heating	kW	12.8	13.3
Fan Motor	Model		YSK180-4	YSK180-4
	Brand		KANGBAO	KANGBAO
	Output Power	W	180	180
	Capacitor	uF	8	8
	Speed (Hi/Mi/Lo)	r/min	1100/990/920	1100/990/920
Coil	Number Of Row		3	3
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	985x369x38.1	985x369x38.1
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	2000/1600/1400	2000/1600/1400
	Noise Level(Hi/Mi/Lo)	dB(A)	51/43/40	51/43/40
	External Static Pressure	Pa	50/80	50/80
	Net Dimension (WxDxH)	mm	1250x785x290	1250x785x290
	Packing Dimension (WxDxH)	mm	1460x870x360	1460x870x360
	Net Weight	Kg	53	53
	Gross Weight	Kg	60	60
Refrigerant Pipe	Liquid Side	mm	9.52	9.52
	Gas Side	mm	19.05	19.05
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	50~75	50~90
Stuffing Quantity	20/40/40H	Unit	63/133/155	63/133/155

Note:

1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference : 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference : 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

GREEN GRV Medium Static Pressure Duct Type


Model			IDGRV48P1/M	IDGRV50P1/M
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	14.0	15.0
	Heating	kW	15.0	16.0
Indoor Fan Motor	Model		YSK180-4	YSK180-4
	Brand		KANGBAO	KANGBAO
	Output Power	W	180	180
	Capacitor	uF	8	8
	Speed (Hi/Mi/Lo)	r/min	1100/990/920	1100/990/920
Indoor Coil	Number Of Row		3	3
	Tube Pitch(a)x Row Pitch(b)	mm	20.5x12.7	20.5x12.7
	Fin Pitch	mm	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7,Inner grooved	7,Inner grooved
	Coil Length x Height x Width	mm	985x369x38.1	985x369x38.1
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	2000/1600/1400	2000/1600/1400
	Noise Level(Hi/Mi/Lo)	dB(A)	51/43/40	51/43/40
	External Static Pressure	Pa	50/80	50/80
	Net Dimension (WxDxH)	mm	1250x785x290	1250x785x290
	Packing Dimension (WxDxH)	mm	1460x870x360	1460x870x360
	Net Weight	Kg	53	53
	Gross Weight	Kg	60	60
Refrigerant Pipe	Liquid Side	mm	9.52	9.52
	Gas Side	mm	19.05	19.05
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	60~100	65~110
Stuffing Quantity	20/40/40H	Unit	63/133/155	63/133/155

Note:

1. Cooling Capacity:Indoor temp.27°CDB,19°CWB,outdoor temp.35°CDB,24°CWB /Equivalent piping length :7.5m,level difference : 0 m.
2. Heating Capacity:Indoor temp.20°CDB, outdoor temp.7°CDB,6°CWB /Equivalent piping length :7.5m,level difference : 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.


3.Dimension

16000 TO 34000




Unit: mm

38000 TO 51000



Unit: mm


4.Piping Diagram



Refrigerant pipe connection port diameters

Model	(mm)	
	Gas	Liquid
16000/18000	12.7	6.35
24000 TO 34000	15.88	9.52
38000 TO 51000	19.05	9.52

5.Wiring Diagram



6. Electric Characteristics

Model	Indoor Unit				Supply Power		IFW	
	Hz	Voltage	Min.	Max.	MCA	MFA	kW	FLA
16000	50	220-240	198	254	1.13	16	0.10	0.90
18000	50	220-240	198	254	1.13	16	0.10	0.90
24000	50	220-240	198	254	1.50	16	0.16	1.20
28000	50	220-240	198	254	1.50	16	0.16	1.20
30000	50	220-240	198	254	1.75	20	0.18	1.40
34000	50	220-240	198	254	1.75	20	0.18	1.40
38000	50	220-240	198	254	1.75	20	0.18	1.40
42000	50	220-240	198	254	1.75	20	0.18	1.40
48000	50	220-240	198	254	1.75	20	0.18	1.40
50000	50	220-240	198	254	1.75	20	0.18	1.40

Symbols:

MCA: Min. Circuit Amps (A)

MFA: Max. Circuit Breaker Amps

KW: Fan Motor Rated Output(kW)

FLA: Full Load Amps (A)

IFM: Indoor Fan Motor

Note:

1. Min. and Max. Voltage: Units are suitable for use on electrical system where voltage supplied to unit terminals is not below or above listed range limits.
2. Maximum allowable voltage unbalance between phases is 2%.
3. $MCA = 1.25 \times FLA$
4. Select wire size based on the MCA.

7.Capacity Tables


Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient

Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature [°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.10	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1.0	1.06	1.13
	Power	0.96	0.97	1.0	1.01	1.03
40	Cooling capacity	0.96	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.90	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.80	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32

Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb [°C]	capacity/power correction coefficient	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.70
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1.0	0.96
	Power	0.94	1.0	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07
	Power	1.05	1.11	1.17
15-24	Heating capacity	0.85 – 1.05 of nominal		
	Power	0.80 – 1.20 of nominal		

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube



Positive side of high head means installation height of outdoor unit should be higher than indoor unit; negative side of high head means installation height of outdoor unit should be lower than indoor unit; (change ratio of basic capacity)

8.Fan Performance


16000/18000			
Static Pressure	Air volume(m ³ /h)		
	High	Medium	Low
(Pa)			
0	1275	1170	1075
10	1270	1165	1070
20	1260	1155	1060
30	1240	1135	1040
40	1210	1105	1010
50	1170	1065	970
60	1120	1015	920
70	1050	945	850
80	950	845	750
90	800	695	600
100	635	515	425
110	375	270	175
120	95	/	/

24000			
Static Pressure	Air volume(m ³ /h)		
	High	Medium	Low
(Pa)			
0	1500	1350	1200
10	1490	1340	1190
20	1480	1330	1180
30	1470	1320	1170
40	1460	1310	1160
50	1420	1270	1120
60	1380	1230	1080
70	1300	1150	1000
80	1200	1050	900
90	1000	850	700
100	750	600	450
110	450	300	150
120	100	/	/

28000/30000			
Static Pressure	Air volume (m ³ /h)		
	High	Medium	Low
(Pa)			
0	1840	1710	1590
10	1835	1705	1585
20	1825	1695	1575
30	1810	1680	1560
40	1780	1650	1530
50	1740	1610	1490
60	1680	1550	1430
70	1600	1470	1350
80	1500	1370	1250
90	1300	1170	1050
100	1000	870	750
110	600	470	350
120	100	/	/

34000 TO 51000			
Static Pressure	Air volume (m ³ /h)		
	High	Medium	Low
(Pa)			
0	2420	2220	2020
10	2410	2210	2010
20	2400	2200	2000
30	2370	2170	1970
40	2320	2120	1920
50	2260	2060	1860
60	2190	1990	1790
70	2100	1900	1700
80	2000	1800	1600
90	1800	1600	1400
100	1400	1200	1000
110	900	700	500
120	300	/	/

9.Sound Levels



Note:


1. The operating condition are assumed to be at standard (JIS Condition).
2. These operating values were obtained in a dead room (conversion values).

Sound level will vary depending on a range of factors such as the construction (acoustic absorption coefficient) of the particular room in which the equipments installed.

Model	220-240V 50Hz		
	High (dB)	Medium (dB)	Low (dB)
16000	42	39	37
18000			
24000	45	42	39
28000	48	45	42
30000			
34000			
38000	51	48	45
42000			
48000			
51000			

10. Installation Manual

10.1 Service Space



10.2 Hoisting of Indoor Unit


◇ Selection of hanging foundation: the foundation must be wooden frame and reinforced concrete structure, which is firm and reliable, able to stand a weight four times of the unit's weight and stand a certain vibration for a long time.

◇ Fixing of hanging foundation: fix hanging with bolt or iron frame or wooden frame as shown in the diagram.

◇ Adjust the relative position of hook on hanging bolt to make the main unit incline towards drainage outlet to facilitate draining.


◇ Tighten nut to ensure tight contact among nut, washer and four mounting hooks without loose hanging;

◇ Ensure there is no loose positioning such as shaking of main unit after installation.




Installation of Ducting

Connect indoor unit and ducting with canvas to reduce unnecessary




Installation of Drain Pipe

◇ Drain pipe must be wrapped with thermal insulation material as follows to prevent condensation or dripping.




Thermal insulation material should be rubber & plastic thermal insulation pipe with thickness above 10mm
◇ Drain pipe should incline downwards with gradient of 1/50-1/100, which will subject to failure such as back flow or water leakage in case of up-and-down fluctuation or upward inclination.



◇ After installation, conduct drainage test to determine if water correctly flows through pipeline and carefully observe the connection to ensure there is no leakage. If the unit is installed in new house, it's recommended to test before decorating ceiling. Conduct drainage test for the unit used for heating only

11.Exploded View

16000 TO 38000



16000

N0.	GREEN code	Component description	Component description	Quantity	Unit
1	16324001000047	DLR-56F/DCZDGS3 蒸发器总成 (内置)	Evaporator assembly(build-in)	1	Set
1.1	16324009000022	GR-51D/DGS3 蒸发器组件	Evaporator components	1	Set
1.2	16325009000022	GR-51D/DGS3 蒸发器出气管组件	Evaporator gas outlet pipe components	1	Set
1.3	16325001000061	DLR-56F/DCZDGS3 蒸发器进液管组件(内置)	Evaporator liquid inlet pipe components(built-in)	1	Set
1.31	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	EXV body CAM-BD18FKS-1	1	PC
2	16421014000035	ALDu-H42A4/R1DI 阀板	Valve plate	1	PC
3	16421005000191	ALDu-H42A4/R1DI 电控盒盖	Electrical control box cover	1	PC
4	16421030000101	GR-51D/DGS3 出风法兰 A	Air outlet flange A	1	PC
5	16421030000102	GR-51D/DGS3 出风法兰 B	Air outlet flange B	1	PC
6	16421015000026	ALDu-H42A4/R1 排水管保护板 B	Drainpipe protection plate B	1	PC
7	16421015000025	ALDu-H42A4/R1 排水管保护板 A	Drainpipe protection plate A	1	PC
8	16321009000105	ALDu-H18A4/R1 凝水盘组件	Drip tray assembly	1	Set
9	16421005000318	ALDu-H18A4/R1 底板(新)	Chassis	1	PC
10	16421005000207	ALDu-H18A4/R1 回风盖板 A	Air return cover plate A	1	PC
	16421005000208	ALDu-H18A4/R1 回风盖板 B	Air return cover plate B	1	PC
11	16421040000024	ALDu-H42A4/R1DI 吊钩	Pothook	4	PCS
12	16321009000128	(ROHS)GR-51D/DGS3 蜗壳固定板组件	Volute fixed plate assembly	1	Set

GREEN GRV High Static Pressure Duct Type

12.1	16421002000173	ALDu-H18A4/R1 蜗壳固定板	Volute fixed plate	1	PC
12.2	16321001000013	ALDu-H42A4/R1DI 电机架组件	Motor bracket assembly	1	Set
12.3	16430001000218	(ROHS)电机 YSK100-4	Fan motor	1	PC
12.4	16421029000010	GR-250D/G 电机抱攀	Fan motor fixity	2	Pcs
12.5	16346001000004	(ROHS)离心风轮 185/170(塑料)	Centrifugal fan assembly	2	Sets
13	16442001000011	过滤器 6.35x 9.52-70(R410A)	Air filter	2	Pcs
14	/	过滤网滑道组件	Filter slideway assembly	1	Set
14.1	16321001000010	ALDu-H42A4/R1DI 左右过滤器滑道组件	Left&Right slideway assembly	2	Sets
14.2	16321009000107	ALDu-H18A4/R1 上下过滤滑道组件	Up&down slideway assembly	2	Sets
14.3	16421030000091	ALDu-H42A4/R1DI 左右过滤器法兰	Left&Right filter flange	2	Pcs
14.4	16421030000096	ALDu-H18A4/R1 上下过滤器法兰	Up&down filter flange	2	Pcs
15	16421010000025	ALDu-H18A4/R1 围板	Coaming	1	PC
16	16322001000033	DLR-56F/DCZDGS3-Y 控制器	Electrical control assembly	1	Set
16.1	16422001000078	控制板 DCZ-SN3F-HCE1	PCB board	1	PC
16.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer	1	PC
16.3	16430007000005	传感器 XH2(白)15K3950 0.9M(塑封)	Coil sensor 15K3950 0.9M(plastic) White	1	PC
16.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Coil sensor 20K3950 1.2M(copper) Green	1	PC
16.5	16430007000016	传感器 XH2(黄)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper) Yellow	1	PC
16.6	16430007000018	传感器 XH2(蓝)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper) Blue	1	PC
16.7	16427001000010	端子板 5 位(600V 4mm ²)AB	Terminal board	1	PC
16.8	16421038000081	ALDu-H42A4/R1DI 电控盒	Electrical control box	1	PC
17	16421005000192	ALDu-H18A4/R1 顶盖板	Top cover plate	1	PC

18000

NO.	GREEN code	Component description	Component description	Quantity	Unit
1	16324001000047	DLR-56F/DCZDGS3 蒸发器总成(内置)	Evaporator assembly(build-in)	1	Set
1.1	16324009000022	GR-51D/DGS3 蒸发器组件	Evaporator components	1	Set
1.2	16325009000022	GR-51D/DGS3 蒸发器出气管组件	Evaporator gas outlet pipe components	1	Set
1.3	16325001000061	DLR-56F/DCZDGS3 蒸发器进液管组件(内置)	Evaporator liquid inlet pipe components(built-in)	1	Set
1.31	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	EXV body CAM-BD18FKS-1	1	PC
2	16421014000035	ALDu-H42A4/R1DI 阀板	Valve plate	1	PC
3	16421005000191	ALDu-H42A4/R1DI 电控盒盖	Electrical control box cover	1	PC
4	16421030000101	GR-51D/DGS3 出风法兰 A	Air outlet flange A	1	PC
5	16421030000102	GR-51D/DGS3 出风法兰 B	Air outlet flange B	1	PC
6	16421015000026	ALDu-H42A4/R1DI 排水管保护板	Drainpipe protection plate B	1	PC

GREEN GRV High Static Pressure Duct Type

B					
7	16421015000025	ALDu-H42A4/R1DI 排水管保护板 A	Drainpipe protection plate A	1	PC
8	16321009000105	ALDu-H18A4/R1 凝水盘组件	Drip tray assembly	1	Set
9	16421005000318	ALDu-H18A4/R1 底板(新)	Chassis	1	PC
10	16421005000207	ALDu-H18A4/R1 回风盖板 A	Air return cover plate A	1	PC
	16421005000208	ALDu-H18A4/R1 回风盖板 B	Air return cover plate B	1	PC
11	16421040000024	ALDu-H42A4/R1DI 吊钩	Pothook	4	Pcs
12	16321009000128	(ROHS)GR-51D/DGS3 蜗壳固定板组件	Volute fixed plate assembly	1	Set
12.1	16421002000173	ALDu-H18A4/R1 蜗壳固定板	Volute fixed plate	1	PC
12.2	16321001000013	ALDu-H42A4/R1DI 电机架组件	Motor bracket assembly	1	Set
12.3	16430001000218	(ROHS)电机 YSK100-4	Fan motor	1	PC
12.4	16421029000010	GR-250D/G 电机抱攀	Fan motor fixity	2	Pcs
12.5	16346001000004	(ROHS)离心风轮组件 185/170(塑料)	Centrifugal fan assembly	2	Sets
13	16442001000011	过滤器 6.35x 9.52-70(R410A)	Air filter	2	Pcs
14	/	过滤网滑道组件	Filter slideway assembly	1	Set
14.1	16321001000010	ALDu-H42A4/R1DI 左右过滤器滑道组件	Left&Right slideway assembly	2	Sets
14.2	16321009000107	ALDu-H18A4/R1 上下过滤滑道组件	Up&down slideway assembly	2	Sets
14.3	16421030000091	ALDu-H42A4/R1DI 左右过滤器法兰	Left&Right filter flange	2	Pcs
14.4	16421030000096	ALDu-H18A4/R1 上下过滤器法兰	Up&down filter flange	2	Pcs
15	16421010000025	ALDu-H18A4/R1 围板(新)	Coaming	1	PC
16	16322001000010	DLR-56F/DCZDGS3 控制器总成	Electrical control assembly	1	Set
16.1	16422001000078	控制板 DCZ-SN3F-HCE1	PCB board	1	PC
16.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer	1	PC
16.3	16430007000005	传感器 XH2(白)15K3950 0.9M(塑封)	Coil sensor 15K3950 0.9M(plastic)	1	PC
16.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.5	16430007000016	传感器 XH2(黄)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.6	16430007000018	传感器 XH2(蓝)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.7	16427001000010	端子板 5位(600V 4mm2)AB	Terminal board	1	PC
16.8	16421038000081	ALDu-H42A4/R1DI 电控盒	Electrical control box	1	PC
17	16421005000192	ALDu-H18A4/R1 顶盖板	Top cover plate	1	PC

24000/28000

NO.	GREEN code	Component description	Component description	Quantity	Unit
1	16324001000046	DLR-71F/DCZDGS3 蒸发器总成(内置)	Evaporator assembly(build-in)	1	Set
1.1	16324009000024	GR-72D/DGS3 蒸发器组件	Evaporator components	1	Set
1.2	16325009000024	GR-72D/DGS3 蒸发器出气管组件	Evaporator gas outlet pipe	1	Set

GREEN GRV High Static Pressure Duct Type

			components		
1.3	16325001000060	DLR-71F/DCZDGS3 蒸发器进液管组件(内置)	Evaporator liquid inlet pipe components(built-in)	1	Set
1.31	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV body CAM-BD18FKS-1	1	PC
2	16421014000035	ALDu-H42A4/R1DI 阀板	Valve plate	1	PC
3	16421005000191	ALDu-H42A4/R1DI 电控盒盖	Electrical control box cover	1	PC
4	16421030000101	GR-51D/DGS3 出风法兰 A	Air outlet flange A	1	PC
5	16421030000102	GR-51D/DGS3 出风法兰 B	Air outlet flange B	1	PC
6	16421015000026	ALDu-H42A4/R1DI 排水管护保护板 B	Drainpipe protection plate B	1	PC
7	16421015000025	ALDu-H42A4/R1DI 排水管护保护板 A	Drainpipe protection plate A	1	PC
8	16321009000105	ALDu-H18A4/R1 凝水盘组件	Drip tray assembly	1	Set
9	164210050000318	ALDu-H18A4/R1 底板(新)	Chassis	1	PC
10	164210050000207	ALDu-H18A4/R1 回风盖板 A	Air return cover plate A	1	PC
	164210050000208	ALDu-H18A4/R1 回风盖板 B	Air return cover plate B	1	PC
11	16421040000024	ALDu-H42A4/R1DI 吊钩	Pothead	4	Pcs
12	16321009000129	(ROHS)GR-72D/GS3 蜗壳固定板总成(改进)	Volute fixed plate assembly	1	Set
12.1	16421002000173	ALDu-H18A4/R1 蜗壳固定板	Volute fixed plate	1	PC
12.2	16321001000013	ALDu-H42A4/R1DI 电机架组件	Motor bracket assembly	1	Set
12.3	16430001000216	(ROHS)电机 YSK160-4	Fan motor	1	PC
12.4	16421029000010	GR-250D/G 电机抱攀	Fan motor fixity	2	Pcs
12.5	16346001000004	(ROHS)离心风轮组件 185/170	Centrifugal fan assembly	2	Sets
13	16442001000011	过滤器 6.35x 9.52-70(R410A)	Air filter	2	Pcs
14	/	过滤网滑道组件	Filter slideway assembly	1	Set
14.1	16321001000010	ALDu-H42A4/R1DI 左右过滤器滑道组件	Left&Right slideway assembly	2	Sets
14.2	16321009000107	ALDu-H18A4/R1 上下过滤滑道组件	Up&down slideway assembly	2	Sets
14.3	16421030000091	ALDu-H42A4/R1DI 左右过滤器法兰	Left&Right filterflange	2	Pcs
14.4	16421030000096	ALDu-H18A4/R1 上下过滤器法兰	Up&down filter flange	2	Pcs
15	16421010000025	ALDu-H18A4/R1 围板(新)	Coaming	1	PC
16	16322001000010	DLR-56F/DCZDGS3 控制器总成	Electrical control assembly	1	Set
16.1	16422001000078	控制板 DCZ-SN3F-HCE1	PCB board	1	PC
16.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer	1	PC
16.3	16430007000005	传感器 XH2(白)15K3950 0.9M	Coil sensor 15K3950 (plastic)	1	PC
16.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Coil sensor 20K3950 (copper)	1	PC
16.5	16430007000016	传感器 XH2(黄)20K3950 1.2M(铜)	Coil sensor 20K3950 (copper)	1	PC
16.6	16430007000018	传感器 XH2(蓝)20K3950 1.2M(铜)	Coil sensor 20K3950 (copper)	1	PC
16.7	16427001000010	端子板 5 位(600V 4mm2)AB	Terminal board	1	PC
16.8	16421038000081	ALDu-H42A4/R1DI 电控盒	Electrical control box	1	PC
17	16421005000192	ALDu-H18A4/R1 顶盖板	Top cover plate	1	PC

30000

N0.	GREEN code	Component description	Component description	Quantity	Unit
1	16324001000046	DLR-71F/DCZDGS3 蒸发器总成(内置)	Evaporatorassembly(build-in)	1	Set
1.1	16324009000024	GR-72D/DGS3 蒸发器组件	Evaporator components	1	Set
1.2	16325009000024	GR-72D/DGS3 蒸发器出气管组件	Evaporator gas outlet pipe components	1	Set
1.3	16325001000060	DLR-71F/DCZDGS3 蒸发器进液管组件(内置)	Evaporator liquid inlet pipe components(built-in)	1	Set
1.31	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	EXV body CAM-BD18FKS-1	1	PC
2	16421014000035	ALDu-H42A4/R1DI 阀板	Valve plate	1	PC
3	16421005000191	ALDu-H42A4/R1DI 电控盒盖	Electrical control box cover	1	PC
4	16421030000101	GR-51D/DGS3 出风法兰 A	Air outlet flange A	1	PC
5	16421030000102	GR-51D/DGS3 出风法兰 B	Air outlet flange B	1	PC
6	16421015000026	ALDu-H42A4/R1DI 排水管保护板 B	Drainpipe protection plate B	1	PC
7	16421015000025	ALDu-H42A4/R1DI 排水管保护板 A	Drainpipe protection plate A	1	PC
8	16321009000105	ALDu-H18A4/R1 凝水盘组件	Drip tray assembly	1	Set
9	16421005000318	ALDu-H18A4/R1 底板(新)	Chassis	1	PC
10	16421005000207	ALDu-H18A4/R1 回风盖板 A	Air return cover plate A	1	PC
	16421005000208	ALDu-H18A4/R1 回风盖板 B	Air return cover plate B	1	PC
11	16421040000024	ALDu-H42A4/R1DI 吊钩	Pothook	4	Pcs
12	16321001000018	DLR-90F/DCZDGS3 蜗壳固定板总成	Volute fixed plate assembly	1	Set
12.1	16421002000173	ALDu-H18A4/R1 蜗壳固定板	Volute fixed plate	1	PC
12.2	16321001000013	ALDu-H42A4/R1DI 电机架组件	Motor bracket assembly	1	Set
12.3	16430001000219	(ROHS)电机 YSK180-4	Fan motor	1	PC
12.4	16421029000010	GR-250D/G 电机抱攀	Fan motor fixity	2	Pcs
12.5	16346001000004	(ROHS)离心风轮组件 185/170	Centrifugal fan assembly	2	Sets
13	16442001000011	过滤器 6.35x 9.52-70(R410A)	Air filter	2	Pcs
14	/	过滤网滑道组件	Filter slideway assembly	1	Set
14.1	16321001000010	ALDu-H42A4/R1D 左右过滤器滑道组件	Left&Right slideway assembly	2	Sets
14.2	16321009000107	ALDu-H18A4/R 上下过滤滑道组件	Up&down slideway assembly	2	Sets
14.3	16421030000091	ALDu-H42A4/R1DI 左右过滤器法兰	Left&Right filter flange	2	Pcs
14.4	16421030000096	ALDu-H18A4/R1 上下过滤器法兰	Up&down filter flange	2	Pcs
15	16421010000025	ALDu-H18A4/R1 围板(新)	Coaming	1	PC
16	16322001000010	DLR-56F/DCZDGS3 控制器总成	Electrical control assembly	1	Set
16.1	16422001000078	控制板 DCZ-SN3F-HCE1	PCB board	1	PC
16.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer	1	PC
16.3	16430007000005	传感器 XH2(白)15K3950 0.9M(塑封)	Coil sensor 15K0.9M(plastic)	1	PC
16.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Coil sensor 20K1.2M(copper)	1	PC
16.5	16430007000016	传感器 XH2(黄)20K3950 1.2M(铜)	Coil sensor 20K1.2M(copper)	1	PC
16.6	16430007000018	传感器 XH2(蓝)20K3950 1.2M(铜)	Coil sensor 20K1.2M(copper)	1	PC
16.7	16427001000010	端子板 5 位(600V 4mm ²)AB	Terminal board	1	PC
16.8	16421038000081	ALDu-H42A4/R1DI 电控盒	Electrical control box	1	PC
17	16421005000192	ALDu-H18A4/R1 顶盖板	Top cover plate	1	PC


34000

NO.	GREEN code	Chinese name	Part Name	Quantity	Unit
1	16324001000051	DLR-100F/DCZDGS3 蒸发器总成(内置)	Evaporator assembly(build-in)	1	Set
1.1	16324009000024	GR-72D/DGS3 蒸发器组件	Evaporator components	1	Set
1.2	16325009000024	GR-72D/DGS3 蒸发器出气管组件	Evaporator gas outlet pipe components	1	Set
1.3	16325001000063	DLR-100F/DCZDGS3 蒸发器进液管组件(内置)	Evaporator liquid inlet pipe components(build-in)	1	Set
1.31	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	EXV body CAM-BD18FKS-1	1	PC
2	16421014000035	ALDu-H42A4/R1DI 阀板	Valve plate	1	PC
3	16421005000191	ALDu-H42A4/R1DI 电控盒盖	Electrical control box cover	1	PC
4	16421030000101	GR-51D/DGS3 出风法兰 A	Air outlet flange A	1	PC
5	16421030000102	GR-51D/DGS3 出风法兰 B	Air outlet flange B	1	PC
6	16421015000026	ALDu-H42A4/R1DI 排水管保护板 B	Drainpipe protection plate B	1	PC
7	16421015000025	ALDu-H42A4/R1DI 排水管保护板 A	Drainpipe protection plate A	1	PC
8	16321009000105	ALDu-H18A4/R1 凝水盘组件	Drip tray assembly	1	Set
9	16421005000318	ALDu-H18A4/R1 底板(新)	Chassis	1	PC
10	16421005000207	ALDu-H18A4/R1 回风盖板 A	Air return cover plate A	1	PC
	16421005000208	ALDu-H18A4/R1 回风盖板 B	Air return cover plate B	1	PC
11	16421040000024	ALDu-H42A4/R1DI 吊钩	Pothook	4	Pcs
12	16321009000133	(ROHS)ALHi-H36A5/S3 蜗壳固定板总成	Volute fixed plate assembly	1	Set
12.1	16421002000173	ALDu-H18A4/R1 蜗壳固定板	Volute fixed plate	1	PC
12.2	16321001000013	ALDu-H42A4/R1DI 电机架组件	Motor bracket assembly	1	Set
12.3	16430001000219	(ROHS)电机 YSK180-4	Fan motor	1	PC
12.4	16421029000010	GR-250D/G 电机抱攀	Fan motor fixity	2	Pcs
12.5	16346001000004	(ROHS)离心风轮组件 185/170	Centrifugal fan assembly	2	Sets
13	16442001000011	过滤器 6.35× 9.52-70(R410A)	Air filter	2	Pcs
14	/	过滤网滑道组件	Filter slideway assembly	1	Set
14.1	16321001000010	ALDu-H42A4/R1DI 左右过滤器滑道组件	Left&Right slideway assembly	2	Sets
14.2	16321009000107	ALDu-H18A4/R1 上下过滤滑道组件	Up&down slideway assembly	2	Sets
14.3	16421030000091	ALDu-H42A4/R1DI 左右过滤器法兰	Left&Right filter flange	2	Pcs
14.4	16421030000096	ALDu-H18A4/R1 上下过滤器法兰	Up&down filter flange	2	Pcs
15	16421010000025	ALDu-H18A4/R1 围板(新)	Coaming	1	PC
16	16322001000010	DLR-56F/DCZDGS3 控制器总成	Electrical control assembly	1	Set
16.1	16422001000078	控制板 DCZ-SN3F-HCE1	PCB board	1	PC
16.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer	1	PC
16.3	16430007000005	传感器 XH2(白)15K 0.9M(塑封)	Coil sensor 15K3950 (plastic)	1	PC
16.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Coil sensor 20K3950 (copper)	1	PC
16.5	16430007000016	传感器 XH2(黄)20K3950 1.2M(铜)	Coil sensor 20K3950 (copper)	1	PC

GREEN GRV High Static Pressure Duct Type

16.6	16430007000018	传感器 XH2(蓝)20K3950 1.2M(铜)	Coil sensor 20K3950 (copper)	1	PC
16.7	16427001000010	端子板 5 位(600V 4mm ²)AB	Terminal board	1	PC
16.8	16421038000081	ALDu-H42A4/R1DI 电控盒	Electrical control box	1	PC
17	16421005000192	ALDu-H18A4/R1 顶盖板	Top cover plate	1	PC

38000 TO 51000



38000 TO 48000

NO.	GREEN code	Chinese name	Part Name	Quantity	Unit
1	16324001000048	DLR-112F/DCZDGS3 蒸发器总成(内置)	Evaporator assembly(build-in)	1	Set
1.1	16324009000026	GR-120D/DGS3 蒸发器组件	Evaporator components	1	Set
1.2	16325004000088	GR-120D/DGS3 集气管组件	Evaporator gas header components	1	Set
1.3	16325001000062	DLR-112F/DCZDGS3 蒸发器进液管组件(内置)	Evaporator liquid inlet pipe components(build-in)	1	Set
1.31	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	EXV body CAM-BD24FKS-1	1	PC
2	16421014000035	ALDu-H42A4/R1DI 阀板	Valve plate	1	PC
3	16421005000191	ALDu-H42A4/R1DI 电控盒盖	Electrical control boxcover	1	PC
4	16421030000103	GR-120D/DGS3 出风法兰 A	Air outlet flange A	1	PC
5	16421030000104	GR-120D/DGS3 出风法兰 B	Air outlet flange B	1	PC
6	16421015000026	ALDu-H42A4/R1DI 排水管保护板 B	Drainpipe protection plate B	1	PC
7	16421015000025	ALDu-H42A4/R1DI 排水管保护板 A	Drainpipe protection plate A	1	PC
8	16321001000008	ALDu-H42A4/R1DI 凝水盘组件	Drip tray assembly	1	Set
9	16421005000317	ALDu-H42A4/R1DI 底板(新)	Chassis	1	PC
10	16421005000206	ALDu-H42A4/R1DI 回风盖板 A	Air return cover plate A	1	PC
	16421005000213	ALDu-H42A4/R1DI 回风盖板 B	Air return cover plate B	1	PC
11	16421040000024	ALDu-H42A4/R1DI 吊钩	Pothook	4	Pcs
12	16330009000016	GR-120D/GS2 风机总成	Fan assembly	1	Set
12.1	16421002000172	ALDu-H42A4/R1DI 蜗壳固定板	Volute fixed plate	1	PC
12.2	16321001000013	ALDu-H42A4/R1DI 电机架组件	Motor bracket assembly	1	Set

12.3	16430001000219	(ROHS)电机 YSK180-4	Fan motor	1	PC
12.4	16421029000010	GR-250D/G 电机抱攀	Fan motor fixity	2	Pcs
12.5	16444007000009	联轴器 14	Coupling	1	PC
12.6	16432016000033	GR-50D/DC2 橡胶轴承	Rubber bearing	1	PC
12.7	16421002000219	GR-50D/DC2 橡胶轴承压板	Rubber bearing holder	1	PC
12.8	16432016000036	橡胶轴承支架 ALDu-H42A4/R1DI	Rubber bearing bracket	1	PC
12.9	16444007000006	加长轴 14x470	Lengthening shaft	1	PC
12.10	16346001000004	(ROHS)离心风轮组件 185/170(塑料)	Centrifugal fan assembly	3	Sets
13	16321001000011	过滤网滑道组件	Filter slideway assembly	1	Set
13.1	16321001000010	ALDu-H42A4/R1DI 左右过滤器滑道组件	Left&Right slideway assembly	2	Sets
13.2	16321001000011	ALDu-H42A4/R1DI 上下过滤滑道组件	Up&down slideway assembly	2	Sets
13.3	16421030000091	ALDu-H42A4/R1DI 左右过滤器法兰	Left&Right filter flange	2	Pcs
13.4	16421030000092	ALDu-H42A4/R1DI 上下过滤器法兰	Up&down filter flange	2	Pcs
14	16442001000011	过滤器 6.35x 9.52-70(R410A)	Air filter	2	Pcs
15	16421010000024	ALDu-H42A4/R1DI 围板(新)	Coaming	1	PC
16	16322001000033	DLR-56F/DCZDGS3-Y 控制器总成	Electrical control assembly	1	Set
16.1	16422001000078	控制板 DCZ-SN3F-HCE1	PCB board	1	PC
16.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer	1	PC
16.3	16430007000005	传感器 XH2(白)15K3950 0.9M(塑封)	Coil sensor 15K3950 0.9M(plastic)	1	PC
16.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Coil sensor 20K3950 0.5M (copper)	1	PC
16.5	16430007000016	传感器 XH2(黄)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.6	16430007000018	传感器 XH2(蓝)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.7	16427001000010	端子板 5位(600V 4mm2)AB	Terminal board	1	PC
16.8	16321001000009	ALDu-H42A4/R1DI 电控盒组件	Electrical control box	1	Set
17	16421005000189	ALDu-H42A4/R1DI 顶盖板	Top cover plate	1	PC

51000

NO.	GREEN code	Chinese name	Part Name	Quantity	Unit
1	16324001000018	DLR-140F/DCZDGS3 蒸发器总成(内置)	Evaporator assembly(build-in)	1	Set
1.1	16324009000026	GR-120D/DGS3 蒸发器组件	Evaporator components	1	Set
1.2	16325004000088	GR-120D/DGS3 集气管组件	Evaporator gas header components	1	Set
1.3	16325001000014	DLR-140F/DCZDGS3 进液管组件(内置)	Evaporator liquid inletpipe components(build-in)	1	Set
1.31	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	EXV body CAM-BD24FKS-1	1	PC
2	16421014000035	ALDu-H42A4/R1DI 阀板	Valve plate	1	PC

3	16421005000191	ALDu-H42A4/R1DI 电控盒盖	Electrical control box cover	1	PC
4	16421030000103	GR-120D/DGS3 出风法兰 A	Air outlet flange A	1	PC
5	16421030000104	GR-120D/DGS3 出风法兰 B	Air outlet flange B	1	PC
6	16421015000026	ALDu-H42A4/R1DI 排水管保护板 B	Drainpipe protection plate B	1	PC
7	16421015000025	ALDu-H42A4/R1DI 排水管保护板 A	Drainpipe protection plate A	1	PC
8	16321001000008	ALDu-H42A4/R1DI 凝水盘组件	Drip tray assembly	1	Set
9	16421005000317	ALDu-H42A4/R1DI 底板(新)	Chassis	1	PC
10	16421005000206	ALDu-H42A4/R1DI 回风盖板 A	Air return cover plate A	1	PC
	16421005000213	ALDu-H42A4/R1DI 回风盖板 B	Air return cover plate B	1	PC
11	16421040000024	ALDu-H42A4/R1DI 吊钩	Pothook	4	Pcs
12	16330009000016	GR-120D/GS2 风机总成	Fan assembly	1	Set
12.1	16421002000172	ALDu-H42A4/R1DI 蜗壳固定板	Volute fixed plate	1	PC
12.2	16321001000013	ALDu-H42A4/R1DI 电机架组件	Motor bracket assembly	1	Set
12.3	16430001000219	(ROHS)电机 YSK180-4	Fan motor	1	PC
12.4	16421029000010	GR-250D/G 电机抱攀	Fan motor fixity	2	Pcs
12.5	16444007000009	联轴器 14	Coupling	1	PC
12.6	16432016000033	GR-50D/DC2 橡胶轴承	Rubber bearing	1	PC
12.7	16421002000219	GR-50D/DC2 橡胶轴承压板	Rubber bearing holder	1	PC
12.8	16432016000036	橡胶轴承支架 ALDu-H42A4/R1DI	Rubber bearing bracket	1	PC
12.9	16444007000006	加长轴 14x470	Lengthening shaft	1	PC
12.10	16346001000004	(ROHS)离心风轮组件 185/170(塑料)	Centrifugal fan assembly	3	Sets
13	16321001000011	过滤网滑道组件	Filter slideway assembly	1	Set
13.1	16321001000010	ALDu-H42A4/R1DI 左右过滤器滑道组件	Left&Right slideway assembly	2	Sets
13.2	16321001000011	ALDu-H42A4/R1DI 上下过滤滑道组件	Up&down slideway assembly	2	Sets
13.3	16421030000091	ALDu-H42A4/R1DI 左右过滤器法兰	Left&Right filter flange	2	Pcs
13.4	16421030000092	ALDu-H42A4/R1DI 上下过滤器法兰	Up&down filter flange	2	Pcs
14	16442001000013	过滤器 9.52x9.52-70	Air filter	2	Pcs
15	16421010000024	ALDu-H42A4/R1DI 围板(新)	Coaming	1	PC
16	16322001000010	DLR-56F/DCZDGS3 控制器总成	Electrical control assembly	1	Set
16.1	16422001000078	控制板 DCZ-SN3F-HCE1	PCB board	1	PC
16.2	16422005000009	(ROHS)变压器 TDB-14-B2B(PTC)	Transformer	1	PC
16.3	16430007000005	传感器 XH2(白)15K3950 0.9M(塑封)	Coil sensor 15K3950 0.9M(plastic)	1	PC
16.4	16430007000011	传感器 XH2(绿)20K3950 0.5M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.5	16430007000016	传感器 XH2(黄)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.6	16430007000018	传感器 XH2(蓝)20K3950 1.2M(铜)	Coil sensor 20K3950 1.2M(copper)	1	PC
16.7	16427001000010	端子板 5 位(600V 4mm ²)AB	Terminal board	1	PC
16.8	16321001000009	ALDu-H42A4/R1DI 电控盒组件	Electrical control box	1	Set
17	16421005000189	ALDu-H42A4/R1DI 顶盖板	Top cover plate	1	PC

12.Spare parts list

16000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Capacitor	11330010000055	R 风机电容 3.0μF/450VAC/70/2000h	1
Fan motor	16430001000218	(ROHS)电机 YSK100-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185x170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000013	缝制过滤网 850x245x6	1
Filter	16442001000011	过滤器 6.35x 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000053	ALDu-H18A4/R1 凝水盘	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

18000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000057	R 风机电容 4.0μF/450VAC/70/2000h	1
Capacitor	11330010000055	R 风机电容 3.0μF/450VAC/70/2000h	1
Fan motor	16430001000218	(ROHS)电机 YSK100-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185x170(白色)	1

Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000013	缝制过滤网 850×245×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000053	ALDu-H18A4/R1 凝水盘	1
The body of Electronic expansion valve	16441014000012	电子膨胀阀阀体 CAM-BD18FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

24000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000056	R 风机电容 3.5μF/450VAC/70/2000h	1
Capacitor	11330010000054	R 风机电容 2.5μF/450VAC/70/2000h	1
Fan motor	16430001000216	(ROHS)电机 YSK160-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185×170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000013	缝制过滤网 850×245×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000053	ALDu-H18A4/R1 凝水盘	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

28000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	11330010000056	R 风机电容 3.5 μ F/450VAC/70/2000h	1
Capacitor	11330010000054	R 风机电容 2.5 μ F/450VAC/70/2000h	1
Fan motor	16430001000216	(ROHS)电机 YSK160-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185x170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000013	缝制过滤网 850x245x6	1
Filter	16442001000011	过滤器 6.35x 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000053	ALDu-H18A4/R1 凝水盘	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

30000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	16430015000019	(ROHS)电容 8 μ F/450V a.c	1
Capacitor	11330010000058	R 风机电容 5.0 μ F/450VAC/70/2000h	1
Fan motor	16430001000219	(ROHS)电机 YSK180-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185x170(白色)	1

Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000013	缝制过滤网 850×245×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000053	ALDu-H18A4/R1 凝水盘	1
The body of Electronic expansion valve	16441014000013	电子膨胀阀阀体 CAM-BD22FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

34000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	16430015000019	(ROHS)电容 8μF/450V a.c	1
Capacitor	11330010000058	R 风机电容 5.0μF/450VAC/70/2000h	1
Fan motor	16430001000219	(ROHS)电机 YSK180-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185×170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000013	缝制过滤网 850×245×6	1
Filter	16442001000011	过滤器 6.35× 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000053	ALDu-H18A4/R1 凝水盘	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1

38000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	16430015000019	(ROHS)电容 8 μ F/450V a.c	1
Capacitor	11330010000059	R 风机电容 6.0 μ F/450VAC/70/2000h	1
Fan motor	16430001000219	(ROHS)电机 YSK180-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185x170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000012	缝制过滤网 1210x245x6	1
Filter	16442001000011	过滤器 6.35x 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000052	ALDu-H42A4/R1DI 凝水盘	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000006	加长轴 14x470	1
Shaft coupling	16444007000009	联轴器 14	1

42000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	16430015000019	(ROHS)电容 8 μ F/450V a.c	1
Capacitor	11330010000059	R 风机电容 6.0 μ F/450VAC/70/2000h	1
Fan motor	16430001000219	(ROHS)电机 YSK180-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1

GREEN GRV High Static Pressure Duct Type

Fan wheel	16444001000005	风轮 185x170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000012	缝制过滤网 1210x245x6	1
Filter	16442001000011	过滤器 6.35x 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000052	ALDu-H42A4/R1DI 凝水盘	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000006	加长轴 14x470	1
Shaft coupling	16444007000009	联轴器 14	1

48000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	16430015000019	(ROHS)电容 8μF/450V a.c	1
Capacitor	11330010000059	R 风机电容 6.0μF/450VAC/70/2000h	1
Fan motor	16430001000219	(ROHS)电机 YSK180-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185x170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000012	缝制过滤网 1210x245x6	1
Filter	16442001000011	过滤器 6.35x 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000052	ALDu-H42A4/R1DI 凝水盘	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000006	加长轴 14x470	1
Shaft coupling	16444007000009	联轴器 14	1

51000

PCB board	16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	1
Transformer	16422005000009	(ROHS)变压器 TDB-14-B2B	1
Terminal board	16427001000010	端子板 5位(600V 4mm2)AB	1
Capacitor	16430015000019	(ROHS)电容 8 μ F/450V a.c	1
Capacitor	11330010000059	R 风机电容 6.0 μ F/450VAC/70/2000h	1
Fan motor	16430001000219	(ROHS)电机 YSK180-4	1
Upper shell	16444002000007	上涡壳 185/170(白色)	1
Lower shell	16444002000008	下涡壳 185/170(白色)	1
temperature Sensor	16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	1
temperature Sensor	16430007000021	温度传感器 20K3950 XH2 绿 1.2m 铜壳 4(组件)	1
temperature Sensor	16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	1
temperature Sensor	16430007000016	温度传感器 20K3950 XH2 黄 1.2m 铜壳 3(组件)	1
Fan wheel	16444001000005	风轮 185x170(白色)	1
Wired controller	16422002000006	线控器 DCZ-XK-HCC1	1
Air Filter	16444013000012	缝制过滤网 1210x245x6	1
Filter	16442001000011	过滤器 6.35x 9.52-70(R410a)	2
Drain Pan/Condensate pan/Drain pump	16421034000052	ALDu-H42A4/R1DI 凝水盘	1
The body of Electronic expansion valve	16441014000003	电子膨胀阀阀体 CAM-BD24FKS-1	1
The coil of Electronic expansion valve	16441015000002	电子膨胀阀线圈 CAM-MD12FKS-5 L=1500	1
Longer shaft	16444007000006	加长轴 14x470	1
Shaft coupling	16444007000009	联轴器 14	1


High Static Pressure Duct Type

1. Features	308
2. Specifications	310
3. Dimension	314
4. Piping Diagram	316
5. Wiring Diagram	317
6. Electric characteristics	320
7. Capacity Tables	321
8. Fan performance	323
9. Sound Levels	324
10. Installation	327
11. Exploded View	330
12. Spare parts list	334

1.Features

(2) High External Static Pressure

External static pressure of Indoor Unit can be up to 196Pa, which allows extensive duct work for flexible applications, so the cool air can be delivered to every indoor corner even in a super-high ceiling. The max.distance of air supply is about 14m; the height of air supply is about 6.5m.



(2) Innovative air supply

The type of air supply and air return was set flexibly and appropriately. It provides homogeneous conditioning of the room temperature.


(3) Conceal design

The unit is installed inside of ceiling, doesn't take room space

(4) Setting or Auto two operation modes

Multi speed wind makes you feel more comfortable;

(5) Auto restart;



(6) Wired controller and remote controller and central controller can be available

(7) Special insulation design

Achieves high heat insulation efficiency and no condensation on shell

(8) with low ambient temperature cooling function

Makes the unit can run normally on the condition that the ambient temperature falls down to -15°C ;



(9) Failure automatic detection

If there is a failure, the indicator will flash and the failure code will display on the wired controller, the failure cause is easier to be found.

(10) Fresh air supply

Fresh air can be drawn in by the Indoor Unit, which can improve the Indoor Air Quality greatly.

(11) High capacity of cooling/heating, efficient, and energy-saving.

(12) It is suitable be used for office, hospital, commercial place and home, the air conditioner will create the comfortable and elegance environment for you.

2.Specifications

Model			IDGRV38P1/M	IDGRV42P1/M
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	11.2	12.5
	Heating	kW	12.8	13.3
Fan Motor	Model		YDF0.8-6	YDF0.8-6
	Brand		HUATE	HUATE
	Output Power	W	200	200
	Capacitor	uF	10	10
	Speed (Hi/Mi/Lo)	r/min	1230/1000/750	1230/1000/750
Coil	Number Of Row		3	3
	Tube Pitch(a)x Row Pitch(b)	mm	22.0x19.05	22.0x19.05
	Fin Pitch	mm	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7.94 Inner grooved	7.94 Inner grooved
	Coil Length x Height x Width	mm	900x352x54.2	900x352x54.2
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	20.69	20.69
	Noise Level(Hi/Mi/Lo)	dB(A)	2000/1600/1400	2000/1600/1400
	External Static Pressure	Pa	60/57/51	60/57/51
	Net Dimension (WxDxH)	mm	196	196
	Packing Dimension (WxDxH)	mm	1200x719x380	1200x719x380
	Net Weight	Kg	1235x760x415	1235x760x415
	Gross Weight	Kg	56	56
Refrigerant Pipe	Liquid Side	mm	59	59
	Gas Side	mm	9.52	9.52
	Drainage	mm	19.05	19.05
Operation Temperature Range		°C	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	50~75	50~90
Stuffing Quantity	20/40/40H	Unit	68/147/168	68/147/168

Notes:

1. Cooling Capacity:Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m,level difference : 0 m.
2. Heating Capacity:Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m,level difference : 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

GREEN GRV High Static Pressure Duct Type

Model			IDGRV48P1/M	IDGRV51P1/M
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	14.0	15.0
	Heating	kW	15.0	16.0
Fan Motor	Model		YDK200-4	YDK200-4
	Brand		HUATE	HUATE
	Output Power	W	200	200
	Capacitor	uF	10	10
	Speed (Hi/Mi/Lo)	r/min	1230/1000/750	1230/1000/750
Coil	Number Of Row		3	3
	Tube Pitch(a)x Row Pitch(b)	mm	22.0x19.05	22.0x19.05
	Fin Pitch	mm	1.6	1.6
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	7.94 Inner grooved	7.94 Inner grooved
	Coil Length x Height x Width	mm	900x352x54.2	900x352x54.2
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	2000/1600/1400	2000/1600/1400
	Noise Level(Hi/Mi/Lo)	dB(A)	60/57/51	60/57/51
	External Static Pressure	Pa	196	196
	Net Dimension (WxDxH)	mm	1200x719x380	1200x719x380
	Packing Dimension (WxDxH)	mm	1235x760x415	1235x760x415
	Net Weight	Kg	56	56
	Gross Weight	Kg	59	59
Refrigerant Pipe	Liquid Side	mm	9.52	9.52
	Gas Side	mm	19.05	19.05
	Drainage	mm	R3/4in(DN20)	R3/4in(DN20)
Operation Temperature Range		°C	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	60~100	65~110
Stuffing Quantity	20/40/40H	Unit	68/147/168	68/147/168

Notes:

1. Cooling Capacity:Indoor temp.27°C DB,19°C WB,outdoor temp.35°C DB,24°C WB /Equivalent piping length :7.5m,level difference : 0 m.
2. Heating Capacity:Indoor temp.20°C DB, outdoor temp.7°C DB,6°C WB /Equivalent piping length :7.5m,level difference : 0 m.
3. Anechoic chamber conversion value,measured in test room.During actual operation.These values are normally somewhat higher as a result of ambient conditions.
4. All the above specification will be changed due to product performance improvement. GREEN reserves the right to change product design without prior notice, everything should subject to parameter on nameplate.

GREEN GRV High Static Pressure Duct Type


Model			IDGRV76P1/M	IDGRV96P1/M
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	22.0	28.0
	Heating	kW	24.5	31.0
Fan Motor	Model		YF139-300-4A	YF139-300-4A
	Brand		Yilida	Yilida
	Output Power	W	300	300
	Capacitor	uF	10	10
	Speed (Hi/Mi/Lo)	r/min	1285/1217/1108	1285/1217/1108
Coil	Number Of Row		3	3
	Tube Pitch(a)x Row Pitch(b)	mm	25.4x22.0	25.4x22.0
	Fin Pitch	mm	1.8	1.8
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	9.52 Inner grooved	9.52 Inner grooved
	Coil Length x Height x Width	mm	1435x457x66	1435x457x66
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	4000/3200/2600	4000/3200/2600
	Noise Level(Hi/Mi/Lo)	dB(A)	60/55/53	60/56/54
	External Static Pressure	Pa	220	220
	Net Dimension (WxDxH)	mm	1755×915×645	1755×915×645
	Packing Dimension (WxDxH)	mm	1890×990×840	1890×990×840
	Net Weight	Kg	130	130
	Gross Weight	Kg	150	150
Refrigerant Pipe	Liquid Side	mm	9.52	9.52
	Gas Side	mm	19.05	19.05
	Drainage	mm	R1/1in(DN25)	R1/1in(DN25)
Operation Temperature Range		℃	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		℃	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	60~100	65~110
Stuffing Quantity	20/40/40H	Unit	68/147/168	68/147/168

GREEN GRV High Static Pressure Duct Type


Model			IDGRV150P3/M	IDGRV190P3/M
Power Supply		V~,Hz,Ph	380~415,50,3	380~415,50,3
Capacity	Cooling	kW	45.0	56.0
	Heating	kW	49.5	61.5
Fan Motor	Model		KT11-45No3.25All0.8KW-6	KT11-45No3.25All0.8KW-6
	Brand		Nantai	Nantai
	Output Power	W	800	800
	Capacitor	uF	/	/
	Speed (Hi/Mi/Lo)	r/min	900	900
Coil	Number Of Row		3	3
	Tube Pitch(a)x Row Pitch(b)	mm	25.4x22.0	25.4x22.0
	Fin Pitch	mm	1.8	1.8
	Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	Tube Outside Dia.and Material	mm	9.52 Inner grooved	9.52 Inner grooved
	Coil Length x Height x Width	mm	1800x762x66	1800x762x66
Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	8000	8000
	Noise Level(Hi/Mi/Lo)	dB(A)	63	63
	External Static Pressure	Pa	200	200
	Net Dimension (WxDxH)	mm	2115x990x855	2115x990x855
	Packing Dimension (WxDxH)	mm	2225x1025x1015	2225x1025x1015
	Net Weight	Kg	225	225
	Gross Weight	Kg	260	260
Refrigerant Pipe	Liquid Side	mm	12.7	12.7
	Gas Side	mm	22.2	22.2
	Drainage	mm	R1/1in(DN25)	R1/1in(DN25)
Operation Temperature Range		℃	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		℃	-5~52/-20~24	-5~52/-20~24
Application Area		m ²	60~100	65~110
Stuffing Quantity	20/40/40H	Unit	68/147/168	68/147/168

3.Dimension


38000 TO 51000



76000/96000




150000/191000




4.Piping Diagram

38000 TO 51000



76000 TO 191000




Refrigerant pipe connection port diameters

(mm)


model	Gas	Liquid
38000 TO 96000	19.05	9.52
150000/190000	22.2	12.7

5.Wiring Diagram


38000 TO 51000



76000/96000



150000/191000



Electric connection diagram indoor unit 164.370100000248

6. Electric characteristics

Model	Units				Power supply		IFM	
	Hz	Volts	Min	Max	MCA	MFA	KW	FLA
38000	50	220-240	198	264	5.5	30	0.4	4.4
42000	50	220-240	198	264	5.5	30	0.4	4.4
48000	50	220-240	198	264	5.5	30	0.4	4.4
51000	50	220-240	198	264	5.5	30	0.4	4.4
76000	50	220-240	198	264	9.3	30	0.6	7.4
96000	50	220-240	198	264	9.3	30	0.6	7.4
150000	50	380-415	342	418	5.8	30	1.6	4.6
190000	50	380-415	342	418	5.8	30	1.6	4.6

Symbols:

MCA: Min. Circuit Amps (A)

MFA: Max. Circuit Breaker Amps

KW: Fan Motor Rated Output(kW)

FLA: Full Load Amps (A)

IFM: Indoor Fan Motor

Note:

5. Min. and Max. Voltage: Units are suitable for use on electrical system where voltage supplied to unit terminals is not below or above listed range limits.
6. Maximum allowable voltage unbalance between phases is 2%.
7. $MCA = 1.25 \times FLA$
Select wire size based on the MCA.

7.Capacity Tables

Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient


Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature [°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.10	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1.0	1.06	1.13
	Power	0.96	0.97	1.0	1.01	1.03
40	Cooling capacity	0.83	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.90	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.80	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32

Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb [°C]	capacity/power correction	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.70
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1.0	0.96
	Power	0.94	1.0	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07
	Power	1.05	1.11	1.17

15-24	Heating capacity	0.85 – 1.05 of nominal
	Power	0.80 – 1.20 of nominal

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube



Positive side of high head means installation height of outdoor unit should be higher than indoor unit; negative side of high head means installation height of outdoor unit should be lower than indoor unit; (change ratio of basic capacity)

8.Fan performance


38000 TO 51000			
Static Pressure	Air Volume(m³/h)		
(Pa)	High	Mid	Low
0	3345	3095	2845
10	3340	3090	2840
20	3330	3080	2830
30	3310	3060	2810
40	3280	3030	2780
50	3240	2990	2740
60	3200	2950	2700
70	3150	2900	2650
80	3100	2850	2600
90	3040	2790	2540
100	2980	2730	2480
110	2910	2660	2410
120	2840	2590	2340
130	2760	2510	2260
140	2665	2415	2165
150	2560	2310	2060
160	2470	2220	1970
170	2370	2120	1870
180	2270	2020	1770
190	2150	1900	1650
200	2000	1750	1500
210	1800	1550	1300
220	1500	1250	1000
230	1200	950	700
240	800	550	300
250	300	/	/

Warning!


In order to ensure the use reliability of the wind turbine, the requirements set in installation and use of static pressure in the range of 120-220Pa. The data curve as follows:

76000/96000		
Static Pressure	Air Volume	FLA
(Pa)	m3/h	A
0	4927	7.25
10	4885	7.10
20	4832	7.01
30	4789	6.96
40	4741	6.87
50	4734	6.69
60	4728	6.59
70	4682	6.52
80	4618	6.45
90	4574	6.35
100	4521	6.30
110	4479	6.23
120	4404	6.13
130	4371	6.07
140	4287	5.97
150	4233	5.89
160	4148	5.78
170	4084	5.68
180	3991	5.58
190	3938	5.51
200	3856	5.41
210	3814	5.30
220	3780	5.21
230	3742	5.10
240	3701	5.01
250	3656	4.89

150000/190000		
Static Pressure	Air Volume	FLA
Pa	m ³ /h	A
0	11537	5.11
10	11416	5.07
20	11286	5.02
30	11154	4.97
40	11013	4.91
50	10883	4.87
60	10735	4.82
70	10610	4.77
80	10410	4.72
90	10279	4.68
100	10149	4.63
110	10011	4.59
120	9822	4.54
130	9681	4.47
140	9486	4.41
150	9333	4.34
160	9099	4.29
170	8920	4.23
180	8730	4.18
190	8553	4.12
200	8323	4.06



9.Sound Levels




Note:

1. The operating condition are assumed to be at standard (JIS Condition).
 2. These operating values were obtained in a dead room (conversion values).
- Sound level will vary depending on a range of factors such as the construction (acoustic absorption coefficient) of the particular room in which the equipments installed.

Model	220~240V 50Hz		
	H	M	L
38000	60	57	51
42000	60	57	51
48000	60	57	51
51000	60	57	51
76000	60	55	53
96000	60	56	54
Model	380~415V 50Hz		
150000	63		
190000	63		

10. Installation

10.1 The distance between indoor unit and obstacle



10.2 Suspension unit

◇ Select the suspension foundation

The suspension foundation is a structure of either wooden frame or reinforced concrete. It must be firm and reliable to bear at least 4 times weight of itself and capable of bearing vibration for long periods;


◇ Fixing of suspension foundation

Fix the suspension bolts either as shown in the picture or by a steel or wooden bracket;

◇ Adjust the relative positions of the suspension hooks to ensure the indoor unit is level in all directions. Use a spirit level to ensure this, otherwise water leakage, air leakage etc. will be resulted;


◇ Tighten the nuts and ensure that the hooks are tightly connected to the nuts and shims, and there is no phenomenon of virtual hanging;

◇ After the unit is installed ensure it is secure and does not shake or sway.




10.4 Duct pipeline installation

◇ Using canvas to connect between indoor unit and duct pipeline, in order to save unnecessary vibration, as to the detail connection method please refer to the following picture.



10.5 Drainage pipe installation


◇ Drainage pipes must be wrapped with heat insulation materials, otherwise it will cause frost or droplets, see picture as follows:



Notice:

Heat insulation material: rubber insulation pipe with the thickness of more than 8mm


◇ Drainage pipe must have a downward gradient (1/50--1/100). If the drain pipe is installed ups and downs, it will cause water backflow or leakage etc.



◇ When finish installation please carry out the drainage test to ensure that the water flow through the pipeline fluently, and carefully observe the junction to ensure that there is no water leakage at the junction. If the unit is installed in the newly built house, strongly recommend that this test taken before the ceiling installation. Even it is the heating only unit, this test is unavoidable.

10.6 Remote controller receiver installation.

◇ Installation site: recommend that the receiver is mounted with the distance of 30~50 cm to the indoor unit air outlet (on your choice as well), while must ensure that the receiver can get the signal that the remote controller sends, please refer to the following installation picture:




Notes:

The remote control signal effectively work for straight line from 8 meters, when the battery after the power consumption, effective work will shorten the distance.

◇ Mounting hole set up: please use certain instrument to dig a square hole with 88x88mm on the ceiling

◇ Remote controller receiver installation.


Hold the two sides (with clip sides) of the receiver, set the spring clip in the vertical way then put it into the mounting hole, if the two sides of the receiver is in the same level with the ceiling the installation is finished.



◇ Signal line connection: connect the wire of remote controller receiver to the CN-DISP terminal board on PCB of indoor unit wire box then fix it.

11.Exploded View


38000 TO 51000



38000 TO 51000

NO.	GREEN code	Chinese name	Part Name	Quantity	Unit
1	16421032000042	空气过滤门 1	Air filtration door1	2	Pcs
2	16421023000032	进风框竖条	Into wind box erect bar	2	Pcs
3	16421001000186	侧板左连接板	Endplates left linking slab	1	Pc
4	16421005000120	顶盖板	Top cover	1	Pc
5	16421001000184	左侧板	Left board	1	Pc
6	16444005000003	离心风轮组件 SYZ7-7I	Centrifugal rotor components SYZ7-7I	2	Sets
7	16321009000091	风机固定架组件	Fan fixed frame components	2	Sets
7.1	16421002000094	风机固定条	Fan stents	2	Pcs
7.2	16445999000015	六角头螺栓(不锈钢)M6*20 GB5783	Hexagon bolts (stainless steel) M6*20 GB5783	8	Pcs
8	16432011000001	帆布软接	Canvas soft connect	2	Pcs
9	16421004000114	出风面板	The wind panel	1	Pc
10	16421030000085	出风法兰 A	Exhaust flange A	2	Pcs
11	16421030000087	出风法兰 B	Exhaust flangeB	4	Pcs
12	16321009000097	底盘组件	Chassis components	1	Set
12.1	16421027000009	底脚	Bottom feet	4	Pcs
12.2	16421028000049	底盘	Chassis	1	Pc
12.3	16445999000015	六角头螺栓(不锈钢)M6*20 GB5783	Hexagon bolts (stainless steel) M6*20 GB5783	8	Pcs
13	16430001000126	电机 YDK200-4	Motor YDK200-4	2	Pcs
14	16421001000185	右侧板	Right board	1	Pc
15	16322009000035	电控盒总成	Electric control box assembly	1	Set
15.1	16421038000036	电控盒盖	Electric control box incautiously	1	Pc
15.2	16421005000122	电控盒底板	Electric control box floor	1	Pc
15.3	11222009001192	R控制板 FGJ(H)-RQD-3F-SYE2	R panel FGJ (H) - RQD - 3F - SYE2	1	Pc
15.4	16430007000046	传感器 5K3470 XH2 0.6m(铜壳)	Sensor 5K3470 XH2 0.6 m (copper)	1	Pc
15.5	16430007000102	传感器 5K3470 XH2 1.2m(塑封)	XH2 1.2 m (5K3470 encapsulation)	1	Pc
15.6	16427001000003	端子板 5位(600V 4mm2)IV	Terminal board 5 (600V 4mm2) IV	1	Pc
15.7	16430015000012	(ROHS)电容 10Uf/450V AC	(ROHS) 10Uf / 450V AC capacitance	2	Pcs
15.8	16422005000017	(ROHS)变压器 TDB-8-B(PTC)	(ROHS) transformer TDB-large - 8 - B (PTC)	2	Pcs
16	16421014000020	阀板	disc	1	Pc
17	16421034000047	接水盘	Wet pan	1	Pc
18	16324009000049	蒸发器总成	Evaporator assembly	1	Set
18.1	16324009000050	蒸发器组件	Evaporator components	1	Set
18.2	16325009000070	蒸发器铜管套件	Evaporator brass suite	1	Set
19	16421001000187	侧板右连接板	Endplates right linking slab	1	Pc
20	16444013000006	空气过滤器	Air filter	1	Pc
21	16321009000090	滑槽组件 1	Sliding channel component 1	2	Sets
21.1	16421032000054	滑槽	Sliding channel	2	Pcs
21.2	16421023000022	进风框横条	Into wind box stripes	2	Pcs
22	16421023000022	电子膨胀阀	33 EXV	1	Pc


76000/96000



76000/96000

N0.	GREEN code	Chinese name	Part Name	Quantity	Unit
1	16321009000068	顶盖板	Top cover	1	Pc
2	16321001000029	出风面板组件	The wind panel	1	Pc
3	16321004000023	检修板组件 B	Repair board components B	2	Pc
4	16444005000171	离心风轮组件 SYZ8-8l	Centrifugal rotor components SYZ8-8l	2	Sets
5	16321009000067	右侧板组件	Right board component	1	Set
6	16324001000104	蒸发器总成	Evaporator assembly	1	Set
7	16421023000018	进风框竖条 A	Into wind box erect bar A	2	Pcs
8	16321009000070	进风框横条组件	Into wind box stripes components	2	Sets
9	16421028000073	底盘	Chassis	1	Pc
10	16421022000081	底脚	Bottom feet	2	Pcs
11	16321001000030	出风框组件	out wind box stripes component	1	Set
12	16322001000069	电控盒总成	Electric control box assembly	1	Set
13	16321009000071	阀板组件	disc component	1	Set
14	16421002000311	风机固定架	Fan stents	2	Pcs
15	16321009000054	风机固定架组件	Fan fixed frame components	2	Sets
16	16331001000041	接水盘组件	Wet pan component	1	Pc

150000/190000



N0.	GREEN code	Chinese name	Part Name	Quantity	Unit
1	16321009000084	顶盖板组件	Top cover components	1	Pc
2	16321009000083	出风面板组件	The wind panel	1	Pc
3	16321004000024	检修板组件	Repair board components	2	Pc
4	16444005000027	离心风机组件	Centrifugal rotor components	2	Sets
5	16321009000076	右侧板组件	Right board component	1	Set
6	16324001000102	蒸发器总成	Evaporator assembly	1	Set
7	16421023000013	进风框竖条 A	Into wind box erect bar A	2	Pcs
8	16321009000085	进风框横条组件	Into wind box stripes components	2	Sets
9	16421028000046	底盘	Chassis	1	Pc
10	16421027000008	底脚	Bottom feet	2	Pcs
11	16321009000041	出风框组件	out wind box stripes component	1	Set
12	16322001000078	电控盒总成	Electric control box assembly	1	Set
13	16321009000060	阀板组件	disc component	1	Set
14	16421026000102	风机固定架	Fan stents	2	Pcs
15	16321009000054	风机固定架组件	Fan fixed frame components	2	Sets
16	16331001000045	接水盘组件	Wet pan component	1	Pc

12.Spare parts list

38000/51000

GREEN code	Chinese name	Part Name	Quantity
16421032000042	空气过滤门 1	Air filtration door1	2
16421023000032	进风框竖条	Into wind box erect bar	2
16444005000003	离心风轮组件 SYZ7-7I	Centrifugal rotor components SYZ7-7I	2
16421004000114	出风面板	The wind panel	1
16421030000085	出风法兰 A	Exhaust flange A	2
16421030000087	出风法兰 B	Exhaust flangeB	4
16430001000126	电机 YDK200-4	Motor YDK200-4	2
11222009001192	R 控制板 FGJ(H)-RQD-3F-SYE2	R panel FGJ (H) - RQD - 3F - SYE2	1
16430007000046	传感器 5K3470 XH2 0.6m(铜壳)	Sensor 5K3470 XH2 0.6 m (copper)	1
16430007000102	传感器 5K3470 XH2 1.2m(塑封)	XH2 1.2 m (5K3470 encapsulation)	1
16427001000003	端子板 5 位(600V 4mm2)IV	Terminal board 5 (600V 4mm2) IV	1
16430015000012	(ROHS)电容 10Uf/450V AC	(ROHS) 10Uf / 450V AC capacitance	2
16422005000017	(ROHS)变压器 TDB-8-B(PTC)	(ROHS) transformer TDB-large - 8 - B (PTC)	2
16421034000047	接水盘	Wet pan	1
16444013000006	空气过滤器	Air filter	1
16321009000090	滑槽组件 1	Sliding channel component 1	2
16421032000054	滑槽	Sliding channel	2
16421023000022	进风框横条	Into wind box stripes	2
16421023000022	电子膨胀阀	EXV	1

76000/96000

GREEN code	Chinese name	Part Name	Quantity
16421023000018	进风框竖条	Into wind box erect bar	2
16444005000171	离心风轮组件 SYZ8-8I	Centrifugal rotor components SYZ8-8I	2
16421004000267	出风面板	The wind panel	1
16422001000092	控制板 DCZ-SN3F-SYE2(R8C)	panel DCZ-SN3F-SYE2(R8C)	1
16430007000018	温度传感器 20K3950 XH2 蓝 1.2m 铜壳 2(组件)	Sensor 20K3950XH2 1.2 m (copper2)	1
16430007000005	温度传感器 15K3950 XH2 白 0.9m 塑封 1(组件)	XH2 0.9 m (15K3950 encapsulation)	1
16427001000010	端子板 5 位(600V 4mm2)AB	Terminal board 5 (600V 4mm2) AB	1
16430015000012	(ROHS)电容 10Uf/450V AC	(ROHS) 10Uf / 450V AC capacitance	2
16422005000009	(ROHS)变压器 TDB-14-B2B	(ROHS) transformer TDB-large - 14 – B2B	2
16421034000045	接水盘	Wet pan	1
16444013000039	空气过滤器	Air filter	1
16421032000039	滑槽	Sliding channel	2
16421023000017	进风框横条	Into wind box stripes	2
16441014000003	电子膨胀阀	EXV	2

150000/190000

GREEN code	Chinese name	Part Name	Quantity
16421023000013	进风框竖条 A	Into wind box erect barA	2
16444005000027	离心风机组件	Centrifugal rotor components	2
16421004000112	出风面板	The wind panel	1
11222047000031	CJR 控制板 DCZ-SN3F(R8C)-SYE2	CJR panel DCZ-SN3F(R8C)-SYE2	1
16430007000018	传感器 20K3950 XH2 蓝 1.2m 铜壳 2	Sensor 20K3950 XH2 1.2 m (copper 2)	1
16430007000005	传感器 15K3950 XH2 白 0.9m 塑封 1	Sensor 15K3950 XH20.9m (encapsulation1)	1
16427001000059	(ROHS)端子板 7 位(600V 4mm2)	Terminal board 7 (600V 4mm2)	1
16422005000009	(ROHS)变压器 TDB-14-B2B	(ROHS) transformer TDB-14-B2B	2
16421034000059	接水盘	Wet pan	1
16444013000041	空气过滤器 1848×774×10	Air filter 1848×774×10	1
16421032000041	滑槽	Sliding channel	2
16421023000021	进风框横条	Into wind box stripes	2
16441014000015	电子膨胀阀阀体 DPF(Q)3.2(R410a)	EXV DPF(Q)3.2(R410a)	1


Fresh Air Processing Unit

1. Features	338
2. Specifications	340
3. Dimension	342
4. Piping Diagram	343
5. Wiring Diagram	344
6. Electric characteristics	346
7. Capacity Tables	347
8. Sound Levels	349
9. Installation.....	350

1. Features


(1) 100% Fresh air processing units

Indoor units and fresh air units can be connected to the same GRV system, increase design flexibility and greatly reduce total system costs.




(2) High External Static Pressure

External static pressure of Indoor Unit can be up to 220Pa, which allows extensive duct work for flexible applications, so the cool air can be delivered to every indoor corner even in a super-high ceiling. The max.distance of air supply is about 16m; the height of air supply is about 6.5m.



(2) Innovative air supply


The type of air supply and air return was set flexibly and appropriately. It provides homogeneous conditioning of the room temperature.



(3) Setting or Auto two operation modes

Multi speed wind makes you feel more comfortable;

(4) Auto restart;



(5) Wired controller and remote controller and central controller can be available

(6) Special insulation design

Achieves high heat insulation efficiency and no condensation on shell

(7) with low ambient temperature cooling function

Makes the unit can run normally on the condition that the ambient temperature falls down to -15°C ;



(8) Failure automatic detection

If there is a failure, the indicator will flash and the failure code will display on the wired controller, the failure cause is easier to be found.

(9) High capacity of cooling/heating, efficient, and energy-saving.

(10) It is suitable to be used for office, hospital, commercial place and home, the air conditioner will create the comfortable and elegant environment for you.

2. Specifications

Model	Indoor		IDFAGRV76P1	IDFAGRV96P1
Power Supply		V~,Hz,Ph	220~240,50,1	220~240,50,1
Capacity	Cooling	kW	22.0	28.0
	Heating	kW	24.5	31.0
Indoor Fan Motor	Model		SYZ-9-4II0.15KW-4	SYZ-9-4II0.15KW-4
	Brand		Yilida	Yilida
	Output Power	W	150	150
	Capacitor	uF	10	10
	Speed (Hi/Mi/Lo)	r/min	/	/
Indoor Coil	a.Number Of Row		3	3
	b.Tube Pitch(a)x Row Pitch(b)	mm	25.4*22	25.4*22
	c.Fin Pitch	mm	1.8	1.8
	d.Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	e.Tube Outside Dia.And Material	mm	9.52, Inner grooved	9.52, Inner grooved
	g.Heat Exchanging Area	m ²	/	/
	Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	2800
Noise Level(Hi/Mi/Lo)		dB(A)	44	45
External Static Pressure		Pa	220	220
Net Dimension (WxDxH)		mm	1755x915x645	1755x915x645
Packing Dimension (WxDxH)		mm	1890x990x840	1890x990x840
Net Weight		Kg	110	110
Gross Weight		Kg	130	130
Refrigerant Pipe	Liquid Side	mm	9.52	9.52
	Gas Side	mm	19.05	19.05
	Drainage	mm	R1in(DN25)	R1in(DN25)
Operation Temperature Range	°C	16~32	16~32	
Ambient Temperature Range(Cooling/Heating)	°C	-5~52/-20~24	-5~52/-20~24	
Stuffing Quantity	20/40/40H	Unit	12/24/36	12/24/36

Notes:

- 1.Cooling Capacity: Indoor temperature 27°C DB/19°C WB;Outdoor temperature:35°C DB/24°C WB.
- 2.Heating Capacity:Indoor temperature 20°C DB;Outdoor temperature:7°C DB/6°C WB.
- 3.Piping Length:Equivalent piping length:7.5m,level difference:0m.
- 4.Sound level is measured at 1.4m from the air outlet
- 5.The above designs and specifications are subject to change of product improvement without prior notice.

Connection Conditions:

The following restrictions must be observed in order to maintain the indoor units connected to the same system.

When outdoor-air processing units are connected,the total connection capacity must be within 50% to 100% of that of the outdoor units.

When outdoor-air processing units are standard indoor unigs are connected,the total connection capacity of the outdoor-processing units must not exceed 30% of that of the outdoor units.

Outdoor-air processing units can be used without indoor units.

Model	Indoor		IDFAGRV150P1	IDFAGRV190P1
Power Supply		V~,Hz,Ph	380~415,,50,3	380~415,,50,3
Capacity	Cooling	kW	45.0	56.0
	Heating	kW	49.5	61.5
Indoor Fan Motor	Model		SYB-225II0.45KW-4	SYB-225II0.45KW-4
	Brand		Yilida	Yilida
	Output Power	W	450	450
	Capacitor	uF	/	/
	Speed (Hi/Mi/Lo)	r/min	/	/
Indoor Coil	a.Number Of Row		3	3
	b.Tube Pitch(a)x Row Pitch(b)	mm	25.4*22	25.4*22
	c.Fin Pitch	mm	1.8	1.8
	d.Fin Material		Hydrophilic aluminum fin	Hydrophilic aluminum fin
	e.Tube Outside Dia.And Material	mm	9.52, Inner grooved	9.52, Inner grooved
	g.Heat Exchanging Area	m ²	75.98	91.17
Indoor Unit	Indoor Air Flow (Hi/Mi/Lo)	m ³ /h	4000	5000
	Noise Level(Hi/Mi/Lo)	dB(A)	57	59
	External Static Pressure	Pa	220	220
	Net Dimension (WxDxH)	mm	1820x990x855	2115×990×855
	Packing Dimension (WxDxH)	mm	1935 x 1025 x 1015	2225 x 1025 x 1015
	Net Weight	Kg	150	225
	Gross Weight	Kg	170	255
Refrigerant Pipe	Liquid Side	mm	12.7(1/2)x2	12.7(1/2)x2
	Gas Side	mm	22.2(7/8)x2	22.2(7/8)x2
	Drainage	mm	R1in(DN25)	R1in(DN25)
Operation Temperature Range		°C	16~32	16~32
Ambient Temperature Range(Cooling/Heating)		°C	-5~52/-20~24	-5~52/-20~24
Stuffing Quantity	20/40/40H	Unit	12/24/24	12/24/24

Notes:

- 1.Cooling Capacity: Indoor temperature 27°CDB/19°CWB;Outdoor temperature:35°CDB/24°CWB.
- 2.Heating Capacity:Indoor temperature 20°CDB;Outdoor temperature:7°CDB/6°CWB.
- 3.Piping Length:Equivalent piping length:7.5m,level difference:0m.
- 4.Sound level is measured at 1.4m from the air outlet
- 5.The above designs and specifications are subject to change of product improvement without prior notice.

Connection Conditions:


The following restrictions must be observed in order to maintain the indoor units connected to the same system.
When outdoor-air processing units are connected,the total connection capacity must be within 50% to 100% of that of the outdoor units.

When outdoor-air processing units are standard indoor unigs are connected,the total connection capacity of the outdoor-processing units must not exceed 30% of that of the outdoor units.

Outdoor-air processing units can be used without indoor units.

3. Dimension


76000 TO 190000



Model	A	B	C	D	E	F	H	J	K	L	M	N	P
76000	1655	915	645	715	1755	1715	1545	610	1105	305	300	365	445
96000	1655	915	645	715	1755	1715	1545	610	1105	305	300	365	445
150000	1710	990	855	770	1820	1780	1610	830	1200	265	350	325	440
190000	2020	990	855	770	2120	2080	1910	830	1260	310	380	370	440

4. Piping Diagram

◇ 76000 TO 190000




Refrigerant pipe connection port diameters

(mm)


model	Gas	Liquid
76000/96000	19.05	9.52
150000/190000	22.2	12.7

5. Wiring Diagram

76000/96000



150000/190000



6. Electric characteristics

Units				
Model	Hz	Volts	Min	Max
76000	50	220-240	198	264
96000	50	220-240	198	264
150000	50	380-415	342	418
190000	50	380-415	342	418

Note:

1. Min. and Max. Voltage: Units are suitable for use on electrical system where voltage supplied to unit terminals is not below or above listed range limits.
2. Maximum allowable voltage unbalance between phases is 2%.

7. Capacity Tables

Cooling Capacity of Outdoor Dry Bulb Temperature and Indoor Dry/Wet Bulb Temperature or Power Consumption Correction Coefficient

Outdoor dry bulb temperature [°C]	Correction coefficient	Indoor dry/wet bulb temperature [°C]				
		22/15	24/17	27/19	29/21	32/23
-15~20	Cooling capacity	80 - 110 % of nominal				
	Power	25 - 50 % of nominal				
25	Cooling capacity	0.97	1.03	1.10	1.16	1.22
	Power	0.78	0.79	0.81	0.82	0.84
30	Cooling capacity	0.92	0.98	1.05	1.11	1.17
	Power	0.88	0.89	0.91	0.92	0.93
35	Cooling capacity	0.87	0.94	1.0	1.06	1.13
	Power	0.96	0.97	1.0	1.01	1.03
40	Cooling capacity	0.83	0.89	0.95	1.02	1.08
	Power	1.05	1.07	1.08	1.09	1.11
45	Cooling capacity	0.77	0.84	0.90	0.96	1.02
	Power	1.16	1.18	1.19	1.2	1.23
50	Cooling capacity	0.75	0.80	0.86	0.91	0.98
	Power	1.24	1.27	1.28	1.3	1.32


Heating Capacity of Outdoor Dry/Wet Bulb Temperature and Indoor Dry Bulb Temperature or Power Consumption Correction Coefficient

Outdoor ambient temperature of dry/wet bulb [°C]	capacity/power correction	Indoor back temperature of dry bulb [°C]		
		15	20	25
-20/-21	Heating capacity	0.58	0.53	0.49
	Power	0.50	0.56	0.62
-15/-16	Heating capacity	0.64	0.59	0.55
	Power	0.60	0.66	0.72
-10/-12	Heating capacity	0.71	0.66	0.62
	Power	0.72	0.78	0.84
-7/-8	Heating capacity	0.76	0.72	0.67
	Power	0.81	0.87	0.93
-1/-2	Heating capacity	0.79	0.74	0.70
	Power	0.86	0.92	0.98
2/1	Heating capacity	0.81	0.76	0.72
	Power	0.89	0.95	1.01
7/6	Heating capacity	1.04	1.0	0.96
	Power	0.94	1.0	1.06
10/9	Heating capacity	1.1	1.06	1.01
	Power	0.99	1.05	1.11
15/12	Heating capacity	1.16	1.12	1.07
	Power	1.05	1.11	1.17


15-24	Heating capacity	0.85 – 1.05 of nominal
	Power	0.80 – 1.20 of nominal

Length Correction Coefficient of Indoor/Outdoor Unit Connecting Tube

High head(m)




High head(m)



Positive side of high head means installation height of outdoor unit should be higher than indoor unit;
 negative side of high head means installation height of outdoor unit should be lower than indoor unit;
 (change ratio of basic capacity)

8. Sound Levels




Note:

3. The operating condition are assumed to be standard(JIS Condition).
4. These operating values were obtained in a dead room (conversion values).
Sound level will vary depending on a range of factors such as the construction (acoustic absorption efficient) of the particular room in which the equipment installed.

Model	220~240V 50Hz
76000	44
96000	45
Model	380~415V 50Hz
150000	57
190000	59

9. Installation

9.1 The distance between indoor unit and obstacle



9.2 Suspension unit

◇ Select the suspension foundation

The suspension foundation is a structure of either wooden frame or reinforced concrete. It must be firm and reliable to bear at least 4 times weight of itself and capable of bearing vibration for long periods;


◇ Fixing of suspension foundation

Fix the suspension bolts either as shown in the picture or by a steel or wooden bracket;

◇ Adjust the relative positions of the suspension hooks to ensure the indoor unit is level in all directions. Use a spirit level to ensure this, otherwise water leakage, air leakage etc. will be resulted;


◇ Tighten the nuts and ensure that the hooks are tightly connected to the nuts and shims, and there is no phenomenon of virtual hanging;

◇ After the unit is installed ensure it is secure and does not shake or sway.




9.3 Duct pipeline installation

◇ Using canvas to connect between indoor unit and duct pipeline, in order to save unnecessary vibration, as to the detail connection method please refer to the following picture.



9.4 Drainage pipe installation


◇ Drainage pipes must be wrapped with heat insulation materials, otherwise it will cause frost or droplets, see picture as follows:



Notice:

Heat insulation material: rubber insulation pipe with the thickness of more than 8mm


◇ Drainage pipe must have a downward gradient (1/50--1/100). If the drain pipe is installed ups and downs, it will cause water backflow or leakage etc.



◇ When finish installation please carry out the drainage test to ensure that the water flow through the pipeline fluently, and carefully observe the junction to ensure that there is no water leakage at the junction. If the unit is installed in the newly built house, strongly recommend that this test taken before the ceiling installation. Even it is the heating only unit, this test is unavoidable.

9.5 Remote controller receiver installation.

◇ Installation site: recommend that the receiver is mounted with the distance of 30~50 cm to the indoor unit air outlet (on your choice as well), while must ensure that the receiver can get the signal that the remote controller sends, please refer to the following installation picture:




Notes:

The remote control signal effectively work for straight line from 8 meters, when the battery after the power consumption, effective work will shorten the distance.

◇ Mounting hole set up: please use certain instrument to dig a square hole with 88x88mm on the ceiling

◇ Remote controller receiver installation.

Hold the two sides (with clip sides) of the receiver, set the spring clip in the vertical way then put it into the mounting hole, if the two sides of the receiver is in the same level with the ceiling the installation is finished.




◇ Signal line connection: connect the wire of remote controller receiver to the CN-DISP terminal board on PCB of indoor unit wire box then fix it.

Part 4 Installation of outdoor units

1.Preparation on installation	354
2. Installation of Outdoor Unit.....	356
3. Installation of refrigerant auxiliary pipe	359
4.Additional refrigerant and lubrication oil.....	372
5. Insulation	373
6. Electrical connection.....	374

1.Preparation on installation

1.1 Installation procedure



1.2 Preparation and Tools before Installation

◇Please buy the following parts from the market before installation

Hanging bolt (4 per unit)
PVC drain pipe
Some cable ties
Connecting copper tube
Branch manifold (choose according to actual installation situation)
Thermal insulation materials for connecting copper tube (PEF foaming materials with thickness above 8mm)
Power cord and power connection line (it's required to wire according to requirement for line diameter in wiring diagram)

Note:

Due to the difference between the characteristics of R410A and R22 refrigerant, it's necessary to use dedicated tools of R410A for some tools during installation.

- ◇ The selected position hanging indoor unit should be able to support the weight of unit without noise and additional vibration. It's necessary to reinforce before installation if reinforcement is required;
- ◇ The space of selected ceiling should be enough for holding indoor unit;
- ◇ The installation location should be easy for drainage;
- ◇ It shouldn't be installed in places (such as kitchen, laundry and mechanical workshop, etc.) of heat source, vapor source and more oil mist to prevent degradation of heat exchanger, electric shock and unit damage caused by plastic parts corrosion;
- ◇ Install in the place at least one meter away from TV and radio to prevent interfering TV and radio.
- ◇ There is no barrier blocking ventilation nearby and cold air should be able to evenly distribute to each indoor corner;
- ◇ There should be certain spacing between the surrounding and barrier of indoor unit to ease maintenance;
- ◇ The unit uses R410A environment-friendly refrigerant that is a kind of nonflammable and nontoxic gas. Since the refrigerant has larger specific gravity than air, it will suffuse on the ground in case of leakage. Therefore, the unit must be well ventilated if installed in closed room to prevent

suffocation. In case of refrigerant leakage, immediately stop unit operation, timely contact maintenance personnel and avoid any open fire on site because refrigerant will decompose hazardous gas when exposed to open fire.

Tool	Application	R410A	Reasons
Pipe cutter	cutting tube		—
Flaring <i>tool</i>	flaring tube and flaring opening when welding		It's required to increase extension allowance of copper tube when using R410A.
Tube bender	bending tube		—
Torque <i>wrench</i>	tightening flare nut		The torque of 1/2 and 5/8 is increased and torque reference is changed
Welding torch, 2B silver solder	welding auxiliary tube		—
Oxygen, acetylene			—
Nitrogen			Prevent the oxidation of the copper pipe while welding
Vacuum pump with return flow stop valve (pumping speed $\geq 4L/S$)	Vacuum piping system		Don't use original vacuum pump. It must be ensured that the oil in vacuum pump can't flow into A/C system.
Refrigerant holder	dosing of refrigerant charge		R410A should be charged in liquid state.
Electronic scale			—
Pressure gauge	inspection equipment refrigerant pressure while vacuumizing, charging ,running		The old pressure gauge can't be used due to the need of different pressure. MAX: HP5.3Mpa LP3.5Mpa
Connecting hose			
Leak detector	Checking the leakage of system		Don't use Freon leak detector of CFCs or HCFCs, because there is no chlorine in new refrigerant. It's necessary to use hydrogen leak <i>detector</i> or R134a leak <i>detector</i> .

◇ **Note:** universal special for R410A

2. Installation of Outdoor Unit

2.1 Installation Location and Foundation

The installation location should efficiently stand the weight of outdoor unit, isolate noise and vibration;
 The installation location should keep away from direct sunlight. It's preferable to erect a sunshade is necessary;

The installation location must be able to drain rainwater and water formed by frost;

The installation location must be able to ensure A/C system can't be buried by snow;

The installation location must be able to ensure *air* outlet can't face to strong wind;

The installation location must be able to ensure air discharge and operation noise of unit can't disturb neighbors;

The installation location must be free from waste and oil mist.


Warning:

Outdoor unit may subject to failure if it runs in the air environment containing oil source (including motor oil), salt (coastal area) and sulfide gas (nearby hot spring and refinery).

2.2 Maintenance and Ventilation Space of modular outdoor unit



◇In case of installation, after reserving maintenance space as shown below, install outdoor unit and install power supply device at side of outdoor unit by referring to installation instruction of power supply device manual.

◇Ensure necessary installation and maintenance space, and modules of the same system must be placed at the same height (see the following diagram).



◇If two rows of outdoor units, we suggest face to face, because easy to maintenance; no air short circuit.

◇If there is barrier above outdoor unit, install according to the following diagram:




Note:

If there is stacking objects around outdoor unit, it should be at least 1000mm higher than the top of outdoor unit. If it is lower than the above height, it's required to add mechanical discharge device to improve the ventilation.

2.3 Installation of Outdoor Unit


- ◇ Tighten outdoor unit on mounting support with M10 bolt and nut, and keep it horizontal. The bolt should have a proper length of 20mm more than base surface.
- ◇ The outdoor unit with biggest capacity in the combination should be set as master unit.

◇ In case of installing on roof, it is necessary to firmly secure A/C system to prevent the attack of earthquake or strong wind; ◇ The installation space for anchor bolt please refer to the following drawing



Model	A	B
8HP,10HP,12HP	935	807
14HP,16HP,18HP	1240	1117


◇ The foundation can be made of channel steel or concrete. Reserve the space for discharging the condensate water from outdoor units.



- ◇ Install drainage channels to ensure condensed water flow out smoothly;
- ◇ Try not to use four-square base to support outdoor unit; rubber anti-vibration pads are necessary to avoid vibration.



- ◇ If the outdoor unit need to side out of the wind by ducting work , it is essential to remove out the wind grille



2.4 Installation of indoor unit (refer to the part of indoor unit)

3. Installation of refrigerant auxiliary pipe

3.1 Installation notice

◇ Please use seamless red copper auxiliary pipe.

◇ Ensure to fill nitrogen for protection when welding.

It's mandatory to fill purge nitrogen to prevent oxidation layer (Cu_2O) formed in copper Auxiliary pipe when welding, otherwise substantial oxidation layers will cause fatal failure of A/C system;

Foreign matters (oxides) will cause blockage of capillary tube or expansion valve, abnormal discharge temperature, poor cooling (no heating) capacity, and blocking cylinder of compressor. Mostly, foreign matters cause blocking cylinder of compressor by blocking the oil return hole of gas/liquid separator;


◇ When welding auxiliary pipe of the same diameter, you are required to expand the inside diameter at connection area with flaring tool, then butt and weld two Auxiliary pipes. It's absolutely prohibited butting and welding with flaring opening;

◇ Please purge with nitrogen or air before connection to remove dust and moisture inside auxiliary pipe; Don't install refrigerant Auxiliary pipe when it rains to prevent water ingress; Suspend and fix outdoor Auxiliary pipe to prevent water ingress;

Impact of water on system: blocking capillary or expansion valve, generating acid iron/copper erosion due to refrigerant hydrolysis, generating foreign matter crystal (cage compounds) due to reaction of refrigeration oil;

Don't let dust or foreign matter such as concrete fragment, sand and copper slag ingress into the system;

◇ Specification of refrigerant Auxiliary pipe should be selected according to unit requirement



◇ Refrigerant auxiliary pipe should be fixed.

When running, refrigerant Auxiliary pipe will sway, expand or shrink, if unfixed, load will concentrate on certain part, resulting fracture of refrigerant Auxiliary pipe that should be fixed every 2~3m.

◇ Please lay out the Auxiliary pipe according to its orientation. Don't repeat bending and unbending operation over three times on the same position of Auxiliary pipe (because Auxiliary pipe will be hardened in this way);

◇ Auxiliary pipe bender must be used for auxiliary pipe bending. The curvature can't be too small, otherwise the auxiliary pipe may be bent and shrunken, affecting refrigerant flow;

3.2 Combination Ratio of Capacity

For VRF system, combination ratio of indoor unit and outdoor unit should meet the following requirement:


$$\text{N\%} = \frac{\text{rated cooling capacity of indoor unit}}{\text{rated cooling capacity of outdoor unit of one system}}$$

Note:

1. The recommended value of N% is not bigger than 100%. If indoor units not fully opened very often, value of N% can be up to 130%;
2. Maximum cooling capacity of unit is determined by the rated cooling capacity of outdoor unit;
3. If permitted, it's recommended to use less indoor units and shorter pipeline

3.3 Connection schematic diagram of auxiliarpipes

Connection Schematic Diagram of system



		Allowable value		Part of Auxiliary pipe
	overall length of auxiliary pipe (equivalent length)	<20HP	700m	L1+L2+L3+L4+L5+L6+L7+L8+a+b+c+d+e+f+j+h+i
		>20HP	1000m	
Length of Auxiliary pipe	Max. length between outdoor unit and fastest indoor unit	actual length	165m	L1+L5+L6+L7+L8+i
		equivalent length	190m	190
	Max. length between indoor unit and the first Y branch pipe		40m	L5+L6+L7+L8+i
	Difference of the fastest indoor unit to the closest indoor unit		40m	
	Distance between outdoor unit and general branch pipe of outdoor unit	actual length		10m
equivalent			13m	
High head	level difference of indoor unit and outdoor unit	outdoor unit is at the upper part	70m	_____
		outdoor unit is at the lower part	90m	_____
	level difference among indoor units		15m	_____

Note:

Equivalent length refers to conversion length of parts such as elbow after considering pressure loss.
 Equivalent length: actual length of pipe + quantity of elbow x equivalent length of each elbow + quantity of oil trap x equivalent length of each oil trap

Elbow and oil trap recommend dimension list

Type Diameter of pipe(mm)	90° elbow(m)	Oil trap(m)
9.52	0.18	1.3
12.7	0.20	1.5
15.88	0.25	2.0
19.05	0.35	2.4
22.2	0.40	3.0
25.4	0.45	3.4
28.6	0.50	3.7
31.8	0.55	4.0
34.93	0.58	4.2
41.3	0.63	4.6
44.5	0.66	5.0

Example:

When actual length of 10HP outdoor unit is 80m, diameter of pipe is 25.40mm and 12 elbows & 2 oil traps are used, the equivalent length should be calculated:


$$80+0.45 \times 12 + 3.4 \times 2 = 92.2(\text{m})$$

Note:

If there is relatively big high head of indoor and outdoor unit, "S"-shaped oil trap must be installed every 8~10m for vertical pipe.

3.4 Determination method of auxiliary pipe and branch pipe

◇Selecting type of refrigerant auxiliary pipe



Type of Auxiliary pipe	Connecting parts	No.
Main Auxiliary pipe	between outdoor unit and the 1 st . branch pipe	1
	between branch pipe and branch pipe	2
Branch Auxiliary pipe	between branch pipe and indoor unit	3

◇Diameter of auxiliary pipe 1 depends on auxiliary pipe specification of outdoor unit.

Model	Gas side(mm)	liquid side(mm)	The 1 st Branch pipe
8HP	22.2	12.7	RBPK-12
10HP	22.2	12.7	
12HP	28.6	12.7	
14HP	28.6	12.7	RBPK-24
16HP	28.6	12.7	
18<A≤24 HP	28.6	15.88	RBPK-24
24<A≤34 HP	34.93	19.05	RBPK-34
34<A≤50 HP	41.3	19.05	RBPK-50
50<A≤64 HP	47.6	22.2	RBPK-64

◇Diameter of auxiliary pipe "2" depends on the total capacity of indoor unit connected to the Branch pipe.

Total capacity of indoor unit (HP)	Gas side(mm)	liquid side(mm)	selection of Branch pipe
0 < B 2.2	12.7	6.35	RBPK-00
2.2 < B 4.0	15.88	9.52	RBPK-00
4.0 < B < 8.0	19.05	9.52	RBPK-00
8 B 12	22.2	12.7	RBPK-12
12 < B 24	28.6	15.88	RBPK-24
24 < B 34	34.93	19.05	RBPK-34
34 < B 50	41.3	19.05	RBPK-50
50 < B 64	47.6	22.2	RBPK-64

Note:

The 1st. Branch pipe should be based on total capacity of outdoor unit and other Branch pipes
Shouldn't larger than the 1st Branch pipe.

◇ Diameter of auxiliary pipe “3” depends on indoor unit.

Cooling capacity of indoor unit(kW)	Gas pipe(mm)	Liquid pipe(mm)	Remark
2.2	9.52	6.35	
2.8	9.52	6.35	Cassette and Ceiling & Floor unit: 12.7/6.35
3.6	12.7	6.35	
4.5	12.7	6.35	
5.6	12.7	6.35	
7.1	15.88	9.52	
8.0	15.88	9.52	
9.0	15.88	9.52	
10.0	15.88	9.52	
11.2	19.05	9.52	
12.5	19.05	9.52	
14.0	19.05	9.52	
15.0	19.05	9.52	

◇ Minimum wall thickness of auxiliary pipe should meet data of the following table.

Diameter of Auxiliary pipe (mm)	6.35	9.52	12.7	15.88	19.05	22.2
Minimum wall thickness (mm)	0.8	0.8	1.0	1.0	1.0	1.2
Diameter of Auxiliary pipe (mm)	25.4	28.6	34.93	41.3	44.5	47.6
Minimum wall thickness (mm)	1.2	1.3	1.5	1.5	2	2


3.5 Type and physical dimension of branch pipe

Notice:


In addition to ensuring compliance with joint of main auxiliary pipe, it's allowable to select Branch pipe with similar specification as long as it meets pressure-proof requirement. It's required that no leaking at gas pressure of 4.5Mpa and no distortion and leaking at hydraulic pressure of 6.3MPa.

RBPK-00 Physical Dimension

Gas side joint




Liquid side joint




RBPK-12 Physical Dimension

Gas side joint




Liquid side joint




RBPK-24 Physical Dimension

Gas side joint




Liquid side joint




RBPK-34 Physical Dimension

Gas side joint




Liquid side joint




RBPK-50 Physical Dimension

Gas side joint




Liquid side joint




RBPK-64 Physical Dimension

Gas side joint




Liquid side joint



Example of auxiliary pipe design

Three modules combination of (12+16+16) HP is taken as the example to explain selection of auxiliary pipe.



Parallel connection of outdoor modules:

1. Pipe diameter of L, M and N depends on HP of corresponding outdoor unit, which is 22.2/ 12.7、28.6/ 12.7、 28.6/ 12.7 respectively.
2. Corresponding HP of 1 is "12HP +16HP =28HP" and its pipe diameter is 34.93/ 19.05. Y-type branch pipe "a" should use the type of RBPK-34A.
3. Pipe "2" is main pipe. Dimension of both pipe "2" and Branch pipe depends on total capacity of outdoor unit. Sum of total capacity of outdoor units is "12+16+16=44HP". Dimension of pipe "2" is 41.3/ 19.05. Y-type branch pipe "c" should use RBPK-34 and Y-type branch pipe "b" should use RBPK-50A.

For indoor side:

1. Branch auxiliary pipes include 10~18 and the dimension is 19.05/ 9.52.
2. Downstream indoor units of main auxiliary pipe "9" include 8# and 9#. Its HP sum is "5+5=10HP". Dimension of pipe "9" is 22.2/ 12.7. Branch pipe "j" should use RBPK -12A.
3. Downstream indoor units of auxiliary pipe "8" include 7#, 8# and 9#. Its HP sum is "5x3=15HP". Dimension of pipe "8" is 28.6/ 12.7. Branch pipe "i" should use RBPK -24A.
4. Downstream indoor units of main auxiliary pipe "7" include 6# ~ 9#. Its HP sum is "5x4=20HP". Dimension of pipe "7" is 28.6/ 15.88. Branch pipe "h" should use RBPK -24A.
5. Downstream indoor units of main auxiliary pipe "6" include 5# ~ 9#. Its HP sum is "5x5=25HP". Dimension of pipe "6" is 34.93/ 19.05. Branch pipe "g" should use RBPK -34A.
6. Downstream indoor units of main auxiliary pipe "5" include 4# ~ 9#. Its HP sum is "5x6=30HP". Dimension of pipe "5" is 41.3/ 19.05. Branch pipe "f" should use RBPK -34A.
7. Downstream indoor units of auxiliary pipe "4" include 3#~9#. Its HP sum is "5x7=35HP". Dimension of pipe "4" is 41.3/ 19.05. Branch pipe "e" should use RBPK -50A.
8. Downstream indoor units of auxiliary pipe "3" include 2#~9#. Its HP sum is "5x8=40HP". Dimension of pipe "3" is 41.3/ 19.05. Branch pipe "d" should use RBPK -50A.



Note:


Y-type fitting "a" and "b" must be put horizontally, otherwise, uneven distribution of refrigerant will be caused.

3.6 Connection and Welding of auxiliary pipe

Requirement for flaring opening connection:

- ◇ Debur the auxiliary pipe before flaring, then flare auxiliary pipe with flaring tool as per the dimensions of flaring opening in the following table:
- ◇ Apply a thin layer of refrigeration oil on both inside and outside at the flaring part;
- ◇ Align flaring opening with threaded joint of indoor unit, manually and tightly screw flared nut, then screw with torque wrench as per the tightening torque in the following table.
- ◇ Remove valve cap on liquid valve and air valve of shutoff valve of outdoor unit, align flaring opening with shutoff valve of outdoor unit, sufficiently screw flared nut with hand, and then screw with torque wrench as per the tightening torque in the following table.

Diameter of Auxiliary pipe	Tightening torque	Machining dimension of flared section (A)	Shape of flaring opening	Apply oil
1/4in(6.35mm)	15-19 (N·m)	8.8-9.1mm		
3/8in(9.52mm)	35-40 (N·m)	12.8-13.2mm		
1/2in(12.7mm)	50-60 (N·m)	16.2-16.6mm		
5/8in(15.88mm)	68-80 (N·m)	19.2-19.6mm		
3/4in(19.05mm)	100-120 (N·m)	23.6-24mm		




Requirement of welding connection:

- ◇ If welding connection method is used to connect auxiliary pipe and Branch pipe, you are required to weld before system connection and purge with nitrogen to prevent oxidation layer formed inside copper auxiliary pipe when welding.

3.7 Air Tightness Test

It aims to confirm if there is leakage in auxiliary pipe by using nitrogen and the steps are as follows:



Gradual pressurization test

According to each refrigerant system, do gradual pressurization test (nitrogen is required) on gas pipe and liquid pipe.

Phase 1: 3.0 kg / cm²; Pressurize at least 3 minutes; Large hole may be found.
 Phase 2: 15.0 kg / cm²; Pressurize at least 3 minutes; Large hole may be found.
 Phase 3: 43.0 kg / cm²; Retain the pressure for about 24 hours. Small hole may be found.
 Even if pressurize up to 43.0kg / cm², it's impossible to find small hole in very short time. Therefore, in phase 3, it's required to place for 24 hours to observe after pressurization.

Observe pressure drops.

It's necessary to correct if pressurized temperature is different from observed ambient temperature with difference of

0.1 kg / cm² per 1°C. Correction value =(pressurized temperature - observed temperature)x0.1

Example:

pressure is 43.0 kg/cm² and temperature is 25°C in case of pressurization.

After 24 hours, if pressure is 42.5kg/cm² and temperature is 20°C, it is deemed qualified.

Check leaking hole.


listening check: larger leaking hole can be found by listening.

Touch check: feel if there is leaking by putting hand at pipe joint.

Soapsuds check: bubble can be found at leaking part.

In order to find small leaking hole or pressure drop is found but leaking hole can't be found in pressurization test

- 1) Discharge nitrogen to the position of 3.0 kg/cm².
- 2) Charge fluorine (R410a) up to the position of 5.0 kg/cm² (namely the mixed state of nitrogen and fluorine)
- 3) Check with halogen lamp, butane gas (petroleum gas) detector and electric detector.
- 4) If leaking hole can't be found, recheck by continuously pressurize up to 28 kg/cm². (maximum pressure is 43 kg/cm²)



Note:


Super-long pipeline should be checked section by section.

1. From each indoor unit to each Auxiliary pipe well;
2. Standpipe inside each Auxiliary pipe well;
3. From each auxiliary pipe well to outdoor unit;
4. From indoor unit to outdoor unit as a whole.
5. After sir tightness test of the system is completed, it's preferable to reduce nitrogen pressure to 5~10 kgf/cm².

3.8 Vacuum Drying

Note:

1. The vacuum break shall use nitrogen to carry out. If use other gas mistakenly, it may cause explosion.
2. The vacuum drying adopts the vacuum pump to turn the water (liquid) in pipe to steam (gas) and discharge it to the outside pipe, and dry the pipe. Under the normal air pressure, the boiling point of water (steam temperature) is 100°C, but the pressure in vacuum pump pipe is near vacuum, this makes the boiling point lower to below the outside air temperature, and the water in the pipe is evaporated.



Water's boiling point(°C)	Pressure (mmHg)	Vacuum degree(mmHg)
40	55	-705
30	36	-724
26.7	25	-735
24.4	23	-737
22.2	20	-740
20.6	18	-742
17.8	15	-745
15.0	13	-747
11.7	10	-750
7.2	8	-752
0	5	-755

Example:

when the air temperature is at 7.2°C, the vacuum drying can be carried out under -752mmHg.

Selection of the vacuum pump

The following 2 points shall be noted in selection of the vacuum pump:

- ① Select the vacuum pump with prospected vacuum requirement (vacuum reaches -755mmHg)
- ② require the pumps with large exhaust capacity (around 40L / min or above).

Moreover, before operation, the vacuum meter shall be checked to ensure its measuring range can reach -755mmHg below. Lube oil rotating vacuum pump needs to change the lube oil every one or two month, and check the vacuum state.


(Reference) The types and vacuum state of vacuum pump

Type	Exhaust volume in maximum vacuum state	Function	
		Vacuum drying	Exhaust
Oil lubrication pump shaft (with oil)	0.02mmHg 100L/min	Suited	Suited
Oil free pump shaft (without oil)	10mmHg 50L/min	Unsuited	Suited
	0.02mmHg 40L/min	Suited	Suited

Vacuum drying

For the methods of the vacuum drying, according to different environments, there are two methods can be selected.

1 common method operation



① Vacuum drying (at the first time)

connect the multimeter to the inlets of liquid pipe and air pipe, and operate the vacuum pump for 2 hours or more. (The vacuum state shall be below -755mmHg)

If the extraction lasts for 2 hours, but the vacuum state cannot reach -755mmHg below, then there exists water or leakage in the system, at this time, extraction will continue for 1 hour.

If the extraction lasts for 3 hours, and the vacuum state cannot reach -755mmHg, then check whether there exists leakage hole.

② Vacuum layout test

When the vacuum state reaches -755mmHg, lay out the vacuum dryer, if the vacuum meter value is stable, it means qualified; if the value rises then it means there is water or leakage hole.

③ Add additional refrigerant

Connect the refrigerant tank to the maintenance pipe of the liquid pipe to facilitate adding of the system need refrigerant.

④ Open all the open-close valves of the liquid pipes and air pipes

(Notes) vacuum extraction operation carries out in liquid pipe direction and air pipe direction (because there are all kinds of parts equipped in indoor unit, the process may interrupted).


2 Special vacuum drying method

This kind of vacuum drying method is used in the condition that there is water mixed in the pipe. Such as When flushing refrigerant pipe, water is found.

When the project carried out in raining weather, there may be condensate in the pipe.

If the project last for a long time, there may be water enter the pipe.

In project, the rainwater may enter the pipe.



Method is that insert break the nitrogen vacuum work procedure for more than one time during common vacuum drying process.

Operation procedures:

- ① Vacuum drying (at the first time).....extraction for 2 hours
- ② Break vacuum (at the second time).....add nitrogen to 0.5kg/cm²
Since the nitrogen is a kind of drying gas, when breaking the vacuum, it can accomplish drying effect, but if there is lot of water, the drying effect is not complete. Therefore, in refrigerant project, water penetration and condensate in the pipe shall be specially noted.
- ③ Vacuum drying (at the second time).....extraction for more than 1 hour
Judgment: when reaches -755mmHg or below, it is qualified. If it cannot reach this value within 2 hours, then vacuum break ② and ③ shall be carried out repeatedly.
- ④ Vacuum layout test.....1 hour.
- ⑤ Additional refrigerant injection
- ⑥ Open the open-close valve

4. Additional refrigerant and lubrication oil

4.1 Add refrigerant

Please add refrigerant as the following chart tell us on the basis of total length of connection pipe, the methods of adding refrigerant are as follows:


Diameter of liquid duct(mm)	L1(25.4)	L2(22.22)	L3(19.05)	L4(15.88)	L5(12.7)	L6(9.52)	L7(6.35)
Additional amount of refrigerant (kg/m)	0.45	0.34	0.25	0.17	0.11	0.054	0.022

Additional amount of refrigerant = length of liquid pipe in refrigerant auxiliary pipe × corresponding additional amount of refrigerant for each meter of liquid pipe.

$$\text{Additional amount of refrigerant} = (L1 \times 0.45) + (L2 \times 0.34) + (L3 \times 0.25) + (L4 \times 0.17) + (L5 \times 0.11) + (L6 \times 0.054) + (L7 \times 0.022)$$

Note:

1. It must record the calculation result (better make a table);
2. To pour the liquid refrigerant into liquid duct from shut-off valve on side of liquid duct when it is completely dried;
3. It may pour the gas refrigerant into liquid duct from air duct through the operation of compressor on trial run, when refrigerant is not completely poured into;
4. It must measure the injection of refrigerant with electronic scale



4.2 Additional amount of lubrication oil

For a system (single module or multiple modules), when the average refrigerant of every module ≤ 20kg, it no necessary to add freeze oil, when the average refrigerant of every module > 20kg, then add 1 kg refrigerant, and add 100 ml freeze oil at the same time.

Model	GRV08P3T3	GRV10P3T3	GRV12P3T3	GRV14P3T3	GRV16P3T3	GRV18P3T3
Specification of oil	FVC68D					
Lubrication oil charge when leaving factory	4	4	4	5.5	5.5	5.5


5. Insulation

Thermal insulation wrapping of auxiliary pipe

Thermal insulation materials should be used for drain pipe and auxiliary pipe to prevent condensation or water leakage.

Note:


- ◇ Wrap auxiliary pipe with thermal insulation materials of good insulation performance ($>120^{\circ}\text{C}$).
- ◇ Notice for high-humidity environment: the A/C system is verified by condensation conditions test. However, it may subject to dripping if working in high-humidity (condensation temperature $>23^{\circ}\text{C}$) environment for a long time. In this case, please add the following thermal insulation materials:
- ◇ The thermal insulation materials should be glass fiber thermal insulation materials with 10–20mm thickness.



Sealing of Wall Opening

After installing auxiliary pipe and drain pipe, it's necessary to seal the gap among wall opening, Auxiliary pipe, drain pipe and electric wire with mortar or putty to prevent capacity degradation or water leakage caused by rainwater or foreign matter from ingressing into room and A/C system.

If outdoor unit is higher than indoor unit, it's necessary to bend auxiliary pipe to ensure the lowest point of auxiliary pipe is lower than wall opening and prevent rainwater flowing into room or A/C system along the tubing.



6. Electrical connection

Caution	All field wiring and components must be installed by a licensed electrician.
	Please separately design the special power of indoor units and outdoor units.
	Be sure to use a dedicated power circuit, Never use a power supply shared by another appliance. The connection fixing circuit installs all polar disconnecting device with contact gap above 3mm.
	The indoor units' power, creepage protector and manual switch connecting to the same outdoor unit must be general. All indoor units must be the same circuit, and must simultaneously on or off; otherwise, system life will seriously effect, and appear the situation not to solve.
	The communication line between indoor units and outdoor units please use 2 core shielded wiring, while don't use the multi core wiring without shielded affect, for the interference is reduced each other.
	Purchased wiring, parts and materials should be in compliance must comply with relevant local and national regulations.
	Air conditioning equipment should be grounded according to the relevant local and national electrical regulations.
	Don't switch on power supply before electrical operation. Maintenance operation should be conducted after switching off power supply.
	This is machine includes an inverter device. Connect earth and leave charge to eliminate the impact on other devices by reducing noise generated from the inverter device and to prevent leaked current from being charged in the outer hull of the product.
	Don't connect the ground wire to gas pipe, water pipe, telephone ground wires or lightning rod and other ground wires.
	Leakage protector, power switch and breaker must be installed on power supply to prevent electric shock accident.
	The specification of single-phase control board fuse is F3.15AL 250V,
	The specification of outdoor unit control board fuse is F6.3AL 250V;
	The specification of three-phase outdoor unit control board fuse is F3.15AL 250V,
	The specification of fan unit control board fuse is F10AL 250V.
	Reliable grounding is required, because electric shock will be caused by improper grounding.
Never install a phase advancing capacitor.As this unit is equipped with an inverter ,installing a phase advancing capacitor will not only deteriorate power factor improvement effect,but also may cause capacitor abnormal heating accident due to high-frequency waves.	
Notice	Electrical wiring must be done in accordance with the wiring diagrams and the description herein.
	Signal wire and power wire must be separated, and can't share the same wire. It's strictly prohibited connecting signal wire to heavy current.
	When connecting wiring and wire holder, use cable clamp to fix and make sure no exposure.
	Refrigerant piping system and wiring system of indoor and outdoor unit belongs to the different system.
	When power wire is parallel with signal wire, put wires to their own wire tube and remain proper gap
	Voltage discrepancy of power wire terminal (side of power transformer) and end voltage (side of unit) should be less than 2%. If its length could not be shortened, thicken the power wire. Voltage discrepancy between phases shall not pass 2% rated value and Current discrepancy between highest and lowest phase should be less than 3% rated value.
	Never connect the power supply in reversed phase. The unit can not operate normally in reversed phase. If you connect in inversed phase, replace two of the three phases.


6.2Electrical Wiring of indoor unit and outdoor unit (refer to the part of indoor unit and outdoor unit)

6.3 Wiring Diagram of Indoor Unit and Outdoor Unit

Note:

- Power line must be properly fixed;
- Each outdoor unit must be grounded;
- Each indoor unit must be grounded;
- Power line must be thickened when it is overlong.

Wiring Diagram of Modular Outdoor Unit




Recommended Specification for Power Line of Outdoor Unit (stand-alone power supply)

Unit Type		Item	Power supply	Sectional area of power line (mm ²)	Rated current breaker (A)	Rated current of creepage breaker Leakage current Operate time	Containing an area of ground wire(mm ²)
separate power	8HP	380V-415V 3N~ 50Hz		6	32	40 A,30mA, <0.1 sec.	6
	10HP			6	32	40A,30mA, <0.1 sec.	6
	12HP			6	32	40A,30mA, <0.1 sec.	6
	14HP			16	50	70A,30mA, <0.1 sec.	16
	16HP			16	50	70A,30mA, <0.1 sec.	16
	18HP			16	50	70A,30mA, <0.1 sec.	16


Recommended Specification for Power Line of Indoor Unit (separate power supply from outdoorunit)

Unit Type		Item	Power supply	Sectional area of power line (mm ²)	Rated current of over current breaker (A)	Rated current of creepage breaker Leakage current Operate time
Separate power	<10 A	Single-phase 220-240V/ 50Hz		2.5	16	20 A,30mA, <0.1 sec.
	10 A and <15 A			4	20	25A,30mA, <0.1 sec.
	15 A and <22 A			6	32	40 A,30mA, <0.1 sec.
	27 A			10	40	50 A,30mA, <0.1 sec.

6.4 Communication Line Connection



6.5 Specification for Communication Line



Note:

- ◇ Currently, there are two length specifications as shown in the following table for indoor and outdoor communication line: L=10m and L=20m.
- ◇ Communication Line Specification of Indoor Unit and Wired Controller
- ◇ Sectional area of power cord is the minimum value, which should be enlarged to higher specification to prevent voltage drop in case of long power supply connecting line. If single double-layer wire is used, please choose Grade 1 cross-section specification and wrap with dedicated sheaths for electricians;

6.6 Wiring

- 1) Open electric controlled box cover of indoor unit, wire according to electrical schematic diagram on electric controlled box cover, firmly press connecting line on connecting terminal without loosening, ground wire must be connected at designated position.
- 2) Open cover plate of electric appliance on right of outdoor unit and wire according to electrical schematic diagram on backside of electric appliance cover plate.
- 3) Be noted to thread connecting line through tension disc and press firmly, wire end must be firmly pressed on connecting terminal without loosening and ground wire must be connected at designated position.
- 4) After wiring, properly bind connecting auxiliary pipe, connecting line and drain pipe with bandage as shown below:

Note:

1. Be noted that unit connecting line can't be put together with thermal insulation material and should be at least 20cm away from unit connecting pipe.
2. Don't flatten drainpipe when binding

6.7 Parameter setting (refer to the part of control system)

Part 5 Controller System

1 Controller introduction.....	379
2 Remote controller	379
3 Wired Controller.....	383
4 Centralized Controller	389
Accessory : Centralized Controller Adaptor.....	396
5 Centralized Controller Software	398
Accessory of central control system	Error! Bookmark not defined.
6 Wireless Network Centralized Control System	441
7 Selection software	444
8 Parameter setting of indoor unit	459

1 Controller introduction

Remote Controller		Wired Controller		Centralized Controller	Centralized controller adapter plate
YK-F(set) (DLRG-YK-HCE1(F06SET))	YK-H YKR-H/009E	XK-05A XK03-DCZ-SYE1	XK-02A (DCZ-XK-RKC1)	DCZCC-XK-SYE1	232-485 converter Gateway Computer

Control component list

Type	Model	Function description
Remote controller	YK-F(set) (DLRG-YK-HCE1(F06SET))	More the following functions than general wireless remote controller add address setting function.
	YK-K (YKR-K/001E)	General wireless remote controller, none address setting function, with 2 swing, clock function, and etc.
	YK-H (YKR-H/009E)	General wireless remote controller, none address setting function, with back light display, clock function, and etc.
	YK-F (Q-YK-HCE1(F001))	General wireless remote controller, big screen and LCD display, none address setting function, with back light display, clock function, and etc.
Wired controller	XK-02A (DCZ-XK-RKC1)	With a directly connecting 10m display board wire,add setting address function. For the display board of indoor unit with wiredcontrol port.Control Max. 16 indoor units.
Centralized controller	DCZCC-XK-SYE1	With weekly timer.Control Max. 64 indoor units.Can control multiple refrigeration systems,but each refrigeration system must connect centralized controller adaptor and SMPS.
Centralized controller adaptor	Adaptor DCZ-ZJB-HCE1 SMPS HF10W-S-12	Centralized controller adaptor and switch-mode power supply.Accessories equipment of centralized controller.
Centralized Control Software		Control Max. 256 outdoor units and 4096 indoor units. Can control 64 refrigeration systems.but each refrigeration system must connect gateway.Whole control system must connect a 232-485 converter and a special computer.
Centralized Control Software Adaptor	232-485 converter Gateway Computer	Accessories equipment of centralized controller software.
Monitoring Software	GREEN-GRV-monitoring	The central control monitor of outdoor unit. Can only control a refrigeration system.Monitor Max. 4 outdoor unit.Must connect USB-485 communication
Selection Software	GREEN Project Express (GREENSelectionV1.08_)	Without password.Select branch pipe and copper pipe faster and more accurate.
Charge-by-household	To be continued	/
BMS system	To be continued	/

2 Remote controller

POWER button:Switch the unit ON/off.

MODE button: Select mode , push the button one time, then the operation modes will change in turn as Auto-Cooling-Dehumidify-Heating 

TEMP + button and **TEMP - button:** Temperature adjustment range: 16~32

FAN button: Change the fan speed will change in turn as: Low-Medium-High-Auto

SWING button: Press this button for the first time when operation, it will start the swing function. Push the button for the second time, cancel the swing function. (The function is available matched with the concerned unit)

TIMER/CLOCK button:

Clock Setting: Normally display the clock set currently (display 12:00 for the first electrifying or resetting). When press the button for 5 seconds, the time display zone will flicker, then press **【+】** and **【-】** button and to adjust hour that uses 12-hour clock including “A.M.” and “P.M.” time; press the button again to complete the setting.

Timer setting: Press the button to set TIMER ON/OFF , press the button then “ON” will flicker on the display screen. then press **【+】** and **【-】** button and to adjust hour that uses 12-hour clock including “A.M.” and “P.M.” time; press the button again to complete the setting. The “OFF” setting is the same methods.

Remark: When setting functions such as mode, temperature, air port and air velocity, display screen displays all presetting parameters and remains constant; after reaching presetting time, air conditioner will automatically start as per presetting state.

After setting timing ON and OFF function, pressing button of **【Timer/Clock】** can cancel timing setting.


SLEEP button: Press the button to display sleep symbol and initiate sleep function; press the button again or press button of **【Power】** to cancel sleep function and sleep symbol will disappear.

1 “ON/OFF” button

* Press this button, the unit will start or stop, which can clear the timer or sleeping function of last time.

2 “SPEED” button

* Press this button, speed will change as below:



3 “▲ / ▼ ” button

* When press ▲ button, the setting temperature will be increased by 0.5°C. When press ▼ button, the setting temperature will be decreased by 0.5°C.

* The temperature will be changed quickly by pressing the button continuously and setting temperature range is 16°C to 32°C.

4 “COOL” button

* Press the COOL button, you can directly enter cooling mode.

5 “HEAT” button

* Press the HEAT button, you can directly enter cooling mode.

* **Note: cooling only unit has no heating function.**

6 “SWING” button (SWING ↔ and SWING ↑ ↓)

Press this button to start up/down (left/right) swing function, press it again, fix louver position.

* Up/down (left/right) setting is only valid in this mode; it will not affect louver position in other modes.

* Up/down (left/right) swing has memory function, it can keep primary setting when turn off then turn on or switch from other modes to primary mode.

7. “HEALTH” button

* Press this button; you can turn on or off the health function.

8. “SLEEP” button

* Press SLEEP button, the sleeping indicator light of indoor unit flashes on.

* The air-conditioner runs in sleeping mode for 10 hours and quit sleep mode, recover back to former mode.

* The unit will turn off automatically if the timing mode is running out of time.

* **Note: press the MODE or ON/OFF button, the remote controller clears sleeping mode away.**

9. “iFEEL” button

* Press this button to set “iFEEL” function. The LCD shows the actual room temperature when the function set and it shows the setting temperature when the function cancelled.

* This function is invalid at Fan mode.

10. “DISPLAY” button

* In display mode, press button once, switch off “DISPLAY”, Press “DISPLAY” again, LCD will show ambient & setting temperature after flashing 5s. It’s convenient for users to check ambient or setting temperature at any time in darkness.

11. “iCLEAN” button

* When remote controller is at the off state, press “iCLEAN” button, the unit runs “iCLEAN” function .

* The purpose of this function is to clean dust on evaporator and dry the inside water of evaporator and to prevent the evaporator going moldy due to water deposition and boasting strange smell.

* After setting “iCLEAN” function, press “iCLEAN” button or “ON/OFF” button to quit .

* The clean function will stop working after about 30 minutes running without any operation.

12. “ELE.H” button (for auxiliary electric heating IDU)

In heating mode, press this button, auxiliary electric heating will work.

13. “Anti-FUNGUS” button

* The purpose of this function is to dry the inside of the evaporator and to prevent the evaporator from going mouldy due to water deposition and thus dispersing strange smell.

- * To operate the function: under "off" status of the A/C and the remote controller, press "**Anti-UNGUS**" button for one time, the buzzer keep beeping five times again after five times beep, indicating that this function is ready.
- * To cancel the function: 1. under "OFF" status of the A/C and the remote controller, press "**Anti-FUNGUS**" button again.

14. "**SPOT SWING**" button

- * Press this button, the horizontal wind direction vanes can swing automatically, when you have the desired vertical wind direction.
- * Press "**SPOT SWING**" again, the horizontal wind direction vanes will be stopped depend on you.

15. "**ECO**" button

- * In cooling mode, press this button, the unit will run "**ECO**" economic operation mode which takes the least power consumption.
- * After running for 8h, it will automatically quit. You can press "**ECO**" button once again to quit .
- * Note: The unit will turn off automatically if the timing mode is running out of time.

16. Two white button: Addressing set

- * With the controller off, pressing the two white button simultaneously more than 10 seconds or more to enter address setting. This status displays only temperature and time parameters, temperature display area shows "Serial number" parameters, the range is 0-99. Time display area shows "Set value", the range is 0-255. The initial value is 1.
- * By pressing "**▲ / ▼**" to set serial number + and -.Parameters within the serial number displays from 0 to 99 in circulation.



By pressing "**ECO**" and "**iCLEAN**" to set value number + and -.Parameters within the value number displays from 0 to 255 in circulation. After setting the two numbers, press the MODE button to confirm sending to ODU.

3 Wired Controller

3.1 XK-02A



ON/OFF button: Switch the unit ON/off.

Mode button: Select mode, push the button one time, then the operation modes will change in turn as below: Auto-Cooling-Dehumidify-Heating  →  →  → 

Temp +/- button: Press the button can adjust temperature. Temperature adjustment range: 16~32°C

Fan button: Change the fan speed will change in turn as :Auto-Low-Medium-High-Auto

Swing button: Press this button for the first time when operation, it will start the swing function. Push the button for the second time, cancel the swing function. (The function is available matched with the concerned unit)

Health button: Press this button change to switch mode: Health mode.

Sleep button: Press the button to display sleep symbol and initiate sleep function; press the button again or press button of **【Power】** to cancel sleep function and sleep symbol will disappear.

Timer button: Press the button to set Timer ON/OFF, press the button then “ON” will flicker on the display screen. then press **【Clock +/- button】** and to adjust hour that uses 12-hour clock including “A.M.” and “P.M.” time; press the button again to complete the setting. The “OFF” setting is the same methods.

Remark: When setting functions such as mode, temperature, swing and fan speed, display screen displays all presetting parameters and remains constant; after reaching presetting time, air conditioner will automatically start as per presetting state.

After setting timing ON and OFF function, pressing button of **【Timer】** can cancel timing setting.

Notes:

1. Time sequence of timing ON and OFF determines the order of “Timing ON-Timer OFF” and “Timer OFF- Timing ON” . If the both are the same or either one is the same as time of current clock, it is invalid to press “Timer” button to confirm presetting time; after it reaches the presetting time, it will implement corresponding timing operation.

2. After setting time of timing ON and OFF, pressing “Timer” button can cancel timing.

3. Enter into time setting state of timing function; if there is no input related to time within consecutive 10 seconds, cancel the operation, return to previous state and go on with current time.
4. Default time of timer ON is 08:00 and default time of timer OFF is 18:00.

Clock +/- button: Normally display the clock set currently (display 12:00 for the first electrifying or resetting). When press the **【Timer button】** button for 5 seconds, the time display zone will flicker, then press **【Clock +/- button】** and to adjust hour that uses 12-hour clock including “A.M.” and “P.M.” time, press the **【Timer button】** again to complete the setting.


Filter Net button: When symbol of [Filter Net button] displays after wired controller receives “Filter” cleaning signal sent by indoor unit, press “Filter Net” button, “Filter Net” will go out and send filter cleaning reset signal to indoor unit; if [Filter] didn’t display, it will be ineffective in case of short pressing of filter button.

Self-check button: Press the button to display group number and failure code of this wired controller. (Failure code of wired controller for each unit displays for 3 seconds, then automatically exit after displaying failure state of the whole unit); Continuously press the button for 5 seconds, failure code will be cleared in the normal state.

Parameter setting

Parameter Query and Setting of Indoor Unit of Wired Controller please refer to “6 Parameter setting of indoor unit” of “Part 5 Controller”

4 Touch screen panel wired controller XK-05A



★ Introduction of Functions and Operations

1. "POWER" button--On/Off button

Press "POWER" button after connecting the power, this will turn on the operation indicator and set the air conditioner to operation mode.

Pressing "POWER" button again will turn off the operation indicator and set the air conditioner to standby mode.

2. ">" button and "<" button-- plus and minus buttons

- Depending on functions in different pages, pressing ">" or "<" buttons may be required for setting temperature, time and other parameters.

- When setting time, you may want to speed up the process by pressing and holding ">" or "<" for 2 seconds.


- If the ">" and "<" buttons are pressed simultaneously for 5 seconds or more, The control will be locked, displaying " ". No button operation (the receiver for remote control is still working) is possible when the control is locked.

- To unlock the control: Press ">" and "<" buttons simultaneously for 5 seconds or more, or turn on the power after turning it off (" " will be canceled).

Note: Each press of the ">" button adds the value by 1; Each press of the "<" button minus the value by 1.

3. "M" button--Mode button

By pressing "M", you can switch the operation modes in the following sequence:

[Auto 

The initial temperature of each mode is set at 24°C. There is no set temperature under VENT mode and no automatic air flow under FAN mode.

Note: For units with which some of the above modes are not available, the sequence of the remaining modes is the same as those with all modes.

4. " " --Functional Buttons

- Sleep function setting

After the unit is turned on, each press of the " " button will activate the sleep function (the display of " " indicates the sleep function is activated).

5. “⌚” --Timer button

●Press “⌚” button once:

If the unit is turned on, the wire control will be switched to OFF time setting mode and display “⌚_{OFF}”.

If the unit is turned off, the wire control will be switched to ON time setting mode and display “⌚_{OFF}”.

When in time setting mode, the time column will display default time setting (4 hours after current time). Then, readjust the set time by pressing “<” or “>” button (holding those buttons can accelerate the adjustment).

Press the “⌚” button again to confirm the setting, which will stop the flicker of the time column.

Note: If no button is pressed for 10 continuous seconds, the time setting will be canceled and the timer will return to where there is no time setting.

Pressing “⌚” again or “POWER” after the setting is finished will quit the time setting. The corresponding timer icon will go out and the time column will display the system time.

●By pressing and holding “⌚” button for 5 seconds, you can adjust the clock according to current time (“88:88”) Press the “<” or “>” to add or minus the hour with hour auto-increment (holding those buttons can accelerate the adjustment).

6. “🌀” Button--Air Speed Button

By pressing “🌀”, you can switch the air speeds in the following sequence [Auto 🌀] → [Low 🌀] → [Med 🌀] → [High 🌀] → [Auto 🌀]:

During forced operation, the air speed will be displayed as [Auto 🌀].

7. Indicator

It is used for indicating operation conditions.

When the unit is turned on: When the unit is in operation, the indicator will remain light; or it will start to “breathe” (become bright and dim alternatively) if there is no operation for 10 seconds.

When the unit is turned off: The indicator will go out.

8. Remote control receiver.


It is used for receiving remote control signals.

When operating, aim the emitter of remote controller toward the receiver within 8m away and send operation orders.



9. Other Functions

● Swing function

Start or stop the swing function after the remote control order is received.

The corresponding swing icon “” glows or goes out.


● Sleep function

This function can be set with “” (see the operation instruction of “” button for details) or remote controller after the unit is turned on.

● Lock Function

See the operation instruction of “>” and “<” buttons.

● Defrosting or oil return

When the “” symbol glows, the unit is in the process of automatic defrosting or oil return. This is not a failure of the unit.

● Trouble code display

When the screen displays the interface as shown in figure 1, the unit is reporting a trouble, with the temperature column displaying directly the trouble code, based on which the user may report the trouble to the local service department for repair.




Figure 1) Trouble code display

★ Installation Instruction


1. Installation Diagram

Step 1: Disconnect the power.

Step 2: Open the upper cover by turning the slot at the lower end of the wire control using a flat head screwdriver. If there are two control panels, pull off the wires between them.



Step 3: Connect the wires. Fasten the lower cover into the in the internal box inside the wall according to the direction shown (with the arrow pointing up) using the screws provided in the package box.



2. Specifications:

Press buttons: touch buttons:

Installation hole spacing: 58-61mm;

Temperature setting: 16-32℃;

Work temperature: 0-50℃;

Work humidity: 20-90%RH;

Overall dimension: 86*86*18mm(L×W×T).

5 Centralized Controller

1. Centralized Controllerfunction



1).Operation status of as many as 63 indoor units can be monitored, including wind speed, set temperature, etc.

- 2). Mode, air speed and temperature setting are possible for individual/zoned/all indoor units.
- 3). 3 operation modes are available: Last-in Preferred, Centralized Control and Lock;
- 4). The malfunctions of the indoor units can be monitored and saved for inquiry;
- 5). Timed on/off is possible by specifying the exact time or by weekly schedule.
- 6). Any number of centralized units can be zoned with as many as 63 indoor units set as one zone, so that units in the same zone will carry out the same operation. (As the factory default, a centralized group is considered as a zone)

2. Operating Instructions

Enter main screen

During the initialization, no key inputs are processed until the end of the preliminary communication. After the end of the initialization, the centralized controller will display main screen a:

2011/01/18 10:00 Tue				 	
Unit					
			Working	05	
Total	10		Standby	05	


Main screen a Note ①


Switching between the main screen a, b and c is possible by pressing the “Style” key. The main screen a, b and c are collectively called the “the main screens”.

Main screen a: displays the statistic data for the operation of the networked units.

Main screen b: displays list of the networked units.

Main screen c: displays the function information of individual units.

2011/01/18 10:00 Tue					
0102	0304	05	0708	1011	
25					

2011/01/18 10:00 Tue					
Zone	01	Mode:	Cool		
Unit	01	Temp:	25°C		
		Fan:	Low		

Main screen b Note ②③ Main screen c Note ④

Note

① When among all units, one or more are turned on, the operation indicator will light, otherwise, it will remain off.

② Reverse displayed numbers indicate the units that are currently on and normally displayed ones indicate those that are off. Numbers that are not displayed indicate the units that are either not exist or communicatively failed. Press “Page” key to view the next page.

③ Displays the information of the individual unit whose operation status is indicated by the operation indicator. Press “Page” key to view the information of the next unit.

Quick on/off

◇ When the operation indicator is on under main screen a and b, pressing “Power” key will turn off all units. When the operation indicator is off, pressing “Power” key will turn on all units .

◇ Under main screen c, pressing “Power” key will only switch the operation status of the unit that is currently selected.

Set /change time

Under the main screens, press “Set” key to enter the page “ Set Manu”:

```
1 . S e t   T i m e
2 . T i m e r   M o d e
3 . Z o n e / U n i t   S e t
4 . L a n g u a g e   S e t
```

Page "Set Manu"

Select "Set Time" with the "Select" key , then press "Ok" to enter the page " Time Setting ".

```
2 0 1 1 / 0 1 / 1 8   1 0 : 0 0
Y Y / M M / D D   H H : M M
```

Page "Time setting"

- ◇ Under "Time Setting" screen, switch between the items using the "Select" key. The reversely displayed item is the selected one . Change it using the "Change" key.
- ◇ Then, press "Ok" key to make the change effective and return to page " Set Manu" .
- ◇ If the "Exit" key is pressed during making the change, you will return to the main screen without the change being effective.
- ◇ Pressing and holding the "Change" key for 2 seconds enables fast changing.

Timer Mode

- ◇ Under the main screen, press "Set" key to enter the page "Set Manu".Then, select "Timer Mode" using the "Select" key. The timer mode that is currently selected will display on the right of the line. Using the "Change" key to select the desired timer mode. Then press "Ok" key to enter the corresponding page of timer mode.
- ◇ Under the page "Set Manu", select "Timer Mode", then select "No Timer" using the "Change" key to deactivate the timer function.
- ◇ The centralized controller support 3 timer modes: "Current", "Daily" and "Weekly". Only one timer mode can be activated at the same time.

a.Current/Daily Timing

Open	Time 1:	08:00
Close	Time 1:	17:00
Open	Time 2:	09:00
Close	Time 2:	16:00

Current/Daily Timing


- ◇ Current and daily timer mode each has 4 timers with 2 designated for open and the other 2 for close.
- ◇ Switch between the timers using the “Select” key. The reversely displayed item is the currently selected one.
- ◇ Change the time of it using “Change” key. Pressing and holding the “Change” key for 2 seconds enables fast changing.
- ◇ All timers work at same time.
- ◇ Current timer works only for the current day , with the timer mode automatically switched to “No Timer”. The Daily timer always works.
- ◇ If two timers are of the same time but different types , the one that is set to close will be executed.
- ◇ If it is set to open and close the system at the same time, the close order will be executed.
- ◇ The timers are executed by time order. If the current status of the current unit is the same as the target status set by the timer, the timer will be automatically ignored.
- ◇ As exemplified in the above figure, the system is set to open at 8:00AM and close at 16:00 PM.

b.Weekly Timer

1. Open	08:00	SMTWTF S
2. Close	17:00	SMTWTF S
3. Not Used		
4. Not Used		

The list of weekly timers

- ◇ There are 8 weekly timers and the one with the frame shown is currently selected.
- ◇ “Open” and “Close” indicate the related timer is an open and close timer, respectively.“Not Used” indicates that the timer is invalid.“SMTWTF S” indicate the day selection with each letter representing Sunday, Monday, Tuesday, Wednesday, Thursday, Friday, Saturday, respectively. The reversely displayed letter(s) indicates when the timer will work while the normally displayed one(s) indicates when it won’t work.
- ◇ As exemplified timer 1 is currently selected, timer 1 and timer 2 are activated, other timers are invalid. Thus the timing is as follows: The system is set to open at 8:00 AM and close at 17:00 PM from Monday to Friday each week. No operation on Saturday and Sunday.
- ◇ Switch between timer 1-8 using “select” key , with the selected one shown with frame. Now press “Ok” key to enter the change page of the corresponding timer and make desired settings.




Change weekly timing

- ◇ The 3 lines are “Mode”, “Time” and “Weekly” respectively.
- ◇ The line with the frame shown is currently selected.
- ◇ The “Mode” line is to set whether the timer is activated or not and whether it is set to open or close the unit.
- ◇ The “Time” line is to set the work time of the timer.
- ◇ The “Weekly” line is to set the days on which the timer is activated with those days indicated reversely.
- ◇ Switch between the selected item using “Select” key , with the selected one shown with frame.
- ◇ Press “Change” key to make desired changes.
- ◇ After making all the changes, press “Exit” key to return to the previous screen. The setting is now finished.
- ◇ The operation of the other weekly timers are the same as the above. After making the changes, press “Exit” key to return to the main screen.


Zone/Unit Set

Under the main screen, press “Set” key to enter the page “Set Manu”. Then, select “Zone/Unit Set” using the “Select” key. Press “Ok” key to enter the page “Zone/Unit setting”.



Page “Zone/Unit setting”

Select the number of the zone to set using the “Select” key. Press the “Ok” key to distribute the members.




Page “Member Distribution”

- ◇ Under the page “Member Distribution”, select among the different unit numbers. The selected one will flash and the corresponding unit number will be displayed in the first line. Using the “Change” key to decide whether to join the current zone. The reversely displayed numbers belong to the current zone while the normally displayed ones do not belong to the current zone.
- ◇ Press “Page” keys to display other pages.
- ◇ After all members are set , press “Ok” key to finish the setting of the current zone.
- ◇ To set other zones, select the corresponding numbers and repeat the above operation.

Language Set

Under the main screen, press “Set” key to enter the page “Set Manu”. Then, select “Language Set” using the “Select” key. Press “Ok” key to enter the page “Language Setting”.




Page "Language Setting"

Under page "Language Setting", press "Change" key to select the desired language : Chinese or English. After selecting the desired language, press "Ok" key to activate that language.


Zoned Control

Under the main screens, press "Control" key to enter the page " Set Manu a":



Set Manu a

Under the page "Set Manu a", press "Change" key to select among the 3 control modes: "All", "Zone" and "Unit". After selecting the desired mode, press "Ok" key to enter the submenu. Pressing "All" mode will directly open the page "Control Setting" and others will open the page "Set Manu b". Select the target code and press "Ok" to enter the page "Control Setting".





In the page "Control Setting", the items displayed on the left are the control targets and those displayed on the right are the specific controls. Press "Select" key to switch between the different items and change the controls using "Change" key. After changing the setting, press "Ok" key to make the change effective.

Centralized Control and Lock Functions

Under the main screen, press "Centralize" key to switch between the regular, centralized and lock modes. The upper right icon on the main screen indicates centralize status.

The icon is not displayed in the regular mode and the indoor unit is controlled in "Last-in Preferred" mode.

In the centralized mode, a  icon will display with the indoor unit run under the settings of the centralized controller, but the remote control and line control work for the open and close of the indoor unit.

In the lock mode, a  icon will display with the operation status of the centralized controller remain unchanged. The remote control and the line control do not work for the open and close of the indoor unit.

Failure Inquiry Function

Under the main screens, press and hold the "Style" key to enter the "Historical Failures Inquiry" screen.

F a u l t	(0 1 / 2 0)
<hr/>	
U n i t 0 1	
R e c e n t l y :	a 3
P r e v i o u s l y :	j 4

Historical Failure Inquiries

Under the page “Historical Failure Inquiry”, press “Select” key to switch between the historical failures of each unit, with units that have no historical failures


For the meaning of the specific trouble code, refer to the technical manual of the unit.

Accessory : Centralized Controller Adaptor


Function : Centralized controller adaptor is used with centralized controller together.



Wiring Diagram



Wiring Diagram among Adapter Plate, Centralized Controller, Weekly Timer and Monitor



- (1) Connect to power supply of 220V.
- (2) Connect B and A with communication line of indoor unit;
- (3) Connect 12V, GND, BO and AO with communication line of centralized controller;
- (4) Connect BO and AO with communication line of the others adapters.

5 Centralized Controller Software

5.1 System overview

DC inverter GRV units distribute complicated and dispersedly in buildings. It will adverse to centralized control, management and maintenance, if there has not a good centralized control system. To solve this problem, we develop a GRV centralized control system combine with electronic and computer technologies. Though the RS-485 network, this system can capture and control the function of all the GRV units in buildings. And information will be intuitive reflected in computer; these greatly facilitate users to control the units.




The overall structure of the system shown

5.2 Features:

- ◇ Users do not need to arrive the harsh environment of the site, they can monitor the function of units just through computer. These greatly improve convenience of daily management and the efficiency of central air conditioners;
- ◇ Centralized control can improve the efficiency of air conditioners. It is more energy-efficient and environmental ;
- ◇ Timely find the fault and save the maintenance cost of air conditioner units, minimize losses ;
- ◇ Timer function with multi-period week, fully automated schedule planning of unit;
- ◇ This system is suitable for all DC inverter GRV types of GREEN;
- ◇ Each GRV unit can access at most 63 indoor sets;
- ◇ This system can access at most 64 GRV outdoor systems, it need to access repeater to increase RS485 network equipment if the outdoor systems are more than 64. The way of wiring is instructed in Engineering installation and wiring description;
- ◇ Every GRV unit need to configured a communication adapter plate;
- ◇ If PC has RS-485 interface,there is no need to configuration RS-232 to RS-485/422 Optically isolator.

5.3 Main components of Centralized Controller System

No.	Main components	Required
1	PC	Operation system: Windows XP SP2 and above, Windows 7; Minimum hardware requirements: CPU:P4, 2.0GHz; Hard-disk space: 20G; RAM: 1G; Display:17 inches and above, resolution 1024*768 and above; Serial port: at least one normal work serial port; Others:ensure computer works independently on the system, no connection other network (Internet, Local Area Network).And remove or sealed the external input equipment, such as USB port, CD-rom (CD-rom can be removed after finishing installing the system), to prevent the invasion of computer virus; computer does not install other software which is irrelevant the system; equipped with UPS to prevent computer powered-off more than 1 hour,
2	RS-232 to RS-485/422 converter	
3	RS-485/422 Repeater	GRV System >64 sets must be used.
4	Communications adapter plate	

No.	Main components	Required
1	Host computer	Operation system: Windows XP SP2 and above, Windows 7
2	Communications adapter plate 	Computer and communication protocol and unit end communication protocol are incompatible with each other, must add communication adapter plate to make both communicate.
3	RS-232 to RS-485/422 converter 	The centralized control system RS485 network signal conversion for RS232 serial signal to achieve the interconnection of computers with centralized control system.
4	RS-485/422 Repeater 	Extend the communication distance and increase the number of RS-485 bus network. The repeater is not required, only when there is more than 64 communications equipment or communication distance is more than 800 meters.

5.4 Softwareinstall and uninstall

- 1) Run setup.exe in CD to install;
- 2) If operation system has not installed Windows Install 3.1 and Windows .NET Framework 3.5,the installation program will install the two program first; when programs installation is completed, system installation will be continue, the default installation path is D:\Program Files\GREEN Group\GREEN_GRV_Setup.
- 3) uninstall:select [Control Panel- Add or Remove Programs -GREEN_GRV_Setup],click"Cancel" to uninstall.

5.5Software introduction Main interface

Area 1 --Serial setting area, choose the serial and press "Start Working button, system will in operation, press "Stop Working" button, system will stop working;

Area 2 --The inquire area for air conditioner unit, it can be divided into the system inquire and user-defined group inquire, the inquired unit will be displayed in area 4.


Area 3 --Display area of single air conditioner indoor unit, select one of indoor units in area 4, then the area will display the name, ID (address of indoor unit) , system belonged ,group belonged, current condition, the room temperature of indoor unit , failure etc.

Area 4 --Display area of air conditioner group, as shown in above picture, it displayed all the indoor unit in the group System01.

Area 5 --Control area of air conditioner, it can control one single air conditioner and some air conditioner group, this will be described in detail later.

5.6 System initial setting

click"Aircondition Config" in area 4,it will enter the interface of system initial setting. Initial setting is divided into 3 parts: added/removed outdoor unit system, added/modified/removed air conditioner, add/changed user-defined group.



◇ Added/removed outdoor unit system

Area 6 shown in the figure above is the operation area of added/removed outdoor unit system. The quantity of outdoor unit system of the whole project must match with the added one in figure 6, and the centralized control address (the address displayed on communication adapter plate)of every system must correspond with the system serial number.

Note:


If the outdoor unit system deleted, the indoor unit belonged in it will also be delete! Please handle with care.

◇ Added/deleted indoor unit


Area 7 shown in the figure above is the operation area of added/deleted indoor unit. Before added, user need to select one option in area 6 shows that he would add indoor unit in that outdoor system(the added quantity of indoor unit system must match with the actual quantity in the outdoor system).

5.7 Concrete operation:

Click“Add Aircondition”button,the following dialog box will pop up




Click Based On Gateway button,there will generate a name (the red circle part in the figure below) according to indoor unit address and the system it belongs; click Custom button, user need to set a name by himself.



Then is to choose the group the air conditioners belong. User can choose a group defined by himself in Area Select. If there has not user-defined group, user can establish a user-defined group in Create nodule, detail explanation in Added/changed user-defined group. Click "OK" to complete new group addition after the completion of the new group added.

5.8 Added/changed user-defined group



The red circle part in the figure above is the added and changed operation area.

If user need to add new group, first, click New Zone button and input the name of user-defined group, then click Add Zone button, here will show the name inputted just now, establishment complete;


If user need to modify the name of group, select the group in Zone Select, input the new name, then click the Rename button, modification complete when the new name show in Zone Select.;

Note:


Group deletion does not support now, be careful when adding.

5.9 System query operation

System query operation includes system query and user-defined group query. Query ways can be chosen as the figure below:



- ◇ If the chosen group is in According to System, then all the unit condition of the group will be displayed in area 4 (area 4 will display the condition of all the indoor unit in System01 as the above picture shows).
- ◇ If user chooses one of the group in According to Zone, area 4 will display the condition of all the units in it. In addition, user can move the indoor unit to other groups arbitrarily under the state of user-defined group query, its operation as follow figure:



When system is working (click Start Working in area 1), area 4 will display all the working condition of indoor unit, as shown in the following figure——



- ◇ No background is turned off;
- ◇ Green background is turned on;
- ◇ Red background is system failure;
- ◇ Yellow background is communication failure or electrical failure.

5.10 System control operation

System control can be divided into single unit control; group control and weekly group timing control 3 parts. Single unit control achieves the controlling of one indoor unit; group control achieves the controlling of System group and Zone group; weekly group timing control achieves the weekly timing control of Zone group (user-defined group).

1) Single unit control



Besides on/off, temperature setting, mode setting, indoor speed setting, single unit control added the lock function (lock the 4 function above). If one function is locked, user cannot use it. For example, if ON/OFF is lock(choose Lock in ON/OFF), user cannot turn on/off the locked unit by remote or wired controller. Indoor unit will executive command when click Apply after setting completed.

2) Group control


Group control achieves the unified control of one group, setting interface is shown as following figure:



Besides the general control and locking control of single unit control, group control is added the Active function. The matching state of indoor unit will change only when choose Apply function, unselected ones stay unchanged. For example, choose ON and Active, all the indoor units will be turned on, but the temperature, mode, speed will not be changed like the setting of group. Indoor unit will executive command when click Apply after setting completed.

3) Weekly group timing control

Weekly group time control is one of the control function in user-defined Zone, system group has no this function, setting can be chosen only when the user-defined region is selected in query. Shown as figure below:



Then setting dialog box will pop out when Week Plan is selected, shown as figure below, After completion of set, click the "OK" button to finish the setting.

Notes:

- ◇ All the related intellectual property rights as System patent right, software copyright etc. ownership belongs to Ningbo GREEN Electrical Company Ltd.. Any unit or individual shall not copy, assignment, transact or use related production in other ways without permission. Otherwise Ningbo GREEN Electrical Company Ltd. will have the right to pursue legal responsibilities.
- ◇ If system is damaged by suffering a natural force majeure (such as earthquake fire typhoon, etc.), all losses should be responsible for system investors.
- ◇ The user should use legal copy of Windows XP or Windows 7 and other legal copy of related software and antivirus software, make sure the computer is virus free and the Computer Independent Connecting Billing System is unaffected by other network or external port (USB port etc.), otherwise it is the users' responsibilities if there is any lost or damage.
- ◇ The user should use authorized computers along with UPS, the UPS should use the standard that it

can keep the computer working for at least one hour if the power is suddenly cut off, and during this one hour the administrator would take care of the computer. It is users' responsibilities if any accident or data loss happened because of a sudden power failure.

- ◇ The user must make sure that the Photoelectric isolating converter is placed in a safe place that the converter is not easily damaged by people, make sure the wiring terminal is not loose leading to poor contact, and make sure the power is NOT easily cut off, otherwise it is the users' responsibilities if there is any lost or damage.
- ◇ To make sure the system work for a long time, the user should regularly check and repair it, reboot the computer at a fixed time every day, so that the computer could run in a good environment, ensure the reliability of the system, release the computer resource. Here is what users should do, first stop the communications of Billing System, then exit it, reboot the computer, open the software after the computer is rebooted.

Part 7 Trouble shooting

Poor effect of cooling and heating	408
Error code indication.....	409
Indoor unit error code explanation.....	411
Indoor unit error code explanation.....	411
Outdoor unit error code explanation.....	412
Symbol Description	416
Centralized controller software trouble shooting	417
Appendix	418

1 Poor effect of cooling and heating


Some phenomena in using process are similar to failures, which are not failures in fact. Therefore, when cooling performance isn't satisfactory, eliminate the following factors first:

Phenomenon	Cause Description
If there is high ambient temperature outside and more people in room, air conditioner works in full load and cool air is blown from outlet, but room temperature can't be lowered.	In case of high ambient temperature, infiltration heat from outside increases, which increases cooling load of air conditioner; if there are more people (e.g.10 people) in room, each people discharges 120W heat, 10 people discharge 1200W heat altogether, which consume half cooling capacity of air conditioner, therefore, cooling capacity of air conditioner seems not enough and room temperature can't be lowered. It's normal and not the fault of air conditioner.
Air conditioner is hard to start, stops after starting or fuse is blown due to under voltage of power supply.	It is not failure. It's necessary to check the cause of power supply. If it is caused by under voltage of power grid, user should install additional voltage stabilizer for power supply to enable voltage to reach 220V or 380V and use air conditioner normally.
When it operates under high air velocity, room temperature can't cool down and there is no much air flow volume at outlet.	Filth blockage of air filter makes cooling capacity can't be taken out by flowing air timely, causing insufficient cooling capacity that can be solved by removing and cleaning filtering net.
When it operates under high air velocity, unit vibrates and makes loud noise	It is normal that the unit vibrates and makes loud noise when it operates in maximum speed.
Temperature controller isn't properly adjusted and doesn't bring maximum function of cooling, so room temperature can't cool down.	Adjust temperature controller to solve the problem
Heat pump-type air conditioner has unsatisfactory heating effect in cold winter, which is reasonable.	Minimum ambient temperature for starting heating function of air conditioner is -15°C . So air conditioner can't effectively heat below this temperature.
Improper installation position of air conditioner can also result in uneven indoor temperature or poor cooling effect.	Readjust the installation position of air conditioner.
mist blown out from indoor unit	It is caused when cool airflow in air conditioner cools down the air in indoor unit.
noise	Air conditioner will make noise when stopping operation, because refrigerant in the unit flows to opposite direction;
	Air conditioner will expand or shrink due to air temperature change, causing harsh sound; sound of water flow is caused by refrigerant flowing in the unit.
odor in room sometimes	Air conditioner won't bring odor by itself, so it must be caused by odor accumulated in environment.
	Solution: clean air filtering net.
In case of heating, air isn't blown out immediately after starting the unit and "Operation" indicator flickers when wired controller is used.	The heating state is used to prevent blowing out cool air. Please wait for a moment.
	The unit has restart function upon power-on after power failure. Air conditioner will automatically start in case of power-on after power failure and operate according to the mode set before power failure.

2.Error code indication

Indoor unit error code display

After indoor and outdoor units shut down due to failure, failure code will display on wired controller or remote receiving board. In case of normal protection, no failure code will display on wired controller or remote receiving board of indoor unit. Among others, wired controller doesn't automatically send warning, which requires pressing CHECK button to display corresponding failure codes. Remote receiving board directly displays failure codes. After failures are removed, display will automatically disappear. Wired controller uses failure code of two digits, the first digit of which indicates characters in column "B" and the second digit of which indicates "0~F" characters corresponding to each row.



Remote receiving panel uses three indicators. Power light and timing light have three states respectively corresponding to row "9" and column "B". Flickering times of running light correspond to "0~F" characters of each row. The details are shown below:

Power lamp	Timing lamp	Running lamp	Faults	
○	○	★(1~15times)	Indoor	A
○	●		Outdoor	C
○	★			E
●	○			H
●	●			F
●	★			J
★	○			3
★	●			4
★	★		5	
			1~F-15Faults	

Remarks:

○(dim), ●(on), ★(flashing)

When power light or timing light flickers, it only flickers one time for each warning. After flickering, running light indicates according to specific failure.

For four way cassette panel add the digital light display error code




Outdoor unit error code display

For outdoor units, the error code displays on the main PCB.

Outdoor unit control box



Outdoor unit main PCB



3 Indoor unit error code explanation

Error code	Error code definition	Recovery or not	Problem possible reasons
A1	Indoor ambient temperature sensor failure	Yes	Indoor PCB is broken
			The fuse of indoor PCB is broken
			temperature sensor broken , or exceed test limit
A2	Temperature sensor about middle position of evaporator failure	Yes	Indoor PCB is broken
			The fuse of indoor PCB is broken
			temperature sensor broken , or exceed test limit
A3	Indoor coil pipe inlet temperature sensor failure	Yes	Indoor PCB is broken
			The fuse of indoor PCB is broken
			temperature sensor broken , or exceed test limit
A4	Indoor coil pipe outlet temperature sensor failure	Yes	Indoor PCB is broken
			The fuse of indoor PCB is broken
			temperature sensor is broken , or exceed test limit
A5	Indoor water pump failure	Yes	Water pump no power
			Water pump switch short-circuit or unconnected
			Water pump is broken
			Drain pipe block or up lean
			Indoor PCB is broken
A6	Failure of indoor PG fan	No	Fan motor failure
			Fan motor block
			The connection between PCB and fan motor failure.
			Indoor fan block
A7	Failure of reversible synchronous motor	No	Step motor failure
			The connection between PCB and step motor failure.
A8	Indoor unit ERRPROM module failure	No	Indoor unit PCB is broken
			Error module is broken.
A9	The communication between indoor unit and outdoor unit failed	No	The communication wire between indoor unit and outdoor unit is broken.
			Indoor unit power close
			Indoor PCB is broken
AA	The communication between indoor unit and wire controller failed	No	The communication wire between indoor unit and outdoor unit is broken.
			Indoor unit power close
			Indoor PCB is broken
			Wire controller is broken
AC	Two or more indoor unit central control system address repeated	Yes	The central control address setting incorrect
AE	Operation mode conflict	Yes	The operation mode setting incorrect
AH	Two or more indoor unit refrigerant system address repeated	Yes	System address setting incorrect
AJ	Indoor unit total capacity exceeded	Yes	Stop some indoor units
AF	The EXV leakage	Yes	EXV is blocked
			Indoor unit temperature sensor issue.
			Evaporator inlet sensor failure.
A0	The EXV to open failure	No	

4. Outdoor unit error code explanation

Code	Error code definition	Recovery or not	Possible reason
C1	Ambient temperature sensor "Tao" failure	Yes	Temperature sensor failure or test temperature exceed limit.
			Sensor connection is incorrect.
			Outdoor unit PCB failure.
C2	Defrosting temperature sensor "Tdef1" failure	Yes	Temperature sensor failure or test temperature exceed limit.
			Sensor connection is incorrect.
			Outdoor unit PCB failure.
C3	Discharge temperature of inverter compressor "Tda" failure	Yes	Temperature sensor failure or test temperature exceed limit.
			Sensor connection is incorrect.
			Outdoor unit PCB failure.
C4	Discharge temperature of fixed frequency compressor "Tdb" failure	Yes	Temperature sensor failure or test temperature exceed limit.
			Sensor connection is incorrect.
			Outdoor unit PCB failure.
C6	Suction pipe temperature of compressor "Ts" failure	Yes	Temperature sensor failure or test temperature exceed limit.
			Sensor connection is incorrect.
			Outdoor unit PCB failure.
CH	Subcooling of inlet liquid pipe temperature sensor "Tci" failure	Yes	Temperature sensor failure or test temperature exceed limit.
			Sensor connection is incorrect.
			Outdoor unit PCB failure.
F1	High pressure sensor "Pd" failure	Yes	High pressure sensor failure
			Low pressure sensor connection is incorrect.
			Outdoor unit PCB failure
F3	High pressure sensor "Pd" protection.	Yes	Exhaust pipe or condenser pipe block
			Condenser dirty
			Outdoor unit fan stop or low speed
F4	Low pressure sensor "Ps" failure.	Yes	Refrigerant overcharge
			Low pressure sensor is broken.
			The connection between sensor and outdoor PCB incorrect
F6	Low pressure sensor "Ps" protection.	No	Outdoor unit PCB failure
			Indoor unit fan stop or low speed
			Evaporator dirty
			Indoor EXV full open in cooling mode (Outdoor EXV full open in heating mode)
F8	Compression ratio too high protection	No	Lack refrigerant
			The pipe between evaporator and suction port block
F9	Compression ratio too low protection	No	Once confirm the unrecoverable
FB	DC inverter compressor low discharge temperature "Tdi" limit frequency protection	No	Once confirm the unrecoverable
H1	DC inverter compressor high pressure switch "HPSi" failure	No	System pressure exceed high pressure switch limit.
			High pressure switch failure
			High pressure sensor failure
			Instantaneous power-off
			Stop valve closed

			Outdoor unit fan stop
			Outdoor unit air outlet block
			In heating mode indoor unit fan stop
			In heating mode indoor unit EXV block
H2	Fix speed compressor high pressure switch "HPS1" failure	No	System pressure exceed high pressure switch limit.
			High pressure switch failure
			High pressure sensor failure
			Instantaneous power-off
			Stop valve closed
			Outdoor unit fan stop
			Outdoor unit air outlet block
			In heating mode indoor unit fan stop
			In heating mode indoor unit EXV block
H4	Low pressure switch "LPS" failure	Yes	System pressure lower than low pressure switch limit.
			Low pressure switch failure
			Low pressure sensor failure
			Instantaneous power-off
			Stop valve closed
			In cooling mode indoor unit EXV close or block
			In heating mode outdoor unit EXV close or block
			In heating mode outdoor unit fan stop
			In heating mode outdoor unit air outlet block
H5	Lack refrigerant	No	System leakage
H8	Fix speed compressor 1 over current protection	Yes	The stop valve closed
			Outdoor unit air outlet block
			System supply power voltage exceed limit (Rated voltage 15%)
			Compressor failure
			Current transformer failure
H9	Fix speed compressor 2 over current protection	Yes	The stop valve closed
			Outdoor unit air outlet block
			System supply power voltage exceed limit (Rated voltage 15%)
			Compressor failure
			Current transformer failure
HJ	Main power failure	No	Supply power phase-reversal
			Supply power phase lack
			Outdoor unit PCB failure
E3	DC inverter discharge temperature "Tda" too high shutdown protection	No	System less refrigerant
			DC inverter Compressor failure
			Compressor air return filter block
			EXV open degree is small
			EXV block
			Gas pipe stop valve closed
			Liquid pipe stop valve closed
			System exhaust sensor failure
			Outdoor unit PCB failure

E4	Fixed speed compressor No.1 discharge temperature "Tdb" too high shutdown protection	No	System less refrigerant
			Fix speed compressor failure
			Fix speed compressor air return filter block
			EXV open degree is small
			EXV block
			Gas pipe stop valve closed
			Liquid pipe stop valve closed
			System exhaust temperature sensor failure
			Outdoor unit PCB failure
E5	Fixed speed compressor No.2 discharge temperature "Tdc" too high shutdown protection	No	System less refrigerant
			Fix speed compressor failure
			Fix speed compressor air return filter block
			EXV open degree is small
			EXV block
			Gas pipe stop valve closed
			Liquid pipe stop valve closed
			System exhaust temperature sensor failure
			Outdoor unit PCB failure
EC	Low discharge temperature protection of fixed frequency compressor No.1,"Tdb"	No	Once confirm the unrecoverable
EJ	Low discharge temperature protection of fixed frequency compressor No.2,"Tdc"	No	Once confirm the unrecoverable
J1	The communication between outdoor units failure	Yes	The communication wire between outdoor units is disconnect, short circuit or connect incorrect.
			Outdoor unit PCB failure
			Outdoor unit main power failed
J2	The communication between outdoor unit and indoor unit failure	Yes	The communication wire between indoor unit and outdoor unit disconnect, short circuit or connect incorrect.
			Indoor unit main power failed
			Indoor unit PCB failure
J3	The communication between PCB and INV module failure	Yes	The connection between driving module and main PCB failure
			The communication part of outdoor unit control PCB failure
			Frequency driving board failure
			Compressor failure
J4	The communication between main PCB and DC fan motor drive module failure	Yes	DC fan motor drive module failure
			DC fan failure
J5	Outdoor unit parameter setting incorrect	Yes	Outdoor unit dial switch incorrect
			Mail PCB failure
J7	Outdoor unit main control PCB ERROM module failure	No	Mail PCB failure
JJ	Indoor unit total capacity exceeding	Yes	/
JE	Oil return failure or defrosting failure	Yes	/
JF	"MCU" automatic reset failure	Yes	/

31	Module protection (F0)	Yes	Supply voltage below level let the current excessive
			Supply voltage exceed limit
			Outdoor fan stop or low speed
32	Module hardware protection	Yes	Supply voltage below level let the current excessive
			Supply voltage exceed limit
			Outdoor fan stop or low speed
33	Module software protection	Yes	Supply voltage below level let the current excessive
			Supply voltage exceed limit
			Outdoor fan stop or low speed
34	Compressor unconnected	Yes	The connect of driving module and DC inverter compressor incorrect
			Driving module failure
			Compressor failure
35	Compressor phase current overload protection	Yes	Compressor overload
			Compressor coil disconnect
			Inverter driving board failure
			Compressor failure
36	DC bus voltage over-voltage or under-voltage failure	Yes	Supply voltage below level
			Supply voltage exceed limit
			Driving module failure
37	Temperature sensor of drive module heat fins failure	No	Inverter driving board failure
38	Drive module high temperature limit frequency failure	Yes	Driving module failure
			Compressor failure
			Outdoor unit fan stop or low speed
39	Drive module high temperature shutdown protection	Yes	Driving module failure
			Compressor failure
			Temperature sensor failure
3A	DC fan motor drive module protection	No	Once confirm the unrecoverable
3C	DC fan motor drive module overcurrent protection or overcurrent sensor failure	No	Once confirm the unrecoverable
3H	DC fan motor drive module start failure or Running out of step	No	Once confirm the unrecoverable
3J	DC fan motor drive module over-voltage or under-voltage protection	No	Once confirm the unrecoverable
3E	DC inverter compressor running out of step	No	Once confirm the unrecoverable
41	DC inverter compressor drive module IPM alarm	No	Once confirm the unrecoverable
42	DC fan motor overspeed protection	No	Once confirm the unrecoverable
43	DC fan motor drive module Eeprom data corruption	No	Once confirm the unrecoverable
47	Indoor unit loss failure	Yes	Communication wire between indoor units failure
			Indoor PCB failure
			Power supply of indoor units failure

5.Symbol Description

Symbol	Abbreviation	Detailed information
	Pd	Discharge pressure
	Ps	Suction pressure
	Tda	DC inverter compressor discharge temperature
	Tdb	Fixed speed compressor 1# discharge temperature
	Tcm	Temperature of middle point of condenser
	Ts	Temperature of main suction pipe
	Tao	Outdoor ambient temperature
	Tci	Inlet temperature of plate heat exchanger refrigerant
	Tdef	Defrosting temperature of condenser
	CT1	Fixed speed compressor 1# running current
	CT2	Fixed speed compressor 2# running current
	PMV1	Electronic expansion valve 1 (for heating)
	PMV2	Electronic expansion valve 2
	PMV3	Electronic expansion valve of subcooling
	LPS	Low pressure switch
	HPSa	DC inverter compressor high pressure switch
	HPSb	Fixed speed compressor 1# high pressure switch
	HPSc	Fixed speed compressor 2# high pressure switch
	SVA	Oil return electromagnetic valve of DC inverter compressor
	SVB	Oil return electromagnetic valve of fixed speed compressor
	SV0	Four-way valve
	SV1	Unloading valve
	Tset	Temperature setted
	Tai	Temperature of indoor ambient
	Te1	Refrigerant outlet temperature of indoor coil in cooling mode
	Te2	Refrigerant inlet temperature of indoor coil in cooling mode
	Tem	Temperature of middle point of indoor coil

6. Centralized controller software trouble shooting

Troubles	Possible Reasons	Troubleshooting method
Software on the communication failure warning, some or all of the air conditioners cannot indicate or query the status.	Some Communication wires are not Twisted-pairs	Replace them with Twisted-pairs
	The CN2 of the communication adapter plate has loosening or shedding in connection.	Rotating the Communication wire of CN2
	Communication wires have breakages	Welding the Communication wires or replace new ones
	Spring inside the socket cannot bounce or has been pushed to the end result in the Communication wire not connected.	Repair or replace socket
	Communication wire A&B short circuit or connected to wrong places.	Repair the short circuit section or exchange port A&B.
	Communication wire and the power line got too close (< 15cm)	Apart the Communication wire and the power line to at least 15cm, otherwise wrap them with shield steel pipes.
Line inspection is normal, but some or all of the some or all of the air-con cannot indicate or query the status, or the address got conflict.	Serial port of the computer terminal Communication wire and the software selection one does not match.	Replace the ports or change the serial port setting.
	The communication adapter plate does not supply power after reset the address and result in the new address not effective.	Power on communication adapter plate again.
	Unit has no power supply.	Power on unit
	The address of the computer groups got error or repeated.	One more check and modify the address setting.
Line inspection is normal, but one of the air-con cannot indicated or query the status.	Communication adapter plate got system halted or hardware damaged.	Change communication adapter plate
	Maybe the repeater need installing or gets incorrect connection.	Installing the repeater correctly.

7.Appendix

Relation between temperature sensor of compressor and resistance

R25=50K ±1%			
B25/50=3950K ±1%			
T [°C]	Rmin [K]	Rnom [K]	Rmax [K]
-20	449.9	464.7	479.9
-19	425.7	439.5	453.6
-18	402.9	415.7	428.8
-17	381.5	393.4	405.6
-16	361.3	372.3	383.6
-15	342.2	352.5	363.0
-14	324.3	333.9	343.7
-13	307.5	316.4	325.5
-12	291.5	299.8	308.3
-11	276.6	284.3	292.2
-10	262.4	269.6	276.9
-9	249.0	255.7	262.5
-8	236.5	242.7	249.0
-7	224.5	230.3	236.2
-6	213.3	218.7	224.2
-5	202.7	207.7	212.8
-4	192.7	197.3	202.0
-3	183.2	187.5	191.9
-2	174.3	178.3	182.4
-1	165.8	169.5	173.3
0	157.7	161.2	164.7
1	150.2	153.4	156.7
2	142.9	145.9	148.9
3	136.1	138.9	141.7
4	129.7	132.3	134.93
5	123.6	126.0	128.4
6	117.8	120.0	122.3
7	112.2	114.3	116.4
8	107.1	109.0	111.0
9	102.1	103.9	105.7
10	97.42	99.08	100.8
11	92.97	94.51	96.06
12	88.74	90.17	91.61
13	84.73	86.05	87.38
14	80.92	82.14	83.37
15	77.29	78.42	79.56
16	73.84	74.89	75.95
17	70.57	71.54	72.51
18	67.46	68.35	69.25
19	64.49	65.32	66.15
20	61.68	62.44	63.20

21	59.00	59.70	60.40
22	56.44	57.09	57.74
23	54.02	54.61	55.20
24	51.70	52.25	52.80
25	49.50	50.00	50.50
26	47.37	47.87	48.37
27	45.34	45.84	46.34
28	43.41	43.91	44.41
29	41.59	42.08	42.57
30	39.84	40.33	40.82
31	38.18	38.66	39.15
32	36.59	37.07	37.55
33	35.07	35.55	36.03
34	33.64	34.11	34.58
35	32.27	32.73	33.20
36	30.95	31.41	31.87
37	29.70	30.15	30.61
38	28.50	28.95	29.40
39	27.37	27.81	28.25
40	26.29	26.72	27.16
41	25.24	25.67	26.10
42	24.25	24.67	25.09
43	23.31	23.72	24.14
44	22.41	22.81	23.22
45	21.53	21.93	22.33
46	20.71	21.10	21.50
47	19.92	20.30	20.69
48	19.16	19.54	19.92
49	18.44	18.81	19.18
50	17.75	18.11	18.48
51	17.08	17.44	17.80
52	16.44	16.79	17.14
53	15.84	16.18	16.53
54	15.26	15.59	15.93
55	14.69	15.02	15.35
56	14.16	14.48	14.81
57	13.65	13.96	14.28
58	13.15	13.46	13.77
59	12.69	12.99	13.30
60	12.23	12.53	12.83
61	11.80	12.09	12.39
62	11.39	11.67	11.96
63	10.98	11.26	11.54
64	10.60	10.87	11.15
65	10.23	10.50	10.77
66	9.880	10.14	10.41
67	9.537	9.792	10.05

68	9.211	9.460	9.715
69	8.897	9.141	9.391
70	8.595	8.834	9.078
71	8.306	8.539	8.778
72	8.028	8.256	8.490
73	7.759	7.983	8.212
74	7.501	7.720	7.944
75	7.254	7.468	7.687
76	7.016	7.225	7.440
77	6.786	6.991	7.201
78	6.565	6.765	6.971
79	6.352	6.548	6.749
80	6.147	6.339	6.536
81	5.950	6.138	6.331
82	5.761	5.944	6.133
83	5.578	5.757	5.942
84	5.401	5.577	5.758
85	5.231	5.403	5.580
86	5.069	5.237	5.410
87	4.912	5.076	5.245
88	4.760	4.921	5.087
89	4.615	4.772	4.934
90	4.474	4.628	4.787
91	4.338	4.489	4.645
92	4.207	4.354	4.506
93	4.081	4.225	4.374
94	3.958	4.099	4.245
95	3.840	3.978	4.121
96	3.726	3.861	4.001
97	3.616	3.748	3.885
98	3.509	3.639	3.773
99	3.407	3.534	3.665
100	3.308	3.432	3.560
101	3.212	3.333	3.459
102	3.119	3.238	3.361
103	3.030	3.146	3.267
104	2.942	3.056	3.174
105	2.858	2.970	3.086
106	2.778	2.887	3.000
107	2.699	2.806	2.917
108	2.623	2.728	2.837
109	2.549	2.652	2.758
110	2.479	2.579	2.683
111	2.410	2.508	2.610
112	2.343	2.439	2.539
113	2.279	2.373	2.471
114	2.216	2.308	2.404

115	2.156	2.246	2.340
116	2.097	2.186	2.278
117	2.040	2.127	2.217
118	1.985	2.070	2.158
119	1.932	2.015	2.102
120	1.880	1.962	2.047

Relation between Temperature Sensor of Coil Pipe and Resistance

R25=20K ±1%							
B25/50=3950K ±1%							
Temp ()	resistance(K)			(resist.tol)		(temp.tol)	
	Rmax	R(t) Normal	Rmin	MAX(+)	MIN(-)	MAX(+)	MIN(-)
-30	377.571	347.000	318.338	8.81	8.26	1.36	1.36
-29	354.642	326.228	299.608	8.71	8.16	1.35	1.35
-28	333.353	306.927	282.189	8.61	8.06	1.33	1.33
-27	313.547	288.957	265.927	8.51	7.97	1.32	1.32
-26	295.088	272.196	250.774	8.41	7.87	1.31	1.31
-25	277.860	256.541	236.582	8.31	7.78	1.30	1.30
-24	261.761	241.901	223.323	8.21	7.68	1.29	1.29
-23	246.699	228.193	210.873	8.11	7.59	1.27	1.27
-22	232.598	215.349	199.219	8.01	7.49	1.26	1.26
-21	219.385	203.304	188.260	7.91	7.40	1.25	1.25
-20	206.995	192.000	177.984	7.81	7.30	1.24	1.24
-19	195.360	181.376	168.317	7.71	7.20	1.23	1.23
-18	184.441	171.398	159.212	7.61	7.11	1.21	1.21
-17	174.193	162.025	150.667	7.51	7.01	1.20	1.20
-16	164.568	153.215	142.613	7.41	6.92	1.19	1.19
-15	155.527	144.932	135.048	7.31	6.82	1.17	1.18
-14	147.029	137.141	127.911	7.21	6.73	1.16	1.17
-13	138.912	129.812	121.205	7.01	6.63	1.15	1.15
-12	131.406	122.913	114.874	6.91	6.54	1.14	1.14
-11	124.346	116.418	108.921	6.81	6.44	1.12	1.13
-10	117.701	110.300	103.307	6.71	6.34	1.11	1.12
-9	111.446	104.536	98.003	6.61	6.25	1.10	1.11
-8	105.556	99.104	93.009	6.51	6.15	1.08	1.09
-7	100.007	93.983	88.288	6.41	6.06	1.07	1.08
-6	94.780	89.154	83.840	6.31	5.96	1.06	1.07
-5	89.852	84.598	79.632	6.21	5.87	1.05	1.06
-4	85.124	80.298	75.665	6.01	5.77	1.03	1.05
-3	80.746	76.240	71.910	5.91	5.68	1.02	1.03
-2	76.615	72.408	68.368	5.81	5.58	1.01	1.02
-1	72.717	68.789	65.019	5.71	5.48	1.00	1.01
0	69.037	65.370	61.847	5.61	5.39	0.98	1.00
1	65.563	62.139	58.852	5.51	5.29	0.97	0.99
2	62.280	59.084	56.012	5.41	5.2	0.96	0.97
3	59.180	56.196	53.330	5.31	5.1	0.94	0.96
4	56.248	53.463	50.785	5.21	5.01	0.93	0.95
5	53.428	50.879	48.381	5.01	4.91	0.92	0.94
6	50.810	48.432	46.098	4.91	4.82	0.91	0.93
7	48.335	46.117	43.940	4.81	4.72	0.89	0.91
8	45.993	43.924	41.895	4.71	4.62	0.88	0.90
9	43.776	41.847	39.951	4.61	4.53	0.87	0.89
10	41.678	39.879	38.112	4.51	4.43	0.86	0.88
11	39.691	38.015	36.365	4.41	4.34	0.84	0.87

12	37.809	36.247	34.710	4.31	4.24	0.83	0.85
13	36.026	34.571	33.136	4.21	4.15	0.82	0.84
14	34.338	32.982	31.646	4.11	4.05	0.80	0.83
15	32.736	31.474	30.228	4.01	3.96	0.79	0.82
16	31.218	30.043	28.883	3.91	3.86	0.78	0.81
17	29.778	28.685	27.606	3.81	3.76	0.77	0.79
18	28.411	27.395	26.390	3.71	3.67	0.75	0.78
19	27.115	26.170	25.236	3.61	3.57	0.74	0.77
20	25.885	25.007	24.137	3.51	3.48	0.73	0.76
21	24.717	23.902	23.094	3.41	3.38	0.72	0.75
22	23.607	22.851	22.099	3.31	3.29	0.70	0.73
23	22.554	21.853	21.156	3.21	3.19	0.69	0.72
24	21.553	20.903	20.255	3.11	3.1	0.68	0.71
25	20.600	20.000	19.400	3.00	3.00	0.66	0.70
26	19.734	19.141	18.549	3.10	3.09	0.69	0.72
27	18.909	18.323	17.739	3.20	3.19	0.72	0.75
28	18.123	17.545	16.970	3.30	3.28	0.74	0.78
29	17.374	16.804	16.238	3.40	3.37	0.77	0.80
30	16.660	16.098	15.541	3.49	3.46	0.80	0.83
31	15.979	15.426	14.879	3.59	3.55	0.82	0.85
32	15.329	14.785	14.248	3.68	3.63	0.85	0.88
33	14.709	14.175	13.647	3.77	3.72	0.88	0.91
34	14.117	13.593	13.075	3.86	3.80	0.90	0.93
35	13.553	13.038	12.531	3.95	3.89	0.93	0.96
36	13.013	12.508	12.012	4.04	3.97	0.95	0.98
37	12.499	12.003	11.517	4.13	4.05	0.98	1.01
38	12.007	11.521	11.045	4.21	4.13	1.01	1.04
39	11.537	11.062	10.595	4.30	4.21	1.03	1.06
40	11.088	10.622	10.166	4.38	4.29	1.06	1.09
41	10.659	10.203	9.757	4.46	4.37	1.09	1.11
42	10.248	9.803	9.367	4.55	4.45	1.11	1.14
43	9.856	9.420	8.994	4.63	4.52	1.14	1.17
44	9.480	9.054	8.638	4.71	4.60	1.17	1.19
45	9.121	8.705	8.298	4.79	4.67	1.19	1.22
46	8.778	8.371	7.973	4.86	4.75	1.22	1.24
47	8.449	8.051	7.663	4.94	4.82	1.24	1.27
48	8.134	7.745	7.367	5.02	4.89	1.27	1.30
49	7.832	7.453	7.083	5.09	4.96	1.30	1.32
50	7.543	7.173	6.812	5.16	5.03	1.32	1.35
51	7.267	6.905	6.553	5.24	5.10	1.35	1.37
52	7.002	6.649	6.305	5.31	5.17	1.38	1.40
53	6.747	6.403	6.068	5.38	5.24	1.40	1.43
54	6.504	6.168	5.841	5.45	5.30	1.43	1.45
55	6.270	5.942	5.623	5.52	5.37	1.46	1.48
56	6.046	5.726	5.415	5.59	5.43	1.48	1.50
57	5.831	5.519	5.216	5.66	5.50	1.51	1.53
58	5.625	5.321	5.025	5.72	5.56	1.53	1.56
59	5.428	5.131	4.842	5.79	5.62	1.56	1.58
60	5.238	4.948	4.667	5.86	5.69	1.59	1.61

61	5.055	4.773	4.499	5.92	5.75	1.61	1.63
62	4.880	4.605	4.338	5.98	5.81	1.64	1.66
63	4.712	4.444	4.183	6.05	5.87	1.67	1.68
64	4.551	4.289	4.035	6.11	5.93	1.69	1.71
65	4.396	4.140	3.893	6.17	5.98	1.72	1.74
66	4.247	3.998	3.756	6.23	6.04	1.75	1.76
67	4.103	3.861	3.625	6.29	6.10	1.77	1.79
68	3.966	3.729	3.500	6.35	6.15	1.80	1.81
69	3.833	3.603	3.379	6.41	6.21	1.82	1.84
70	3.706	3.481	3.263	6.46	6.26	1.85	1.87
71	3.583	3.364	3.152	6.52	6.32	1.88	1.89
72	3.466	3.252	3.045	6.58	6.37	1.90	1.92
73	3.352	3.144	2.942	6.63	6.42	1.93	1.94
74	3.243	3.040	2.843	6.68	6.47	1.96	1.97
75	3.138	2.940	2.748	6.74	6.53	1.98	2.00
76	3.037	2.844	2.657	6.79	6.58	2.01	2.02
77	2.940	2.751	2.569	6.84	6.63	2.04	2.05
78	2.846	2.662	2.485	6.89	6.67	2.06	2.07
79	2.756	2.577	2.403	6.95	6.72	2.09	2.10
80	2.669	2.494	2.325	7.00	6.77	2.11	2.13
81	2.585	2.415	2.250	7.04	6.82	2.14	2.15
82	2.504	2.338	2.178	7.09	6.86	2.17	2.18
83	2.426	2.264	2.108	7.14	6.91	2.19	2.20
84	2.351	2.193	2.041	7.19	6.96	2.22	2.23
85	2.279	2.125	1.976	7.24	7.00	2.25	2.26
86	2.209	2.059	1.914	7.28	7.04	2.27	2.28
87	2.142	1.995	1.854	7.33	7.09	2.30	2.31
88	2.077	1.934	1.796	7.37	7.13	2.33	2.33
89	2.014	1.875	1.740	7.42	7.17	2.35	2.36
90	1.954	1.818	1.687	7.46	7.22	2.38	2.39
91	1.895	1.763	1.635	7.50	7.26	2.41	2.41
92	1.839	1.710	1.585	7.55	7.30	2.43	2.44
93	1.785	1.659	1.537	7.59	7.34	2.46	2.46
94	1.732	1.609	1.490	7.63	7.38	2.48	2.49
95	1.681	1.561	1.446	7.68	7.43	2.51	2.52
96	1.632	1.515	1.402	7.72	7.47	2.54	2.54
97	1.585	1.471	1.360	7.76	7.51	2.56	2.57
98	1.539	1.428	1.320	7.80	7.55	2.59	2.59
99	1.495	1.386	1.281	7.85	7.59	2.62	2.62
100	1.452	1.346	1.243	7.89	7.63	2.64	2.64
101	1.411	1.307	1.207	7.93	7.68	2.67	2.67
102	1.371	1.270	1.172	7.98	7.72	2.70	2.70
103	1.332	1.233	1.137	8.02	7.76	2.72	2.72
104	1.295	1.198	1.104	8.07	7.81	2.75	2.75
105	1.258	1.164	1.070	8.11	8.11	2.77	2.77

Relation between Ambient Temperature Sensor and Resistance

R25 = 15.0 K ± 3%			
B25/50 = 3950K ± 2%			
T [°C]	R min [K]	R nom [K]	R max [K]
-25	183.4	199.1	216
-24.5	178	193.1	209.4
-24	172.8	187.4	203
-23.5	167.8	181.8	196.9
-23	162.9	176.5	190.9
-22.5	158.2	171.3	185.2
-22	153.7	166.2	179.6
-21.5	149.3	161.4	174.3
-21	145	156.7	169.1
-20.5	140.9	152.1	164.1
-20	136.9	147.7	159.2
-19.5	133	143.4	154.6
-19	129.2	139.3	150
-18.5	125.6	135.3	145.6
-18	122.1	131.4	141.4
-17.5	118.7	127.7	137.3
-17	115.4	124.1	133.3
-16.5	112.2	120.6	129.5
-16	109.1	117.2	125.7
-15.5	106.1	113.9	122.1
-15	103.1	110.7	118.6
-14.5	100.3	107.6	115.3
-14	97.59	104.6	112
-13.5	94.94	101.7	108.8
-13	92.37	98.88	105.8
-12.5	89.87	96.16	102.8
-12	87.45	93.52	99.92
-11.5	85.11	90.96	97.13
-11	82.83	88.48	94.43
-10.5	80.63	86.07	91.81
-10	78.48	83.74	89.27
-9.5	76.41	81.48	86.82
-9	74.39	79.29	84.43
-8.5	72.43	77.16	82.12
-8	70.54	75.1	79.88
-7.5	68.69	73.1	77.71
-7	66.9	71.15	75.61
-6.5	65.17	69.27	73.57
-6	63.48	67.44	71.59
-5.5	61.84	65.67	69.66
-5	60.25	63.95	67.8
-4.5	58.71	62.27	65.99
-4	57.21	60.65	64.24
-3.5	55.75	59.08	62.54
-3	54.34	57.55	60.89

-2.5	52.96	56.06	59.29
-2	51.63	54.62	57.73
-1.5	50.33	53.22	56.22
-1	49.07	51.86	54.76
-0.5	47.84	50.54	53.33
0	46.65	49.25	51.95
0.5	45.49	48	50.61
1	44.37	46.79	49.31
1.5	43.27	45.61	48.04
2	42.21	44.47	46.81
2.5	41.17	43.36	45.62
3	40.17	42.28	44.46
3.5	39.19	41.23	43.33
4	38.24	40.2	42.24
4.5	37.31	39.21	41.17
5	36.41	38.25	40.14
5.5	35.53	37.31	39.13
6	34.68	36.39	38.16
6.5	33.85	35.51	37.21
7	33.05	34.64	36.29
7.5	32.26	33.8	35.39
8	31.5	32.99	34.52
8.5	30.75	32.19	33.67
9	30.03	31.42	32.84
9.5	29.33	30.67	32.04
10	28.64	29.94	31.26
10.5	27.97	29.22	30.5
11	27.32	28.53	29.77
11.5	26.69	27.86	29.05
12	26.07	27.2	28.35
12.5	25.47	26.56	27.67
13	24.89	25.94	27.01
13.5	24.32	25.33	26.37
14	23.76	24.74	25.74
14.5	23.22	24.17	25.13
15	22.69	23.61	24.54
15.5	22.18	23.06	23.96
16	21.68	22.53	23.4
16.5	21.19	22.02	22.85
17	20.72	21.51	22.32
17.5	20.26	21.02	21.8
18	19.8	20.55	21.3
18.5	19.36	20.08	20.8
19	18.94	19.63	20.33
19.5	18.52	19.19	19.86
20	18.11	18.75	19.4
20.5	17.71	18.33	18.96
21	17.33	17.93	18.53
21.5	16.95	17.53	18.11

22	16.58	17.14	17.7
22.5	16.22	16.76	17.3
23	15.87	16.39	16.91
23.5	15.53	16.03	16.53
24	15.19	15.68	16.16
24.5	14.87	15.33	15.8
25	14.55	15	15.45
25.5	14.23	14.67	15.12
26	13.91	14.36	14.8
26.5	13.61	14.05	14.49
27	13.31	13.74	14.18
27.5	13.02	13.45	13.88
28	12.73	13.16	13.59
28.5	12.45	12.88	13.31
29	12.18	12.6	13.03
29.5	11.92	12.34	12.76
30	11.66	12.08	12.49
30.5	11.41	11.82	12.23
31	11.17	11.57	11.98
31.5	10.93	11.33	11.73
32	10.69	11.09	11.49
32.5	10.47	10.86	11.26
33	10.24	10.63	11.03
33.5	10.03	10.41	10.8
34	9.816	10.2	10.59
34.5	9.609	9.987	10.37
35	9.408	9.782	10.16
35.5	9.211	9.581	9.957
36	9.019	9.385	9.758
36.5	8.831	9.194	9.563
37	8.648	9.007	9.372
37.5	8.469	8.824	9.185
38	8.294	8.645	9.003
38.5	8.123	8.471	8.825
39	7.957	8.3	8.651
39.5	7.794	8.134	8.481
40	7.635	7.971	8.315
40.5	7.479	7.812	8.152
41	7.328	7.657	7.993
41.5	7.179	7.505	7.838
42	7.034	7.356	7.686
42.5	6.893	7.211	7.537
43	6.755	7.069	7.391
43.5	6.619	6.93	7.249
44	6.487	6.795	7.11
44.5	6.358	6.662	6.974
45	6.232	6.532	6.841
45.5	6.108	6.405	6.711
46	5.988	6.282	6.584

46.5	5.87	6.16	6.459
47	5.755	6.042	6.337
47.5	5.642	5.926	6.218
48	5.532	5.812	6.101
48.5	5.424	5.701	5.987
49	5.319	5.593	5.875
49.5	5.216	5.486	5.766
50	5.115	5.382	5.659
50.5	5.016	5.28	5.553
51	4.919	5.18	5.45
51.5	4.825	5.083	5.35
52	4.732	4.987	5.251
52.5	4.642	4.894	5.155
53	4.553	4.802	5.06
53.5	4.467	4.713	4.968
54	4.382	4.625	4.877
54.5	4.3	4.54	4.789
55	4.219	4.457	4.703
55.5	4.139	4.374	4.618
56	4.061	4.293	4.534
56.5	3.985	4.214	4.452
57	3.911	4.137	4.373
57.5	3.839	4.062	4.295
58	3.767	3.988	4.218
58.5	3.698	3.916	4.143
59	3.63	3.845	4.07
59.5	3.563	3.776	3.998
60	3.498	3.708	3.927
60.5	3.434	3.642	3.859
61	3.371	3.577	3.791
61.5	3.31	3.513	3.725
62	3.25	3.45	3.66
62.5	3.191	3.389	3.596
63	3.134	3.329	3.534
63.5	3.077	3.271	3.473
64	3.022	3.213	3.413
64.5	2.968	3.157	3.354
65	2.915	3.102	3.297
65.5	2.863	3.048	3.241
66	2.813	2.995	3.185
66.5	2.763	2.943	3.131
67	2.714	2.892	3.078
67.5	2.666	2.842	3.026
68	2.62	2.793	2.975
68.5	2.574	2.745	2.925
69	2.529	2.698	2.876
69.5	2.485	2.652	2.828
70	2.442	2.607	2.781
70.5	2.399	2.563	2.734

71	2.358	2.519	2.689
71.5	2.317	2.477	2.645
72	2.278	2.435	2.601
72.5	2.239	2.394	2.558
73	2.2	2.354	2.516
73.5	2.163	2.315	2.475
74	2.126	2.276	2.435
74.5	2.09	2.238	2.395
75	2.055	2.201	2.356
75.5	2.02	2.165	2.318
76	1.986	2.129	2.28
76.5	1.953	2.094	2.244
77	1.92	2.06	2.208
77.5	1.888	2.026	2.172
78	1.857	1.993	2.138
78.5	1.826	1.961	2.103
79	1.796	1.929	2.07
79.5	1.766	1.898	2.037
80	1.737	1.867	2.005
80.5	1.709	1.837	1.973
81	1.681	1.808	1.942
81.5	1.653	1.779	1.912
82	1.626	1.75	1.882
82.5	1.6	1.722	1.852
83	1.574	1.695	1.824
83.5	1.548	1.668	1.795
84	1.524	1.642	1.767
84.5	1.499	1.616	1.74
85	1.475	1.59	1.713
85.5	1.451	1.565	1.687
86	1.428	1.541	1.661
86.5	1.406	1.517	1.636
87	1.383	1.493	1.611
87.5	1.361	1.47	1.586
88	1.34	1.447	1.562
88.5	1.319	1.425	1.538
89	1.298	1.403	1.515
89.5	1.278	1.381	1.492
90	1.258	1.36	1.47
90.5	1.238	1.34	1.448
91	1.219	1.319	1.426
91.5	1.2	1.299	1.405
92	1.181	1.279	1.384
92.5	1.163	1.26	1.364
93	1.145	1.241	1.343
93.5	1.128	1.222	1.324
94	1.11	1.204	1.304
94.5	1.093	1.186	1.285
95	1.077	1.168	1.266

95.5	1.06	1.151	1.248
96	1.044	1.134	1.229
96.5	1.028	1.117	1.212
97	1.013	1.1	1.194
97.5	0.9976	1.084	1.177
98	0.9826	1.068	1.16
98.5	0.9679	1.052	1.143
99	0.9535	1.037	1.127
99.5	0.9392	1.022	1.11
100	0.9252	1.007	1.095
100.5	0.9115	0.9922	1.079
101	0.8981	0.9778	1.064
101.5	0.8848	0.9636	1.049
102	0.8717	0.9497	1.034
102.5	0.8589	0.936	1.019
103	0.8463	0.9225	1.005
103.5	0.8339	0.9093	0.9906
104	0.8218	0.8963	0.9767
104.5	0.8098	0.8835	0.9631
105	0.7981	0.871	0.9497